AVAPS Drop Log

Project: Hurri 21 Mission: TS Ida Flight ID: 20210827I1

Take Off: _____ Landing: _____ Flt Dir: Carpenter Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203810276	1	Ø	0941	JW	NWR	END 1	✓
2	203630325	2	-5	0952		NWS	Midpoint	✓
3	203810264	3	Ø	0958		ONR	1/4 Point	✓
4	202520487	4	Ø	1007		NWS	CTR 1	✓
5	203630323	5	Ø	1014		ONR	1/4 Point	✓
6	202630526	6	Ø	1020		NWS	Midpoint	✓
7	202630342	7	Ø	1031			END 2	✓
8	203810262	8	Ø	1110			END 3	✓
9	203350229	1	Ø	1113			Midpoint	✓
10	202630498	2	Ø	1119		ONR	1/4 point	✓
11	202610676	3	Ø	1137		ONR	1/4 Point	✓
12	203420252	4	Ø	1141		NWS	Midpoint	✓
13	203510303	5	Ø	1154			END 4	✓
14	203631817	6	Ø	1210			END 5	✓
15	202630523	7	Ø	1221			Midpoint	✓
16	203350232	8	-8	1228		ONR	1/4 point	✓
17	203350240	1	-5	1232		NWS	CTR	✓
18	203520169	2	Ø	1242		ONR	1/4 Point	✓
19	203630324	3	Ø	1247		NWS	Midpoint	✓
20	203350231	4	Ø	—			Note L/D	X
21	203350225	5	Ø	1259			— Back up —	✓
22	202610685	6	Ø	1335			END Point 6	✓
23	202610686	7	Ø	1347			END point 7	✓
24	203810259	8	Ø	1353		ONR	1/4 Point	✓
25	204521419	1	Ø	1400		NWS	CTR	✓
26	204530816	2	Ø	1407		ONR	1/4 Point	✓
27	203420276	3	Ø	1413		NWS	Midpoint	✓
28	203530370	4	Ø	1420		NWS	END Point 8	✓
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: HURR21 Mission: Hurricane Ida Flight ID: 20210828I1

Take Off: 0757Z Landing: Flt Dir: Carpenter Launcher S/N: 002

25.10

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204521237	1	-.5	0919	JW		IP 1	✓
2	203630335	2	-.4	0932			Midpoint	✓
3	203350246	3	-1.1	0940			RMW	✓
4	204650038	4	Ø	0944			CTR	✓
5	204530504	5	Ø	0950			RMR	✓
6	204650399	6	-.5	1001			Midpoint	✓
7	204521383	7	-.3	1011			ENDpoint 1	✓
8	204521408	8	-.5	1042			IP 2	✓
9	204521286	1	-.5	1050			Midpoint	✓
10	204521375	2	-.5	1058			RMW	✓
11	204521386	3	-.5	1101			CTR	✓
12	204260589	4	-.5	1113			RMW	✓
13	203350274	5	-1.1	1121				✓
14	204650034	6	-.3	1127				✓
15	204521378	7	-.5	1143				X
16	204521377	8	-.5	1144				X
17	204521385	1	-.3	1154				✓
18	204710299	2	Ø	1203				✓
19	204650035	3	Ø	1205				✓
20	204521374	4	-.4	1210				✓
21	204521381	5	-.4	1222				✓
22	204270015	6	-.4	1227			Late L/D	✓
23	204530194	7	-.5	1228				✓
24	204530743	8	-.4	1236				✓
25	204521382	1	-.3	1246				✓
26	204521384	2	-.5	1334				✓
27	204520776	3	Ø	1347				✓
28	204520795	4	Ø	1358				✓
29	204520783	5	Ø	1402				✓
30	204650036	6	Ø	1405				✓
31	204520779	7	Ø	1415				✓
32	204650398	8	Ø	1429				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurr 21 Mission: IDA Flight ID: 20210829I1

Take Off: 0738Z Landing: _____ Flt Dir: Carpenter Launcher S/N: 001

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204521405	1	-.5	0852	JW	HRD	IPSE C	✓
2	204520777	2	-.5	0903		HRD	Midpoint C	✓
3	203040058	3	Ø	0914		ONR	RMW	✓
4	203040036	4	Ø	0914		ONR	RMW	✓
5	203040062	5	Ø	0914		ONR	RMW	✓
6	203040061	6	Ø	0917		ONR	CTR C	✓
7	203040067	7	Ø	0926		ONR	RMW	✓
8	203040031	8	Ø	0926		ONR	RMW	✓
9	203310044	1	Ø	0926		ONR	RMW	✓
10	204850520	2	Ø	0935		HRD	Midpoint C	✓
11	203031071	3	Ø	0946		HRD	Endpoint C	✓
12	203040081	4	Ø	1014		NWS	RMW	✓
13	203031073	5	Ø	1018		NWS	CTR	✓
14	204650326	6	Ø	—		ONR	No GPS/LD	X
15	203040066	7	Ø	1022		ONR	RMW	✓
16	203040086	8	Ø	1023		ONR	RMW	✓
17	203040032	1	Ø	1029		HRD		✓
18	204650463	2	Ø	1033		HRD		✓
19	204530472	3	Ø	1048		HRD		✓
20	204650325	4	Ø	1058		HRD		✓
21	203310043	5	Ø	1107		HRD		✓
22	204650327	6	Ø	1116		ONR	RMW	✓
23	204640125	7	Ø	1116		ONR	RMW	✓
24	204640092	8	Ø	1116		ONR	RMW	✓
25	203040057	1	Ø	118		ONR	CTR	✓
26	204530487	2	Ø	—		HRD	No L/D	X
27	204530392	3	Ø	1141		HRD		✓
28	204530388	4	Ø	1233		HRD	RMW	✓
29	204640462	5	Ø	1234		HRD	RMW	✓
30	204530501	6	Ø	1236		HRD		✓
31	204530474	1	Ø	1316		HRD		✓
32	203250852	2	Ø	1317		HRD		✓
33	203310161	3	Ø	1344		HRD		✓
34	204640123	4	Ø	1358		HRD		✓
35	203250854	5	Ø	1359	JW	HRD		✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect