AVAPS Drop Log

Project: Harr 21 Mission: Larry Flight ID: 20210906I1

Take Off: 1447 Z Landing: _____ Flt Dir: Holmes Launcher S/N: 646

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	212350113	1	Ø	1703	JW	NWS	ENDPOINT 1	✓
2	204521421	2	Ø	1718		NWS	Midpoint #1	✓
3	204520770	3	Ø	1726		HRD	CTR #1	✓
4	204520759	4	Ø	1744		NWS	Midpoint #2	✓
5	211921024	5	Ø	1754		NWS	ENDPOINT #2	✓
6	212250268	6	Ø	1852		NWS	ENDPOINT #3	✓
7	211921032	7	Ø	1905		NWS	Midpoint #3	✓
8	211921052	8	Ø	1912		NWS	RUN W	✓
9	203850398	1	Ø	1918		HRD	CTR	✓
10	211910514	2	Ø	1933		NWS	Midpoint	✓
11	212250276	3	Ø	1945		NWS	ENDPOINT	✓
12	212250296	4	Ø	1959		ONR	Mid Down	✓
13	211821404	5	Ø	2011		NWS	NO L/D EP	✗
14	212350114	6	Ø	2015		NWS	ENDPOINT	✗
15	212510221	7	Ø	2023		NWS	Midpoint	✗
16	212350121	8	Ø	2028		NWS	ENDPOINT	✓
17	211921030	1	Ø	2036		HRD	CTR	✓
18	212250274	2	Ø	2106		HRD	CTR	✓
19	203940550	3	Ø	2115		HRD	RUN W	✓
20	211921022	4	Ø	2122		NWS	Midpoint	✓
21	212250267	5	Ø	2136	JW	NWS	ENDPOINT	✓
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

END POINTS & MID POINTS EMC

6-7 mid ONR CTR HRD

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

20210907I1

AVAPS Drop Log

Project: Hurr 21 Mission: Larry #2 Flight ID: 20210906I1

Take Off: 1708 Z Landing: _____ Flt Dir: Holmes Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	212250283	1	Ø	1922	JW	NWS	CTR #1	✓
2	212250299	2	Ø	2037	JW	NWS	CTR #2	✓
3	212810214	3	Ø	2136	JW	NESDIS	RMW	X
4	210550235	4	Ø	2136	JW	NESDIS	RMW	✓
5	212810215	5	Ø	2145	JW	NESDIS	RMW	✓
~~6~~	~~210620005~~	~~6~~	~~Ø~~					
~~7~~	~~210550239~~	~~7~~	~~Ø~~					
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Center / NWS

2150Z / NESDIS

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect