AVAPS Drop Log

Project: Hurricanes 2021 Mission: Elsa Flight ID: 20210702N1

Take Off: _____ Landing: _____ Flt Dir: Henning/Kalen Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	202270140	1	0.0	1829Z	NGU	NWS	Point #1	✓
2	203240717	2	0.0	1840Z			Point #2	✓
3	202270598	3	0.0	1851Z			Point #3	✓
4	203030567	4	-0.4	1901Z			Point #4	✓
5	203310506	1	0.0	1912Z			Point #5	✓
6	203150616	2	-0.4	1924Z			Point #6	✓
7	202311644	3	0.0	1935Z			Point #7	✓
8	203240045	4	-0.6	1946Z			Point #8, fast fall	X
9	203240797	1	0.0	1947Z			Point #8 backup	✓
10	203150293	2	0.0	2009Z			Point #9	✓
11	203240722	3	0.0	2018Z			Point #10	✓
12	202311645	4	0.0	2029Z			Point #11	✓
13	203240719	1	0.0	2041Z			Point #12	✓
14	203150615	2	0.0	2127Z			Point #13	✓
15	202311607	3	0.0	2154Z			Point #14	✓
16	202311608	4	0.0	2213Z			Point #15	✓
17	203210180	1	0.0	2232Z			Point #16	✓
18	203310505	2	0.0	2250Z			Point #17	✓
19	202260919	3	0.0	2303Z			Point #18	✓
20	203210055	4	0.0	2315Z			Point #19	✓
21	203040646	1	-0.4	2327Z			Point #20, fast fall	X
22	203240048	2	0.0	2328Z			Point #20 backup	✓
23	201520309	3	-0.4	2339Z			Point #21	✓
24	203440053	4	0.0	2351Z			Point #22, fast fall	X
25	202311591	1	0.0	2352Z			Point #22 backup	✓
26	203240721	2	0.0	0003Z			Point #23	✓
27	203240798	3	-0.4	0014Z			Point #24	✓
28	203150668	4	0.0	0026Z			Point #25	✓
29	203040648	1	0.0	0049Z			Point #26	✓
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricanes 2021 Mission: Elsa Flight ID: 20210703N1

Take Off: _____ Landing: _____ Flt Dir: Kalen Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	20315050 2	1	-0.4	1812Z	NGU	NWS	Point #1, Steinindr	X
2	2034 31802	2	-0.4	1813Z			Point #1 backup	✓
3	2006 50646	3	-0.8					
4		4						
5		1						
6		2						
7		3						
8		4						
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: TS Mission: TS Grace Flight ID: 20210814N1

Take Off: _____ Landing: _____ Flt Dir: Quinn/Rich Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204260615	1	0	1719	AJP	HRD		✓
2	203830032	2	0	1730				✓
3	204031037	3	0	1740				✓
4	203030995	4	-0.5	1749				✓
5	204260609	1	0	1800				✓
6	211450535	2	0	1812				✓
7	203150617	3	-0.5	1824				✓
8	204330181	4	0	1837				✓
9	211440951	1	0	1850				✓
10	204031028	2	0	1903				✓
11	204270002	3	0	1922				✓
12	204270007	4	0	1933				✓
13	203830665	1	0	1950				✓
14	204260594	2	0	2003			NO PTH	X
15	203440007	3	0	2004			Back up of 14	✓
16	203830577	4	0.5	2014				✓
17	204260582	1	0	2026		ONR		✓
18	204031015	2	0	2039				✓
19	204031205	3	0	2051				✓
20	204260586	4	0	2102				✓
21	204260636	1	0	2113				✓
22	203431801	2	0	2125				✓
23	204120637	3	0.5	2137			Fast fall	X
24	204031120	4	0	2138				✓
25	203830673	1	0	2148				✓
26	203240790	2	-0.7	2159				✓
27	203640260	3	0.5	2211			NO PTH	X
28	203940495	4	0	2212				✓
29	204130106	1	0.5	2217				✓
30	204260587	2	0	2223				✓
31	204031207	3	0	2228				✓

ONR → TCIR

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	204141152	4	0.5	2231	AJP	HRD		✓
33	204031206	1	0	2254	|	|	Dew/Humidity died Halfway?	
34	204260617	2	0	2303	|	|		✓
35	204030666	3	0	2312	|	|		✓
36	204330206	4	0	2324	|	|		✓
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

1st 10 to HRD
Rest to ONR

AVAPS Drop Log

Project: TS Mission: Grace Flight ID: 20210815N1

Take Off: _____ Landing: _____ Flt Dir: Quinn/Rich Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203830675	1	0	1539	AJP	HRD		✓
2	203840504	2	0	1549				✓
3	204031211	3	-0.5	1603				✓
4	203840949	4	-0.5	—			No launch detect	X
5	204120666	1	0	1616				✓
6	203830037	2	0	1626				✓
7	203310591	3	-0.8	1641			fast fall	X
8	203840493	4	0	1642				✓
9	204120669	1	0	1654				✓
10	204030663	2	0	1702				✓
11	204260644	3	0	1710				✓
12	203830036	4	0	1718				✓
13	203830039	1	0	1727		ONR		✓
14	203840503	2	0	1734				✓
15	203830040	3	0	1742				✓
16	203840782	4	0	1759				✓
17	204130103	1	0	1811				✓
18	203840497	2	0	1822				✓
19	204030618	3	0	1834				✓
20	203830672	4	0	1843				✓
21	203840481	1	0	1855				✓
22	203750635	2	0	1905			late launch detect	✓ ?x
23	204031121	3	0	1905				✓
24	203240116	4	0	1914				✓
25	203840924	1	0	1928				✓
26	204031208	2	0	1950				✓
27	204130046	3	0	—			No launch detect	X
28	203240119	4	0	2001				
29	203830043	1	0	—			No launch detect	X
30	204031036	2	0	2014				✓
31	204030661	3	0	2035				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	204130056	4	0	2045				✓
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

1st 19 HRD
Rest ONR

AVAPS Drop Log

Project: Hurricane Mission: Hurr. Grace Flight ID: 20210818N1

Take Off: _____ Landing: _____ Flt Dir: Quinn/Rich Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	203840499	1	0	1712	AJP	HRD		✓
2	203840921	2	0	1723				✓
3	203840913	3	0	1733				✓
4	204140948	4	0	—			No launch detect	✗
5	203840008	1	0	1748			late launch detect	✓
6	203840119	2	0	1758				✓
7	204140950	3	0	1810				✓
8	203830662	4	0	1823				✓
9	204120668	1	0	1835				✓
10	204031214	2	0	1841				✓
11	204031118	3	-1.0	1854			noisy data	? ✗
12	203840951	4	0	1858				✓
13	203840500	1	0	1906				✓
14	204520789	2	0	1922			fast fall	✗
15	203840247	3	-0.6	1923	Rick			✓
16	203830647	4	0	1935	AJP			✓
17	204140953	1	0	—			No launch detect	✗
18	204140947	2	-0.4	1946				✓
19	203830576	3	0	1953				✓
20	203830574	4	0	2002				✓
21	204520775	1	0	2014				✓
22	204520762	2	0	2026		—		✓
23	203830663	3	0	2038		ONR		✓
24	204140946	4	0	2051				✓
25	203840123	1	0	2104				✓
26	204120672	2	0	2116				✓
27	204520781	3	0	2122				✓
28	203840012	4	0	2129			lost GPS halfway	✗
29	204521427	1	0	2136				✓
30	204450387	2	0	2142				✓
31	204520757	3	0	2148				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	204520793	4	0	2155	AJP	ONR		✓
33	204520771	1	0	2201				✓
34	204520794	2	0	2207				✓
35	204520763	3	0	2214				✓
36	204520786	4	0	2222				✓
37	204520791	1	0	2229				✓
38	204520761	2	0	2234				✓
39	204520784	3	0	2241			noisy data	✗
40	203840122	4	0	2242				✓
41	204520769	1	0	2252				✓
42	204140949	2	0	2204			late launch detect	✓
43	204650382	3	0	2303			backup 42	✓
44	204520765	4	0	2316				✓
45								
46								
47								
48								
49								
50								

38/44

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

Points 12–24 critical

AVAPS Drop Log

Project: TS Mission: _____ Flight ID: _____

Take Off: _____ Landing: _____ Flt Dir: mRich Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204330209	1	0	1856	AJP	NWS		✓
2	204330182	2	0	1907				✓
3	203631650	3	0	—			No launch detect to late	X
4	204031266	4	0	1918				✓
5	203631775	1	0	1928				✓
6	204031159	2	0	1938				✓
7	204031202	3	0	1949				✓
8	204031201	4	0	2005			Initially fast fall	X
9	204330184	1	0	2007				✓
10	204031261	2	0	2016				✓
11	203840116	3	-0.4	2029				✓
12	204520788	4	0	2038				✓
13	204031203	1	0	2050				✓
14	204450349	2	-0.5	2101			fast fall noisy data stable data	X
15	204031079	3	0	2103				✓
16	204330207	4	0	2117				✓
17	204031070	1	0	2130				✓
18	203631816	2	0	2142				✓
19	210440451	3	0	2153				✓
20	204130049	4	0	—			No launch detect	X
21	204121014	1	0	2206				✓
22	203840013	2	0	2217				✓
23	204030668	3	0	2232				✓
24	210440398	4	0	2242				✓
25	203631822	1	0	2258				✓
26	203631648	2	0	2306				✓
27	204031139	3	0	2322				✓
28	203631647	4	0	2330				✓
29	204121012	1	0	2342				✓
30	204120016	2	0	2352				✓
31	204031050	3	0	0000				

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	204120018	4	0	0009	AJP	NWS		✓
33	203830052	1	0	0018				✓
34	203830050	2	0	0027				✓
35	210440402	3	0	0038				✓
36	203830063	4	0	0049				✓
37	204031072	1	0	0100				✓
38	204130055	2	0	0109				✓
39	204031138	3	0	0118				✓
40	204121028	4	0	0130				✓
41	210440461	1	0	0141				✓
42								
43								
44								
45								
46								
47								
48								
49								
50								

37/41

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: _____ Mission: Henri Flight ID: 20210820N1

Take Off: _____ Landing: _____ Flt Dir: Holmes Launcher S/N: 2

	Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
	1	204 031 204	1	Ø	0621	JEH	NWS		✓
	2	204 270 016	2	Ø	0631				✓
	3	204 530 814	3	Ø	0648				✓
	4	204 130 029	4	Ø	0652				✓
	5	204 120 631	1	Ø	0704			Late launch detect	
pt5	6	203 830 595	2	Ø	0704			backup for pt5	✓
pt 6	7	204 521 417	3	Ø	0713				✓
pt 7	8	204 521 238	4	Ø	0724				✓
pt 8	9	204 031 265	1	Ø	0738				✓
pt 9	10	203 631 724	2	Ø	0750				✓
	11	204 330 208	3	Ø	0802				✓
	12	204 530 741	4	Ø	0818				✓
	13	204 450 353	1	Ø	0827				✓
	14	203 830 723	2	Ø	0843				✓
	15	204 270 006	3	Ø	0856				✓
	16	210 820 079	4	Ø	0911				✓
	17	203 830 661	1	Ø	0930				✓
	18	204 120 596	2	Ø	0943				✓
	19	203 631 646	3	Ø	0952				✓
	20	204 130 077	4	Ø	1007				✓
	21	204 260 612	1	Ø	1017				✓
	22	204 450 368	2	Ø	1026				✓
	23	204 450 371	3	Ø	1037				✓
	24	204 260 631	4	Ø	1045				✓
	25	203 830 630	1	Ø				NOLD	
	26	204 270 010	2	Ø	1054			backup for 25	✓
	27	204 031 225	3	Ø	1102			fast fall-ish	✓
	28	204 530 811	4	Ø	1112				✓
	29	204 260 590	1	Ø	1126				✓
	30	204 521 418	2	Ø	1142				✓
	31	204 260 643	3	Ø	1151				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	203 840 011	4	Ø	1200	JSL	NWS		✓
33	204 270 003	1	Ø	1211				✓
34	203 840 010	2	Ø	1224			Late launch detect	
35	204 050 401	3	Ø	1223			backup	✓
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: TS Mission: TS Henri Flight ID: 2020820N2

Take Off: _____ Landing: _____ Flt Dir: Quinn/Rich Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204120650	1	0	1828	AJP	NWS	lost Humidity	✓
2	204130030	2	-0.9	1842				✓
3	204120649	3	0	1852				✓
4	203830061	4	0	1901				✓
5	203830721	1	0	1911				✓
6	210340286	2	0	1924				✓
7	203830065	3	0	1936				✓
8	203830041	4	0	1951				✓
9	204050403	1	0	2001				✓
10	204054402	2	0	—			NO LD	X
11	203840494	3	0	2018				✓
12	204030665	4	0	2028				✓
13	203631823	1	0	2042				✓
14	204141151	2	0	2053				✓
15	203840501	3	0	2111				✓
16	204130051	4	0	2120				✓
17	204250137	1	0	2137				✓
18	204120652	2	0	2147				✓
19	203830066	3	0	2201				✓
20	203830643	4	0	2214				✓
21	203830654	1	0	2235				✓
22	204120012	2	0	2245				✓
23	204130048	3	0	2254				✓
24	203830668	4	0	—			NO LD	X
25	203830676	1	0	2307				✓
26	211440954	2	0	2314				✓
27	203830653	3	0	2325				✓
28	204250134	4	0	2333				✓
29	211441008	1	0	2341				✓
30	210820083	2	0	2351				✓
31	204121013	3	0	—			Launch detected 20 kft	X

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	204120638	4	0	0001	AJP	NWS		✓
33	203631815	1	0	0013				✓
34	203830053	2	0	0025				✓
35	204130108	3	0	0033				✓
36	203830051	4	0	0045				✓
37	204121011	1	0	0058				✓
38	204050404	2	0	0109				✓
39	210340124	3	0	0120				✓
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

36/39

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: _____ Mission: Henri Flight ID: 20210821N1

Take Off: _____ Landing: _____ Flt Dir: Holmes Launcher S/N: 2

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	204 650 042	1	Ø	0626	JEK	NWS		✓
2	204 850 209	2	Ø	0633			Medium fall	✓
3	204 521 409	3	Ø	0643				✓
4	204 250 136	4	Ø	0654				✓
5	204 650 368	1	Ø	0707				✓
6	204 650 041	2	Ø	0721				✓
7	204 650 402	3	Ø	0728				✓
8	204 640 098	4	Ø	0734				✓
9	205 050 300	1	Ø	0745				✓
10	204 521 391	2	Ø	0757			Late LD	✓
11	205 050 260	3	Ø	0818	CFL			✓
12	204 770 385	4	Ø	0835				✓
13	204 260 905	1	0	0845				✓
14	204 260 894	2	0	0902				✓
15	205 050 270	3	0	0926				✓
16	204 850 547	4	0	0937				✓
17	205 050 248	1	0	0947				✓
18	204 850 207	2	0	0956				✓
19	205 050 259	3	0	1004				✓
20	205 050 237	4	0	1015				✓
21	204 840 590	1	0	1028				✓
22	204 850 210	2	0	1036				✓
23	204 521 369	3	0	1045				✓
24	204 640 095	4	0	1052				✓
25	204 530 490	1	0	1100				✓
26	204 521 420	2	0	1109				✓
27	204 521 287	3	0	1119				✓
28	204 650 379	4	0	1129				✓
29	204 521 422	1	0	1139				✓
30	204 650 039	2	0	1151				✓
31	204 650 371	3	0	1159				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	205 050 264	4	0	1207	CFL	NWS		✓
33	204 840 555	1	0	1215				✓
34	204 120 632	2	Ø	1222			Late GPS	
35	204 530 812	3	Ø	1224			back up	✓
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect