AVAPS Drop Log

Project: Hurr. Sam Mission: Sam Flight ID: 20210925N1

Take Off: _____ Landing: _____ Flt Dir: Quinn / Paul Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	212730339	1	0	1931	AJP	HRD		✓
2	212040721	2	0	1952			NO PTU	X
3	212720377	3	0	1954				✓
4	212720372	4	0	2014				✓
5	211030704	1	0	2025				✓
6	211921044	2	0	2036				✓
7	211850540	3	0	2046		ONR		✓
8	212220217	4	0	2056			GPS issue back & for	X
9	211850544	1	0	2058				✓
10	211850536	2	0	2106				✓
11	212340263	3	0	2116				✓
12	212011547	4	0	2127				✓
13	212730348	1	0	2137				✓
14	212011412	2	0	2148				✓
15	212703 34	3	0	2158				✓
16	211921033	4	0	2209			fast fall / vert. speed bounces too much	X
17	212730345	1	0.5	2211				✓
18	212320045	2	0.4	2219				✓
19	212320048	3	0	2230				✓
20	212730381	4	0.5	2236				✓
21	211850538	1	0	2241				✓
22	212011153	2	0	2246				✓
23	212250455	5	0.4	2252	GD			✓
24	212750432	3	0.5	2258				✓
25	212730346	4	0.5	2303				✓
26	212320055	1	0.7	2309				✓
27	211920259	6	0	2316	GD			✓
28	212250367	2	0	2324	AJP			✓
29	212011548	3	0	2330				✓
30	212011413	4	0	2336				✓
31	212720368	1	0	0004				✓
32	212750350	2	0.6	0026				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricane Mission: SAM Flight ID: 20210926N1

Take Off: _____ Landing: _____ Flt Dir: Quinn/Paul Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	211011015	1	0	1823	AJP	NWS		✓
2	212710399	2	0.5	1841				✓
3	212710436	3	0	1854				✓
4	212710433	4	0.6	1907			fast fall	X
5	212640783	1	0.5	1909				✓
6	212710437	2	0	1920				✓
7	211030703	3	0	1931				✓
8	212730528	4	0	1941				✓
9	211030491	1	0	1952				✓
10	212710551	2	0	2003				✓
11	211010868	3	0	2014				✓
12	212640288	4	0	2025				✓
13	212710425	1	0.6	2036				✓
14	212340668	2	0	2048				✓
15	212430891	3	0	2057				✓
16	212330325	4	0	2111				✓
17	212250328	1	0	2123			Little noisy data	✓
18	212640823	2	0.5	2138				✓
19	212710495	3	0	2150				✓
20	212320058	4	0.5	2205				✓
21	212640270	1	0.7	2221				✓
22	212710547	2	0	2230				✓
23	212640885	3	0	2240	GD/AJP		late GPS after 1 min	✓
24	212710440	4	0	2249				✓
25	212640831	1	0	2301				✓
26	212640826	2	0.5	2311			Died @ 2000 m left	✓
27	211011019	3	0	2322				✓
28	212110085	4	0.5	2334				✓
29	212250327	1	0.6	2354	AJP			✓
30								
31								

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32								
33								
34								
35								
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing.
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect

AVAPS Drop Log

Project: Hurricane Mission: SAM Flight ID: 20210927N1

Take Off: _____ Landing: _____ Flt Dir: Quinn/Paul Launcher S/N: _____

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
1	212410276	1	0	1837	AJP	NWS		✓
2	212340580	2	0.4	1848				✓
3	212340589	3	0	1859				✓
4	212710094	4	0.5	1910				✓
5	212710089	1	0	1920				✓
6	212710445	2	0	1931				✓
7	212710439	3	0	1944				✓
8	212710397	4	0.5	1955				✓
9	212650783	1	0	2007				✓
10	212710540	2	0	2018				✓
11	212340625	3	0	2029				✓
12	212350589	4	0	2039				✓
13	212720452	1	0	2050				✓
14	211910179	2	0.5	2102				✓
15	211910173	3	0	2116				✓
16	211831152	4	0	2131				✓
17	211921037	1	0	2146				✓
18	211831110	2	0	2210				✓
19	212350606	3	0	2228				✓
20	211920988	4	0	2242			fast initial fall for a couple minutes	X
21	211921036	1	0	2245				✓
22	211920989	2	0	2259			fast fall	X
23	211831108	3	0	2300				✓
24	211910178	4	0	2308			fast fall / got little stable after halfway	X
25	211831148	1	0.5	2311				✓
26	211930589	2	0	2319				✓
27	211920979	3	0	2332				✓
28	211920946	4	0	2341				✓
29	212410271	1	0	2350				✓
30	211920981	2	0	2359				✓
31	211930592	3	0	0008				✓

Drop #	Sonde Serial #	Rcvr #	Press Offset	Launch Time	Operator	Charge $$ To	Comments	Good ?
32	212430911	4	0	0020	AJP	NWS		✓
33	211930079	1	0.5	0035				✓
34	212320057	2	0	0050				✓
35	212730347	3	0	0103				✓
36								
37								
38								
39								
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								

Drop Station Operator Notes

Charge $$ To Options (DO NOT USE FUNDING CODES):
AOC, NWS, HRD, NESDIS, IR/SST, AR, STAN (Stanford), SAT (JPSS/NESDIS/HRD)

AVAPS Pre-Flight Check:

- If time-permits, verify cabin pressure sensor w/ lab standard
- Start AVAPS., then start Soundings and set the Project Name and Full Flight ID (example: 20120823N2).
- Verify the Frequency band allocation as required:
  Band A: 53rd WRS - Band B: N42RF - Band C: N43RF - Band D: N49RF - Band E: Unallocated
- Select the **GPS Reference** tab from the **Soundings Displays** page and verify good GPS data
- Perform a prelaunch check on each channel, look for reasonable data and no CRC error status lights.
- Verify data is available on Remote AVAPS, then terminate the sonde.
- Verify the AVAPS Data mission folder has been created
- Verify AVAPS PC Time is correct – if time is off by >4sec, no data will display
- Early launch detects are caused usually by remanufactured sondes with the chute riser line not properly coiled below the PCB ear. This may also cause fast falls. If this is suspected, repack the riser line as time permits
- Perform RH Regeneration on all sondes – Multiple RD41 sondes may be processed at once

AVAPS Launch:

- Select a sonde frequency in the Green band and away from other sondes
- Enter sonde pressure error offset if 0.4mB or greater using cabin pressure sensor – warning, this can not be used during a climb
- If the Cal lab pressure standard and the cabin pressure standard match, apply pressure offset +/- 0.1 mB
- Wait until GPS available (green) on the pre-launch screen before continuing
- Select "begin data collection" and verify good data with winds prior to putting sonde in launch tube
- On N42 & N43, remove about ½ of the ribbon. Do not shorten the ribbon on N49. Loosen ribbon and extend end of ribbon to near, but not over, the sensor end of the sonde. Place excess orange tape on end of ribbon to form a pocket.
- Place the sonde in the launch tube, sensor arm up, with the power pin socket facing right
- Verify the sonde is actively tracking GPS data prior to launch and no early launch detect