

Week 3 Exercises

Steven Simonsen

March 25, 2024

Please complete all exercises below. You may use any library that we have covered in class UP TO THIS POINT.

1) Two Sum - Write a function named `two_sum()`

Given a vector of integers `nums` and an integer `target`, return indices of the two numbers such that they add up to `target`.

You may assume that each input would have exactly one solution, and you may not use the same element twice.

You can return the answer in any order.

Example 1:

Input: `nums = [2,7,11,15]`, `target = 9` Output: `[0,1]` Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`. Example 2:

Input: `nums = [3,2,4]`, `target = 6` Output: `[1,2]` Example 3:

Input: `nums = [3,3]`, `target = 6` Output: `[0,1]`

Constraints:

$2 \leq \text{nums.length} \leq 10^4$ $-10^9 \leq \text{nums}[i] \leq 10^9$ $-10^9 \leq \text{target} \leq 10^9$ Only one valid answer exists.

Note: For the first problem I want you to use a brute force approach (loop inside a loop)

The brute force approach is simple. Loop through each element x and find if there is another value that equals to $\text{target} - x$

Use the function `seq_along` to iterate

```
library(purrr)

nums_vector <- c(5,7,12,34,6,10,8,9)
target <- 13

#Assign initial loop_work variable to 0 for comparison to hashloop later
loop_work <- 0

two_sum <- function(nums_vector,target){
  #Empty character vector assigned to variable loop vector for now
  loop_vector <- character()
  #nested for statements using
  #seq_along to iterate over the num_vector.
  for(i in seq_along(nums_vector)) {
    loop_work <- loop_work + 1
    for(j in seq_along(nums_vector)) {
```

```

    #if the sum of position [i] and position [j] equal the target
    #and aren't the same number,
    #concatenate and output the indices on a line
    loop_work <- loop_work + 1
    if(i < j && nums_vector[i] + nums_vector[j] == target) {
        loop_vector <- c(loop_vector, paste(i, j))
    }
}
}
#Return used outside of the for loop, but within function!
return(loop_vector)
}
#run the function by assigning result to the function
result <- two_sum(nums_vector, target)
#print the result
print(result)

```

```
## [1] "1 7" "2 5"
```

```

# Test code
#expected answers
# [1] 1 7
# [1] 2 5
# [1] 5 2

```

- 2) Now write the same function using hash tables. Loop the array once to make a hash map of the value to its index. Then loop again to find if the value of target-current value is in the map.

The keys of your hash table should be each of the numbers in the nums_vector minus the target.

A simple implementation uses two iterations. In the first iteration, we add each element's value as a key and its index as a value to the hash table. Then, in the second iteration, we check if each element's complement (target - nums_vector[i]) exists in the hash table. If it does exist, we return current element's index and its complement's index. Beware that the complement must not be nums_vector[i] itself!

```
library(hash)
```

```
## hash-2.2.6.3 provided by Decision Patterns
```

```

nums_vector2 <- c(5,7,12,34,6,10,8,9)
target2 <- 15

```

```

#Assign hash_work variable to 0
hash_work <- 0

```

```

two_sum2 <- function(nums_vector2,target2){
    #Assign h to an empty hash map
    h<-hash()
    #As noted above, assign each element's value as a key and its index as a value to the hash table.
    for(i in seq_along(nums_vector2)) {
        #Add 1 to hash_work for comparison to loop work at end. Use <- global
        #assignment operator to update the variable outside of the function
        hash_work <- hash_work + 1
        h[(nums_vector2[i])] <- i
    }
}

```

```

#Empty character vector for iteration #2
result2 <- character()
for(i in seq_along(nums_vector2)) {
  #Add again to hash_work
  hash_work <- hash_work + 1
  #As noted above, complement is equal to target less the nums_vector[i]
  complement <- target2 - nums_vector2[i]
  #The first part of the if statement checks to make sure the complement is
  #less than nums_vector2[i] to avoid duplication.
  #The second part of the if statement checks to see if the complement is
  #contained within the keys (names) of nums_vector2[i]
  if(complement < nums_vector2[i] && complement %in% names(h)) {
    #If found, append to result2 vector with the value (indices) of the
    #complement, and the index of the original nums_vector2 that corresponds
    #with the value whos sum is equal to the target, 15.
    #as.character is needed because R converts keys to a character type.
    #Since our values are numeric, I converted to character to ensure keys are
    #treated as characters. Before adding this, I was getting very
    #strange,unexpected errors.
    result2 <- c(result2, paste(h[[as.character(complement)]], i))
  }
}
#I made sure to use return OUTSIDE of the for loops, but still within function!
return(result2)
}

#Assign result two to running the function
result2 <- two_sum2(nums_vector2, target2)
#Print the result2
print(result2)

## [1] "1 6" "2 7" "5 8"

#comparison of hashwork vs loopwork. Much more efficient to use hash!
print(hash_work)

## [1] 16

print(loop_work)

## [1] 72

#expected answers
#[1] 10 5
#[1] 8 7
#[1] 9 6
#[1] 5 10
#[1] 7 8
#[1] 6 9

```