June 21, 2017

**Subject: Grab bar reinforcement**

To whom it may concern,

This letter is in reference to the compliance of Aquatic units with respect to the installation of aftermarket grab bars.

The reinforcement (made of wood and/or ArmorCore) offered on Aquatic units meets or exceeds the requirements of CSA B45.5-11/IAPMO Z124-2011, in terms of grab bar structural strength of 292 lbf (see clause 5.2.1.1 below), provided that :

- The grab bar itself is certified to meet the requirements of CSA B45.5-11/IAPMO Z124.2011
- The grab bar is installed as per the manufacturer's instructions

**5.2.1.1 Load test for grab bars**

The load test for grab bars shall be conducted as follows:

(a) For horizontally mounted bars, apply the load vertically downward. For vertically mounted bars, apply the load pulling downward at an angle of 30 ± 5° from the wall.

(b) Over a period of 30 s, gradually apply a load of 1.3 kN (292 lbf) on the middle 90 mm (3.5 in) section of the specimen.

(c) Hold the load for 5 min ± 10 s.

You can find the list of Aquatic units that meet the CSA B45.5-11/IAPMO Z124-2011 standard at:

http://www.icc-es-pmg.org/Listing_Directory/pdf/PMG-1240.pdf

If there are any additional concerns or comments please do not hesitate to contact Aquatic.

Sincerely,

Tom Kobel
Sr. Product Manager
Aquatic