ACCIDENT PREVENTION PROGRAM

19 West Harrison Apartments
19 West Harrison, Seattle, WA 98119

One-Way Plumbing, LLC.

Date Last Reviewed:
February 17, 2015

TABLE OF CONTENTS

SUBJECT	PAGE
General Information	2
Management's Safety and Health Policy Statement	3
Responsibilities	4-5
Disciplinary Policy	6
Employee Orientation Checklist – Safety	7
Hazard Communications Program (Information)	8
One-Way Plumbing, LLC. written Hazard Communications Program	9-10
Master List of Chemicals	11
Employee Orientation Checklist – Hazardous Substances	12
Employee Responsibilities	13
Personal Work Rules	14
General Work Rules	15
Safety Rules for Ladders	16-17
Scaffold Safety Rules	18
Motorized Vehicle and Equipment Safety Rules	19
Trenching and Excavation Safety Rules	20
1st-Aid Training, Kits, and Posters	21
Blood borne Pathogens program	22
Procedures for Job site Injuries	23
Safety Bulletin Board	24
How to Hold a Good Safety Meeting	25
Crew/Leader Safety Meetings	26
Emergency Procedures	27
Fire Prevention & Protection Policy	28-31
Appendices	32-76

A. OSHA Record Keeping Information
B. Basic Rules for Accident Investigation
C. Supervisor's Report of Accident form
D. Employee's Report of Accident form
E. Crew/Leader Safety Meeting Documentation form
F. Weekly Safety & Health Inspection Checklist
G. Barometer of Safety Attitudes – Construction Self-Inspection Guide
H. Equipment Safety Inspection Checklist
I. Job Safety Analysis Worksheet
J. Fall Protection Program Information
K. (Site Specific) Fall protection Work Plan
L. Heat Related Illness Policy
M. Hearing Loss Prevention
N. Personal Protective Equipment Form
O. Forklift Safety Plan
P. Aerial Lift Safety Plan
Q. Confined Space Entry Program & Permit Form

GENERAL INFORMATION

A. **Overview**

Industrial injury accidents create a no-win situation for everyone involved.. Employees experience pain, suffering and incapacitation while the company suffers from the loss of the injured person's contributions. This document is designed to assist all personnel in assuring that such an undesirable situation will not develop in this company. It provides information and guidance for the establishment and maintenance of an accident-free work environment.

B. **Procedures**

The Appendices to Accident Prevention Program contain guidance for safety procedures to be followed and forms to be used. Supervisors are expected to integrate the procedures into the appropriate work activity and employees are expected to apply them on the job. The sample forms are to be used if they apply to the job concerned.

C. **Dissemination**

A copy of this document will be issued to all supervisory and management personnel. A copy of the program will be posted on company safety and health bulletin boards or at the following locations:

One-Way Plumbing, LLC.

Site job shacks

D. **Regulations**

A copy of the following documents will be maintained on each job site (if there is a job shack):

1. A copy of this Accident Prevention Program

2. Safety Standards for Construction Chapter 155 (WAC 296-155). Chapter 155 is available from the Division of Industrial Safety and Health, Washington State Department of Labor and Industries.

3. The WISHA Poster, Form F 416-081-000, which tells employees and employers their rights under the Washington Industrial Safety and Health Act (WISHA).

SAFETY and HEALTH POLICY
For One Way Plumbing, LLC.

- The purpose of this policy is to develop a high standard of safety throughout all operations of One-Way Plumbing, LLC. and to ensure that no employee is required to work under any conditions that are hazardous or unsanitary.

We believe that the individual employee has the right to derive personal satisfaction from his/her job and the prevention of occupational injury or illness is of such consequence to this belief that it will be given top priority at all times.

It is our intention here at One-Way Plumbing, LLC. to initiate and maintain complete accident prevention and safety training programs. Each individual from top management to the working person is responsible for the safety and health of those persons in their charge and coworkers around them. By accepting mutual responsibility to operate safely, we will contribute to the well being of all personnel.

_____

Jeff Gerard
Safety Manager

RESPONSIBILITIES

Responsibilities for safety and health include the establishment and maintenance of an effective communication system between workers, supervisors and management officials. To this end, all personnel are responsible to assure that their messages are received and understood by the intended receiver.

Specific safety and health responsibilities for company personnel are as follows:

A. **Management Officials.** Active participation in and support of safety and health programs is essential. Management officials will display their interest in safety and health matters at every opportunity. At least one manager (as designated) will participate in project safety and health meetings, accident investigations and job site inspections. Each manager will establish realistic goals for accident reduction in his/her area of responsibility and will establish the necessary implementation instructions for meeting the goals. Goals and implementation instructions shall be within the framework established by this document. Incentives will be included as a part of implementation instructions.

B. **Supervisors.** Safety and health of the employees they supervise is a primary responsibility of the supervisors. To accomplish this obligation, supervisors will:

1. Assure that all safety and health rules, regulations, policies and procedures are understood by conducting pre-job safety orientations with all workers and reviewing rules as the job or conditions change or when individual workers show a specific need.

2. Require the proper care and use of all needed protective equipment.

3. Identify and eliminate job hazards expeditiously through job safety analysis procedures. See the sample Job Hazard Analysis in Appendix I of this document.

4. Inform and train all employees on the hazardous chemicals they **MAY** encounter under normal working conditions or during an emergency situation. See the company's Hazard Communications Program on pages 8-10 of this document.

5. Conduct Crew/Leader meetings at the start of each job and at least weekly thereafter. Hold a safety discussion the first five minutes of each work shift to cover safety matters and work plans for the workday.

6. Receive and take initial action on employee suggestions, awards or disciplinary measures.

7. Train employees (new and experienced) in the safe and efficient methods of accomplishing each job or task as necessary.

8. Review accident trends and establish prevention measures.

9. Attend safety meetings and actively participate in the proceedings.

10. Participate in investigations and inspections on safety and health related matters.

11. Promote employee participation in the safety and health program.

12. Actively follow the progress of injured workers and display an interest in their rapid recovery and return to work. The Department of Labor & Industries can assist you in developing a program to effectively follow and manage injury claims.

C. **Employees.** Observe the items of responsibility established in this document as well as job safety rules which may apply to specific task assignments.

SAFETY DISCIPLINARY POLICY

One-Way Plumbing, LLC. believes that a safety and health accident prevention program is unenforceable without some type of disciplinary policy. Our company believes that in order to maintain a safe and healthy workplace that the employees must be cognizant and aware of all company, City/County, State and Federal safety and health regulations as they apply to the specific duties required. The following disciplinary policy is in effect and will be applied to all safety and health violations.

The following steps will be followed unless in the unlikely event that the seriousness of the violation would dictate going directly to Step 2 or Step 3.

1. A first violation will be discussed orally between the company supervisor and the employee. This will be done as soon as possible, after the violation occurs.

2. A second time violation will be followed up in written form and a copy of this written documentation entered into the employee's personnel folder.

3. A third time violation will result in time off or possible termination, depending upon the seriousness of the violation.

EMPLOYEE ORIENTATION CHECKLIST – SAFETY

Employee Name: _____ Date Hired: _____
Location:_____ Title:_____

This checklist is a guideline for conducting employee safety orientations for employees new to One-Way Plumbing, LLC.. Once completed and signed by both supervisor and employee, it serves as documentation the orientation has taken place.

Place a check in each box to indicate the subject has been covered:

1. Explain the company Safety Program. Including:
   A. Orientation
   B. On the job training
   C. Safety Meeting (Time and Place)
   D. Accident Investigation and reporting
   E. Function of the Safety Committee

2. Personal Protective Equipment required.
   A. Safety Glasses
   B. Hard Hat
   C. Class II High Visibility Vest
   D. Boots or shoes with a hard sole and leather uppers or rubber boots with a steel shank.
   E. Hearing Protection (when needed)
   F. Long pants that are free from tears, rips, or holes and fit snugly without restricting movement. Shirts free from tears, rips, or holes and have sleeves that at least cover the shoulder area.

3. Line of communication and responsibility for immediately reporting accidents.
   A. When to report an injury
   B. How to report an injury
   C. Who to report an injury to
   D. Filling out Accident Report forms

4. General overview of operation, procedures, methods and hazards as they relate to the specific job and duties.

5. Pertinent safety rules of the Company, City/County and Washington State Safety and Health Codes.

6. 1st-aid Supplies, equipment and training
   A. Obtaining treatment
   B. Location of 1st-aid facilities/kits
   C. Location and names of 1st-aid trained employees

7. Emergency plan.
   A. Exit locations and evacuation routes
   B. Use of fire fighting equipment (extinguishers or hoses – if requires and trained)
   C. Specific emergency procedures (medical, chemical, fire, etc.)

8. Vehicle safety.

9. Personal work habits.
   A. Serious consequences of horseplay
   B. Fighting
   C. Inattention
   D. Smoking policy
   E. Good housekeeping practices
   F. Proper lifting techniques

NOTE TO EMPLOYEES: **DO NOT SIGN UNLESS ALL** ITEMS ARE COVERED AND **ALL** QUESTIONS ARE SATISFACTORLY ANSWERED.

The signatures below document that the appropriate elements have been discussed to the satisfaction of both parties, and that both the supervisor and the employee accept responsibility for maintaining a safe and healthful work environment.

Date _____ Employee's Signature _____

Date _____ Supervisor's Signature _____

HAZARD COMMUNICATION PROGRAM

Purpose:

The purpose of the Hazard Communication Program is to ensure that the hazards of all chemicals produced or imported by chemical manufacturers or importers are evaluated, and that information concerning their hazards is transmitted to affected employers and employees before they use the products.

Procedures:

- Inventory Lists – Know the hazardous chemicals in your workplace that are a potential physical or health hazard. Make an inventory list of these hazardous chemicals; this lost must be part of your written program.

- MSDS – Make sure there is a Material Safety Data Sheet (MSDS) for each chemical and that the inventory list and labeling system reference the corresponding MSDS for each chemical.

- Labeling System – Each container entering the workplace must be properly labeled with the identity of the product, the hazardous warning, and the name and address of the manufacturer.

- Information and Training – Determine appropriate ways in which to inform and train employees on the specific chemicals in your workplace and their hazards.

- Written Program – Develop, implement and maintain a comprehensive written hazard communication program at the workplace that includes provisions for container labeling, material safety data sheets, and an employee training program.

Employees must be made aware of where hazardous chemicals are used in their work areas. They also must be informed of the requirements of the Hazardous Communications Standard, the availability and location of the written program, the list of hazardous chemicals, and the material safety data sheets.

The code specifically requires employers to train employees in the protective practices implemented in their workplace, the labeling system used, how to obtain and use MSDS's, the physical and health hazards of the chemicals, and the recognition, avoidance and prevention of accidental entrance of hazardous chemicals into the work environment.

HAZARD COMMUNICATIONS PROGRAM

For

One-Way Plumbing, LLC.

1. Company Policy

To ensure that information about the dangers of all hazardous chemicals used by the One-Way Plumbing, LLC. are known by all affected employees, the following hazardous information has been established.

All work units of the company will participate in the hazard communications program. This written program will be available in the Kirkland main office for review by any interested employee.

2. Container labeling

Jeff Gerard will verify that all containers received for use will be clearly labeled as to the contents, note the appropriate hazard warning and list the name and address of the manufacturer.

The supervisor in each section will ensure that all secondary containers are labeled with either an extra copy of the original manufacturer's label or with labels that have the identity and the appropriate hazard warning.

NOTE: ***If written alternatives to in-plant container labeling are used, add a description of the system used.***

Jeff Gerard will review the company labeling procedures every **6 months** and update as required.

3. Material Safety Data Sheets (MSDS)

Jeff Gerard is responsible for establishing and monitoring the company's MSDS program. Jeff will make sure procedures are developed to obtain the necessary MSDSs and will review incoming MSDSs for new or significant health and safety information. Jeff will see that any new information is passed on to affected employees.

MSDSs will be available to all employees during each work shift. If an MSDS is not available, immediately contact Jeff Gerard.

NOTE: ***If an alternative to printed material safety data sheets is used (such as computer data), provide a description of the format and insure employee training in the use of the system***

4. Employee training and information

Jeff Gerard is responsible for the company's employee training program. Jeff will ensure that all program elements specified below are carried out.

Prior to starting work, each new employee of One-Way Plumbing, LLC. will attend a health and safety orientation that includes the following information and training:

- An overview of the requirements contained in the Hazard Communication Standard.
- Hazardous chemicals present at his/her workplace.
- Physical and health risk of the hazardous chemical.
- The symptoms of an overexposure.
- How to determine the presence or release of hazardous chemicals in his/her work area.
- How to reduce or prevent exposure to hazardous chemicals through the use of control procedures, work practices and personal protective equipment (PPE).
- Steps the company has taken to reduce or prevent exposure to hazardous chemicals.
- Procedures to follow if employees are overexposed to hazardous chemicals.

- Location of the MSDS file and the written Hazard Communication Program.

Prior to introducing a new chemical hazard into any section of this company, each employee in that section will be given information and training as outlined above for the new chemical hazard.

5. Hazardous non-routine tasks

Periodically, employees are required to perform hazardous non-routine tasks. Some examples of non-routine tasks are: Confine space entry, tank cleaning and painting reactor vessels. Prior to starting work on projects, each affected employee will be given information by the manager about the hazardous chemicals he or she may encounter during such activity. This information will include specific chemical hazards, protective and safety measures the employee can use, and steps the company is using to reduce the hazards, including ventilation, respirators, presence of another employee and emergency procedures.

6. Multi-employer workplaces

It is the responsibility of Jeff Gerard to provide employees of any other employer at the work site copies of MSDSs (or make them available at a central location) for any hazardous chemicals that the employer(s)' employees may be exposed to while working on the site. Jeff Gerard will also inform other employers of any precautionary measures that need to be taken to protect employees during normal operating conditions or in foreseeable emergencies, and provide other employers with an explanation of the labeling system used at the work site.

7. List of hazardous chemicals

The following is a list of all known hazardous chemicals used by our employees. Further information on each chemical may be obtained by reviewing MSDSs located at the Kirkland shop as well as all job-shacks.

NOTE: See page 11 for the Master List of Chemicals.

Master List of Chemicals

TAB	CHEMICAL NAME	MANUFACTURER'S NAME
A	ABS BLACK CEMENT	OATEY
B	SILICONE SEALANT	POLYSEAMSEAL
C	PVC RAIN-R-SHINE BLUE CEMENT	OATEY
D	PVC PIPE FITTING COVERS & JACKETING	JOHNS MANVILLE
E	PVC MEDIUM CLEAR OR GRAY CEMENT	OATEY
F	PLUMBERS PUTTY	OATEY
G	PURPLE OR CLEAR PRIMER	OATEY
H	GREAT WHITE PIPE JOINT COMPOUND	OATEY
I	PVC HEAVY DUTY CLEAR OR GRAY CEMENT	OATEY
J	FLUX-RITE 90 PASTE	LA-CO INDUSTRIES
K	CPVC FLOWGUARD GOLD CEMENT 1-STEP	OATEY
L	DARK THREAD CUTTING OIL	OATEY
M	CAULK, TUB & TILE ADHEISIVE, WHITE	POLYSEAMSEAL
N	CAULK, TUB & TILE ADHEISIVE, CLEAR	POLYSEAMSEAL
O	ALL PURPOSE CEMENT	OATEY
P	STERLING LEAD-FREE SOLDER	LENOX
Q	FIRE STOP	3M

EMPLOYEE ORIENTATION CHECKLIST – HAZARDOUS SUBSTANCES

Employee Name _____ Title_____

Division _____ Date Hired _____

This checklist is to inform employees of the One-Way Plumbing, LLC. Hazard communication Program. Place a check in each box to indicate that the subject has been covered.

The supervisor has reviewed the following Hazard Communication Program information with me.

1. The purpose of the Hazard Communication Standard is to require chemical manufacturers or importers to assess the hazards of chemicals they produce or import. All employers must provide information to their employees about the hazardous chemicals to which they may be exposed.

   Employees must be informed about the hazard communication program; labeling and other forms of warning, Material Safety Data Sheets (MSDSs), and they must have training (before exposure) on the hazardous substances they may encounter.

2. The supervisor has reviewed the Master List of Chemicals with me.

3. The supervisor has shown the employee the:

   A. Location of hazardous chemicals within the employee's work site.

   B. Location of the written Hazard Communication Program.

   C. Location of the Material Safety Data Sheets for all hazardous chemicals in my assigned work area.

   D. Location of the list of persons trained and authorized to handle the hazardous chemicals.

The signatures below document that the appropriate elements have been discussed to the satisfaction of both the supervisor and employee and that both the supervisor and the employee are responsible for maintaining a safe and healthful work environment.

Date _____ Employee's Signature _____

Date _____ Supervisor's Signature _____

NOTE TO SUPERVISORS: If this employee is expected to actually handle chemicals please notify Jeff Gerard for training before the employee begins actual work with the chemicals.

EMPLOYEE RESPONSIBILITY

A. Report all on the job injuries promptly.

B Report all equipment damage to your supervisor immediately.

C. Don't take chances – use your safety equipment as directed.

D. Follow instructions – ask questions of your supervisor when in doubt about any phase of your operation.

E. Observe and comply with all safety signs and regulations.

F. Report all unsafe conditions or situations that are potentially hazardous.

G. Operate only equipment you are trained and authorized to operate. When in doubt, ash for directions.

H. Talk to management at any reasonable time about problems that affect your safety or work conditions.

The most important part of this program is the individual employee – **YOU!!** Without your cooperation, the most stringent program will be ineffective. Protect yourself and your fellow workers by following the rules. REMEMBER: Work safely so you can go home to your family and friends - they need you.

Don't take chances - SAFETY FIRST

THINK!!!!

PERSONAL WORK RULES

1. Report every injury, no matter how slight, to your supervisor.

2. Horseplay, fighting, gambling, possession of firearms and possession or use of alcoholic beverages or drugs (except as prescribed by a qualified physician) is strictly forbidden.

3. Running on any construction site it strictly prohibited except in extreme emergencies.

4. Wear clothing suitable for the weather and your work. Torn, loose clothing, cuffs, sleeves, etc. are hazardous and could cause accidents.

5. Jewelry (rings, bracelets, neck chains, etc.) should not be worn while working.

6. Hard hats, safety glasses and high visibility vests must be worn in all required areas.

7. Proper eye protection must be worn where you are exposed to flying objects, dust, harmful rays, chemicals, flying particles, etc.

8. Proper foot wear must be worn on all construction sites; safety boots are highly recommended. The wearing of sport shoes, sandals, dress shoes and similar footwear is strictly prohibited.

9. Always use gloves, aprons or other protective clothing when handling rough materials, chemicals, and hot or cold objects.

10. When spray painting, finish spraying, burning, exposed to large quantities of dust, or to other toxic hazards, always wear the correct respirator as required

Special safety equipment is for your protection. Use it when required. Keep it in good condition and report loss or damage of it to your supervisor immediately.

GENERAL SAFETY RULES

1. Always store materials in a safe manner. Tie down or support piles if necessary to prevent falling, rolling or shifting.

2. Shavings, dust, scraps, oil or grease should not be allowed to accumulate. Good housekeeping is a part of your job.

3. Refuse piles must be removed as soon as possible. Refuse is a safety and fire hazard.

4. Remove or clinch nails in lumber that has been used or removed from a structure.

5. Immediately remove all loose materials from stairs, walkways, ramps, platforms, etc.

6. Do not block aisles, traffic lanes, fire exits, gangways or stairs

7. Avoid shortcuts – use ramps, stairs, walkways, ladders, etc.

8. Standard guardrails must be erected around all floor openings and excavations must be barricaded. Contact your supervisor for the correct specifications.

9. Get help with heavy or bulky material to avoid injury to you or damage to material.

10. Keep all tools and materials away from the edges of scaffolding, platforms, shaft openings, etc.

11. Do not use tools with split, broken or loose handles, and burred or mushroomed heads. Keep cutting tools sharp and carry all tools in a container.

12. Know the correct use of hand and power tools. **Use the right tool for the job.**

13. All electric power tools (unless double insulated), extension cords and equipment shall be properly grounded.

14. All electric power tools and extension cords shall be properly insulated. Damaged cords shall be **replaced**.

15. Know the location and use of fire extinguishing equipment and the procedure for sounding a fire
16. alarm.

17. Flammable liquids shall be used only in small amounts at the job location and in approved safety cans.

18. Proper guards or shields must be installed on all power tools before use. Do not use any tools without the guards in their proper working condition. No “homemade” handles or extensions “cheaters” will be used.

19. Do not operate any power tool or equipment unless you are trained in its operation and authorized by your company to do so.

20. Use tools only for their designed purpose.

21. Do not remove, deface or destroy any warning, danger sign or barricade, or interfere with any form of accident prevention device or practice provided for your use or which other workmen are using.

22. All electric power equipment and must be grounded or double insulated.

LADDERS/TRAINING

1. General

a. Inspect before use for physical defects.

b. Ladders are not to be painted except for numbering purposes.

c. Do not use ladders for skids, braces, workbenches or any purpose other than climbing.

d. When you are ascending or descending a ladder, do not carry objects that will prevent you from grasping the ladder with both hands.

e. Always face the ladder when ascending or descending.

f. If you must place a ladder over a doorway, barricade the door to prevent its use and post a warning sign.

g. Only one person is allowed on a ladder at a time.

h. Always keep both feet on the ladder rungs. Do not step laterally from a ladder onto another object.

i. Do not jump from al adder when descending.

j. All joints between steps, rungs and side rails shall be tight.

k. Safety feet shall be in good order and in place.

l. Rungs shall be free of grease and/or oil.

2. Straight Type or Extension Ladders

a. All straight or extension ladders must extend at least three feet beyond the supporting object when used as an access to an elevated work area.

b. After rising the extension portion of a two or more stage ladder to the desired height, check to ensure that the safety dogs or latches are engaged.

c. All extension or straight ladders must be secured or tied off at the top.

d. All ladders must be equipped with safety (non-skid) feet.

e. Portable ladders shall be used at such a pitch that the horizontal distance from the top support to the foot of the ladder is about ¼ of the working length of the ladder.

LADDERS/TRAINING (cont.)

3. Step ladders

a. Do not place tools or materials on the steps or platform of a stepladder.

b. Do not use the top two steps or cap of a stepladder as a step or stand.

c. Always level all four feet and lock the spreaders in place.

d. Do not use a stepladder as a straight ladder.

4. **Storage and Transportation of Ladders**

a. Store ladders in a manner that provides easy access for inspection and permits safe withdrawal for use. Ladders must not be stored where they present a tripping hazard, nor where they can fall on personnel. When stored horizontally, ladders should be supported at several points to avoid sagging. The ladders should be kept away from sources of heat and moisture and in a well-ventilated area. Aluminum ladders should not be stored in certain atmospheres (e.g., acidic) due to severe corrosion problems. Ultraviolet rays of the sun can cause deterioration in fiber-glass ladders. Wax fiber-glass ladders with paste wax for extended storage and increased life span of use.

b. Assistance may be needed in transporting heavy or long ladders. When transported on vehicles, ladders should be adequately supported (preferably on hardwood or rubber-covered pipe) to avoid sagging and should be fastened securely.

For other rules and regulations regarding ladders, see Part J, Chapter 155 Washington State Department of Labor and Industries, Division or Industrial Safety and Health Construction Safety Standards.

SCAFFOLDING SAFETY RULES

1. General ***(only qualified and authorized persons may assemble/disassemble scaffolds and must be under the supervision of a competent person).***

   Before starting work on a scaffold, inspect it for the following:

   a. Are guardrails, toe boards and planking in place and secure?

   b. Are locking pins at each joint in place?

   c. Are all wheels on movable scaffolds locked?

2. Do not attempt to gain access to a scaffold by climbing on it (unless it is specifically designed for climbing) – always use a ladder.

3. Scaffolds and their components shall be capable of supporting 4 times the maximum intended load.

4. Any scaffold including accessories such as braces, brackets, trusses, screw legs, ladders, etc. damaged or weakened in any way, shall be immediately repaired or replaced.

5. Scaffold planks shall extend over their end supports not less than 6 inches or more than 12 inches, unless otherwise specifically required.

6. Scaffold platforms shall not be less than 18 inches wide unless otherwise specifically required or exempted.

7. Where persons are required to work or pass under the scaffold, scaffolds shall be provided with a screen between the toe board and guardrail, extending along the entire opening, of No. 18 gauge U.S. Standard wire ½ inch mesh or equivalent protection.

8. All scaffolding must be erected level, plumb and on a solid footing.

9. Do not change or remove scaffold members unless authorized.

10. Do not allow workmen to ride on a rolling scaffold when it is being moved. Remove or secure all materials and tools on the deck before moving.

11. Do not alter any scaffold member by welding, burning, cutting, drilling or bending.

    For other rules and regulations regarding scaffolds, see Part J-1, Washington State Department of Labor and Industries, Division on Industrial Safety and Health Construction Safety Standards.

MOTORIZED VEHICLES and EQUIPMENT

1. Do not ride on motorized vehicles or equipment unless a proper seat is provided for each rider.

2. Always be seated when riding authorized vehicles (unless they are designed for standing).

3. Do not operate any motorized vehicle or equipment unless you are trained and specifically authorized to do so by your foreman or supervisor.

4. Always use your seat belt in the correct manner.

5. Obey all speed limits and other traffic regulations.

6. Always be aware of pedestrians and give them the right-of-way.

7. Always inspect your vehicle or equipment before and after daily use.

8. Never mount or dismount vehicles or equipment while they are still in motion.

9. Do not dismount any vehicle without first shutting down the engine, setting the parking brake and securing the load.

10. Do not allow other persons to ride the hook or block, dump box, forks, bucket, or shovel of any equipment.

11. Each operator must be knowledgeable of all hand signals and obey them.

12. Each operator is responsible for the stability and security of their load.

13. Do not talk on your cellular phone while operating a motorized vehicle unless you are using a hands free device. Pull off to the side of the road or return the call after you have stopped your vehicle.

    For other rules and regulations regarding Motor Vehicles and Mechanized Equipment, see Part M, Chapter 155, Washington State Department of Labor and Industries, Division of Industrial Safety and Health Construction Safety Standards.

TRENCHING and EXCAVATING

1. The determination of the angle of repose and design of the supporting system shall be based on careful evaluation of pertinent factors such as:

   a. Depth and/or cut/soils classification.

   b. Possible variation in water content of the material while excavation is open.

   c. Anticipated changes in materials from exposure to air, sun, water or freezing.

   d. Loading imposed by structures, equipment, overlaying material or stored material.

   e. Vibration from equipment, blasting, traffic or other sources.

2. Walkways or bridges with standard railings shall be provided when employees or equipment are required to cross over excavations.

3. The walls and faces of all excavations in which employees are exposed to danger from moving ground shall be guarded by a shoring system, sloping of the ground or some other equivalent means.

4. No person shall be permitted under loads handled by power shovels, derricks or hoists.

5. All employees shall be protected with personal protective equipment for the protection of the head, eyes, respiratory system, hands feet and other parts of the body.

For other rules and regulations regarding Trenching and Excavating, see Part N, Chapter 155, Washington State Department of Labor and Industries, Division of Industrial Safety and Health Construction Safety Standards.

1ST-AID TRAINING, KITS, and POSTER

Purpose: To afford the employees immediate and effective medical attention should an injury result. Jeff Gerard will ensure that an employee trained in 1st-aid will be available.

1. To meet the above objectives, the following procedures will be followed:

   a. All supervisors or persons in charge of crews will be 1st-aid trained unless their duties require them to be away from the job site, whereby other persons will be designated as the 1st-aid trained person.

   b. Other persons will be trained as designated by management in order to augment or surpass the standard requirements.

   c. Valid 1st-aid cards are recognized as ones which include **both** 1st-aid and cardiopulmonary resuscitation (CPR) and have not reached the expiration date.

2. First aid kits will be in accordance with the requirements of WAC 296-155-125.

   a. 1st-aid kits will be located at the following locations:

      1) Company office
      2) One-Way Plumbing, LLC. trucks
      3) All site job shacks

   b. Jeff Gerard is designated to ensure that the 1st-aid kits are properly maintained and stocked.

3. Posters listing emergency numbers, procedures, etc. will be strategically located, such as on the 1st-aid kits, at the telephones, etc.

   NOTE: If cell phones are used to report emergencies, be sure to tell the operator your location.

1ST-AID PROCEDURES in CONSTRUCTION
(Blood borne Pathogens Program)

We have 1st-aid trained workers here but we do not have "designated" 1st-aiders. 1st-aid at the job site is done on a Good Samaritan basis.

If 1st-aid trained employees are involved in a situation involving blood, they should:

1. Avoid skin contact with blood/OPIM (other potentially infectious materials) by letting the victim help as much as possible, and using gloves provided in the 1st-aid kit.

2. Remove clothing, etc. with blood on it after rendering help.

3. Wash thoroughly with soap and water to remove blood. A 10% chlorine bleach solution is good for disinfecting areas contaminated with blood (spills, etc.).

4. Report such 1st-aid incidents immediately to your supervisor (time, date, blood presence, exposure and the names of people helping).

The company should provide full Hepatitis B vaccinations as soon as possible but not later than 24 hours after the incident.

If an exposure incident occurs, the company should make available immediately, appropriate:

A. Post exposure evaluation

B. Follow-up treatment

C. Follow-up as listed in the Center for Disease Control (CDC) guidelines

Training covering the above information should be covered as job site safety meetings.

PROCEDURES for INJURY or ILLNESS ON THE JOB

A. **Owner or Supervisor immediately takes charge.**

1. Call 911 EMS.
2. Render Good Samaritan 1st-aid.
3. Arrange for transportation (ambulance, helicopter, company vehicle, etc.), depending on the seriousness of the injuries.
4. Notify top management (if not already present).
5. Do not move anything unless necessary (to administer 1st-aid), pending an investigation of the accident.
6. Accompany or take the injured person to doctor, hospital, home, etc. (depending on the extent of the injuries).
7. Take injured to family doctor if available.
8. Remain with the injured person until relieved.
9. When the injured person's immediate families is known by the management or supervisor, they should be notified, preferably in person or have an appropriate person do so.

B. **Documentation**

1. Minor injuries (requiring doctor/outpatient care). After the emergency actions following an accident, the immediate supervisor and the safety committee or safety officer (as appropriate) will conduct an investigation of the accident. The findings shall be documented on our accident report form.
2. Major injuries (fatality or multiple hospitalizations). Top management must see that the **Department Of Labor and Industries is notified within 8 hours by calling : (425) 290-1404 or 1-800-423-7233.**
   They will then assist the Department in the ensuing investigation.

C. **Near Misses**

1. All near misses (close calls) shall be investigated.
2. Document findings on company Accident Report form.
3. Review findings at weekly/monthly safety meetings (sooner if the situation warrants).

SAFETY BULLETIN BOARD

A. **Purpose:** To increase employee's safety awareness and convey the company's safety message. If a proper place can be found for a bulletin board, this is a good tool.

B. **The following items are required to be posted:**

1. WISHA poster F416-081-00 (Required)
2. Industrial Insurance poster (Required)
3. NOTICE (to report all injuries) (Recommended)
4. Citation and Notice (As appropriate)
5. Emergency Telephone Numbers (As appropriate)
6. OSHA 300A Log (Required during February of each year)

C. **Suggested Items:**

1. Safety posters (hard hats, eye/ear protection, proper shoes, etc.)
2. Weekly site safety meeting minutes and company safety committee meeting minutes
3. Pertinent safety items (new policies, information on new equipment, etc.)

How to "Hold a GOOD Safety Meeting"

1. Be certain everyone knows the time and location of the next meeting.

2. Insist that everyone attend. Before the next meeting, remind those that were late or failed to attend that ***attendance is not an option.***

3. Pick an appropriate topic (something that you will be dealing with).

4. Start the meeting **ON TIME** (respect the people that are on time).

5. Don't waste time – give the meeting your undivided attention.

6. Discuss the topic you have chosen and prepared. Don't wait until the meeting to choose your topic.

7. Use handouts or posters to illustrate your topic.

8. Discuss current job safety events, accidents and close calls.

9. Encourage employees to discuss safety problems as they arise. Do not save safety concerns for the meetings. Allow some time for employee questions or input at the end of the meeting.

10. Invite managers or owners to speak. Ask fellow employees to speak on a safety topic.

11. If you prevented one accident, it is time well spent. Your topic may be one that some employees have hears many times, but there may be one person who is new or has never been told of the safety requirements for the topic. Repeating topics several times during the course of a project is beneficial as long as it applies to the work being done.

12. Follow up on employee concerns or questions and get back to them with the answer before the next meeting.

13. Be certain to document the attendance and the topic discussed.

14. Ensure that the discussion is on safety issues **NOT** of personnel issues.

CREW LEADER SAFETY MEETINGS

We believe that there is no magic formula for the prevention of accidents – hard work and perseverance are required, with the crew leader being the key to a successful result.

A. **Purpose:** To assist in the detection and elimination of unsafe conditions and work procedures.

B. **Weekly meetings:**

These meetings should be held in accordance with various circumstances involved or when necessity dictates. No set pattern will suit all cases. It is important, however, that the leader talk daily on accident prevention and immediately on witnessing an unsafe act.

a. Safety meetings shall be held at the start of each job and at least weekly thereafter.
b. The attendance and subjects discussed shall be documented and maintained for 1 year.
c. Copies of the minutes should be made available to the employees by posting or other means.

C. **Scope of Activities:** (certain employees as may be designated by their supervisor will assist)

1. Conduct in-house safety inspections with supervisor concerned.
2. Accident investigation to uncover trends
3. Review accident reports to determine means of elimination.
4. Accept and evaluate employee suggestions.
5. Review jobs procedures and recommended improvements.
6. Monitor the safety program effectiveness.
7. Promote and publicize safety.

D. **Documentation:** Weekly safety meetings will be documented on copies of Crew/Leader Safety Meeting Documentation form (found in the Appendices to this program).

EMERGENCY PROCEDURES (Medical, Fire, Chemical)

1. **Medical Emergency:** In the event of a medical emergency we will treat to level of our 1st-aid training and call **911**, if necessary.

1. **Fire Emergency:** In the event of a fire emergency we will evacuate the building, rally at a predetermined point, and call **911.**

3. **Chemical Emergency:** In the event of a chemical emergency we will follow the instructions/directions on the Material Safety Data Sheet (MSDS) and call **911**, if necessary.

Fire Prevention & Protection Policy

(1) General

(a) One Way Plumbing, LLC shall be responsible for development of a fire protection program to be followed throughout all phases of construction and demolition work, and One Way Plumbing, LLC shall provide for fire fighting equipment as specified in this part. As fire hazards occur, there shall be no delay in providing necessary equipment.

(b) Access to all available fire fighting equipment shall be maintained at all times.

(c) All fire fighting equipment, provided by the employer, shall be conspicuously located.

(d) All fire fighting equipment shall be periodically inspected by a competent person, and maintained in operating condition. Defective equipment shall be immediately replaced.

(e) As warranted by the project, the employer shall provide a trained and equipped fire fighting organization (fire brigade) to assure adequate protection to life.

(2) Water supply.

(a) A temporary or permanent water supply, of sufficient volume, duration, and pressure, required to properly operate fire fighting equipment shall be made available as soon as combustible materials accumulate.

(b) Where underground water mains are to be provided, they shall be installed, completed, and made available for use as soon as practicable.

(3) Portable fire fighting equipment.

(a) A fire extinguisher, rated not less than 2A, shall be provided for each 3,000 square feet of a combustible building area, or major fraction thereof. Travel distance from any point of the protected area to the nearest fire extinguisher shall not exceed a horizontal distance of 100 feet.

(c) One or more fire extinguishers, rated not less than 2A, shall be provided on each floor. In multistory buildings, where combustibles are present, at least one fire extinguisher shall be located adjacent to a stairway.

(d) Extinguishers subject to freezing shall be protected from freezing.

(e) A fire extinguisher, rated not less than 10B, shall be provided within 50 feet of wherever more than 5 gallons of flammable or combustible liquids or 5 pounds of flammable gas are being used on the jobsite. This requirement does not apply to the integral fuel tanks of motor vehicles.

(f) Carbon tetrachloride and other toxic vaporizing liquid fire extinguishers are prohibited.

(g) Portable fire extinguishers shall be inspected periodically and maintained in accordance with Maintenance and Use of Portable Fire Extinguishers, NFPA No. 10A-1981 and WAC 296-800-300.

(h) Fire extinguishers which have been listed or approved by a nationally recognized testing laboratory, shall be used to meet the requirements of this part. (See Table D-1)

	YES	YES	YES	YES	YES	NO	NO	NO	YES	YES
B	NO	NO	NO	NO	YES	YES	YES	YES	YES	YES
C	NO	NO	NO	NO	NO	YES	YES	YES	YES	YES
	SPECIAL EXTINGUISHING AGENTS APPROVED BY RECOGNIZED TESTING LABORATORIES									

Note: One hundred feet, or less, of 1-1/2 inch hose, with a nozzle capable of discharging water at 25 gallons or more per minute, may be substituted for a fire extinguisher rated not more than 2A in the designated area provided that the hose line can reach all points in the area.

(i) If fire hose connections are not compatible with local fire fighting equipment, the contractor shall provide adapters, or equivalent, to permit connections.

(j) During demolition involving combustible materials, charged hose lines, supplied by hydrants, water tank trucks with pumps, or equivalent, shall be made available.

(4) Fixed fire fighting equipment.

(a) Sprinkler protection.

(i) If the facility being constructed includes the installation of automatic sprinkler protection, the installation shall closely follow the construction and be placed in service as soon as applicable laws permit following completion of each story.

(ii) During demolition or alterations, existing automatic sprinkler installations shall be retained in service as long as reasonable. The operation of sprinkler control valves shall be permitted only by properly authorized persons.

Note: Modification of sprinkler systems to permit alterations or additional demolition should be expedited so that the automatic protection may be returned to service as quickly as possible. Sprinkler control valves shall be checked daily at close of work to ascertain that the protection is in service.

(b) Standpipes. In all structures in which standpipes are required, or where standpipes exist in structures being altered, they shall be brought up as soon as applicable laws permit, and shall be maintained as construction progresses in such a manner that they are always ready for fire protection use. The standpipes shall be provided with Siamese fire department connections on the outside of the structure, at the street level, which shall be conspicuously marked. There shall be at least one standard hose outlet at each floor.

(5) Fire alarm devices.

(a) An alarm system, e.g., telephone system, siren, etc., shall be established by the employer whereby employees on the site and the local fire department can be alerted for an emergency.

(b) The alarm code and reporting instructions shall be conspicuously posted at phones and at employee entrances.

(6) Fire cutoffs.

(a) Fire walls and exit stairways, required for the completed buildings, shall be given construction priority. Fire doors, with automatic closing devices, shall be hung on openings as soon as practical.

(b) Fire cutoffs shall be retained in buildings undergoing alterations or demolition until operations necessitate their removal.

Fire prevention.

(1) Ignition hazards.

(a) Electrical wiring and equipment for light, heat, or power purposes shall be installed in compliance with the requirements of Part I of this standard.

(b) Internal combustion engine powered equipment shall be so located that exhausts are well away from combustible materials. When exhausts are piped to outside the building under construction, a clearance of at least 6 inches shall be maintained between such piping and combustible material.

(c) Smoking shall be prohibited at or in the vicinity of operations which constitute a fire hazard, and shall be conspicuously posted: “No smoking or open flame.”

(d) Portable battery powered lighting equipment, used in connection with the storage, handling, or use of flammable gases or liquids, shall be of the type approved for the hazardous locations.

(e) The nozzle of air, inert gas, and steam lines or hoses, when used in the cleaning or ventilation of tanks and vessels that contain hazardous concentrations of flammable gases or vapors, shall be bonded to the tank or vessel shell. Bonding devices shall not be attached or detached in hazardous concentrations of flammable gases or vapors.

(f) Workers shall not take open lights or open flames near or in an open sewer manhole, gas main, conduit or other similar place until the absence of explosive or harmful gases has been assured.

Open lights or flames shall not be carried into areas and enclosures where flammable vapors or exposed low flash point solvents exist. Only approved and suitable protected lights shall be used.

(2) Temporary buildings.

(a) No temporary building shall be erected where it will adversely affect any means of exit.

(b) Temporary buildings, when located within another building or structure, shall be of either noncombustible construction or of combustible construction having a fire resistance of not less than 1 hour.

(c) Temporary buildings, located other than inside another building and not used for the storage, handling, or use of flammable or combustible liquids, flammable gases, explosives, or blasting agents, or similar hazardous occupancies, shall be located at a distance of not less than 10 feet from another building or

structure. Groups of temporary buildings, not exceeding 2,000 square feet in aggregate, shall, for the purpose of this part, be considered a single temporary building.

(3) Open yard storage.

(a) Combustible materials shall be piled with due regard to the stability of piles and in no case higher than 20 feet.

(b) Driveways between and around combustible storage piles shall be at least 15 feet wide and maintained free from accumulation of rubbish, equipment, or other articles or materials. Driveways shall be so spaced that a maximum grid system unit of 50 feet by 150 feet is produced.

(c) The entire storage site shall be kept free from accumulation of unnecessary combustible materials. Weeds and grass shall be kept down and a regular procedure provided for the periodic cleanup of the entire area.

(d) When there is a danger of an underground fire, that land shall not be used for combustible or flammable storage.

(e) Method of piling shall be solid wherever possible and in orderly and regular piles. No combustible material shall be stored outdoors within 10 feet of a building or structure.

(f) Portable fire extinguishing equipment, suitable for the fire hazard involved, shall be provided at convenient, conspicuously accessible locations in the yard area. Portable fire extinguishers, rated not less than 2A, shall be placed so that maximum travel distance to the nearest unit shall not exceed 100 feet.

(4) Indoor storage.

(a) Storage shall not obstruct, or adversely affect, means of exit.

(b) All materials shall be stored, handled, and piled with due regard to their fire characteristics.

(c) Noncompatible materials, which may create a fire hazard, shall be segregated by a barrier having a fire resistance of at least 1 hour.

(d) Material shall be piled to minimize the spread of fire internally and to permit convenient access for firefighting. Stable piling shall be maintained at all times. Aisle space shall be maintained to safely accommodate the widest vehicle that may be used within the building for fire- fighting purposes.

(e) Clearance of at least 36 inches shall be maintained between the top level of the stored material and the sprinkler deflectors.

(f) Clearance shall be maintained around lights and heating units to prevent ignition of combustible materials.

(g) A clearance of 24 inches shall be maintained around the path of travel of fire doors unless a barricade is provided, in which case no clearance is needed. Material shall not be stored within 36 inches of a fire door opening.

APPENDICES

The following Forms and Guides are intended to help us comply with the WISHA requirements for documentation of certain activities.

A.	OSHA 300 Log (record keeping information)	33
B.	Basic Rules for Accident Investigation	34
C.	Supervisor's Report of an Accident Form	35
D.	Employee's Report of an Accident Form	36
E.	Crew Leader Safety Meeting Documentation Form	37
F.	Weekly Safety and Health Inspection Form	38-39
G.	Barometer of Safety Attitudes – Construction Self-Inspection	40-41
H.	Equipment Safety Inspection Checklist	42-43
I.	Job Safety Analysis Worksheet	44
J.	Fall Protection Program Information	45-47
K.	Fall Protection Work Plan	48-49
L.	Heat-Related Illness Policy	50-52
M.	Hearing Loss Prevention	53
N.	Personal Protection Equipment Form	54-56
O.	Jobsite Hazard Analysis	57-59
P.	Forklift Safety Plan	60-63
Q.	Aerial Lift Plan	64-66

OCCUPATIONAL INJURY and ILLNESS RECORDKEEPING

A. **Purpose:** In accordance with applicable requirements of the WISHA standards, each location of One-Way Plumbing, LLC. will ensure that the appropriate records are kept as follows:

1. Maintain a Log and Summary of Occupational Injuries and Illnesses on OSHA form 300. Recordable Cases include:
   a. Every occupational death
   b. Every occupational illness
   c. Every occupational injury that involves:
      (1) Unconsciousness
      (2) Inability to perform all phases of the regular job
      (3) Inability to work full-time on a regular job
      (4) Temporary assignment(s) to another job
      (5) Medical treatment ***OTHER*** than 1st-aid

2. Keep copies of all reports generated when an employee is injured on the job.

3. During the month of February, post the completed Summary portion of the OSHA 300 form from the previous year.

4. Maintain records for 5 years following the year to which they relate.

5. Enter each recordable injury or illness on the job as early as practical, but no later than 6 working days after receiving the information that a recordable case has occurred.

6. In addition to the OSHA 300, a supplementary record for each occupational injury or illness will be maintained. Other reports, such as worker compensation forms, are acceptable, if they contain the information required to fill out the OSHA 300.

B. **Responsibility:** Jeff Gerard is responsible for maintaining records and ensuring that the OSHA 300 Log is properly posted.

BASIC RULES for ACCIDENT INVESTIGATION

The purpose of an investigation is to find the **cause** of an accident and **prevent** future occurrences, **NOT** to fix blame. An unbiased approach is necessary to obtain objective findings.

Visit the accident scene as soon as possible – while facts are fresh and before witnesses **forget** important details.

If possible, interview the injured worker at the scene of the accident and "walk" him/her through a re-enactment. Be careful not to actually repeat the act that caused the injury.

All interviews should be conducted as privately as possible. Interview witnesses one at a time (try to keep witnesses from talking to each other before you interview them). Talk with anyone who has knowledge of the accident, even if they did nor actually witness the mishap.

Consider taking signed statements in cases where facts are unclear or there is an element of controversy.

Graphically document details of the accident; area, tools, and equipment. Use sketches, diagrams and photos as needed, and take measurements when appropriate.

Focus on causes and hazards. Develop an analysis of what happened and how it could have been prevented. Determine what caused the accident itself, not just the injury.

How will you prevent such accidents in the future? Every investigation should include an action plan.

If a third party of defective product contributed to the accident, save any evidence. It could be critical to the recovery of the claim costs.

Supervisor's Report of an Accident

Supervisor's name: _____
Date: _____ Exact time reported to you _____
Injured employee's name: _____
Who reported it? _____
Names of witnesses: _____
Describe the accident: _____
_____
_____
_____
_____
_____
Was 1st-aid required? _____
Did the accident require a doctor's treatment? _____
Date and time of the next doctor's appointment: _____
Was this employee competent and skillful in his/her job? _____
What were the causes? _____
_____
_____
_____
_____
_____
_____
_____
Will this be a time-loss case? _____
If so, was the employee instructed to keep the company informed of his/her progress?_____
If not, why? _____
Has this employee had other industrial injuries? _____ How many? _____
EXPLAIN IN DETAIL: What part of the body was injured: _____
_____
_____
Other details of the accident: _____
_____
_____
_____
_____
Supervisor's signature: _____ Date: _____

Employee's Report of an Accident

(To be filled out for all occupational injuries or illnesses)

Employee's name: _____
Job Title: _____
Exact time of injury; _____ Date of Injury; _____
Plant location where injury occurred: _____
Name of person to whom this accident was reported: _____
Names of witnesses: _____
Summarize what you think happened: _____
_____
_____
_____
_____
_____
What could have been done to avoid the accident? _____
_____
_____
_____
_____
_____
_____
Is this an original injury or a re-injury? _____
If a re-injury, when and where was the previous injury? _____
Who was the employer?_____ Claim # _____
Would you be willing to perform light duty work during your recovery? _____
Date and time you sought medical attention: _____
Whom did you see? _____ Date: _____

Employee's Signature: _____ Date _____

This form is to be returned to your employer as soon as possible.

Date employer receiver report: _____
NOTE: Washington Administrative Code number 296-24-025-(6) states: Employee's responsibility: "Employees shall make a prompt report to their immediate supervisor of each individual injury".

CREW LEADER SAFETY MEETING

Firm Name _____ Address _____

Date _____ Time _____ # of Employees _____

Subjects Discussed

MINUTES:_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

_____

Crew Leader Comments: _____

_____

_____

_____

Weekly Safety and Health Inspection Check List

One-Way Plumbing, LLC._____ Date: _____

This format is intended only as a reminder to look for unsafe practices, accidents, potential and/or near-miss accidents, and then report them to the Safety Committee.

(S) *Indicates satisfactory* **(U) indicates** *unsatisfactory*

Date of inspection / Walk around												
Machinery												
Point of Operation Guard												
Belts, pulleys, gears, shafts, etc.												
Oiling, cleaning, and adjusting												
Maintenance and oil leaks												
Pressure equipment												
Steam equipment												
Air receivers and Compressors												
Gas cylinders and hoses												
Unsafe Practices												
Excessive speed of vehicles												
Improper lifting												
Smoking in dangerous areas												
Horseplay												
Running in aisles or on stairs												
Improper use of air hoses												
Removing machine or other guards												
Working under suspended loads												
Working on machine while in motion												
1st-aid												
1st-aid kits and rooms												
Stretchers and/or Fire blankets												
Emergency showers												
Emergency Eyewash stations												
All injuries and illnesses reported												
Hazard Communications												
Acids and caustics												
Solvents												
Dusts, vapors, or fumes												
Radiation												
New chemicals / processes												
(date of inspection / walk around)												

Tools												
Power tools, wiring, and grounding												
Hand tools (condition)												
Powder actuated tools												
Use and care of tools												
Personal Protective Equipment												
Goggles or face shield												
Safety shoes												
Hard hat												
Gloves												
Respirator												
Protective clothing												
Fire Protection												
Portable fire extinguishers (fully charged and inspected)												
Standpipes, hoses, sprinkler heads, and valves												
Exits, stairs, and signs												
Storage of flammable materials												
Materials handling equipment												
Ladders and scaffolds												
Power trucks and hand trucks												
Elevators												
Cranes and hoists												
Conveyors												
Cables, ropes, chains, slings												
Housekeeping												
Aisles, stairs, and floors												
Storage and piling of material												
Wash and locker rooms												
Light and ventilation												
Disposal of waste												
Yards and parking lots												
Bulletin Boards												
Only safety and health materials posted												
Neat and attractive												
Display regularly changed												
Well illuminated												

BAROMETER OF SAFETY ATTITUDES
CONSTRUCTION SELF INSPECTION GUIDE

Power lines: Minimum 10' clearance / insulate – de-energize, under 50kw; over 50kw refer to Chapter 155 of the WACs.

Trench / excavation: Any trench 4 feet or more (in depth) must be sloped, shored or braced.

Guardrails: Any opening 4 feet or more above the ground (or next working level) must be guarded.

Standard guardrail: Top rail =39" to 45" above working surface, Mid-rail = 18" with a toe board

Scaffold / guard rail: Fully planked

Flight of stairs: Four or more risers – must have handrails

Fall protection: Any exposure to the hazard of falling from elevations of 10' or greater must be eliminated by the use of safety harness/belt, lanyard or lifeline, horizontal lines, or cantinary lines. Positive fall protection must be utilized at all times.

Open belts and pulleys, chains and sprockets, and points of operation must be guarded to prevent accidental contact. Air compressors and electric motor pulleys are the most common hazards.

Radial saws: Cutting head must return easily to start position when released; Blade must not extend past the edge of the work table; off/on switch should be at front of operator's position

Table saw: Upper hood guard; anti-kickback, push stick, belt, pulley

Circular saws: Blade guard instantly returns to covering position

Never wedge or pin a guard

Chain saw: Ballistic nylon leg protection; eye, ear, face protection; hard hat

Angle grinder: 180 degree guard required

Ladders: Extend 36" above landing and secured at top to prevent displacement

Articulating boom lift: Full body harness and lanyard

Floor holes / openings covered, secured; be sure no tripping hazards are in the area

Extension cords / electric power tools, daily inspection for cord condition

Minimum of short sleeve shirts, long pants and substantial footwear – no recreational shoes

Hard hat readily accessible / worn when there is an overhead hazard

Oxygen / acetylene storage areas chained and separated

Personal protective equipment: head, eye, ear, respiratory, and leg protection – high visibility vests are required

Housekeeping: Workers responsible for own areas of exposure

BAROMETER OF SAFETY ATTITUDES
CONSTRUCTION SELF INSPECTION GUIDE (cont.)

1st-aid kit and Fire extinguishers

Minimum of one person at all times – 1st-aid/CPR trained

Accident Prevention Program

Fall Protection Work Plan

Hazard Communications Program

Crew Leader safety meetings: at the start of each job and at least weekly there after; meetings specifically tailored to each subcontractor

For specific information, refer to the Safety and Health standards, chapters 24, 62, and 155.

EQUIPMENT SAFETY INSPECTION CHECKLIST

This form is used as a check list for equipment coming into a project.

The items to be checked are listed and are required to be checked as a minimum pre-work inspection.

Any item that needs attention will be corrected before the equipment is put to work on a project.

The report will be filed at the Field Office for the duration of the project. A copy will also be sent to the main office.

Company safety personnel as well as governmental safety representatives will inspect these forms.

The Project Manager is responsible for ensuring that the pre-operating safety check is properly done.

EQUIPMENT SAFETY INSPECTION CHECKLIST

Date: _____

Project: _____ Equipment # _____

All guards and fenders	_____ OK	_____ Needs Repair
Brakes	_____ OK	_____ Needs Repair
Lights – front, rear, side, dash	_____ OK	_____ Needs Repair
Backup alarm – horn	_____ OK	_____ Needs Repair
Ladders / stairs / hand tools	_____ OK	_____ Needs Repair
R O P S	_____ OK	_____ Needs Repair
Seat belts	_____ OK	_____ Needs Repair
Fire extinguishers	_____ OK	_____ Needs Repair
Glass _____ OK	_____ Needs Repair	
Tires _____ OK	_____ Needs Repair	

Other Items Checked:

Oil – level and leaks	_____ OK	_____ Needs Repair	_____ Add	_____ Change
Hydraulic oil - level and leaks	_____ OK	_____ Needs Repair	_____ Add	_____ Change
Anti-freeze – level and leaks	_____ OK	_____ Needs Repair	_____ Add	_____ Change
Fuel – level and leaks	_____ OK	_____ Needs Repair	_____ Add	_____ Change
1st-aid kit	_____>OK	_____ Needs Repair	_____ Add	_____ Change

Repaired by: _____

Checked BY: _____

JOB SAFETY / PERSONAL PROTECTIVE EQUIPMENT ANALYSIS WORKSHEET

Project:_____
Date _____

One Way Plumbing, LLC's Safety Manager is to perform this Hazard/Safety/PPE Analysis

Analysis made by _____

Sequence of basic Job steps	Potential accidents or hazards	Recommended safe job procedure	Personal Protective Equipment

Requirements of a full Fall Protection Program

Falls form elevated work surfaces continue to produce injuries and death to workers at a high rate. In one year alone, five deaths within the construction industry were caused by falls.

Through the Washington Industrial Safety and Health Act (WISHA), the Department of Labor and Industries developed a comprehensive safety standard that became effective February 12, 1991 to address fall hazards (WAC 296-155-245).

This standard requires a written fall protection work plan to be developed and maintained on the job site. The plan must describe how the employer will protect employees on a given work site when they are working **10 feet or more** above the ground, other work surface, or water.

The six primary elements to be included in the plan are as follows:

- Identify all fall hazards in the work area.
- Describe the method of fall arrest or fall restraint to be provided.
- Describe the correct procedures for the assembly, maintenance, inspection and disassembly of the fall protection system to be used.
- Describe the correct procedures for handling, storage, and securing of tools and materials.
- Describe the method of providing overhead protection for workers who may be in, or pass through, the area below the work site.
- Describe the method for prompt, safe removal of injured workers.

Definitions

Definitions are included on the first page of the standard (WAC 296-155-24503).

Two if the most important definitions you will need to understand before an effective plan can be developed are summarized below.

- Fall arrest system – Equipment used to protect a person from falling more than six feet or from striking a lower object in the event of a fall, whichever distance is less.

- Fall restraint system – Equipment used to keep a person from reaching a fall point (i.e., edge of the roof).

This equipment includes scaffolding or other work platforms with standard guardrails; or approved safety belts (or harnesses) and lanyards attached to secure anchorage points; or nets.

Developing a Fall Protection Work Plan

1 Identify your company and the work site to which the plan applies.

This information should be listed as the first item in you plan.

2 Identify all fall hazards in the work area.

All jobs and tasks to be done must be reviewed to make this determination. Replacing siding on a building, building forms for a highway overpass, replacing skylights, or building the top deck of a building are some samples of fall hazards.

After all fall hazards have been identified, list those requiring employees to work 10 feet or more above the ground, other work surface, or above water. See the appendix to Part C-1 (WAC 296-155-24525) for specific safety codes requiring the use of fall protection equipment. These are in addition to the general requirements contained in Part C-1, WAC 296-155-245.

3 Determine the method of fall arrest or fall restraint to be provided for each job and task to be done that is 10 feet or more above the ground, other work surface, or water.

You might decide to use scaffolding with standard guardrails for replacing siding on a building, and full-body harness with lanyard secured to an anchorage point for building forms for a highway overpass or replacing skylights.

Building the top deck of a building might best be done by using different kinds of fall protection such as fall restraint for those working away from the leading edge and fall arrest for those working near the edge of the unprotected deck..

If a safety monitor system is used, you must use special care to ensure full compliance with WAC 296-155-24521.

4 Describe the procedures for assembly, maintenance, inspection, and disassembly of the fall protection system to be used.

Examples of how this requirement might appear on the document are as follows:

Tube and coupler scaffolding with standard guardrails will be used to replace siding on building # 2140. The scaffold will be erected and disassembled by "Z" Scaffolding company. The supervisor will inspect the scaffolding before allowing employees to work on it at the start of each work day and after major changes in the weather conditions. The scaffolding must meet the requirements of WAC 296-155-485.

Some critical items are:

- It must be on a firm base.
- The planks must be in good condition and secured from shifting. They must also be fitted to fill the scaffolding frame.
- All open sides and ends must be enclosed with guardrails and toe boards.

Fall arrest equipment, including approved full-body type III harness, lanyards, and horizontal lifelines attached to secure anchor points will be used for replacing skylights.

Employees will put the equipment on **before** climbing on the roof. They will snap into the horizontal lifeline immediately after mounting the roof.

The employee using it each day before putting it on will inspect all equipment.

The inspection will include checking for damage, wear, and mildew.

Any defective equipment will be taken to the job shack for evaluation by the job supervisor and turned in for repair or destroyed, as appropriate.

The lifeline will be secured to the roof by employees wearing fall blocks anchored to the roof and will be removed after the deck crew is off the roof.

5 Describe the correct procedures for handling, storage, and security of tools and material.

Some examples follow:

All fall protection equipment will be kept in a designated place or in the job equipment Shack. It will be picked up from the shack at the start of each workday by each using employee and returned after the shift is over. Employees will advise the job supervisor of any damage to the equipment.

Webbing will be washed, if dirty.

Tools will be secured as follows:

- Tool belts will be used to carry hand tools to the elevated work surface.
- Rope and pulley will raise tools too large for the tool belt.
- When hand tools are used, they will be returned to the tool belt immediately after use.

- Large tools, such as Skill saws, will be secured to the scaffold guardrails with the cable provided.
- Siding materials will be raised to the work platform by crane and sling. No more than 3 stacks of material will be kept on the platform at any time. It will be secured inside the guardrails not more than one stack high.

6 Describe the method of providing overhead protection for workers who may be in, or pass through, the area below the work site.

An example follows:

- The area under the scaffold will have a warning line installed to protect against other employees accidentally walking under it.
- The scaffolding will have # 18 screen installed between the toe board and the guardrail at all locations where employees must work below.
- The area above the scaffold will be decked over at all points where the siding crew must work immediately under the roofing crew or other employees.

7 Describe the method for prompt, safe removal of injured workers.

An example of this requirement might be as follows:

If a siding crew member is injured, the supervisor will evaluate the employee's condition and administer 1st-aid. If the employee's condition appears serious, the supervisor or designated person will call **(911)** or other local rescue unit to request assistance. The lift platform will be used to lower the injured person to the ground.

8 Include where (on the job site) a copy of this plan will be posted (i.e., the job shack).

9 Train and instruct all personnel in all of the above items (equipment to use, how to use it, etc.).

10 Keep a record of employee training and maintain it on the job site.

ONE WAY PLUMBING, LLC.
127-10th Street South, Suite 200
Kirkland, WA 98033
PHONE: (425) 968-8314
FAX: (425) 968-8794

TO: Exxel Pacific
RE: 19 West Harrison Apartments 11/09/15
Address: 19 West Harrison, Seattle, WA 98119

FALL PROTECTION PLAN

1. One Way Plumbing, LLC. Uses three legged, fiberglass step ladders in heights of 5', 6', 8', 10' and 12'. Per OSHA guidelines 1910.25, One Way Plumbing will not use nor does it own a stepladder in excess of 20'. Our ladders are compliant with OSHA guidelines and have not been altered, tampered with or intentionally damaged. Any ladder that does not meet or exceed OSHA guidelines will be taken out of service and repaired or replaced. All manufacturers labeling, warnings, care instructions and recommendations shall be followed and left unaltered.

Employees are prohibited from standing on or above the second to last rung from the top, and every employee shall observe the "belt buckle" rule: No climbing, leaning or standing on any ladder whereby the employee's belt buckle is higher than the top rung or step of the ladder.

Employees are prohibited from using any unapproved extension ladder or any extension ladder that exceeds 60', per OSHA guidelines 1910.25. One Way Plumbing will provide extension ladders that meet or exceed OSHA guidelines 1910.25. Any ladder that is broken or damaged will be removed from service until it can be repaired or replaced. Defective, damaged or broken ladders will be tagged "Dangerous, Do Not Use", per OSHA guidelines 1910.25.

Employees are prohibited from using any ladder, regardless of its height, until such time as he or she has been trained and cleared to use such ladder. In the event that One Way Plumbing changes ladder type, brand or configuration, retraining will be implemented before any employee will be allowed to operate the ladder. No stepladder or extension ladder will be used for any purpose other than that for which it is designed. No stepladder will be used as an extension ladder. No ladder will be placed on any unacceptable base in an effort to extend its height above the manufacturers' specifications. Non-conductive wood or fiberglass ladders only will be used where the possibility of electrical shock exists.

One Way Plumbing workers shall inspect ladders before each use and monthly (with our monthly vehicle and equipment report). Ladders will be kept free from dirt, grease and oil. Ladders will be properly stored and protected, when not in use. As a matter Company policy, new ladders will be treated with a wood sealer to protect the ladder from the elements and to protect the ladder from unnecessary water damage.

Store ladders in a manner that provides easy access for inspection and permits safe withdrawal for use. Ladders must not be stored where they present a tripping hazard, nor where they can fall on personnel. When stored horizontally, ladders should be supported at several points to avoid sagging. The ladders should be kept away from sources of heat and moisture and in a well-ventilated area. Aluminum ladders should not be stored in certain atmospheres (e.g., acidic) due to

severe corrosion problems. Ultraviolet rays of the sun can cause deterioration in fiber-glass ladders. Wax fiber-glass ladders with paste wax for extended storage and increased life span of use.

Assistance may be needed in transporting heavy or long ladders. When transported on vehicles, ladders should be adequately supported (preferably on hardwood or rubber-covered pipe) to avoid sagging and should be fastened securely.

2. Scaffolding will be operated, placed, assembled, moved and stored per manufacturer's recommendations. Scaffolding that does not meet or exceed OSHA guidelines will not be used by One Way Plumbing, LLC. All manufacturers' safety recommendations will be followed. All labeling will be left in place and unaltered.

Employees will be trained in proper scaffolding assembly, operation and climbing before using any scaffolding. No employee is permitted to move a scaffold while it is occupied by themselves or by others. All necessary bracing, supports, railings and safety equipment will be in place at all times. Wheels will be properly locked and chocked prior to occupancy. No scaffolding will be assembled higher than it is designed to be erected. Flooring around the scaffolding will be level and free from debris that could cause tipping while the scaffold is being moved.

All planking will be scaffold grade planking, per OSHA guideline 1910.28. No planking will exceed the length prescribed in table 1910.28. Only approved fasteners will be used in the assembly of scaffolding. No employee is allowed to work under or around the scaffolding while the scaffold is in use. Care will be taken to ensure that all objects on the scaffolding are secure and properly stored.

Scaffolding will be transported and stored safely when not in use.

3. Fall protection. Employees are not permitted on pitched roofs. One Way Plumbing does not own harnessing equipment nor does it train its employees for pitched roof work. Employees working on any flat roof without safety railings, unless the surface is less than four feet off the ground, are prohibited.

For safety reasons, One Way Plumbing does not permit its employees to work above or below the first floor in any building that does not have a fixed, permanent stairway with approved safety railings. One Way Plumbing employees are not permitted to construct their own stairways nor are they allowed to alter an existing stairway to facilitate its use.

The fall protection program is not limited to the above guidelines. Our employees are required to evaluate every situation and they are required to pull off of any job that will compromise their safety or that of their fellow workers. It should be clearly understood that One Way Plumbing does not permit any of its employees to work in any area where specialized fall equipment is required.

One Way Plumbing, LLC.
Heat-Related Illness Policy:

It is the policy of One Way Plumbing, LLC. That all affected employees are required to comply with this Heat-Related Illness policy and are encouraged to actively participate in identifying ways to reduce the risk of experiencing heat-related illness in the work place.

Supervisors are responsible for the safety of their employees and as a part of their daily duties must check the workplace for unsafe conditions, monitor the health and safety of employees, and take prompt action in response to any identified Heat-Related Illness hazards.

The company's designated safety person for One Way Plumbing, LLC., and/or crew foremen, will identify and evaluate the environmental factors on a day-to-day basis.

DOSH Directive 18.50 indicates a heat index of 80 as a trigger for consideration.

When heat related illness hazards are present you should hydrate yourself with at least one quart of water per hour. This is necessary to reduce the risk of heat related illnesses.

During times when you are exposed to HRI hazards more frequent than usual rest breaks may be necessary. If you start feeling overheated, take a rest break and follow the guidelines for cooling off.

When heat-related illness hazards are present and work will be at a remote site, foremen will make sure their crews always have open channels of communication, to request breaks, water, or help.

TRAINING

All affected One Way Plumbing, LLC. employees and supervisors will be trained on recognizing and responding to heat-related illness before being exposed to HRI hazards. They will also receive refresher training annually after that. Completion of training will be documented.

METHODS OF EVALUATION

If any of the following **Factors** are checked, then at least one at least one **Control and Methods** box for each factor must be checked.

Factors	Controls and Methods
☐ Air Temperature	☐ Provide cooling vests; ☐ Provide misters or other cooling devices; ☐ Wet down clothing; ☐ Perform work during the cooler parts of the day or in the shade when possible; ☐ Encourage workers to take frequent short breaks in a shaded or cooled area; ☐ Use the buddy system; ☐ Implement an acclimatization program; and ☐ Ensure first-aid trained personnel are on site

☐ Relative Humidity	☐ Provide cooling vests; ☐ Encourage employees to wear breathable, light colored clothing; ☐ Perform work during the cooler parts of the day or in the shade when possible; ☐ Encourage workers to take frequent short breaks in a shaded or cooled area; and ☐ Encourage employees to bring a change of clothing, and change their clothes if they become saturated
☐ Radiant Heat	☐ Eliminate unnecessary sources of radiant heat; ☐ Install insulation or shielding devices; ☐ Provide wide brimmed hats for employees; ☐ Perform work during the cooler parts of the day or in the shade when possible; ☐ Encourage employees to wear breathable, light colored clothing; and ☐ Provide and encourage workers to take frequent short breaks in a shaded or cooled area. ☐ Encourage the use of sunscreen lotions; and ☐ Wear shaded goggles or sunglasses
☐ Air Movement	<u>At 95˚F or below:</u> ☐ Provide misters or other cooling devices; ☐ Increase air movement through the use of fans or other devices; and ☐ Loosen or reduce clothing <u>At 96 ˚F or above:</u> ☐ Reduce air temperature; and ☐ Cover the body to reduce rate of heat gain by convection
☐ Conductive Heat Sources	☐ Provide protective gloves and footwear (insulation); ☐ Perform work during the cooler parts of the day or in the shade when possible; and ☐ Encourage workers to take frequent short breaks in a shaded or cooled area
☐ Workload Activity and Duration	☐ Rotate employees performing particularly physically demanding jobs; ☐ Perform work during the cooler parts of the day or in the shade when possible; ☐ Enforce work/rest schedules; ☐ Encourage workers to take frequent short breaks in a shaded or cooled area; ☐ Use the buddy system; ☐ Routinely monitoring the employee's status; ☐ Implement an acclimatization program; and ☐ Ensure first-aid trained personnel are on site
☐ Personal Protective Equipment (PPE)	☐ Remove PPE during breaks; ☐ Perform work during the cooler parts of the day or in the shade when possible; and ☐ Encourage workers to take frequent short breaks in a shaded or cooled area; ☐ Routinely monitoring the employee's status; and ☐ Ensure first-aid trained personnel are on site

RESPONSE PROCEDURES TO HEAT-RELATED ILLNESSES

One Way Plumbing, LLC. will make the following information available at each job site when heat-illness hazards are present. Driving directions to the work site will also be posted at each job site.

Heat-related illness	*Signs and Symptoms*	*First Aid*
Sunburn	- Red, hot skin - May Blister	- Move to shade, loosen clothing - Apply cool compresses or water
Heat Rash	- Red, itchy skin - Bumpy skin - Skin infection	- Apply cool water or compresses - Keep affected area dry - Control itching and infection with prescribed medication
Heat Cramps	- Muscle cramps or spasms - Grasping the affected area - Abnormal body posture	- Drink water or sport drinks - Rest, cool down - Massage affected muscle - Get medical evaluation if cramps persist
Heat Exhaustion	- High pulse rate - Extreme sweating - Pale face - Insecure gait - Headache - Clammy and moist skin -Weakness - Fatigue -Dizziness	- Move to shade and loosen clothing - Initiate rapid cooling - Lay flat and elevate feet - Monitor recovery - Drink small amounts of water - Evaluate metal status (ask who? where? when? questions) - If no improvement call 911
Heat Stroke	- Any of the above but more severe - Hot, dry skin (25-50% of cases - Altered mental status with confusion or agitation - Can progress to loss of consciousness and seizures. - Can be fatal	- **Call 911** - Immediately remove from work - Start rapid cooling - Lay flat and elevate feet - ***If conscious*** give **sips** of water - Monitor airway and breathing – administer CPR if needed

Hearing Loss Prevention
For
One Way Plumbing, LLC.

Hearing conservation is very important. Noise-induced hearing loss can be temporary or permanent but it is preventable. Hearing conservation programs can protect workers with high occupational noise exposures from hearing impairment. A report released in September 2004 by the University of Washington Department of Environmental and Occupational Health Sciences states that construction workers were exposed to 85 Dba or more in about 30% of shifts using the WISHA exposure standard.

The noise level on construction worksites is highly variable. One Way Plumbing, LLC. requires anyone that is exposed to noise at or above 85 decibels averaged over an 8 hour working period to get audiometric testing within 180 days of starting work in order to get a baseline reading and annually thereafter to measure any hearing loss. All field employees must get tested. The testing is to be done by a Group Health clinic free of charge to the employee.

Hearing protection is provided to all field employees upon commencement of employment along with all other required personal protective equipment. The hearing protection we have on hand is:

Moldex Pura-fit foam ear plugs
Radnor NRR25 Multi-Position Earmuffs

If neither of these work for you please notify your supervisor who will work with you to find a style that works best for you. If your hearing protection gets lost or damaged additional hearing protection is available from your supervisor.

Using earmuffs or earplugs in noisy areas actually makes it easier to hear coworkers or machinery. They reduce the overwhelming loud background noise. They are similar to sunglasses that reduce the sun's glare making it easier to see.

When you receive your hearing protection you will also receive training on the effects of noise on hearing, the purpose of hearing protectors including advantages and disadvantages of various types and the purpose of audiometric testing and how it's done. Retraining will be done annually.

Hearing protection is required when the following equipment is used; Hole hawg and Sawzall or when near hammering or other loud equipment.

Identifying excessive noise sources is the responsibility of the onsite foreman and should be reported to OWP management and the General Contractor immediately. If needed, a hand held sound level meter can be used to assess the excessive noise. If the excessive noise cannot be reduced to acceptable levels, then hearing protection must be used. The onsite foreman is responsible for continuous monitoring of onsite noise levels and will report to OWP management and the General Contractor if any problems arise.

Name:_____ Date_____
(Please Print)

The following **PPE** (Personal Protection Equipment) has been issued to the above employee in good condition.

_____Safety Glasses

_____Hard Hat

_____Hearing Protection

_____Class II High Visibility Vest

The above employee has been shown how to properly put on, adjust, wear and remove PPE.

Issued By: _____ Date _____
(Please Print)

Understanding the use for PPE

WISHA (Washington Industrial Safety and Health Act), and **One Way Plumbing, LLC** requires that our employees wear **PPE** to prevent against any hazards.

Below is a list of PPE equipment and areas of hazard.

1. **Eye Protection/Face Protection:** To be used in areas when eyes or face is exposed to hazards from flying particles, molten metals, liquid chemicals, acids or caustic liquids, chemical gases or vapors, or potentially injurious light radiation.
2. **Head Protection:** To be used in areas of work where there is a potential for injury to the head from falling or flying objects.
3. **Foot Protection:** To be worn on all job-site work situations. Protective footwear shall be worn in all areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, and where an employee's feet are exposed to electrical hazards.
4. **Hand Protection:** To be used where hands are exposed to hazards such as those from skin absorption of harmful substances; severe cuts or lacerations; severe abrasions; punctures; chemical burns; and harmful temperature extremes.
5. **Ear Protection:** To be used where loud noise is a hazard for employee.

One Way Plumbing provides systematic and random check on all PPE for maintenance, care and disposal.
One Way Plumbing, LLC conducts a Hazard Assessment on each job-site

NOTE: Workers should NOT perform work requiring PPE until the demonstrate "an understanding" of what was learned, and "the ability to PPE properly."

I, _____ understand how and when to wear my PPE. Date_____
(Please Sign)

Safety Representative Signature_____ Date_____
(Please Sign)

ONE WAY PLUMBING, LLC – **Plumbers Safety**

Name:_____ Date:_____

Position:_____

General Safety

General safety and hazard observance is to be shown prior to the employee entering the field.

	General Safety/Hazard Observance	**YES**	**NO**
1	Shown the location of the fire extinguishers and first aid kits		
2	Shown how to check a fire extinguisher for serviceability		
3	Shown how to check the job site for potential hazards		
4	Instructed when to wear hard hats, safety glasses and hearing protection.		
5	Shown how to unload truck		
6	Shown potential soldering hazards and preventions		
7	Shown how to lift properly		
8	Shown how to dig using limited back work		

Tool and Hazard

Tool Safety to be shown prior to entering the field.

	Tool Safety Item	**YES**	**NO**
1	Shown how to operate a drill, and chuck a drill bit– hole hawg, right angle drill, and cordless drill.		
2	Shown how to operate saws, including circular, and install a saw blade		
3	Shown how to drill, saw and cut wood		
4	Shown how to operate a Roto Hammer/Chipping Hammer		
5	Shown how to operate a torch (Turbo torch and B-Tank)		
6	Shown how to solder		
7	Shown how to inspect all tools and equipment for damage, breakage or defects		
8	Shown how to use a ladder		

Safety ---Dress Code for Field Employees

All field employee's, regardless of the job, are required to adhere to the following dress code.

1. Boots or shoes with a hard sole and leather uppers or rubber boots with a steel shank.
2. Long pants that are free from tears, rips, or holes and fit snugly without restricting movement

Shirts free from tears, rips, or holes and have sleeves that at least cover the shoulder area.

Employee Comments:_____
_____
_____
_____

Evaluations

At the end of the first day, the new employee is given a brief evaluation on his/her work practices and has been given a constructive analyses of the days activities. The employee will be given a follow up evaluation after: One week, one month, and as recommended by the safety representative.

_____ _____
Employee Signature Date

_____ _____
Safety Representative Date

1st Follow up _____ _____
(Safety Representative) Date

2nd Follow up_____ _____
(Safety Representative) Date

3rd Follow up_____ _____
(Safety Representative) Date

SITE SPECIFIC JOB HAZARD ANALYSIS

PROJECT INFORMATION		
Project Name:		
Project Location:		
Date of Analysis:		
Analysis Completed by:		Title:
General Work Description:		

OBJECTIVE
It is the policy of One Way Plumbing LLC that accident prevention shall be considered of primary importance in all phases of our operation and administration. It is the intention of the company's management to provide safe and healthy working conditions to establish and insist upon safe working practices at all times by all employees. This Site Specific Job Hazard Analysis will be used to identify potential unsafe working conditions, hazards or potential accidents that could occur and ensure that each item is sufficiently addressed before any work proceeds. NOTE: ALWAYS ATTACH A SEPARATE LIST OF PPE REQUIRED FOR THESE ACTIVITIES.

JOB HAZARD ANALYSIS		
ITEM #1		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:
ITEM #2		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:
ITEM #3		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:
ITEM #4		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:

ITEM #5		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:
ITEM #6		
Tasks/Activity/Situations:	Hazards:	Preventive Actions:

ATTENDEES SIGNATURES:

The following is a list of example work tasks and/or situations that list some potential hazards and preventive actions that could be taken. This is only to be used as an example. Many situations will have different hazards and/or require different preventive actions. Always refer to WISHA/OSHA regulations, OWP safety plan and General Contractor site specific safety requirements before proceeding.

EXAMPLES		
Excavation	Struck by and/or caught between machinery.	Wear safety vests at all times and maintain constant operator awareness. Make eye contact with operator before coming near machinery.
Installing Pipe/Trench Shoring	Cave in Vehicle & Pedestrian Traffic	Use of shoring or trench boxes as conditions require. (Anything deeper than 4 feet will be shored/boxed or stepped. Safe egress required. Emplyees supervised by designated competent person at all times.) Work in roadways and sidewalks require approved traffic control plan. All employees involved will be trained on the traffic control plan.
Jobsite Cleanup	Tripping/Falling/Foreign Object Debris	The Jobsite will to be cleaned and maintained at all times to prevent any transportation dangers or difficulties.
Material Handling	Strains/Sprains	Use necessary equipment and proper rigging and hoisting procedures. All material manually lifted will be done using proper lifting techniques, which all OWP employees have be trained in.
Using Hand/Power Tools	Lacerations, etc.	OWP utilizes lockout/tagout procedures. All tools are inspected prior to use. Any defects that increase the hazard of the tool or compromises efficiency of the tool, such as bad cords, missing or broken parts, cracks and/or significant wear, etc. will be noted and tool will be locked out and tagged out and removed from the job. All employees are trained in the use of tools of our trade.
Debris caused by wind, machinery, etc.	Foreign object in eye	Safety glasses are required to be worn by every OWP employee. Eye wash station will be on site. If dust/debris is heavy, goggles or face shield may be utilized.
Welding/Cutting/ Grinding Steel	Burns, fire, Laceration, Debris	All welding/Cutting/Grinding will be completed while using proper PPE and by trained personnel with approved hotwork permits. All grinders will have necessary guards and face shields will be utilized.

FORKLIFT SAFETY PLAN

OBJECTIVE
It is the policy of One Way Plumbing LLC that accident prevention shall be considered of primary importance in all phases of our operation and administration. It is the intention of the company's management to provide safe and healthy working conditions to establish and insist upon safe working practices at all times by all employees. This Forklift Safety Plan will be used to review all procedures for forklift use prior to beginning work and identify potential unsafe working conditions, hazards or potential accidents that could occur while using and ensure that each item is sufficiently addressed before any work proceeds. NOTE: ALWAYS ATTACH A SEPARATE LIST OF PPE REQUIRED FOR THESE ACTIVITIES.

FORKLIFTS

General Requirements

Nameplates and markings should remain intact and should be maintained in legible condition. The manufacturer's written approval must be obtained for any modifications that affect forklift capacity or safe operation. If a modification is made, the capacity, operation and maintenance instruction plates, tags or decals should be changed.

Safety Guards

The following safety guards should be provided on forklifts:

Enclosure Guards: All hazardous moving parts should be guarded, such as exposed gears and chain-and-sprocket drives. Tires should also be guarded to prevent objects from being propelled toward the operator.

Overhead Guard: An overhead guard should be provided where there is a danger of falling objects or where loads are lifted higher the operator's head. These guards should extend beyond the operator's position.

Vertical Load Backrest Extension: A load backrest extension should be provided when the type of load present a hazard to the operator.

Battery Maintenance

The following safety rules should be followed when charging/changing batteries:

- Batteries should be charged only in the battery charging area.
- Forklifts should be properly positioned and the brake applied before attempting to change or charge batteries. Material handling equipment should be provided for handling batteries.
- Facilities should be provided for:
- Flushing and neutralizing spilled electrolyte
- Fire protection
- Protecting charging apparatus from damage by trucks
- Ventilation for dispersal of fumes from gassing batteries
- A carboy tilter or siphon should be provided for handling electrolyte.
- When changing batteries, acid should be poured into water; water should not be poured into acid.
- Ensure that vent caps are functioning. The battery or compartment covers should be open to dissipate heat.
- Take precautions to prevent open flames, sparks or electric arcs in the battery charging area.

- Smoking is prohibited in the charging area.
- Keep tools and metallic objects away from the top of uncovered batteries.
- Make sure that reinstalled batteries are properly positioned and secured in the truck.

Fuel Handling and Storage

Liquid fuels (gasoline, diesel fuel) should be handled and stored in accordance with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code (NFPA No. 30).
Liquefied petroleum gas (LPG) should be handled and stored in accordance with NFPA Storage and Handling of Liquefied Petroleum Gases (NFPA No. 58).

- The engine should be stopped and the driver should dismount the vehicle before a truck is refueled.
- Fuel tanks will not be filled while the engine is running. Spillage will be avoided. Refueling must be performed out of all buildings and away from open doors.
- Spillage of oil or fuel will be carefully washed away or completely evaporated and the fuel tank cap replaced before restarting engine.
- No forklift will be operated with a leak in the fuel system until the leak has been corrected.

Control of Noxious Gases and Fumes

To control the levels of carbon monoxide, gasoline engines should not be idled in enclosed areas for long periods of time.

Routine Inspection and Maintenance

- Operators will be held responsible for checking the mechanical condition of their forklifts at the start of each shift or before initial use.
- Operators will be instructed never to make adjustments or repairs on forklifts, but to promptly report any faulty mechanical condition to maintenance for repair.
- Maintenance employees will make a thorough mechanical inspection of all forklifts at least once a month, at which time necessary repair and parts replacement will be made.
- If at any time a powered industrial forklift is found to be in need of repair, defective or in any way unsafe, the forklift will be taken out of service until it has been restored to safe operating condition.
- Open flames will not be used for checking electrolyte level in storage batteries or gasoline level in fuel tanks.
- All powered industrial forklifts should be maintained in safe operating condition at all times. Maintenance activities should include regular inspections, preventive maintenance and overhauls when necessary. Forklifts that are not in safe operating condition should be removed from service until repairs are made. Repairs should be made only by authorized personnel.
- Documentation should be maintained of all inspection and maintenance activities. A file containing the maintenance and inspection records should be maintained for each forklift.

Powered Industrial Vehicle Safe Operating Rules

Because of the hazards involved with powered industrial vehicle operations, the following safe operating practices have been developed to ensure that authorized employees drive in a safe manner.

<u>General</u>

- Safeguard any pedestrians at all times.
- When leaving a forklift unattended (definition: forklift not in view or is in view, but is more than 25 feet away), the operator should ensure the following:
- Forks will be fully lowered.
- The transmission is in neutral.
- Power shut off.
- Brakes set and key or connector plug is removed.
- Wheels are chocked if the forklift is parked on an incline.
- Brakes will be set and wheel chocks will be in place to prevent movement of trucks while loading or unloading.
- A load backrest extension should always be used to minimize the possibility of the load or part of it from falling forward.
- No person will be allowed to stand or pass under the elevated portion of any vehicle whether loaded or empty.
- Unauthorized personnel will not be permitted to ride on powered industrial vehicles.
- The driver will never push one load with another load.
- Vehicles will never be used to lift people.
- Dockboards or bridge plates will be properly secured before they are driven over. Dockboard or bridge plates will be driven over carefully and slowly and their rate capacity never exceeded.
- Never pick up loads in excess of the rated capacity of the vehicle.

Traveling

- All traffic regulations will be observed, including observing all stop signs and yield signs.
- The driver must always slow down and sound the horn at cross aisles and when approaching blind corners, intersections or other locations where vision is obstructed.
- If the load being carried obstructs forward view, the driver must travel with a trained and authorized spotter.
- Grades will be ascended or descended slowly, keeping the load uphill. Never operate diagonally across an incline.
- Operators should never reach through the mast of a vehicle to adjust the load.
- Keep forks slightly tilted back so load is cradled by the backrest to aid in stabilizing loads when traveling.
- When traveling the forks must be just high enough to clear the floor.

Operation of the Vehicle

- Vehicles will be inspected before being placed in service. Defects when found will be immediately reported and corrected.
- If at any time during your shift a vehicle is found to be in need of repair or in anyway unsafe, the vehicle will be taken out of service until it has been restored to safe operating condition.
- Fuel tanks will not be filled while the engine is running, spillage will be avoided.

- No vehicle will be operated with a leak in the fuel system or hydraulic system.
- Before changing tanks on liquefied propane powered vehicles, the tank valve should always be turned off and the engine allowed to run until out of gas.
- Smoking is not allowed when changing storage batteries or placing them on charge or taking them off charge for electric powered vehicles.

Loading/Stacking

- Only stable or safely arranged loads will be handled.
- Only loads within the rated capacity of the vehicle will be handled.
- The forks must be placed under the load as far as possible. The mast will be carefully tilted backward.
- Extreme care should be used when tilting the load forward or backward, especially when the load is raised.
- When stacking or tiering, the operator should use only enough backward tilt to stabilize the load.
- The operator must be careful not to damage lights, pipes, sprinkler systems, overhead doors, vertical beams, walls, etc., when stacking material.
- The uppermost portion of any staked loads will never be closer than 18 inches under overhead installations, lights, etc.
- Never tilt the load except where the load is on a deposit position over a rack or stack.
- If material is not banded or correctly piled and the load obviously is wobbly, the operator will not attempt to lift it.
- Never stack material so that it causes blind spots at corners and intersections.
- Only stack material on a stable base that is sufficient in size and capable of supporting the stacked weight.
- The operator should remove unsafe containers and damaged pallets.

Training Requirements

Operator Training

Operator training will be conducted prior to allowing anyone to operate an industrial vehicle, with recertification for experienced drivers every three years. Methods will be devised to train operators in the safe operation of powered industrial lifts. This training should include the following:

- Operators certified to drive vehicles should be given a certification card to be carried with them whenever operating a vehicle.

Nonoperator Training

Employees working in areas where powered industrial vehicles operate should be made aware of the following general rules:

- Never pass under the raised forks of a vehicle, whether they are loaded or not.
- Walk around forks of a vehicle, never over or between them.
- Never “hitch a ride” on someone else’s vehicle.
- Allow vehicles the right of way.

AERIAL LIFT SAFETY PLAN

OBJECTIVE
It is the policy of One Way Plumbing LLC that accident prevention shall be considered of primary importance in all phases of our operation and administration. It is the intention of the company's management to provide safe and healthy working conditions to establish and insist upon safe working practices at all times by all employees. This Aerial Lift Safety Plan will be used to review all procedures for aerial lift use prior to beginning work and identify potential unsafe working conditions, hazards or potential accidents that could occur while using and ensure that each item is sufficiently addressed before any work proceeds. NOTE: ALWAYS ATTACH A SEPARATE LIST OF PPE REQUIRED FOR THESE ACTIVITIES.

SCISSOR LIFTS / AUTOMATIC PLATFORM LIFTS
Only trained and authorized personnel will be permitted to operate a scissor lift. Scissor lifts powered by gasoline, diesel, or propane will produce carbon monoxide gas. If the lift is used within a structure the Foreman will ensure adequate ventilation. Operators manuals will be provided with the scissor lift or the lift will not be accepted by the Foreman. Operators must read and understand all decals, warnings, operators manual, and instructions on the scissor lift . Questions must be directed to your Foreman On a daily basis, before the scissor lift is used, operators will give the scissor lift a thorough inspection, which will include: (A).Inspection for defects such as cracked welds, hydraulic leaks, damaged control cable, loose wire connections and tire damage.(B) Inspection of functional controls for proper operation. The supervisor will correct any unsafe items before further use of the scissor lift is authorized. Never modify or remove any part of the equipment unless authorized by the manufacturer. Altering or disabling of safety devices such as limit switches is prohibited. Check the path of travel, above, below and all around for hazards. Watch Out for other trades!! Before the scissor lift is used, the operator will survey the area for hazards such as: Untamed earth fills, Ditches, Drop-offs or holes, Bumps and floor obstructions, Debris, Overhead obstructions and high-voltage conductors, Other crafts working in the same area. Before elevating the scissor lift, the operator will: (A) Check for overhead obstructions and high-voltage conductors. A minimum distance of ten feet from energized high-voltage conductors will be maintained at all times between the conductors and the operator and platform equipment; (B) Ensure that the work platform is elevated only on a firm and level surface; (C) Ensure that the load and its distribution on the platform are below manufacturer's rated capacity. The manufacture's recommended load limits will never be exceeded; (D) Ensure that outriggers and stabilizers are used if the lift is supplied with them. (E) Ensure that guardrails are properly installed, and gates or openings are closed. Before elevating the scissor lift, the operator will: (A) Check for overhead obstructions and high-voltage conductors. A minimum distance of ten feet from energized high-voltage conductors will be maintained at all times between the conductors and the operator and platform equipment; (B) Ensure that the work platform is elevated only on a firm and level surface; (C) Ensure that the load and its distribution on the platform are below manufacturer's rated capacity. The manufacture's recommended load limits will never be exceeded; (D) Ensure that outriggers and stabilizers are used if the lift is supplied with them. (E) Ensure that guardrails are properly installed, and gates or openings are closed. Before and during driving while the scissor lift is elevated, the operator will: (A) be required to look in the direction of, and keep a clear view of, the path of travel and assure that the path of travel is firm and level. (B) maintain a safe distance from obstacles, debris, drop-offs, holes, depressions, ramps. (C) maintain a safe distance from overhead obstacles. The operator will limit travel speed according to conditions. Conditions to be observed are: Ground surface, congestion's, slope, location of personnel, and other factors that may create a hazard of collision or injury to personnel.

Operators will maintain a safe distance to electrical power lines at a minimum of 10 feet.

Operators will keep others away from the scissor lift's work area while in use.

Operators will maintain a firm footing on the platform while working unless they are secured by personal fall arrest system.

Use of railings or planks, ladders or any other device on the scissor lift for achieving additional height is prohibited.

The operator will immediately report defects or malfunctions which become evident during operation and will stop use of the scissor lift until correction has been made.

Care shall be taken to prevent ropes, electric cords, air hoses, paint hoses, etc. from tangling with the scissor lift when the platform is being elevated, lowered, or moved.

Scissor lift rated capacities will not be exceeded when loads are transferred to the platform at elevated heights.

The operator will ensure that the area surrounding the scissor lift is clear of personnel and equipment before lowering the platform.

Fuel tanks will not be filled while the engine is running. Spillage will be avoided.

Batteries will be charged in open, well-ventilated areas, free of flames, smoking, sparks, or fire.

If the machine is left unattended, lower platform, shut off engine, engage parking brake and remove key. Key's must be given to your Foreman.

BOOM SUPPORTED ELEVATED WORK PLATFORMS

Only trained and authorized personnel will be permitted to operate a Boom lift.

Boom lifts powered by gasoline, diesel, or propane produce carbon monoxide gas. If the lift is used within a structure the Foreman will ensure adequate ventilation.

Use of railing, planks, ladders, or any other device within the platform for achieving additional height is prohibited.

Before using a boom lift, the operator will: **A.** Read and understand the manufacturer's operating instructions and safety rules. **B.** Read all decals, warnings, and instructions displayed on the work platform.

Daily, before use, operators will inspect their boom lift. Inspect for: **A**. Visual inspection for cracked welds or other structural defects, hydraulic leaks, damaged control cables, loose wire connections, and tire damage. **B**. Function test of the operating controls to ensure that they perform their intended functions. **C**. All unsafe items will be brought to the Foreman's attention and corrected before further use of the boom lift. **D**. Before the boom lift is used and during use, the job site will be checked for hazards such as ditches, drop-offs or holes, bumps and floor obstructions, debris, overhead obstructions and high-voltage conductors, and other possible hazardous conditions.

Before each elevation of the boom lift, the operator will: **A**.Check for overhead obstructions and high-voltage conductors. A minimum distance of ten feet from energized high-voltage conductors will be maintained at all times between the conductors and the operator and boom lift. **B**. Ensure the boom lift is elevated only on a firm and level surface.
C. Ensure that the load and its distribution on the platform are in accordance with the manufacturer's rated capacity. The manufacturer's rated workload will never be exceeded. **D**. Ensure that outriggers or stabilizers are used in accordance with manufacturer's instructions. Wheel chocks shall be installed

before using an aerial lift on an incline, provided they can be safely installed. **E**. Ensure that platform guardrails are properly installed and gates or openings are closed. **F**. Check to see that all occupants' full body harnesses are on and attached to the provided anchor point.

Before and during driving while elevated, the operator will:
A. Be required to look in the direction of, and keep a clear view of, the path of travel and make sure that the path is firm and level. **B.** Maintain a safe distance from obstacles, debris, drop-offs, holes, depressions, ramps, and other hazards to safe elevated travel.
C. Maintain a safe distance from overhead obstacles.

Under all travel conditions the operator will limit speed according to conditions of ground surface, congestion, slope, location of personnel, and other factors which may create a hazard of collision or injury to personnel.

Stunt driving and horseplay is not be permitted.

Personnel will maintain a firm footing on the platform while working.

If the operator or riding personnel must get out of the platform while elevated they will use a double lanyard, personal fall protection system. Release the lanyard attached to the platform anchor point only after securing the second lanyard to an approved anchor point outside the platform (See project fall protection work plan).

The operators will immediately report to their supervisor any defects or malfunctions which become evident during operation. Any defects or malfunctions that affect safe operation will be repaired by the supplier prior to continued use of the boom lift.

Operators will not alter, modify, or disable safety devices, such as limit switches or interlocks.

Care will be taken to prevent ropes, electric cords, and hoses from becoming entangled in the boom lift when it is being elevated, lowered or moved.

Boom lift rated capacities will not be exceeded when loads are transferred to the platform at elevated heights.

The operator will ensure that the area surrounding the work platform is clear of personnel and equipment before lowering the platform.

Refueling: Fuel tanks will not be filled while the engine is running. Caution will be used while filing tanks to avoid spilling fuel.

Battery charging: Batteries will not be charged except in an open, well ventilated area free of flame, smoking, spark and fire.

ONE WAY PLUMBING LLC

CONFINED SPACE ENTRY PROGRAM

OVERVIEW

This confined space entry program:

- Identifies all permit-required confined spaces in our workplace

  and
- Describes our procedures for worker safety and health in permit-required confined spaces

Employees will participate in developing and implementing the program in the following ways:

One Way Plumbing employees will need to enter the sump pump basins in the lowest garage levels to install the sump pumps and associated piping. Employees are required to review and follow this plan prior to and during confined space entry. Employees will participate in the development and implementation of this program by; reviewing the plan and providing feedback, reviewing site specific conditions as it relates to the confined space entry program, and ensuring the safe working conditions of all workers._____

ONE WAY PLUMBING CONFINED SPACE ENTRY POLICY:

1. The only employees of One Way Plumbing that are allowed to enter confined spaces are those that are certified in confined-space entry. Non-certified employees are not allowed to enter confined spaces.
2. Entry supervisors are required to be certified in confined-space entry. An entry supervisor must be present at all times during confined-space entry.
3. A confined-space entry permit must be filled out every time confined space entry occurs, whether it is permit required or not. This requirement is intended to ensure the safety of employees at all times.

One Way Plumbing LLC will treat all confined spaces as permit-required spaces until they have been evaluated **and** are documented to be nonpermit.

ROLES & RESPONSIBILITIES

The following shows which employees are responsible for the tasks outlined:

Responsibility:	**Person assigned this responsibility:**
Evaluate our work locations and determine: ✓ [Check appropriate box(es)] • Confined space(s) exist at the worksite. • Permit-required confined space(s) exist at the worksite.	
Evaluate the confined space(s) to determine whether hazards are present.	
Evaluate hazards and determine the appropriate entry procedure for the space. **Note:** • Until evaluated and documented otherwise, all confined spaces will be considered permit-required spaces.	

• Alternate entry procedure may apply when the only hazard remaining in the space is a potential hazardous atmosphere controlled by the use of forced air ventilation.	
Re-evaluate the space when the use, configuration, or hazards of a confined space change.	
Monitoring and testing as follows: • Conduct initial monitoring to identify and evaluate any potentially hazardous atmospheres • Complete atmospheric testing in the following order: – Oxygen – Combustible gases – Toxic gases and vapors • Record the data *Pre-Hazard Analysis* • Keep these records on-site in *GC Jobsite Office*_____	
Inform exposed or potentially-exposed employees of the existence and hazards of confined spaces using the methods described below under "Control Confined Space Entry."	
Provide employees entering confined spaces, or their designated representative, an opportunity to observe pre-entry testing and any subsequent testing. - All test results will be provided to the entrants or their representatives upon request. - The space will be re-evaluated if entrants or their representatives believe that the permit space was inadequately tested.	
Make sure that all equipment needed for safe entry into any confined space is available and in proper working order.	
Conduct a review using the canceled entry permits to identify and correct any deficiencies in our program.	

IDENTIFY CONFINED SPACES AND HAZARDS

The following table provides a list of our confined spaces and hazards:

Confined Spaces and Hazards

Confined Space (name or number)	**Type of Space** (tank, hopper, sump, pit etc.)	**Location**	**Hazards**

PERMIT ENTRY PROCEDURES

Our entry procedures for permit spaces include the following: **SEE ATTACHED CONFINED SPACE ENTRY PERMIT. THIS MUST BE FILLED OUT.**

ALTERNATE ENTRY PROCEDURES

Our permit spaces that have as their only hazard an actual or potential hazardous atmosphere may use alternate entry procedures. These alternate entry procedures do not require the use of an entry permit.

Alternate entry procedures can be used for the spaces listed in the following table:

Confined Space Name or Number	Hazards	Method of Hazard Elimination	Potential Hazardous Atmosphere	Ventilation Equipment Required

We will do all of the following when using alternate entry procedures:

- Eliminate unsafe conditions before removing entrance covers.

  - After removing entrance covers, promptly guard the opening with a railing, temporary cover, or other temporary barrier to prevent accidental falls through the opening and protect entrants from objects falling into the space.

  - Certify that pre-entry measures have been taken (such as safe removal of the cover and having protection needed to gather pre-entry data), with the date, location of the space, and signature of the person certifying.

  - Make the pre-entry certification available to each entrant before entry.

- Before an employee enters the confined space, test the internal atmosphere with a calibrated, direct-reading instrument for all of the following, in this order:
  1. Oxygen content
  2. Flammable gases and vapors
  3. Potential toxic air contaminants.

- Provide entrants, or their authorized representatives, with an opportunity to observe the pre-entry and periodic testing.

  - Make sure the atmosphere within the space is not hazardous when entrants are present.

- Use continuous forced air ventilation, as follows:

  - Wait until the forced air ventilation has removed any hazardous atmosphere before allowing entrants into the space.

  - Direct forced air ventilation toward the immediate areas where employees are, or will be, and continue ventilation until all employees have left the space.

  - Provide the air supply from a clean source and make sure it does not increase hazards in the space.

- Test the atmosphere within the space as needed to make sure hazards do not accumulate.

- If a hazardous atmosphere is detected during entry, we will do all of the following:
  - Evacuate employees from the space immediately.
  - Evaluate the space to determine how the hazardous atmosphere developed.
  - Implement measures to protect employees from the hazardous atmosphere before continuing the entry operation.
  - Verify the space is safe for entry before continuing the entry operation.

- The written documentation is available to each employee entering the space or to that employee's representative at the confined space bulletin board.

CLASSIFY A CONFINED SPACE AS A NONPERMIT SPACE

- A space will be classified nonpermit only for as long as all the hazards remain eliminated.

- If someone must enter the space to eliminate of any of the hazards, we will follow all the requirements listed under the permit entry procedures.

- Documentation that no permit-required confined space hazards exist will include the following:

  - The date, location, and signature of the person making the determination.
  - How we determined that no permit-required confined space hazards exist.
  - Documentation will be available to entrants or their authorized representatives by posting at the entry to the space.

The following spaces can be classified as nonpermit spaces by following the listed methods of hazard elimination:

Date	**Location of Confined Space**	**Hazards**	**Method of Hazard Elimination**
(Input your specific information)			

NONPERMIT SPACE DOCUMENTATION FORM

Nonpermit confined space name or number	*(Insert your specific information here)*
Location	
Documentation	
Date	
Signature	

TRAINING

We will provide permit space training to employees at the following times:

- Before they are assigned permit space entry duties
- When their assigned duties change
- When there is a change in a space that creates hazards for which they have not been trained.

OUR RESPONSIBILITIES TO GENERAL CONTRACTORS

A copy of this Confined Space Entry Program will be provided to the general contractor.

RESCUE AND EMERGENCY SERVICES

We have developed the following rescue and emergency action plan:

ENTRY RESCUE PLANS

Following are 3 options for you to consider when developing rescue plans as outlined in the helpful tool, Evaluating Rescue Teams or Services, which is located in the Resources section of the Confined Spaces book.

Option 1

The entry supervisor will contact _*(name of rescue service)*_____ at _*(phone number)*___ to do both of the following:

- Coordinate entry
- Schedule an entry date and time.

Option 2

Complete the following information.

Train employees on the specific procedures for summoning the rescue and emergency services.

Name of rescue service: _____

Telephone number: _____

Location: _____

Approximate response time: _____

Name of emergency medical service: _____

Telephone number: _____

Location: _____

Approximate response time: _____

Option 3

The specific procedures for summoning rescue and emergency services for our workplace are:
_____
_____
_____
_____
_____

Following are the permit spaces that require stand-by rescue services during entry. The rescue service will be available at the space during the entire entry procedure to ensure prompt entrant rescue.

Permit Spaces Requiring Stand-by Rescue Services	
Permit space:	**Stand-by rescue service name and telephone number:**

PERMIT-REQUIRED CONFINED SPACE PROGRAM REVIEW

At least every 12 months we will conduct a review using canceled entry permits to identify any deficiencies in our program. We will conduct a review immediately if there is reason to believe that the program does not adequately protect our employees, such as the following situations:

- Unauthorized entry of a permit space
- Discovery of a hazard not covered by the permit
- Detection of a condition prohibited by the permit
- An injury or near-miss during entry
- Change in the use or configuration of the space

  or

- Employee complaints of permit space program ineffectiveness.

Corrective measures will be documented by revising the program. Employees will participate in revising the program, and will be trained on any changes.

If no permit space entry operations are conducted during the year, no review is needed.

ALLWEST UNDERGROUND, INC.
230 Frontage Rd. S.
Pacific, WA 98047
(253) 735-2204 • (800) 828-8505 • FAX (253) 735-2223
SEATTLE • PORTLAND • LOS ANGELES

CONFINED SPACE ENTRY PERMIT

INSTRUCTIONS (** Nobody will enter a confined space until permit is complete.)

1) Complete permit before entry begins. 2) Post permit at entrance to confined space until work in the confined space is complete. 3) Send permit to safety coordinator for review within 24 hours of completion of the work in the confined space.

GENERAL INFORMATION

JOBSITE:

PERMIT BEGINS: Date: _____ Time: _____ AM / PM PERMIT EXPIRES: Date: _____ Time _____ AM / PM

LOCATION & DESCRIPTION OF CONFINED SPACE:

PURPOSE OF ENTRY:

NAMES OF AUTHORIZED INDIVIDUALS (Please print.)

AUTHORIZED ENTRY SUPERVISOR: WILL HE/SHE SUPERVISE ENTRY: YES NO

AUTHORIZED ATTENDANTS	AUTHORIZED ENTRANTS
1)	1)
2)	2)
3)	3)
4)	4)

METHOD OF COMMUNICATION

DESCRIBE:

EQUIPMENT REQUIRED FOR ENTRY

Hard Hats	YES	NO
Coveralls	YES	NO
Boots	YES	NO
Safety Glasses	YES	NO
Safety Goggles	YES	NO
Face Shield	YES	NO
Ear Protection	YES	NO
Encapsulated Suit	YES	NO
Gloves	YES	NO
Safety Lights	YES	NO
Lockout Devices	YES	NO
Warning Signs	YES	NO
Fire Extinguisher	YES	NO
Ventilator/Blower	YES	NO
Non-Spark Tools	YES	NO
Rescue Equipment	YES	NO
Other: _____	YES	NO
Other: _____	YES	NO

RESPIRATORS REQUIRED FOR ENTRY

ARE RESPIRATORS REQUIRED? YES NO IF YES, WHAT TYPE:

AIR-PURIFYING: Half-Mask _____ Full-Face _____

Type Of Filters: _____

AIR-SUPPLIED: _____ and/or _____ and/or _____
Air Bottles Compressor Egress Bottles

SELF-CONTAINED BREATHING APPARATUS (SCBA): _____

*** NOTE: *Air-supplied respirators with egress bottle or SCBA respirators are required for atmospheres that are Immediately Dangerous To Life Or Health (IDLH).*

RESCUE EQUIPMENT REQUIRED FOR ENTRY

SCBA	YES	NO
Harness/Lifeline	YES	NO
Wristlets	YES	NO
Tripod/Manlift	YES	NO
Winch	YES	NO
First-Aid Kit	YES	NO
Stretcher	YES	NO

EMERGENCY SERVICES:

_____
Identify

_____
Method of Communication

_____
Phone Number

ISOLATION REQUIREMENTS (Please circle appropriate method, check YES or NO, and initial.)

	YES	NO	COMPLETED BY:
Electrical: DISCONNECT – LOCKOUT – TAGGED – Other:_____	___	___	_____
Mechanical Moving Parts: LATCH – CHAIN – CHOCK – BLOCK – Other:_____	___	___	_____
Hydraulics: BLANKED – BLEED – DISCONNECT – Other:_____	___	___	_____
Pipelines: BLANKED – BLEED – DISCONNECT – Other:_____	___	___	_____
Valves: LOCKOUT – DISCONNECT – TAG – Other:_____	___	___	_____
Belt Drives: DISCONNECT – TAG – Other:_____	___	___	_____
Chain Drives: DISCONNECT – TAG – Other:_____	___	___	_____
Shaft Drives: DISCONNECT – TAG – Other:_____	___	___	_____
Space Purged: INERT GAS – WATER – Other:_____	___	___	_____
Other: _____	___	___	_____
Other: _____	___	___	_____

ACCEPTABLE ENTRY CONDITIONS

OXYGEN: _____%	FLAMMABLE/COMBUSTIBLES: _____% LEL	OTHER: _____
HYDROGEN SULFIDE: _____ PPM	CARBON MONOXIDE: _____ PPM	OTHER: _____

TESTING AND MONITORING CHECKLIST

MAKE, MODEL & SERIAL # OF TESTING EQUIPMENT:

DATE EQUIPMENT CALIBRATED:	INTERMITTENT TESTING:	CONTINUOUS MONITORING:

	TEST 1	TEST 2	TEST 3	TEST 4	TEST 5	TEST 6	TEST 7	TEST 8
Date:	_____	_____	_____	_____	_____	_____	_____	_____
Time:	_____AM / PM	_____AM / PM	_____AM / PM	_____AM / PM	_____AM / PM	_____AM / PM	_____AM / PM	_____AM / PM
Oxygen:	_____%	_____%	_____%	_____%	_____%	_____%	_____%	_____%
LEL:	_____%	_____%	_____%	_____%	_____%	_____%	_____%	_____%
CO:	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM
H_2S:	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM	_____PPM
Tox:	_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____	_____
Tested by: (Initials)	_____	_____	_____	_____	_____	_____	_____	_____

CONFINED SPACE HAZARDS CHECKLIST (Please check YES or NO.)

	YES	NO	IF YES, HOW IS HAZARD CONTROLLED:
Oxygen Deficiency (<19.5%)	___	___	_____
Oxygen Enriched (>22%)	___	___	_____
Toxic Atmosphere	___	___	_____
Flammable/Combustible Atmosphere	___	___	_____
Electrical	___	___	_____
Mechanical	___	___	_____
Entrapment	___	___	_____
Pipelines	___	___	_____
Bacteria/Infectious	___	___	_____
Insects/Rodents	___	___	_____
Temperature	___	___	_____
Falls	___	___	_____
Other: _____	___	___	_____
Other: _____	___	___	_____

HOT WORK PERMIT

IS A HOT WORK PERMIT REQUIRED? YES NO IF YES, IS IT ATTACHED TO THIS PERMIT? YES NO

SIGNATURE OF ATTENDANTS AND ENTRANTS

The confined space job and it's safety aspects have been explained to us, and we have read and understand the above permit. We consider it safe to proceed with the confined space entry work. (Please sign, date and initial below.)

ATTENDANTS			ENTRANTS		
1)	Date:	Initials:	1)	Date:	Initials:
2)	Date:	Initials:	2)	Date:	Initials:
3)	Date:	Initials:	3)	Date:	Initials:
4)	Date:	Initials:	4)	Date:	Initials:

SIGNATURE OF ENTRY SUPERVISOR

SIGNATURE:	DATE:	TIME: AM / PM

CANCELLATION OF PERMIT

DATE CANCELED:	TIME CANCELED: AM / PM	CANCELED BY: (Signature)

REASON PERMIT WAS CANCELED:

EVALUATION (Review within 24 hours of completion of the work in the confined space.)

EVALUATED BY: (Signature)	DATE:	TIME: AM / PM