Type 611D/613D Perforated galvanized steel grate (ADA)

Product Features

- Certified to EN 1433 Load Class C - 56,000 lbs - 967 psi
- Uses 'DrainLok' boltless locking system
- Suitable for use with K200, KS200, H200K-13, and H200KS-13 channels
- Manufactured from 13 gauge galvanized steel
- Complies with ADA - American Disabilities Act of 1990 Section 4.5.4
- Bicycle Tire Penetration Resistant to AS 3996 - 2006



Specifications

General
The surface drainage system shall be ACO Drain K200, KS200, H200K-13, and H200KS-13, channels* complete with ACO Type 611D/613D perforated galvanized steel grate (ADA) with 'DrainLok' locking as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials
The covers shall be manufactured from galvanized steel and have ***minimum*** properties as follows:

- ***Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 967 psi***
- ***13 gauge galvanized steel***
- ***Intake area of 22.3 sq. in. (143.87 cm²) per half meter of grate***

The overall width of 9.41" (239mm) and overall length of 39.37" (1000mm) (Type 611D) and overall length of 19.69" (500mm) (Type 613D). Perforations measure 0.25" (6.4mm) in diameter.

Installation
The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as appropriate

ACO Specification Information

ACO Specification Information

ACO DRAIN

Type 611D/613D Perforated galvanized steel grate (ADA)

Plan view



Side elevation



Description	Part No.	Length inches *(mm)*	Width inches *(mm)*	Weight lbs.
DrainLok grate				
Type 611D Perforated galvanized steel grate	**138080**	39.37 *(1000)*	9.41 *(239)*	21.0
Type 613D Perforated galvanized steel grate	**138081**	19.69 *(500)*	9.41 *(239)*	10.5

'DrainLok' locking mechanism



ACO DrainLok™ is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The DrainLok™ mechanism simply clips into the channel edge rail for rapid installation. ACO DrainLok™ grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

ACO Polymer Products, Inc.

Northeast Sales Office
9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230
Toll free: (800) 543-4764
Fax: (440) 639-7235

West Sales Office
825 W. Beechcraft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-9899

Southeast Sales Office
4211 Pleasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on

Electronic Contact:
info@ACODrain.us
www.ACODrain.us

© August 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice.