🌻 Simple AI coding

The **Simple Mode** provides a streamlined AI coding workflow inside the normal left pane. It keeps the app structure familiar while reducing clutter.

Quick start: If you have roughly 5–100 pages of text, you can usually **just run everything** and get decent results. Press **Run all** and let it run. You can then go back and adjust the coding (edit links, tweak prompts, re-run specific steps) if you want. For longer texts or high-stakes coding, work incrementally: use the **source limit** in Auto-code (1, 5, 20%, 50%, 100%) and the **Links limit** in Recode to process a sample first, check quality, then scale up.
You can activate it with the **"Simple AI coding"** switch just below the Sources bar. When you sign up and choose to have AI options switched on and active, Simple AI is turned on by default. Other users can switch it on later if they wish.

AI usage consumes **credits** (see Responses Panel); credits renew monthly and do not roll over. Costs depend on model and workflow, but very roughly you might autocode around 30 pages for about 1 credit.

Users with dedicated AI plans receive a larger batch of AI credits each month; other users receive 10 free AI credits per month (the free credits do not stack with paid plans).

The Simple Workflow

When Simple Mode is active:

- the **Sources bar** is hidden (to keep focus),
- the right-hand output tabs stay available,
- the Create/Filter sub-tabs are replaced by one combined simple workflow panel.

The workflow is broken down into six straightforward sections:

1. **Run all**: Optional one-click runner. Press **Run all** to run Auto-code, then Revise codebook, then Recode in order.
2. Runner pre-steps: clears Filter Links, turns filter pipeline on, and (if links already exist) asks once whether to delete all links before starting. You always start fresh.
3. **Recode target suffix**: Choose blank (simpler — synthesised labels go straight into cause/effect) or e.g. _recoded (keeps raw labels, writes synthesised to temp columns so you can compare).

© Causal Map Ltd 2026 · causalmap.app · CC BY-NC 4.0

4. Runner uses one top-level confirmation and suppresses the extra per-step confirm dialogs.
5. **Background**: Give the AI project context before coding. A status tick indicates whether enough background text is set.
6. **Auto-code**: This is where the AI reads your documents and extracts causal links.
7. You can choose to process a small sample first (e.g., `1` or `5` sources) to test your prompt, or process `100%` of them.
8. The "Skip coded" switch ensures you don't waste time and money re-processing documents that already have links.
9. Default model in Simple AI is **Qwen Flash**.
10. **Revise codebook**: Once you have some causal links, the AI can review them and suggest a cleaner, more consistent list of factor labels (a "codebook"). The header tick shows whether the Recode codebook area currently contains suggestions.
11. Includes a **Target clusters** slider; see Target clusters.
12. Optional **Use automatic pre-clustering** switch (default OFF).
13. When pre-clustering is OFF, the AI tries to find the clusters directly from the factor list using the standard Revise codebook prompt. This prompt supports macro replacement: use `[number]` (or `[cluster_count]`) and the **effective** target cluster count is injected at run time (same as the slider logic below).
14. When pre-clustering is ON, the app first groups factor labels semantically using embeddings, then sends those clustered groups to the AI with a separate labelling prompt plus a **Representatives per cluster** slider (`8` to `20`, default `8`).
15. Pre-clustering is more systematic than asking the AI to find all clusters "in its head" from a long raw list. It reduces the black-box / WEIRD-data risk a bit, and may make it easier to preserve more unusual or divergent concepts instead of collapsing them into whatever the model finds most typical.
16. Default model in Simple AI is **Gemini 3 Flash Preview**.
17. **Recode**: Apply the AI's suggested, cleaned-up labels back to your existing causal links. Paste the codebook (from Revise codebook or your own), add a recode instruction, and run.
18. The AI returns index mappings (row → codebook item) rather than full label text, reducing tokens and improving reliability.
19. Default instruction: *"For each raw label give me the NUMBER of the best-matching codebook item by meaning. Use 0 when no codebook item fits. Return only codebook label numbers, never words. Never invent labels."*
20. **Skip recoded**: When on, only processes links that have at least one unrecoded label (cause or effect). Use this when recoding again to focus on remaining work.
21. **Links limit** (1, 5, 20%, 50%, 100%): When not 100%, a random sample of links is recoded. Non-sampled links keep their existing recoded values (or stay blank on first run).
22. The header progress bar is segmented: grey = empty recoded fields, orange = recoded equals original cause/effect, green = recoded non-empty and different.

© Causal Map Ltd 2026 · causalmap.app · CC BY-NC 4.0

23. Default model in Simple AI is **Qwen Flash**.
24. **Filter links**: The normal Filter Links panel appears as the final section of the same accordion, so filtering is part of one continuous simple flow.
25. After a successful **Run all**, filters are auto-set to: **Factor Frequency** (top `12`) → **Link Frequency** (top `30`). The global Label set controls which `cause`/`effect` columns Recode writes to (no separate "recode suffix" in this panel).

Run all (Simple AI)

- Optional sequencer for the three main AI actions.
- When enabled, **Go** runs Auto-code → Revise codebook → Recode, stopping on the first non-successful stage.
- Before running, it clears filters, enables pipeline, and deletes all existing links (if any) after one confirmation — so you always start from a clean slate.
- **Recode target**: Use the global Label set below the Sources bar. Create a new suffix there first if you want Recode to fill `cause_suffix` / `effect_suffix` instead of only the default columns.

Background (Simple AI)

- Sets shared project context used by AI coding prompts.
- The status tick indicates whether enough background text is present.

Auto-code (Simple AI)

- Runs AI coding across selected/all sources using your prompt and model.
- Use source limit + skip coded options to test quickly and avoid rework.
- **Add source prompt** (switch): when ON, each source's optional *Source Prompt* (edit above the source text when viewing a source) is prepended to your main Auto-code prompt for that source. Saved per project in the browser. Use when sources need different context; skip when one background prompt in **Background** is enough.
- **Status line** under the settings shows progress, per-chunk detail, and stop — same behaviour as the former "Code with AI" card.
- **Iterative prompts**: put `====` alone on a line in your prompt to split into separate iterations; later steps see prior user/assistant turns. Only the last iteration's result is written to links; all iterations appear in Responses.
- **Confirm** before a run shows model, chunking, word count, and cost estimate. **Stop** cancels after current chunk tasks finish.
- Timeouts scale by model and iteration count (cap ~540s total). **Concurrency** (1–5) is in Advanced; raise for speed, lower if you see 429/timeouts.
- Tips on using the prompt history (same chrome as other prompt fields).

© Causal Map Ltd 2026 · causalmap.app · CC BY-NC 4.0

- Default model is **Qwen Flash**.

Revise codebook (Simple AI)

- Suggests a cleaner consolidated codebook from existing links.
- Use this after you have enough coded links for a representative sample.
- Header tick indicates whether the Recode codebook area currently has content.
- **Target clusters**: see Target clusters.
- Optional **Use automatic pre-clustering** switch (default OFF).
- With pre-clustering OFF, the AI clusters the factor list directly from the Revise codebook prompt. That prompt supports `[number]` / `[cluster_count]`.
- With pre-clustering ON, embeddings are used first to group labels semantically, then the AI only has to label those grouped clusters. This is a bit more systematic, less dependent on the AI doing all clustering internally as a black box, and may help preserve unusual or divergent concepts.
- Pre-clustering also adds a **Representatives per cluster** slider (8-20, default 8) and uses a separate labelling prompt.
- Default model is **Gemini 3 Flash Preview**.

Target clusters (Revise codebook)

- The **Target clusters** control is a slider with **50 positions**. The **far left** is **Default**; moving right sets an explicit target of **2** through **50** clusters (one step per cluster count).
- **Default** (far left): the app derives a target count K from the number of **unique factor labels** n in the **current filtered pipeline** (same scope as Revise codebook): $K = \max(\lfloor n/3 \rfloor, 25)$ — at least **25**, or roughly **one label in three** as clusters, whichever is larger.
- **Explicit** positions (not Default): the requested K is the number shown by the slider (**2–50**). If K is **greater than** n, the run uses n instead (you cannot have more clusters than distinct labels); the app may show a short notice when that cap applies.
- Pre-clustering, embedding clustering, and `[number]` / `[cluster_count]` in prompts all use this **effective** K.

Recode (Simple AI)

- Applies your codebook back onto existing links, turning raw factor labels into cleaner synthesised ones.
- **Recoding** (radio buttons): **AI** — the model maps each raw label to a codebook line by index; **Magnetic** — embedding similarity to codebook lines (same magnet machinery as the pipeline's soft-recode path; similarity threshold). Both write hard updates to links; the names refer to the mapping method, not "soft recoding" in the filter sense.

© Causal Map Ltd 2026 · causalmap.app · CC BY-NC 4.0

- **Recode target**: the global Label set (`default` = standard `cause`/`effect`; a suffix = read/write `cause_suffix` / `effect_suffix` in `metadata.custom_columns`, with top-level `cause`/`effect` holding the default-set pair).
- Supports sampled recoding and skip-recoded behavior (skip-recoded only applies when using a non-default label set).
- Header bar shows recode coverage mix across all cause/effect recoded fields.
- Default model is **Qwen Flash**.

Filter links (Simple AI)

- This is the same Filter Links workflow, embedded as the final simple-ai accordion section.
- Use it to refine/select links before reviewing outputs on the right.
- Run-all completion auto-applies top-12 factor frequency, then top-30 link frequency (no longer injects the deprecated Temporary Factor Labels filter).

Advanced Settings

Each section header is clickable and opens/collapses its settings panel. Section headers also include contextual **Help** buttons. The advanced sections are inline (not flyouts), and only one section is expanded at a time.

Inside advanced panels you can:

- Edit the exact **Prompt** the AI uses.
- View your prompt history and load previous prompts.
- Change the **AI Model** (e.g., switch to a "Pro" model for complex reasoning, or a "Flash" model for speed).
- Tweak technical settings like chunk size, concurrency, and temperature.

© Causal Map Ltd 2026 · causalmap.app · CC BY-NC 4.0