

WDC WD181KFGX-68AFPN0 — 4ZGB861V

Captured from
Syn918p
on 2026-10-05 15:32 UTC. SMART interface:
`smartctl -a -d sat /dev/sdc`
.

Drive identity and health

Field	Captured value
Model	WDC WD181KFGX-68AFPN0 (Western Digital Red Pro)
Serial	4ZGB861V
Capacity	18,000,207,937,536 bytes (18.0 TB)
Rotation	7,200 rpm
Power-on hours	34,797
SMART overall	PASSED
Reallocated sectors	0
Pending sectors	0
Offline uncorrectable sectors	0
UDMA CRC errors	0
Temperature at capture	41 °C (min/max 20/53 °C)

Full SMART report

smartctl 6.5 (build date Mar 2 2021) [x86_64-linux-4.4.59+] (local build)
Copyright (C) 2002-16, Bruce Allen, Christian Franke, www.smartmontools.org



=== START OF INFORMATION SECTION ===

Model Family: Western Digital Red Pro
Device Model: WDC WD181KFGX-68AFPN0
Serial Number: 4ZGB861V
LU WWN Device Id: 5 000cca 2a6c51ed8
Firmware Version: 83.00A83
User Capacity: 18,000,207,937,536 bytes [18.0 TB]
Sector Sizes: 512 bytes logical, 4096 bytes physical
Rotation Rate: 7200 rpm
Form Factor: 3.5 inches
Device is: In smartctl database [for details use: -P show]
ATA Version is: Unknown(0x0ffc) (unknown minor revision code: 0x009c)
SATA Version is: SATA >3.2 (0x1ff), 6.0 Gb/s (current: 6.0 Gb/s)
Local Time is: Mon Oct 5 10:32:41 2026 -05
SMART support is: Available - device has SMART capability.
SMART support is: Enabled

=== START OF READ SMART DATA SECTION ===

SMART overall-health self-assessment test result: PASSED

General SMART Values:

Offline data collection status: (0x82) Offline data collection activity
was completed without error.

Auto Offline Data Collection: Enabled.

Self-test execution status: (0) The previous self-test routine completed
without error or no self-test has ever
been run.

Total time to complete Offline
data collection: (101) seconds.

Offline data collection
capabilities: (0x5b) SMART execute Offline immediate.
Auto Offline Data Collection on/off support.
Suspend Offline collection upon new
command.

Offline surface scan supported.
 Self-test supported.
 No Conveyance Self-test supported.
 Selective Self-test supported.
 SMART capabilities: (0x0003) Saves SMART data before entering
 power-saving mode.
 Supports SMART auto save timer.
 Error logging capability: (0x01) Error logging supported.
 General Purpose Logging supported.
 Short self-test routine
 recommended polling time: (2) minutes.
 Extended self-test routine
 recommended polling time: (1796) minutes.
 SCT capabilities: (0x003d) SCT Status supported.
 SCT Error Recovery Control supported.
 SCT Feature Control supported.
 SCT Data Table supported.

SMART Attributes Data Structure revision number: 16

Vendor Specific SMART Attributes with Thresholds:

ID#	ATTRIBUTE_NAME	FLAG	VALUE	WORST	THRESH	TYPE	UPDATED	
WHEN_FAILED	RAW_VALUE							
1	Raw_Read_Error_Rate	0x000b	100	100	001	Pre-fail	Always	-
0								
2	Throughput_Performance	0x0004	135	135	054	Old_age	Offline	-
100								
3	Spin_Up_Time	0x0007	083	083	001	Pre-fail	Always	-
350	(Average 351)							
4	Start_Stop_Count	0x0012	100	100	000	Old_age	Always	-
248								
5	Reallocated_Sector_Ct	0x0033	100	100	001	Pre-fail	Always	-
0								
7	Seek_Error_Rate	0x000a	100	100	001	Old_age	Always	-
0								
8	Seek_Time_Performance	0x0004	140	140	020	Old_age	Offline	-
15								
9	Power_On_Hours	0x0012	096	096	000	Old_age	Always	-
34797								
10	Spin_Retry_Count	0x0012	100	100	001	Old_age	Always	-
0								

12	Power_Cycle_Count	0x0032	099	099	000	Old_age	Always	-
110								
22	Helium_Level	0x0023	100	100	025	Pre-fail	Always	-
100								
192	Power-Off_Retract_Count	0x0032	100	100	000	Old_age	Always	-
2106								
193	Load_Cycle_Count	0x0012	100	100	000	Old_age	Always	-
2106								
194	Temperature_Celsius	0x0002	052	052	000	Old_age	Always	-
41	(Min/Max 20/53)							
196	Reallocated_Event_Count	0x0032	100	100	000	Old_age	Always	-
0								
197	Current_Pending_Sector	0x0022	100	100	000	Old_age	Always	-
0								
198	Offline_Uncorrectable	0x0008	100	100	000	Old_age	Offline	-
0								
199	UDMA_CRC_Error_Count	0x000a	100	100	000	Old_age	Always	-
0								

SMART Error Log Version: 1
No Errors Logged

SMART Self-test log structure revision number 1

Num	Test_Description	Status	Remaining	LifeTime(hours)	LBA_of_first_error
# 1	Short offline	Completed without error	00%	34594	-
# 2	Short offline	Completed without error	00%	33851	-
# 3	Short offline	Completed without error	00%	33108	-
# 4	Short offline	Completed without error	00%	32389	-
# 5	Short offline	Completed without error	00%	31646	-
# 6	Short offline	Completed without error	00%	31197	-
# 7	Short offline	Completed without error	00%	30926	-
# 8	Extended offline	Aborted by host	70%	30645	-
# 9	Short offline	Completed without error	00%	30183	-
#10	Short offline	Completed without error	00%	29512	-
#11	Short offline	Completed without error	00%	28768	-
#12	Short offline	Completed without error	00%	28025	-
#13	Short offline	Completed without error	00%	27306	-
#14	Short offline	Completed without error	00%	26563	-
#15	Extended offline	Aborted by host	70%	26281	-
#16	Short offline	Completed without error	00%	25843	-

#17 Short offline	Completed without error	00%	25101	-
#18 Short offline	Completed without error	00%	24356	-
#19 Short offline	Completed without error	00%	23638	-
#20 Short offline	Completed without error	00%	22893	-
#21 Short offline	Completed without error	00%	22175	-

SMART Selective self-test log data structure revision number 1

SPAN	MIN_LBA	MAX_LBA	CURRENT_TEST_STATUS
------	---------	---------	---------------------

1	0	0	Not_testing
2	0	0	Not_testing
3	0	0	Not_testing
4	0	0	Not_testing
5	0	0	Not_testing

Selective self-test flags (0x0):

After scanning selected spans, do NOT read-scan remainder of disk.

If Selective self-test is pending on power-up, resume after 0 minute delay.