

# WDC WD181KFGX-68AFPN0 — 4ZGBV7MV

Captured from  
Syn918p  
on 2026-10-05 15:32 UTC. SMART interface:  
`smartctl -a -d sat /dev/sdd`

## Drive identity and health

| Field                         | Captured value                                  |
|-------------------------------|-------------------------------------------------|
| Model                         | WDC WD181KFGX-68AFPN0 (Western Digital Red Pro) |
| Serial                        | 4ZGBV7MV                                        |
| Capacity                      | 18,000,207,937,536 bytes (18.0 TB)              |
| Rotation                      | 7,200 rpm                                       |
| Power-on hours                | 34,911                                          |
| SMART overall                 | PASSED                                          |
| Reallocated sectors           | 0                                               |
| Pending sectors               | 0                                               |
| Offline uncorrectable sectors | 0                                               |
| UDMA CRC errors               | 0                                               |
| Temperature at capture        | 40 °C (min/max 15/52 °C)                        |

# Full SMART report

---

smartctl 6.5 (build date Mar 2 2021) [x86\_64-linux-4.4.59+] (local build)  
Copyright (C) 2002-16, Bruce Allen, Christian Franke, www.smartmontools.org



## === START OF INFORMATION SECTION ===

Model Family: Western Digital Red Pro  
Device Model: WDC WD181KFGX-68AFPN0  
Serial Number: 4ZGBV7MV  
LU WWN Device Id: 5 000cca 2a6c5629b  
Firmware Version: 83.00A83  
User Capacity: 18,000,207,937,536 bytes [18.0 TB]  
Sector Sizes: 512 bytes logical, 4096 bytes physical  
Rotation Rate: 7200 rpm  
Form Factor: 3.5 inches  
Device is: In smartctl database [for details use: -P show]  
ATA Version is: Unknown(0x0ffc) (unknown minor revision code: 0x009c)  
SATA Version is: SATA >3.2 (0x1ff), 6.0 Gb/s (current: 6.0 Gb/s)  
Local Time is: Mon Oct 5 10:32:41 2026 -05  
SMART support is: Available - device has SMART capability.  
SMART support is: Enabled

## === START OF READ SMART DATA SECTION ===

SMART overall-health self-assessment test result: PASSED

### General SMART Values:

Offline data collection status: (0x82) Offline data collection activity  
was completed without error.

Auto Offline Data Collection: Enabled.

Self-test execution status: (0) The previous self-test routine completed  
without error or no self-test has ever  
been run.

Total time to complete Offline data collection: (101) seconds.

Offline data collection capabilities: (0x5b) SMART execute Offline immediate.

Auto Offline Data Collection on/off support.

Suspend Offline collection upon new command.

Offline surface scan supported.

Self-test supported.

No Conveyance Self-test supported.

Selective Self-test supported.

SMART capabilities: (0x0003) Saves SMART data before entering power-saving mode.

Supports SMART auto save timer.

Error logging capability: (0x01) Error logging supported. General Purpose Logging supported.

Short self-test routine recommended polling time: (2) minutes.

Extended self-test routine recommended polling time: (1845) minutes.

SCT capabilities: (0x003d) SCT Status supported. SCT Error Recovery Control supported.

SCT Feature Control supported. SCT Data Table supported.

SMART Attributes Data Structure revision number: 16

Vendor Specific SMART Attributes with Thresholds:

| ID#         | ATTRIBUTE_NAME          | FLAG   | VALUE | WORST | THRESH | TYPE     | UPDATED |   |
|-------------|-------------------------|--------|-------|-------|--------|----------|---------|---|
| WHEN_FAILED | RAW_VALUE               |        |       |       |        |          |         |   |
| 1           | Raw_Read_Error_Rate     | 0x000b | 100   | 100   | 001    | Pre-fail | Always  | - |
| 0           |                         |        |       |       |        |          |         |   |
| 2           | Throughput_Performance  | 0x0004 | 136   | 136   | 054    | Old_age  | Offline | - |
| 96          |                         |        |       |       |        |          |         |   |
| 3           | Spin_Up_Time            | 0x0007 | 083   | 083   | 001    | Pre-fail | Always  | - |
| 350         | (Average 350)           |        |       |       |        |          |         |   |
| 4           | Start_Stop_Count        | 0x0012 | 100   | 100   | 000    | Old_age  | Always  | - |
| 261         |                         |        |       |       |        |          |         |   |
| 5           | Reallocated_Sector_Ct   | 0x0033 | 100   | 100   | 001    | Pre-fail | Always  | - |
| 0           |                         |        |       |       |        |          |         |   |
| 7           | Seek_Error_Rate         | 0x000a | 100   | 100   | 001    | Old_age  | Always  | - |
| 0           |                         |        |       |       |        |          |         |   |
| 8           | Seek_Time_Performance   | 0x0004 | 140   | 140   | 020    | Old_age  | Offline | - |
| 15          |                         |        |       |       |        |          |         |   |
| 9           | Power_On_Hours          | 0x0012 | 096   | 096   | 000    | Old_age  | Always  | - |
| 34911       |                         |        |       |       |        |          |         |   |
| 10          | Spin_Retry_Count        | 0x0012 | 100   | 100   | 001    | Old_age  | Always  | - |
| 0           |                         |        |       |       |        |          |         |   |
| 12          | Power_Cycle_Count       | 0x0032 | 099   | 099   | 000    | Old_age  | Always  | - |
| 127         |                         |        |       |       |        |          |         |   |
| 22          | Helium_Level            | 0x0023 | 100   | 100   | 025    | Pre-fail | Always  | - |
| 100         |                         |        |       |       |        |          |         |   |
| 192         | Power-Off_Retract_Count | 0x0032 | 100   | 100   | 000    | Old_age  | Always  | - |
| 2126        |                         |        |       |       |        |          |         |   |
| 193         | Load_Cycle_Count        | 0x0012 | 100   | 100   | 000    | Old_age  | Always  | - |
| 2126        |                         |        |       |       |        |          |         |   |
| 194         | Temperature_Celsius     | 0x0002 | 053   | 053   | 000    | Old_age  | Always  | - |

40 (Min/Max 15/52)

|     |                         |        |     |     |     |         |         |   |
|-----|-------------------------|--------|-----|-----|-----|---------|---------|---|
| 196 | Reallocated_Event_Count | 0x0032 | 100 | 100 | 000 | Old_age | Always  | - |
| 0   |                         |        |     |     |     |         |         |   |
| 197 | Current_Pending_Sector  | 0x0022 | 100 | 100 | 000 | Old_age | Always  | - |
| 0   |                         |        |     |     |     |         |         |   |
| 198 | Offline_Uncorrectable   | 0x0008 | 100 | 100 | 000 | Old_age | Offline | - |
| 0   |                         |        |     |     |     |         |         |   |
| 199 | UDMA_CRC_Error_Count    | 0x000a | 100 | 100 | 000 | Old_age | Always  | - |
| 0   |                         |        |     |     |     |         |         |   |

SMART Error Log Version: 1

No Errors Logged

SMART Self-test log structure revision number 1

| Num | Test_Description | Status                  | Remaining | LifeTime(hours) | LBA_of_first_error |
|-----|------------------|-------------------------|-----------|-----------------|--------------------|
| # 1 | Short offline    | Completed without error | 00%       | 34709           | -                  |
| # 2 | Short offline    | Completed without error | 00%       | 33965           | -                  |
| # 3 | Short offline    | Completed without error | 00%       | 33222           | -                  |
| # 4 | Short offline    | Completed without error | 00%       | 32503           | -                  |
| # 5 | Short offline    | Completed without error | 00%       | 31760           | -                  |
| # 6 | Short offline    | Completed without error | 00%       | 31311           | -                  |
| # 7 | Short offline    | Completed without error | 00%       | 31041           | -                  |
| # 8 | Extended offline | Aborted by host         | 70%       | 30760           | -                  |
| # 9 | Short offline    | Completed without error | 00%       | 30298           | -                  |
| #10 | Short offline    | Completed without error | 00%       | 29626           | -                  |
| #11 | Short offline    | Completed without error | 00%       | 28883           | -                  |
| #12 | Short offline    | Completed without error | 00%       | 28140           | -                  |
| #13 | Short offline    | Completed without error | 00%       | 27421           | -                  |
| #14 | Short offline    | Completed without error | 00%       | 26677           | -                  |
| #15 | Extended offline | Aborted by host         | 70%       | 26396           | -                  |
| #16 | Short offline    | Completed without error | 00%       | 25958           | -                  |
| #17 | Short offline    | Completed without error | 00%       | 25215           | -                  |
| #18 | Short offline    | Completed without error | 00%       | 24471           | -                  |
| #19 | Short offline    | Completed without error | 00%       | 23753           | -                  |
| #20 | Short offline    | Completed without error | 00%       | 23008           | -                  |
| #21 | Short offline    | Completed without error | 00%       | 22290           | -                  |

SMART Selective self-test log data structure revision number 1

|      |         |         |                     |
|------|---------|---------|---------------------|
| SPAN | MIN_LBA | MAX_LBA | CURRENT_TEST_STATUS |
| 1    | 0       | 0       | Not_testing         |

|   |   |   |             |
|---|---|---|-------------|
| 2 | 0 | 0 | Not_testing |
| 3 | 0 | 0 | Not_testing |
| 4 | 0 | 0 | Not_testing |
| 5 | 0 | 0 | Not_testing |

Selective self-test flags (0x0):

After scanning selected spans, do NOT read-scan remainder of disk.

If Selective self-test is pending on power-up, resume after 0 minute delay.