

WDC WD140EFFX-68VBXN0 — QGKBJ6KT

Captured from
Syn918p
on 2026-10-05 15:31 UTC. SMART interface:
`smartctl -a -d sat /dev/sda`
.

Drive identity and health

Field	Captured value
Model	WDC WD140EFFX-68VBXN0
Serial	QGKBJ6KT
Capacity	14,000,519,643,136 bytes (14.0 TB)
Rotation	5,400 rpm
Power-on hours	41,334
SMART overall	PASSED
Reallocated sectors	0
Pending sectors	0
Offline uncorrectable sectors	0
Temperature at capture	36 °C (min/max 14/47 °C)

Full SMART report

smartctl 6.5 (build date Mar 2 2021) [x86_64-linux-4.4.59+] (local build)
Copyright (C) 2002-16, Bruce Allen, Christian Franke, www.smartmontools.org



=== START OF INFORMATION SECTION ===

Model Family: Red
Device Model: WDC WD140EFFX-68VBXN0
Serial Number: QGKBJ6KT
LU WWN Device Id: 5 000cca 29bef8373
Firmware Version: 81.00A81
User Capacity: 14,000,519,643,136 bytes [14.0 TB]
Sector Sizes: 512 bytes logical, 4096 bytes physical
Rotation Rate: 5400 rpm
Form Factor: 3.5 inches
Device is: In smartctl database [for details use: -P show]
ATA Version is: ACS-2, ATA8-ACS T13/1699-D revision 4
SATA Version is: SATA 3.2, 6.0 Gb/s (current: 6.0 Gb/s)
Local Time is: Mon Oct 5 10:31:20 2026 -05
SMART support is: Available - device has SMART capability.
SMART support is: Enabled

=== START OF READ SMART DATA SECTION ===

SMART overall-health self-assessment test result: PASSED

General SMART Values:

Offline data collection status: (0x82) Offline data collection activity
was completed without error.
Auto Offline Data Collection: Enabled.

Self-test execution status: (0) The previous self-test routine completed
without error or no self-test has ever
been run.

Total time to complete Offline
data collection: (101) seconds.

Offline data collection
capabilities: (0x5b) SMART execute Offline immediate.
Auto Offline Data Collection on/off support.
Suspend Offline collection upon new
command.

SMART capabilities: (0x0003) Offline surface scan supported.
 Self-test supported.
 No Conveyance Self-test supported.
 Selective Self-test supported.
 Saves SMART data before entering power-saving mode.
 Supports SMART auto save timer.
 Error logging capability: (0x01) Error logging supported.
 General Purpose Logging supported.
 Short self-test routine recommended polling time: (2) minutes.
 Extended self-test routine recommended polling time: (1516) minutes.
 SCT capabilities: (0x003d) SCT Status supported.
 SCT Error Recovery Control supported.
 SCT Feature Control supported.
 SCT Data Table supported.

SMART Attributes Data Structure revision number: 16

Vendor Specific SMART Attributes with Thresholds:

ID#	ATTRIBUTE_NAME	FLAG	VALUE	WORST	THRESH	TYPE	UPDATED	
WHEN_FAILED	RAW_VALUE							
1	Raw_Read_Error_Rate	0x000b	100	100	001	Pre-fail	Always	-
0								
2	Throughput_Performance	0x0004	135	135	054	Old_age	Offline	-
108								
3	Spin-up_Time	0x0007	081	081	001	Pre-fail	Always	-
30089675133								
4	Start/Stop_Count	0x0012	100	100	000	Old_age	Always	-
291								
5	Re-allocated_Sector_Count	0x0033	100	100	001	Pre-fail	Always	-
0								
7	Seek_Error_Rate	0x000a	100	100	001	Old_age	Always	-
0								
8	Seek_Time_Performance	0x0004	133	133	020	Old_age	Offline	-
18								
9	Power-on_Hours_Count	0x0012	095	095	000	Old_age	Always	-
41334								
10	Spin_Retry_Count	0x0012	100	100	001	Old_age	Always	-
0								

12 Drive_Power_Cycle_Count 291	0x0032	096	096	000	Old_age	Always	-
22 Internal_Environment_Status_(Helium_Status) 100	0x0023	100	100	025	Pre-fail	Always	-
192 Power_Off_Retract_Count 1821	0x0032	100	100	000	Old_age	Always	-
193 Load/Unload_Cycles 1821	0x0012	100	100	000	Old_age	Always	-
194 Temperature 36 (Min/Max 14/47)	0x0002	045	045	000	Old_age	Always	-
196 Relocation_Event_Count 0	0x0032	100	100	000	Old_age	Always	-
197 Current_Pending_Sector_Count 0	0x0022	100	100	000	Old_age	Always	-
198 Off-Line_Scan_Uncorrectable_Sector_Count 0	0x0008	100	100	000	Old_age	Offline	-
199 Ultra_DMA_CRC_Error_Count/Frame_Error_Count 0	0x000a	100	100	000	Old_age	Always	-

SMART Error Log Version: 1
No Errors Logged

SMART Self-test log structure revision number 1

Num	Test_Description	Status	Remaining	LifeTime(hours)	LBA_of_first_error
# 1	Short offline	Completed without error	00%	41131	-
# 2	Short offline	Completed without error	00%	40388	-
# 3	Short offline	Completed without error	00%	39645	-
# 4	Short offline	Completed without error	00%	38926	-
# 5	Short offline	Completed without error	00%	38183	-
# 6	Short offline	Completed without error	00%	37734	-
# 7	Short offline	Completed without error	00%	37463	-
# 8	Extended offline	Aborted by host	10%	37182	-
# 9	Short offline	Completed without error	00%	36720	-
#10	Short offline	Completed without error	00%	36049	-
#11	Short offline	Completed without error	00%	35305	-
#12	Short offline	Completed without error	00%	34562	-
#13	Short offline	Completed without error	00%	33843	-
#14	Short offline	Completed without error	00%	33099	-
#15	Extended offline	Aborted by host	10%	32819	-
#16	Short offline	Completed without error	00%	32380	-

#17	Short offline	Completed without error	00%	31637	-
#18	Short offline	Completed without error	00%	30893	-
#19	Short offline	Completed without error	00%	30174	-
#20	Short offline	Completed without error	00%	29431	-
#21	Short offline	Completed without error	00%	28712	-

SMART Selective self-test log data structure revision number 1

SPAN	MIN_LBA	MAX_LBA	CURRENT_TEST_STATUS
------	---------	---------	---------------------

1	0	0	Not_testing
2	0	0	Not_testing
3	0	0	Not_testing
4	0	0	Not_testing
5	0	0	Not_testing

Selective self-test flags (0x0):

After scanning selected spans, do NOT read-scan remainder of disk.

If Selective self-test is pending on power-up, resume after 0 minute delay.