

Package ‘ICAMS’

June 8, 2019

Type Package

Title In-depth Characterization and Analysis of Mutational Signatures

Version 2.0.0

Author Steve Rozen, Nanhai Jiang, Arnoud Boot, Mo Liu

Maintainer Steve Rozen <steverozen@gmail.com>

Description A toolkit for analysis and visualization of experimentally elucidated mutational signatures -- the kind of analysis and visualization presented in Boot et al., "In-depth characterization of the cisplatin mutational signature in human cell lines and in esophageal and liver tumors", 2018, <https://genome.cshlp.org/content/28/5/654.short>. This package has functions to read in variant call files and to collate the corresponding catalogs of mutational spectra and to analyze and plot catalogs of mutational spectra and signatures.

License GPL-3

Encoding UTF-8

LazyData true

Language en-US

biocViews

Imports Biostrings,
BSgenome,
BSgenome.Hsapiens.1000genomes.hs37d5,
BSgenome.Hsapiens.UCSC.hg38,
data.table,
dplyr,
GenomeInfoDb,
GenomicRanges,
graphics,
grDevices,
IRanges,
RColorBrewer,
stats,
stringi,
utils

Depends R (>= 3.5),

RoxygenNote 6.1.1

Suggests testthat

R topics documented:

as.catalog	2
CatalogRowOrder	3
CollapseCatalog	3
FindDelMH	4
GetVAF	6
ICAMS	6
MutectVCFFilesToCatalog	9
MutectVCFFilesToCatalogAndPlotToPdf	10
PlotCatalog	11
PlotCatalogToPdf	12
ReadAndSplitMutectVCFs	13
ReadAndSplitStrelkaSBSVCFs	13
ReadCatalog	14
ReadStrelkaIDVCFs	15
revc	15
StrelkaIDVCFFilesToCatalog	16
StrelkaIDVCFFilesToCatalogAndPlotToPdf	16
StrelkaSBSVCFFilesToCatalog	17
StrelkaSBSVCFFilesToCatalogAndPlotToPdf	18
TranscriptRanges	19
TransformCatalog	20
VCFsToDBSCatalogs	21
VCFsToIDCatalogs	21
VCFsToSBSCatalogs	22
WriteCatalog	22
Index	24

as.catalog	<i>Create attributes of a catalog</i>
------------	---------------------------------------

Description

Create attributes of a catalog

Usage

```
as.catalog(catalog, ref.genome, region, catalog.type)
```

Arguments

catalog	A catalog as defined in ICAMS .
ref.genome	A ref.genome argument as described in ICAMS .
region	A character string acting as a region identifier, one of "genome", "exome".
catalog.type	One of "counts", "density", "counts.signature", "density.signature".

Value

The original catalog with the following attributes added: ref.genome, region, type, abundance, class.

CatalogRowOrder	<i>Standard order of row names in a catalog.</i>
-----------------	--

Description

This data is designed for those who need to create their own catalogs from formats not supported by this package. The rownames denote the mutation types. For example, for SBS96 catalogs, the rowname AGAT represents a mutation from AGA > ATA.

Usage

```
catalog.row.order
```

Format

A list of character vectors indicating the standard orders of row names in catalogs.

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

CollapseCatalog	<i>"Collapse" a catalog.</i>
-----------------	------------------------------

Description

"Collapse" a catalog.

Usage

```
Collapse192CatalogTo96(catalog)
```

```
Collapse1536CatalogTo96(catalog)
```

```
Collapse144CatalogTo78(catalog)
```

Arguments

catalog	A catalog as defined in ICAMS .
---------	---

Details

Collapse192CatalogTo96 Collapse an SBS 192 catalog to an SBS 96 catalog.

Collapse1536CatalogTo96 Collapse an SBS 1536 catalog to an SBS 96 catalog.

Collapse144CatalogTo78 Collapse a DBS 144 catalog to a DBS 78 catalog.

Value

A catalog as defined in [ICAMS](#).

FindDelMH

*Return the length of microhomology at a deletion.***Description**

Return the length of microhomology at a deletion.

Usage

```
FindDelMH(context, deleted.seq, pos, trace = 0)
```

Arguments

context	The deleted sequence plus ample surrounding sequence on each side (at least as long as del.sequence).
deleted.seq	The deleted sequence in context.
pos	The position of del.sequence in context.
trace	If > 0, cat various messages.

Details

This function is primarily for internal use, but we export it to document the underlying logic.

Example:

GGCTAGTT aligned to GGCTAGAACTAGTT with a deletion represented as:

```
GGCTAGAACTAGTT
GG-----CTAGTT  GGCTAGTT  GG[CTAGAA]CTAGTT
                        ----  ----
```

Presumed repair mechanism leading to this:

```
....
GGCTAGAACTAGTT
CCGATCTTGATCAA
```

=>

```
....
GGCTAG      TT
CC      GATCAA
      ....
```

=>

```
GGCTAGTT
CCGATCAA
```

Variant-caller software can represent the same deletion in several different, but completely equivalent, ways.

```
GGC-----TAGTT GGCTAGTT GGC[TAGAAC]TAGTT
      * --- * ---

GGCT-----AGTT GGCTAGTT GGCT[AGAACT]AGTT
      ** -- ** --

GGCTA-----GTT GGCTAGTT GGCTA[GAACTA]GTT
      *** - *** -

GGCTAG-----TT GGCTAGTT GGCTAG[AACTAG]TT
      ****  ****
```

A deletion in a *repeat* can also be represented in several different ways. A deletion in a repeat is abstractly equivalent to microhomology that spans the entire deleted sequence. For example;

```
GACTAGCTAGTT
GACTA----GTT GACTAGTT GACTA[GCTA]GTT
      *** -*** -
```

is really a repeat

```
GACTAG----TT GACTAGTT GACTAG[CTAG]TT
      ****  ----

GACT----AGTT GACTAGTT GACT[AGCT]AGTT
      **  ---** --
```

This function only flags this case with a -1 return; it does not figure out the repeat extent.

This function finds:

1. The maximum match of undeleted sequence to the left of the deletion that is identical to the right end of the deleted sequence, and
2. The maximum match of undeleted sequence to the right of the deletion that is identical to the left end of the deleted sequence.

The microhomology sequence is the concatenation of items (1) and (2).

Value

The length of the maximum microhomology of `del` . sequence in context.

GetVAF	<i>Extract the VAFs (variant allele frequencies) from a VCF file.</i>
--------	---

Description

Extract the VAFs (variant allele frequencies) from a VCF file.

Usage

```
GetStrelkaVAF(vcf)
```

```
GetMutectVAF(vcf)
```

Arguments

`vcf` said VCF as a `data.frame`.

Value

A vector of VAFs, one for each row of `vcf`.

ICAMS	<i>ICAMS: In-depth Characterization and Analysis of Mutational Signatures</i>
-------	---

Description

A toolkit for analysis and visualization of experimentally elucidated mutational signatures – the kind of analysis and visualization presented in Boot et al., "In-depth characterization of the cisplatin mutational signature in human cell lines and in esophageal and liver tumors", *Genome Research*, 2018, <https://genome.cshlp.org/content/28/5/654.short>.

Details

ICAMS can read in variant call files (VCFs) generated by Strelka or Mutect, and collate the mutations into "catalogs" of mutational spectra. ICAMS can create and plot catalogs of mutational spectra or signatures for single base substitutions (SBS), double base substitutions (DBS), and small insertions and deletions (ID). It can also read and write these catalogs.

Catalogs

A key data type in ICAMS is a "catalog" of mutation counts, of mutation densities, or of mutational signatures.

A catalog has one of the following types:

1. Matrix of mutation counts (one column per sample), representing (counts-based) mutational spectra.
2. Matrix of mutation densities, i.e. mutations per occurrences of source sequences (one column per sample), representing (density-based) mutational spectra.

3. Matrix of mutational signatures, which are similar to spectra. However where spectra consist of counts or densities of mutations in each mutation class (e.g. $ACA > AAA$, $ACA > AGA$, $ACA > ATA$, $ACC > AAC$, ...), signatures consist of the proportions of mutations in each class (with all the proportions summing to 1). A mutational signature can be based on either:
 - mutation counts (a "counts-based mutational signature"), or
 - mutation densities (a "density-based mutational signature").

Many functions take the argument `catalog.type`, with possible values "counts", "density", "counts.signature", or "density.signature", corresponding to the types of catalogs in items 1, 2, 3.1, and 3.2, above.

Catalogs are implemented as S3 objects of class `matrix` and one of the ICAMS classes `SBS96Catalog`, `SBS192Catalog`, `SBS1536Catalog`, `DBS78Catalog`, `DBS144Catalog`, `DBS136Catalog`, `IndelCatalog`.

If you need to create a catalog from a source other than this package (i.e. other than with [ReadCatalog](#) or [StrelkaSBSVCFFilesToCatalog](#), [MutectVCFFilesToCatalog](#), etc.), then use `as.catalog`.

Creating catalogs from variant call files (VCF files)

1. [StrelkaSBSVCFFilesToCatalog](#) creates 3 SBS catalogs (96, 192, 1536) and 3 DBS catalogs (78, 136, 144) from the Strelka SBS VCFs.
2. [StrelkaIDVCFFilesToCatalog](#) creates ID (indel) catalog from the Strelka ID VCFs.
3. [MutectVCFFilesToCatalog](#) creates 3 SBS catalogs (96, 192, 1536), 3 DBS catalogs (78, 136, 144) and ID (indel) catalog from the Mutect VCFs.

Plotting catalogs

The [PlotCatalog](#) functions plot mutational spectra for one sample or plot one mutational signature.

The [PlotCatalogToPdf](#) functions plot catalogs of mutational spectra or of mutational signatures to a PDF file.

Creating catalogs from variant call files (VCF files) and plot them to PDF

1. [StrelkaSBSVCFFilesToCatalogAndPlotToPdf](#) creates 3 SBS catalogs (96, 192, 1536), 3 DBS catalogs (78, 136, 144) from the Strelka SBS VCFs and plot them to PDF.
2. [StrelkaIDVCFFilesToCatalog](#) creates ID (indel) catalog from the Strelka ID VCFs and plot it to PDF.
3. [MutectVCFFilesToCatalog](#) creates 3 SBS catalogs (96, 192, 1536), 3 DBS catalogs (78, 136, 144), ID (indel) catalog from the Mutect VCFs and plot them to PDF.

The `ref.genome` argument

Many functions take the argument `ref.genome`. This can be either

1. A variable from the Bioconductor [BSgenome](#) package that contains a particular reference genome, for example `BSgenome.Hsapiens.1000genomes.hs37d5`. `BSgenome::available.genomes()` returns the available genomes.
2. The strings "hg38" or "GRCh38" are shorthand for `BSgenome.Hsapiens.UCSC.hg38`, and the strings "hg19" or "GRCh37" are shorthand for `BSgenome.Hsapiens.1000genomes.hs37d5`.

The Bioconductor BSgenome package

This package will be installed automatically if [ICAMS](#) is installed with `devtools::install_local` or with `devtools::install_github`. Otherwise you must manually install BSgenome and the necessary genomes, e.g.

```
BSgenome.Hsapiens.1000genomes.hs37d5.
```

See instructions at

<https://bioconductor.org/packages/release/bioc/html/BSgenome.html>.

Genomes other than the two human genomes mentioned above must be installed manually.

Use [available.genomes](#) to get the list of available genomes.

Writing catalogs

The [WriteCatalog](#) functions write a catalog of mutational spectra or of mutational signatures to a file.

Reading catalogs

The [ReadCatalog](#) functions read a file that contains a catalog of mutational spectra or of signatures in standardized format.

Transforming catalogs

The [TransformCatalog](#) function transforms catalogs of mutational spectra or signatures to account for differing abundances of the source sequence of the mutations in the genome.

For example, mutations from ACG are much rarer in the human genome than mutations from ACC simply because CG dinucleotides are rare in the genome. Consequently, there are two possible representations of mutational spectra or signatures. One representation is based on mutation counts as observed in a given genome, and this approach is widely used, as, for example, at <https://cancer.sanger.ac.uk/cosmic/signatures>, which presents signatures based on observed mutation counts in the human genome. We call these "counts-based spectra" or "counts-based signatures".

Alternatively, mutational spectra or signatures can be represented as mutations per source sequence, for example the number of ACT > AGT mutations occurring at all ACT 3-mers in a genome. We call these "density-based spectra" or "density-based signatures".

This function can also transform spectra based on observed genome-wide counts to "density"-based catalogs. In density-based catalogs mutations are expressed as mutations per source sequences. For example, a density-based catalog represents the proportion of ACCs mutated to ATCs, the proportion of ACGs mutated to ATGs, etc. This is different from counts-based mutational spectra catalogs, which contain the number of ACC > ATC mutations, the number of ACG > ATG mutations, etc.

This function can also transform observed-count based spectra or signatures from genome to exome based counts, or between different species (since the abundances of source sequences vary between genome and exome and between species).

Collapsing catalogs

The [CollapseCatalog](#) functions

1. take a mutational spectrum or signature catalog that is based on a fined-grained set of features (for example, single-nucleotide substitutions in the context of the preceding and following 2 bases), and
2. collapse it to a catalog based on a coarser-grained set of features (for example, single-nucleotide substitutions in the context of the immediately preceding and following bases).

Data

1. [CatalogRowOrder](#) Standard order of rownames in a catalog. The rownames of encode the type of each mutation. The rownames denote the mutation types. For example, for SBS96 catalogs, the rowname AGAT represents a mutation from AGA > ATA.
2. [TranscriptRanges](#) Transcript ranges and strand information for a particular reference genome.

MutectVCFFilesToCatalog

Create SBS, DBS and Indel catalogs from Mutect VCF files

Description

Create 3 SBS catalogs (96, 192, 1536), 3 DBS catalogs (78, 136, 144) and Indel catalog from the Mutect VCFs specified by files

Usage

```
MutectVCFFilesToCatalog(files, ref.genome, trans.ranges, region)
```

Arguments

<code>files</code>	Character vector of file paths to the Mutect VCF files.
<code>ref.genome</code>	A <code>ref.genome</code> argument as described in ICAMS .
<code>trans.ranges</code>	a data.table which contains transcript range and strand information. Please refer to TranscriptRanges for more details.
<code>region</code>	A character string acting as a region identifier, one of "genome", "exome".

Details

This function calls [VCFsToSBSCatalogs](#), [VCFsToDBSCatalogs](#) and [VCFsToIDCatalogs](#)

Value

A list of 3 SBS catalogs (one each for 96, 192, and 1536), 3 DBS catalogs (one each for 78, 136, and 144) and ID catalog. Each catalog has attributes added. See [as.catalog](#) for more details.

Note

SBS 192 and DBS 144 catalogs include only mutations in transcribed regions.

MutectVCFFilesToCatalogAndPlotToPdf

Create SBS, DBS and Indel catalogs from Mutect VCF files and plot them to PDF

Description

Create 3 SBS catalogs (96, 192, 1536), 3 DBS catalogs (78, 136, 144) and Indel catalog from the Mutect VCFs specified by files and plot them to PDF

Usage

```
MutectVCFFilesToCatalogAndPlotToPdf(files, ref.genome, trans.ranges,
  region, file, no.context)
```

Arguments

files	Character vector of file paths to the Mutect VCF files.
ref.genome	A ref.genome argument as described in ICAMS .
trans.ranges	a data.table which contains transcript range and strand information. Please refer to TranscriptRanges for more details.
region	A character string acting as a region identifier, one of "genome", "exome".
file	The name of the PDF file to be produced.
no.context	A logical value indicating whether there is preceding and following base context for the plot. Only implemented for SBS192Catalog.

Details

This function calls [MutectVCFFilesToCatalog](#) and [PlotCatalogToPdf](#)

Value

A list of 3 SBS catalogs (one each for 96, 192, and 1536), 3 DBS catalogs (one each for 78, 136, and 144), Indel catalog and their graphs plotted to PDF with specified file name. Each catalog has attributes added. See [as.catalog](#) for more details.

Note

SBS 192 and DBS 144 catalogs include only mutations in transcribed regions.

PlotCatalog	<i>Plot one spectrum or signature.</i>
-------------	---

Description

Plot the spectrum of **one** sample or plot **one** signature. The type of graph is based on one attribute("catalog.type") of the input catalog. You can first use [TransformCatalog](#) to get different types of catalog and then do the plotting.

Usage

```
PlotCatalog(catalog, no.context, cex, grid, upper, xlabel)
```

Arguments

catalog	A catalog as defined in ICAMS with attributes added. See as.catalog for more details.
no.context	A logical value indicating whether there is preceding and following base context for the plot. Only implemented for SBS192Catalog.
cex	A numerical value giving the amount by which mutation class labels, mutation counts(if it exists), y axis and its labels, x axis labels and its annotations(if it exists), sample name and legend(if it exists) should be magnified relative to the default. Only implemented for SBS96Catalog, SBS192Catalog and DBS144Catalog.
grid	A logical value indicating whether to draw grid lines. Only implemented for SBS96Catalog.
upper	A logical value indicating whether to draw horizontal lines and the names of major mutation class on top of graph. Only implemented for SBS96Catalog.
xlabels	A logical value indicating whether to draw x axis labels. Only implemented for SBS96Catalog.

Value

```
invisible(TRUE)
```

Note

The sizes of repeats involved in deletions range from 0 to 5+ in the mutational-spectra and signature catalog rownames, but for plotting and end-user documentation they range from 1 to 6+.

PlotCatalogToPdf	<i>Plot catalog to a PDF file.</i>
------------------	------------------------------------

Description

Plot catalog to a PDF file. The type of graph is based on one attribute("catalog.type") of the input catalog. You can first use [TransformCatalog](#) to get different types of catalog and then do the plotting.

Usage

```
PlotCatalogToPdf(catalog, file, no.context, cex, grid, upper, xlabel)
```

Arguments

catalog	A catalog as defined in ICAMS with attributes added. See as.catalog for more details.
file	The name of the PDF file to be produced.
no.context	A logical value indicating whether there is preceding and following base context for the plot. Only implemented for SBS192Catalog.
cex	A numerical value giving the amount by which mutation class labels, mutation counts(if it exists), y axis and its labels, x axis labels and its annotations(if it exists), sample name and legend(if it exists) should be magnified relative to the default. Only implemented for SBS96Catalog, SBS192Catalog and DBS144Catalog.
grid	A logical value indicating whether to draw grid lines. Only implemented for SBS96Catalog.
upper	A logical value indicating whether to draw horizontal lines and the names of major mutation class on top of graph. Only implemented for SBS96Catalog.
xlabels	A logical value indicating whether to draw x axis labels. Only implemented for SBS96Catalog.

Value

```
invisible(TRUE)
```

Note

The sizes of repeats involved in deletions range from 0 to 5+ in the mutational-spectra and signature catalog rownames, but for plotting and end-user documentation they range from 1 to 6+.

`ReadAndSplitMutectVCFs`*Read and split Mutect VCF files.*

Description

Read and split Mutect VCF files.

Usage

```
ReadAndSplitMutectVCFs(files)
```

Arguments

`files` Character vector of file paths to the Mutect VCF files.

Value

A list with 3 in-memory VCFs and two left-over VCF-like data frames with rows that were not incorporated into the first 3 VCFs, as follows:

1. SBS VCF with only single base substitutions.
2. DBS VCF with only doublet base substitutions as called by Mutect.
3. ID VCF with only small insertions and deletions.
4. `other.subs` VCF like `data.frame` with rows for coordinate substitutions involving 3 or more nucleotides, e.g. `ACT > TGA` or `AACT > GGTA`.
5. `multiple.alternative.alleles` VCF like `data.frame` with rows for variants with multiple alternative alleles, for example `ACT` mutated to both `AGT` and `ACT` at the same position.

See Also

[MutectVCFFilesToCatalog](#)

`ReadAndSplitStrelkaSBSVCFs`*Read and split Strelka SBS VCF files.*

Description

Read and split Strelka SBS VCF files.

Usage

```
ReadAndSplitStrelkaSBSVCFs(files)
```

Arguments

`files` Character vector of file paths to the Strelka SBS VCF files.

Value

A list of 3 in-memory objects as follows:

1. `SBS.vcfs` List of data.frames of pure SBS mutations – no DBS or 3+BS mutations.
2. `DBS.vcfs` List of data.frames of pure DBS mutations – no SBS or 3+BS mutations.
3. `ThreePlus` List of data.tables with the key `CHROM`, `LOW.POS`, `HIGH.POS`. containing rows that that in the input that did not represent SBSs or DBSs.

See Also

[StrelkaSBSVCFFilesToCatalog](#)

ReadCatalog	<i>Read catalog.</i>
-------------	----------------------

Description

Read a catalog in standardized format from path.

Usage

```
ReadCatalog(file, ref.genome, region, catalog.type, strict = TRUE)
```

Arguments

<code>file</code>	Path to a catalog on disk in the standardized format.
<code>ref.genome</code>	A <code>ref.genome</code> argument as described in ICAMS .
<code>region</code>	One of "genome", "exome".
<code>catalog.type</code>	One of "counts", "density", "counts.signature", "density.signature".
<code>strict</code>	If TRUE, do additional checks on the input, and stop if the checks fail.

Details

See also [WriteCatalog](#)

Value

A catalog in standard in-memory format with attributes added. See [as.catalog](#) for more details.

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

ReadStrelkaIDVCFs	<i>Read Strelka ID (insertion and deletion) VCF files.</i>
-------------------	--

Description

Read Strelka ID (insertion and deletion) VCF files.

Usage

ReadStrelkaIDVCFs(files)

Arguments

files	Character vector of file paths to the VCF files.
-------	--

Value

A list of vcfs from files.

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

See Also

[StrelkaIDVCFFilesToCatalog](#)

revc	<i>Reverse complement every string in string.vec.</i>
------	---

Description

Reverse complement every string in string.vec.

Usage

revc(string.vec)

Arguments

string.vec	a vector of type character.
------------	-----------------------------

Value

A vector of type characters with the reverse complement of every string in string.vec.

StrelkaIDVCFFilesToCatalog*Create ID (indel) catalog from Strelka ID VCF files*

Description

Create ID (indel) catalog from the Strelka ID VCFs specified by files

Usage

```
StrelkaIDVCFFilesToCatalog(files, ref.genome, region)
```

Arguments

files	Character vector of file paths to the Strelka ID VCF files.
ref.genome	A ref.genome argument as described in ICAMS .
region	A character string acting as a region identifier, one of "genome", "exome".

Details

This function calls [VCFsToIDCatalogs](#)

Value

An ID (indel) catalog with attributes added. See [as.catalog](#) for more details.

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

StrelkaIDVCFFilesToCatalogAndPlotToPdf*Create ID (indel) catalog from Strelka ID VCF files and plot them to PDF*

Description

Create ID (indel) catalog from the Strelka ID VCFs specified by files and plot them to PDF

Usage

```
StrelkaIDVCFFilesToCatalogAndPlotToPdf(files, ref.genome, region, file)
```

Arguments

files	Character vector of file paths to the Strelka ID VCF files.
ref.genome	A ref.genome argument as described in ICAMS .
region	A character string acting as a region identifier, one of "genome", "exome".
file	The name of the PDF file to be produced.

Details

This function calls [VCFsToIDCatalogs](#) and [PlotCatalogToPdf](#)

Value

An ID (indel) catalog and its graph plotted to PDF with specified file name. The ID (indel) catalog has attributes added. See [as.catalog](#) for more details.

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

StrelkaSBSVCFFilesToCatalog

Create SBS and DBS catalogs from Strelka SBS VCF files.

Description

Create 3 SBS catalogs (96, 192, 1536) and 3 DBS catalogs (78, 136, 144) from the Strelka SBS VCFs specified by files

Usage

```
StrelkaSBSVCFFilesToCatalog(files, ref.genome, trans.ranges, region)
```

Arguments

files	Character vector of file paths to the Strelka SBS VCF files.
ref.genome	A ref.genome argument as described in ICAMS .
trans.ranges	a data.table which contains transcript range and strand information. Please refer to TranscriptRanges for more details.
region	A character string acting as a region identifier, one of "genome", "exome".

Details

This function calls [VCFsToSBSCatalogs](#) and [VCFsToDBSCatalogs](#).

Value

A list of 3 SBS catalogs (one each for 96, 192, and 1536) and 3 DBS catalogs (one each for 78, 136, and 144). Each catalog has attributes added. See [as.catalog](#) for more details.

Note

SBS 192 and DBS 144 catalog only contains mutations in transcribed regions.

StrelkaSBSVCFFilesToCatalogAndPlotToPdf

Create SBS and DBS catalogs from Strelka SBS VCF files and plot them to PDF

Description

Create 3 SBS catalogs (96, 192, 1536) and 3 DBS catalogs (78, 136, 144) from the Strelka SBS VCFs specified by files and plot them to PDF

Usage

```
StrelkaSBSVCFFilesToCatalogAndPlotToPdf(files, ref.genome, trans.ranges,
  region, file, no.context)
```

Arguments

files	Character vector of file paths to the Strelka SBS VCF files.
ref.genome	A ref.genome argument as described in ICAMS .
trans.ranges	a data.table which contains transcript range and strand information. Please refer to TranscriptRanges for more details.
region	A character string acting as a region identifier, one of "genome", "exome".
file	The name of the PDF file to be produced.
no.context	A logical value indicating whether there is preceding and following base context for the plot. Only implemented for SBS192Catalog.

Details

This function calls [StrelkaSBSVCFFilesToCatalog](#) and [PlotCatalogToPdf](#)

Value

A list of 3 SBS catalogs (one each for 96, 192, and 1536), 3 DBS catalogs (one each for 78, 136, and 144) and their graphs plotted to PDF with specified file name. Each catalog has attributes added. See [as.catalog](#) for more details.

Note

SBS 192 and DBS 144 catalogs include only mutations in transcribed regions.

TranscriptRanges	<i>Transcript ranges data</i>
------------------	-------------------------------

Description

Transcript ranges and strand information for a particular reference genome.

Usage

`trans.ranges.GRCh37`

`trans.ranges.GRCh38`

Format

A [data.table](#) which contains transcript range and strand information for a particular reference genome. It contains chromosome name, start, end position, strand information and gene name and is keyed by `chrom`, `chromStart`, and `chromEnd`. It uses one-based coordinate system.

Details

`trans.ranges.GRCh37` A [data.table](#) which contains transcript range and strand information for **Human** GRCh37. It is derived from a raw **GFF3** format file (ftp://ftp.ebi.ac.uk/pub/databases/gencode/Gencode_human/release_30/GRCh37_mapping/gencode.v30lift37.annotation.gff3.gz), only genes that are associated with a CCDS ID are kept for transcriptional strand bias analysis. Needed for [StrelkaSBSCFFFilesToCatalog](#), [StrelkaSBSCFFFilesToCatalogAndPlotToPdf](#), [MutectVCFFilesToCatalog](#), [MutectVCFFilesToCatalogAndPlotToPdf](#), [VCFsToSBSCatalogs](#) and [VCFsToDBSCatalogs](#).

`trans.ranges.GRCh38` A [data.table](#) which contains transcript range and strand information for **Human** GRCh38. It is derived from a raw **GFF3** format file (ftp://ftp.ebi.ac.uk/pub/databases/gencode/Gencode_human/release_30/gencode.v30.annotation.gff3.gz), only genes that are associated with a CCDS ID are kept for transcriptional strand bias analysis. Needed for [StrelkaSBSCFFFilesToCatalog](#), [StrelkaSBSCFFFilesToCatalogAndPlotToPdf](#), [MutectVCFFilesToCatalog](#), [MutectVCFFilesToCatalogAndPlotToPdf](#), [VCFsToSBSCatalogs](#) and [VCFsToDBSCatalogs](#).

Source

ftp://ftp.ebi.ac.uk/pub/databases/gencode/Gencode_human/release_30/GRCh37_mapping/gencode.v30lift37.annotation.gff3.gz

ftp://ftp.ebi.ac.uk/pub/databases/gencode/Gencode_human/release_30/gencode.v30.annotation.gff3.gz

TransformCatalog	<i>Transform between counts and density spectrum catalogs and counts and density signature catalogs.</i>
------------------	--

Description

Transform between counts and density spectrum catalogs and counts and density signature catalogs.

Usage

```
TransformCatalog(catalog, target.ref.genome, target.region,
                 target.catalog.type)
```

Arguments

catalog	An SBS or DBS catalog as described in ICAMS ; must not be an ID (indel) catalog.
target.ref.genome	A ref.genome argument as described in ICAMS .
target.region	One of "genome", "exome"; see as.catalog .
target.catalog.type	A character string acting as a catalog type identifier, one of "counts", "density", "counts.signature", "density.signature"; see as.catalog .

Details

Only the following transformations are legal:

1. counts -> counts (used to transform between target.ref.genome and/or target.region)
2. counts -> density
3. counts -> (counts.signature, density.signature)
4. density -> counts (the semantics are to infer the genome-wide or exome-wide counts based on the densities)
5. density -> (counts.signature, density.signature)
6. counts.signature -> (counts.signature, density.signature)
7. density.signature -> counts.signature
8. density.signature -> density.signature (a null operation)
9. density -> density (a null operation)

Value

A catalog as defined in [ICAMS](#).

VCFsToDBSCatalogs	<i>Create DBS catalogs from VCFs</i>
-------------------	--------------------------------------

Description

Create a list of 3 catalogs (one each for DBS78, DBS144 and DBS136) out of the contents in list.of.DBS.vcfs. The VCFs must not contain any type of mutation other than DBSs.

Usage

```
VCFsToDBSCatalogs(list.of.DBS.vcfs, ref.genome, trans.ranges, region)
```

Arguments

list.of.DBS.vcfs	List of in-memory data frames of pure DBS mutations – no SBS or 3+BS mutations. The list names will be the sample ids in the output catalog.
ref.genome	A ref.genome argument as described in ICAMS .
trans.ranges	a data.table which contains transcript range and strand information. Please refer to TranscriptRanges for more details.
region	A character string acting as a region identifier, one of "genome", "exome".

Value

A list of 3 DBS catalogs, one each for 78, 144, 136: catDBS78 catDBS144 catDBS136. Each catalog has attributes added. See [as.catalog](#) for more details.

Note

DBS 144 catalog only contains mutations in transcribed regions.

VCFsToIDCatalogs	<i>Create ID (insertion and deletion) catalog from ID VCFs</i>
------------------	--

Description

Create ID (insertion and deletion) catalog from ID VCFs

Usage

```
VCFsToIDCatalogs(list.of.vcfs, ref.genome, region)
```

Arguments

list.of.vcfs	List of in-memory VCFs. The list names will be the sample ids in the output catalog.
ref.genome	A ref.genome argument as described in ICAMS .
region	A character string acting as a region identifier, one of "genome", "exome".

Value

An S3 object containing an ID (indel) catalog with class "catalog". See [as.catalog](#) for more details.

VCFsToSBSCatalogs	Create SBS catalogs from SBS VCFs
-------------------	-----------------------------------

Description

Create a list of 3 catalogs (one each for 96, 192, 1536) out of the contents in list.of.SBS.vcfs. The SBS VCFs must not contain DBSs, indels, or other types of mutations.

Usage

```
VCFsToSBSCatalogs(list.of.SBS.vcfs, ref.genome, trans.ranges, region)
```

Arguments

- list.of.SBS.vcfs
List of in-memory data frames of pure SBS mutations – no DBS or 3+BS mutations. The list names will be the sample ids in the output catalog.
- ref.genome
A ref.genome argument as described in [ICAMS](#).
- trans.ranges
a [data.table](#) which contains transcript range and strand information. Please refer to [TranscriptRanges](#) for more details.
- region
A character string acting as a region identifier, one of "genome", "exome".

Value

A list of 3 SBS catalogs, one each for 96, 192, 1536: catSBS96 catSBS192 catSBS1536. Each catalog has attributes added. See [as.catalog](#) for more details.

Note

SBS 192 catalog only contains mutations in transcribed regions.

WriteCatalog	Write a catalog
--------------	-----------------

Description

Write a catalog to a file.

Usage

```
WriteCatalog(catalog, file, strict = TRUE)
```

Arguments

catalog	A catalog as defined in ICAMS ; see also as.catalog .
file	The path to the file to be created.
strict	If TRUE, do additional checks on the input, and stop if the checks fail.

Details

See also [ReadCatalog](#).

Note

In ID (insertion and deletion) catalogs, deletion repeat sizes range from 0 to 5+, but for plotting and end-user documentation deletion repeat sizes range from 1 to 6+.

Index

*Topic **datasets**

- CatalogRowOrder, [3](#)
 - TranscriptRanges, [19](#)
- as.catalog, [2](#), [7](#), [9–12](#), [14](#), [16–18](#), [20–23](#)
- available.genomes, [8](#)
- BSgenome, [7](#)
- catalog.row.order (CatalogRowOrder), [3](#)
- CatalogRowOrder, [3](#), [9](#)
- Collapse144CatalogTo78
(CollapseCatalog), [3](#)
- Collapse1536CatalogTo96
(CollapseCatalog), [3](#)
- Collapse192CatalogTo96
(CollapseCatalog), [3](#)
- CollapseCatalog, [3](#), [9](#)
- data.table, [9](#), [10](#), [17–19](#), [21](#), [22](#)
- FindDelMH, [4](#)
- GetMutectVAF (GetVAF), [6](#)
- GetStrelkaVAF (GetVAF), [6](#)
- GetVAF, [6](#)
- ICAMS, [2](#), [3](#), [6](#), [8–12](#), [14](#), [16–18](#), [20–23](#)
- ICAMS-package (ICAMS), [6](#)
- MutectVCFFilesToCatalog, [7](#), [9](#), [10](#), [13](#), [19](#)
- MutectVCFFilesToCatalogAndPlotToPdf,
[10](#), [19](#)
- PlotCatalog, [7](#), [11](#)
- PlotCatalogToPdf, [7](#), [10](#), [12](#), [17](#), [18](#)
- ReadAndSplitMutectVCFs, [13](#)
- ReadAndSplitStrelkaSBSVCFs, [13](#)
- ReadCatalog, [7](#), [8](#), [14](#), [23](#)
- ReadStrelkaIDVCFs, [15](#)
- revc, [15](#)
- StrelkaIDVCFFilesToCatalog, [7](#), [15](#), [16](#)
- StrelkaIDVCFFilesToCatalogAndPlotToPdf,
[16](#)
- StrelkaSBSVCFFilesToCatalog, [7](#), [14](#), [17](#),
[18](#), [19](#)
- StrelkaSBSVCFFilesToCatalogAndPlotToPdf,
[7](#), [18](#), [19](#)
- trans.ranges.GRCh37 (TranscriptRanges),
[19](#)
- trans.ranges.GRCh38 (TranscriptRanges),
[19](#)
- TranscriptRanges, [9](#), [10](#), [17](#), [18](#), [19](#), [21](#), [22](#)
- TransformCatalog, [8](#), [11](#), [12](#), [20](#)
- VCFsToDBSCatalogs, [9](#), [17](#), [19](#), [21](#)
- VCFsToIDCatalogs, [9](#), [16](#), [17](#), [21](#)
- VCFsToSBSCatalogs, [9](#), [17](#), [19](#), [22](#)
- WriteCatalog, [8](#), [14](#), [22](#)