Docs / Microsoft Graph / API beta reference / Files / Drive items /







Download a file in another format

Article • 07/20/2022 • 4 minutes to read • 9 contributors



In this article

Permissions

HTTP request

Query parameters

Optional request headers

Example

Response

Namespace: microsoft.graph

(i) Important

APIs under the /beta version in Microsoft Graph are subject to change. Use of these APIs in production applications is not supported. To determine whether an API is available in v1.0, use the Version selector.

This endpoint requires TLS 1.2 to function normally. Microsoft announced the deprecation of TLS 1.0 and 1.1 for Office 365 and Azure AD services. Although Microsoft Graph still supports these two protocols, you might experience transportlevel errors. For more information about the TLS 1.0 and 1.1 deprecation, see Enable support for TLS 1.2 in your environment.

Use this API to retrieve the contents of an item in a specific format. Not all files can be converted into all formats.

To download the item in its original format, see download an item's contents.

Permissions

One of the following permissions is required to call this API. To learn more, including how to choose permissions, see Permissions.

Permission type	Permissions (from least to most privileged)
Delegated (work or school account)	Files.Read, Files.ReadWrite, Files.Read.All, Files.ReadWrite.All, Sites.Read.All, Sites.ReadWrite.All
Delegated (personal Microsoft account)	Files.Read, Files.ReadWrite, Files.Read.All, Files.ReadWrite.All
Application	Files.Read.All, Files.ReadWrite.All, Sites.Read.All, Sites.ReadWrite.All

HTTP request

HTTP	🖺 Сору
<pre>GET /drive/items/{item-id}/content?format={format} GET /drive/root:/{path and filename}:/content?format={format}</pre>	

Query parameters

Parameter	Туре	Description
format	string	Specify the format the item's content should be downloaded as.

The following values are valid for the **format** parameter:


Value	Description	Supported source extensions
glb	Converts the item into GLB format	cool, fbx, obj, ply, stl, 3mf
html	Converts the item into HTML format	eml, md, msg

Value	Description	Supported source extensions
jpg	Converts the item into JPG format	3g2, 3gp, 3gp2, 3gpp, 3mf, ai, arw, asf, avi, bas, bash, bat, bmp, c, cbl, cmd, cool, cpp, cr2, crw, cs, css, csv, cur, dcm, dcm30, dic, dicm, dicom, dng, doc, docx, dwg, eml, epi, eps, epsf, epsi, epub, erf, fbx, fppx, gif, glb, h, hcp, heic, heif, htm, html, ico, icon, java, jfif, jpeg, jpg, js, json, key, log, m2ts, m4a, m4v, markdown, md, mef, mov, movie, mp3, mp4, mp4v, mrw, msg, mts, nef, nrw, numbers, obj, odp, odt, ogg, orf, pages, pano, pdf, pef, php, pict, pl, ply, png, pot, potm, potx, pps, ppsx, ppsxm, ppt, pptm, pptx, ps, ps1, psb, psd, py, raw, rb, rtf, rw1, rw2, sh, sketch, sql, sr2, stl, tif, tiff, ts, txt, vb, webm, wma, wmv, xaml, xbm, xcf, xd, xml, xpm, yaml, yml
pdf	Converts the item into PDF format	doc, docx, epub, eml, htm, html, md, msg, odp, ods, odt, pps, ppsx, ppt, pptx, rtf, tif, tiff, xls, xlsm, xlsx

Optional request headers

Name	Value	Description
if- none- match	String	If this request header is included and the eTag (or cTag) provided matches the current tag on the file, an HTTP 304 Not Modified response is returned.

Example



Response

Returns a 302 Found response redirecting to a pre-authenticated download URL for the converted file.

To download the converted file, your app must follow the Location header in the response.

Pre-authenticated URLs are only valid for a short period of time (a few minutes) and do not require an Authorization header to access.

HTTP/1.1 302 Found
Location: https://b0mpua-by3301.files.1drv.com/y23vmagahszhxzlcvhasdhasghasodfi

Error responses

See Error Responses for more information about how errors are returned.