

GAS VOLUME STATEMENT

August 2026

Meter #: 51634-00
Name: Prestage Tx 12-18
Closed Data
Standard Conditions

Pressure Base:	14.730 psia	Meter Status:	Active	CO2	N2	C1	C2	C3	IC4	NC4	IC5
Temperature Base:	60.00 °F	Contract Hr.:	Midnight	0.542	0.785	98.630	0.006	0.006	0.000	0.000	0.000
Atmos Pressure:	13.000 psi	Full Wellstream:	No	NC5	neo	C6	C7	C8	C9	C10	
Calc Method:	AGA3-1992	WV Technique:	Equivalent Dry Volume	0.000		0.001					
Z Method:	AGA-8 Detail (1992)	WV Method:	1955 IGT-Bulletin 8	Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
Tube I.D.:	3.0700 in	HV Cond:	Dry			0.000	0.028	0.002		0.000	1.000
Tap Location:	Upstream	Meter Type:	EFM								
Tap Type:	Flange	Interval:	1 Hour								

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	0.00	17.13	81.91	0.00	0.5635	1.0000	0.00	1000.73	0.00
2	0.00	17.14	83.52	0.00	0.5635	1.0000	0.00	1000.73	0.00
3	0.00	17.46	86.47	0.00	0.5635	1.0000	0.00	1000.73	0.00
4	0.00	17.57	82.47	0.00	0.5635	1.0000	0.00	1000.73	0.00
5	0.00	16.86	82.63	0.00	0.5635	1.0000	0.00	1000.73	0.00
6	24.34	26.48	84.78	11.57	0.5635	1.0000	74.42	1000.73	74.48
7	27.14	24.72	75.06	7.73	0.5635	1.0000	52.08	1000.73	52.12
8	0.00	25.05	84.88	0.00	0.5635	1.0000	0.00	1000.73	0.00
9	0.00	21.03	86.52	0.00	0.5635	1.0000	0.00	1000.73	0.00
10	0.00	20.68	86.77	0.00	0.5635	1.0000	0.00	1000.73	0.00
11	0.00	22.22	84.71	0.00	0.5635	1.0000	0.00	1000.73	0.00
12	0.00	22.71	87.09	0.00	0.5635	1.0000	0.00	1000.73	0.00
13	0.00	20.78	89.09	0.00	0.5635	1.0000	0.00	1000.73	0.00
14	0.00	20.61	87.12	0.00	0.5635	1.0000	0.00	1000.73	0.00
15	0.00	21.62	84.86	0.00	0.5635	1.0000	0.00	1000.73	0.00
16	0.00	21.55	79.72	0.00	0.5635	1.0000	0.00	1000.73	0.00
17	0.00	21.52	78.76	0.00	0.5635	1.0000	0.00	1000.73	0.00
18	24.29	24.65	84.64	11.52	0.5635	1.0000	72.28	1000.73	72.34
19	27.30	25.13	81.19	15.30	0.5635	1.0000	102.97	1000.73	103.04
20	27.57	25.42	80.89	17.57	0.5635	1.0000	119.95	1000.73	120.03
21	0.00	22.57	86.98	0.00	0.5635	1.0000	0.00	1000.73	0.00
22	0.00	22.77	85.79	0.00	0.5635	1.0000	0.00	1000.73	0.00
23	0.00	22.78	86.59	0.00	0.5635	1.0000	0.00	1000.73	0.00
24	0.00	22.67	87.27	0.00	0.5635	1.0000	0.00	1000.73	0.00
25	0.00	22.58	83.38	0.00	0.5635	1.0000	0.00	1000.73	0.00
26	0.00	22.13	79.81	0.00	0.5635	1.0000	0.00	1000.73	0.00
27	0.00	22.26	79.85	0.00	0.5635	1.0000	0.00	1000.73	0.00
28	0.00	22.44	81.66	0.00	0.5635	1.0000	0.00	1000.73	0.00
29	0.00	22.92	85.60	0.00	0.5635	1.0000	0.00	1000.73	0.00
30	0.00	23.01	89.18	0.00	0.5635	1.0000	0.00	1000.73	0.00
31	0.00	23.27	84.14	0.00	0.5635	1.0000	0.00	1000.73	0.00
Total	26.32	25.32	81.57	63.69	0.5635		421.70		422.01

Volume at 14.650 = 424.01 Energy = 422.01

GAS VOLUME STATEMENT

August 2026

Meter #: 51635-00
Name: Prestage TX 19-21
Closed Data
Standard Conditions

Pressure Base:	14.730 psia	Meter Status:	Active	CO2	N2	C1	C2	C3	IC4	NC4	IC5
Temperature Base:	60.00 °F	Contract Hr.:	Midnight	1.328	1.010	97.555	0.000	0.000	0.000	0.000	0.000
Atmos Pressure:	12.850 psi	Full Wellstream:	No	NC5	neo	C6	C7	C8	C9	C10	
Calc Method:	AGA3-1992	WV Technique:	Equivalent Dry Volume	0.000		0.000					
Z Method:	AGA-8 Detail (1992)	WV Method:	1955 IGT-Bulletin 8	Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
Tube I.D.:	3.0690 in	HV Cond:	Dry				0.107	0.000		0.000	1.000
Tap Location:	Upstream	Meter Type:	EFM								
Tap Type:	Flange	Interval:	1 Hour								

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	88.72	21.50	79.92	22.52	0.5724	1.0000	241.73	989.52	239.19
2	141.21	23.54	87.12	14.71	0.5724	1.0000	201.53	989.52	199.42
3	126.84	22.88	77.89	5.69	0.5724	1.0000	74.49	989.52	73.71
4	0.00	12.99	82.19	0.00	0.5724	1.0000	0.00	989.52	0.00
5	0.00	13.02	82.97	0.00	0.5724	1.0000	0.00	989.52	0.00
6	0.00	13.21	85.42	0.00	0.5724	1.0000	0.00	989.52	0.00
7	0.00	13.17	82.59	0.00	0.5724	1.0000	0.00	989.52	0.00
8	0.00	13.37	85.34	0.00	0.5724	1.0000	0.00	989.52	0.00
9	0.00	13.09	86.82	0.00	0.5724	1.0000	0.00	989.52	0.00
10	0.00	13.11	87.19	0.00	0.5724	1.0000	0.00	989.52	0.00
11	0.00	13.11	86.09	0.00	0.5724	1.0000	0.00	989.52	0.00
12	0.00	13.07	87.63	0.00	0.5724	1.0000	0.00	989.52	0.00
13	0.00	13.06	89.50	0.00	0.5724	1.0000	0.00	989.52	0.00
14	0.00	13.10	90.11	0.00	0.5724	1.0000	0.00	989.52	0.00
15	0.00	13.14	84.69	0.00	0.5724	1.0000	0.00	989.52	0.00
16	0.00	13.23	79.14	0.00	0.5724	1.0000	0.00	989.52	0.00
17	99.55	22.46	82.47	10.48	0.5724	1.0000	121.02	989.52	119.76
18	100.51	22.37	80.92	24.00	0.5724	1.0000	278.36	989.52	275.44
19	102.43	22.66	78.76	24.00	0.5724	1.0000	284.00	989.52	281.03
20	106.30	22.89	74.41	7.57	0.5724	1.0000	92.31	989.52	91.34
21	0.00	12.92	88.50	0.00	0.5724	1.0000	0.00	989.52	0.00
22	0.00	12.93	86.41	0.00	0.5724	1.0000	0.00	989.52	0.00
23	0.00	12.91	86.28	0.00	0.5724	1.0000	0.00	989.52	0.00
24	0.00	12.89	88.89	0.00	0.5724	1.0000	0.00	989.52	0.00
25	0.00	12.92	83.62	0.00	0.5724	1.0000	0.00	989.52	0.00
26	0.00	12.96	79.03	0.00	0.5724	1.0000	0.00	989.52	0.00
27	0.00	12.96	80.22	0.00	0.5724	1.0000	0.00	989.52	0.00
28	0.00	12.95	81.17	0.00	0.5724	1.0000	0.00	989.52	0.00
29	0.00	12.89	86.16	0.00	0.5724	1.0000	0.00	989.52	0.00
30	0.00	12.86	88.76	0.00	0.5724	1.0000	0.00	989.52	0.00
31	80.82	21.97	83.91	14.67	0.5724	1.0000	151.94	989.52	150.35
Total	104.17	22.47	81.07	123.63	0.5724		1,445.38		1,430.23

Volume at 14.650 = 1,453.27 Energy = 1,430.23

GAS VOLUME STATEMENT

August 2026

Meter #: 51636-00
Name: Pretage TX 31-34
Closed Data
Standard Conditions

Pressure Base: 14.730 psia Meter Status: Active
Temperature Base: 60.00 °F Contract Hr.: Midnight
Atmos Pressure: 13.000 psi Full Wellstream: No
Calc Method: AGA3-1992 WV Technique: Equivalent Dry Volume
Z Method: AGA-8 Detail (1992) WV Method: 1955 IGT-Bulletin 8
Tube I.D.: 3.0670 in HV Cond: Dry
Tap Location: Upstream Meter Type: EFM
Tap Type: Flange Interval: 1 Hour

CO2	N2	C1	C2	C3	IC4	NC4	IC5
1.699	0.577	97.724	0.000	0.000	0.000	0.000	0.000
NC5	neo	C6	C7	C8	C9	C10	
0.000		0.000					
Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
			0.000	0.000		0.000	1.000

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	0.00	16.49	85.77	0.00	0.5736	1.5000	0.00	991.26	0.00
2	0.00	16.49	87.40	0.00	0.5736	1.5000	0.00	991.26	0.00
3	4.95	17.28	81.77	15.05	0.5736	1.5000	82.72	991.26	82.00
4	5.11	17.22	75.07	24.00	0.5736	1.5000	135.49	991.26	134.31
5	4.38	17.99	75.91	20.67	0.5736	1.5000	109.33	991.26	108.38
6	3.86	21.67	77.06	23.60	0.5736	1.5000	129.14	991.26	128.01
7	2.81	21.00	69.59	7.61	0.5736	1.5000	35.56	991.26	35.25
8	0.00	23.49	89.27	0.00	0.5736	1.5000	0.00	991.26	0.00
9	0.00	19.45	89.58	0.00	0.5736	1.5000	0.00	991.26	0.00
10	0.00	19.39	89.66	0.00	0.5736	1.5000	0.00	991.26	0.00
11	0.00	20.71	88.14	0.00	0.5736	1.5000	0.00	991.26	0.00
12	0.00	21.05	89.88	0.00	0.5736	1.5000	0.00	991.26	0.00
13	0.00	19.48	91.95	0.00	0.5736	1.5000	0.00	991.26	0.00
14	0.00	19.36	90.73	0.00	0.5736	1.5000	0.00	991.26	0.00
15	0.00	20.18	88.27	0.00	0.5736	1.5000	0.00	991.26	0.00
16	0.00	20.08	82.61	0.00	0.5736	1.5000	0.00	991.26	0.00
17	0.00	20.06	81.72	0.00	0.5736	1.5000	0.00	991.26	0.00
18	0.00	20.65	86.44	0.00	0.5736	1.5000	0.00	991.26	0.00
19	0.00	20.88	83.12	0.00	0.5736	1.5000	0.00	991.26	0.00
20	0.00	21.01	90.17	0.00	0.5736	1.5000	0.00	991.26	0.00
21	4.07	21.32	81.96	12.86	0.5736	1.5000	70.26	991.26	69.64
22	3.94	21.45	77.92	24.00	0.5736	1.5000	132.92	991.26	131.75
23	3.84	21.47	78.22	24.00	0.5736	1.5000	131.17	991.26	130.03
24	4.07	21.41	77.77	22.55	0.5736	1.5000	121.00	991.26	119.94
25	3.40	21.47	76.08	13.19	0.5736	1.5000	67.61	991.26	67.02
26	0.00	20.58	83.26	0.00	0.5736	1.5000	0.00	991.26	0.00
27	0.00	20.67	83.05	0.00	0.5736	1.5000	0.00	991.26	0.00
28	0.00	20.80	84.64	0.00	0.5736	1.5000	0.00	991.26	0.00
29	0.00	21.15	88.55	0.00	0.5736	1.5000	0.00	991.26	0.00
30	0.00	21.21	92.48	0.00	0.5736	1.5000	0.00	991.26	0.00
31	2.91	21.97	84.37	7.15	0.5736	1.5000	34.17	991.26	33.88
Total	4.11	20.23	77.64	194.68	0.5736		1,049.38		1,040.20

Volume at 14.650 = 1,055.11 Energy = 1,040.20

GAS VOLUME STATEMENT

August 2026

Meter #: 51637-00
Name: Prestage OK 1-5
Closed Data
Standard Conditions

Pressure Base: 14.730 psia Meter Status: Active
Temperature Base: 60.00 °F Contract Hr.: Midnight
Atmos Pressure: 13.100 psi Full Wellstream: No
Calc Method: AGA3-1992 WV Technique: Equivalent Dry Volume
Z Method: AGA-8 Detail (1992) WV Method: 1955 IGT-Bulletin 8
Tube I.D.: 3.0730 in HV Cond: Dry
Tap Location: Upstream Meter Type: EFM
Tap Type: Flange Interval: 1 Hour

CO2	N2	C1	C2	C3	IC4	NC4	IC5
0.438	0.977	98.472	0.000	0.000	0.000	0.000	0.000
NC5	neo	C6	C7	C8	C9	C10	
0.000		0.000					
Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
		0.000	0.107	0.006		0.000	0.000

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	0.00	13.13	84.24	0.00	0.5636	1.0000	0.00	998.80	0.00
2	0.00	13.14	88.32	0.00	0.5636	1.0000	0.00	998.80	0.00
3	0.00	13.09	91.12	0.00	0.5636	1.0000	0.00	998.80	0.00
4	0.00	13.06	84.60	0.00	0.5636	1.0000	0.00	998.80	0.00
5	0.00	13.08	84.13	0.00	0.5636	1.0000	0.00	998.80	0.00
6	0.00	13.10	86.86	0.00	0.5636	1.0000	0.00	998.80	0.00
7	0.00	13.11	91.21	0.00	0.5636	1.0000	0.00	998.80	0.00
8	0.00	13.12	91.02	0.00	0.5636	1.0000	0.00	998.80	0.00
9	0.00	13.11	92.01	0.00	0.5636	1.0000	0.00	998.80	0.00
10	0.00	13.10	91.16	0.00	0.5636	1.0000	0.00	998.80	0.00
11	0.00	13.10	89.40	0.00	0.5636	1.0000	0.00	998.80	0.00
12	0.00	13.08	91.86	0.00	0.5636	1.0000	0.00	998.80	0.00
13	0.00	13.04	92.19	0.00	0.5636	1.0000	0.00	998.80	0.00
14	0.00	13.05	89.77	0.00	0.5636	1.0000	0.00	998.80	0.00
15	0.00	13.08	87.41	0.00	0.5636	1.0000	0.00	998.80	0.00
16	0.00	13.11	81.08	0.00	0.5636	1.0000	0.00	998.80	0.00
17	0.00	13.12	81.22	0.00	0.5636	1.0000	0.00	998.80	0.00
18	0.00	13.12	87.30	0.00	0.5636	1.0000	0.00	998.80	0.00
19	21.21	21.14	84.78	12.74	0.5636	1.0000	68.59	998.80	68.51
20	20.85	21.67	79.53	11.24	0.5636	1.0000	61.68	998.80	61.60
21	0.00	14.37	88.85	0.00	0.5636	1.0000	0.00	998.80	0.00
22	0.00	13.21	86.98	0.00	0.5636	1.0000	0.00	998.80	0.00
23	0.00	13.16	89.64	0.00	0.5636	1.0000	0.00	998.80	0.00
24	0.00	13.12	90.33	0.00	0.5636	1.0000	0.00	998.80	0.00
25	0.00	13.12	85.70	0.00	0.5636	1.0000	0.00	998.80	0.00
26	0.00	13.14	82.74	0.00	0.5636	1.0000	0.00	998.80	0.00
27	0.00	13.15	82.18	0.00	0.5636	1.0000	0.00	998.80	0.00
28	0.00	13.16	84.04	0.00	0.5636	1.0000	0.00	998.80	0.00
29	0.00	13.13	88.26	0.00	0.5636	1.0000	0.00	998.80	0.00
30	0.00	13.09	91.19	0.00	0.5636	1.0000	0.00	998.80	0.00
31	0.00	13.08	87.63	0.00	0.5636	1.0000	0.00	998.80	0.00
Total	21.04	21.39	82.29	23.98	0.5636		130.27		130.11

Volume at 14.650 = 130.98 Energy = 130.11

GAS VOLUME STATEMENT

August 2026

Meter #: 51638-00
Name: Prestage TX 9-11
Closed Data
Standard Conditions

Pressure Base:	14.730 psia	Meter Status:	Active
Temperature Base:	60.00 °F	Contract Hr.:	Midnight
Atmos Pressure:	13.080 psi	Full Wellstream:	No
Calc Method:	AGA3-1992	WV Technique:	Equivalent Dry Volume
Z Method:	AGA-8 Detail (1992)	WV Method:	1955 IGT-Bulletin 8
Tube I.D.:	3.0690 in	HV Cond:	Dry
Tap Location:	Upstream	Meter Type:	EFM
Tap Type:	Flange	Interval:	1 Hour

CO2	N2	C1	C2	C3	IC4	NC4	IC5
1.125	1.024	97.768	0.000	0.000	0.000	0.000	0.000
NC5	neo	C6	C7	C8	C9	C10	
0.000		0.000					
Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
			0.083	0.000		0.000	1.000

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	0.00	16.62	85.02	0.00	0.5703	1.0000	0.00	991.68	0.00
2	0.00	15.65	85.32	0.00	0.5703	1.0000	0.00	991.68	0.00
3	0.00	14.99	87.81	0.00	0.5703	1.0000	0.00	991.68	0.00
4	19.57	27.29	84.26	10.30	0.5703	1.0000	60.81	991.68	60.30
5	19.32	27.28	85.80	12.95	0.5703	1.0000	75.74	991.68	75.11
6	18.75	27.76	81.93	24.00	0.5703	1.0000	140.51	991.68	139.34
7	18.38	27.38	75.77	2.29	0.5703	1.0000	13.28	991.68	13.17
8	0.00	19.88	87.09	0.00	0.5703	1.0000	0.00	991.68	0.00
9	0.00	17.65	88.50	0.00	0.5703	1.0000	0.00	991.68	0.00
10	0.00	16.32	87.90	0.00	0.5703	1.0000	0.00	991.68	0.00
11	18.84	25.61	81.80	12.77	0.5703	1.0000	71.80	991.68	71.20
12	18.21	25.05	82.19	24.00	0.5703	1.0000	130.92	991.68	129.83
13	15.99	25.02	83.53	16.74	0.5703	1.0000	84.82	991.68	84.12
14	0.87	22.14	76.06	0.01	0.5703	1.0000	0.01	991.68	0.01
15	0.00	18.26	86.32	0.00	0.5703	1.0000	0.00	991.68	0.00
16	0.00	18.56	80.31	0.00	0.5703	1.0000	0.00	991.68	0.00
17	0.00	18.28	79.35	0.00	0.5703	1.0000	0.00	991.68	0.00
18	0.00	18.24	85.56	0.00	0.5703	1.0000	0.00	991.68	0.00
19	0.00	18.24	81.73	0.00	0.5703	1.0000	0.00	991.68	0.00
20	0.00	18.24	87.72	0.00	0.5703	1.0000	0.00	991.68	0.00
21	0.00	18.23	88.16	0.00	0.5703	1.0000	0.00	991.68	0.00
22	0.00	18.23	86.08	0.00	0.5703	1.0000	0.00	991.68	0.00
23	0.00	18.22	87.40	0.00	0.5703	1.0000	0.00	991.68	0.00
24	0.00	18.23	89.14	0.00	0.5703	1.0000	0.00	991.68	0.00
25	0.00	18.22	84.40	0.00	0.5703	1.0000	0.00	991.68	0.00
26	0.00	18.22	81.21	0.00	0.5703	1.0000	0.00	991.68	0.00
27	0.00	18.22	79.15	0.00	0.5703	1.0000	0.00	991.68	0.00
28	0.00	18.22	80.53	0.00	0.5703	1.0000	0.00	991.68	0.00
29	0.00	18.22	85.19	0.00	0.5703	1.0000	0.00	991.68	0.00
30	0.00	18.21	88.36	0.00	0.5703	1.0000	0.00	991.68	0.00
31	18.06	25.49	78.72	11.02	0.5703	1.0000	60.69	991.68	60.18
Total	18.36	26.27	82.43	114.07	0.5703		638.57		633.25

Volume at 14.650 = 642.05 Energy = 633.25

GAS VOLUME STATEMENT

August 2026

Meter #: 750256-00
Name: Monarch RNG EC
Closed Data
Standard Conditions

Pressure Base:	14.730 psia	Meter Status:	Active	CO2	N2	C1	C2	C3	IC4	NC4	IC5
Temperature Base:	60.00 °F	Contract Hr.:	Midnight	1.155	0.256	98.589	0.000	0.000	0.000	0.000	0.000
Atmos Pressure:	13.700 psi	Full Wellstream:	No	NC5	neo	C6	C7	C8	C9	C10	
Calc Method:	AGA3-1992	WV Technique:	Equivalent Dry Volume	0.000		0.000					
Z Method:	AGA-8 Detail (1992)	WV Method:	1955 IGT-Bulletin 8								
Tube I.D.:	3.0700 in	HV Cond:	Dry	Ar	CO	H2	O2	He	H2O	H2S	H2S ppm
Tap Location:	Upstream	Meter Type:	EFM				0.000	0.000		0.000	0.000
Tap Type:	Flange	Interval:	1 Hour								

Day	Differential (In. H2O)	Pressure (psia)	Temp. (°F)	Flow Time (hrs)	Relative Density	Plate (inches)	Volume (Mcf)	Heating Value (Btu/scf)	Energy (MMBtu)
1	8.50	76.34	73.82	2.00	0.5670	1.0000	13.58	1000.03	13.58
2	0.00	69.10	86.79	0.00	0.5670	1.0000	0.00	1000.03	0.00
3	39.12	80.33	81.34	13.88	0.5670	1.0000	203.78	1000.03	203.79
4	37.71	88.90	77.99	23.97	0.5670	1.0000	362.87	1000.03	362.88
5	33.66	90.87	74.94	12.46	0.5670	1.0000	179.05	1000.03	179.06
6	0.00	75.84	89.48	0.00	0.5670	1.0000	0.00	1000.03	0.00
7	4.69	72.50	90.25	6.20	0.5670	1.0000	29.74	1000.03	29.74
8	6.35	71.67	77.79	13.73	0.5670	1.0000	77.35	1000.03	77.35
9	5.00	70.72	84.01	23.95	0.5670	1.0000	108.65	1000.03	108.65
10	6.03	71.00	82.91	23.49	0.5670	1.0000	121.25	1000.03	121.25
11	8.35	71.32	75.55	6.58	0.5670	1.0000	42.71	1000.03	42.71
12	0.00	68.62	94.91	0.00	0.5670	1.0000	0.00	1000.03	0.00
13	0.00	68.35	97.16	0.00	0.5670	1.0000	0.00	1000.03	0.00
14	5.36	78.46	80.09	9.86	0.5670	1.0000	53.27	1000.03	53.27
15	5.41	75.13	81.82	22.28	0.5670	1.0000	118.57	1000.03	118.57
16	6.12	73.63	79.76	21.87	0.5670	1.0000	122.07	1000.03	122.07
17	6.03	72.79	80.52	17.08	0.5670	1.0000	94.42	1000.03	94.42
18	5.67	77.75	81.93	23.74	0.5670	1.0000	130.55	1000.03	130.55
19	4.25	102.23	78.18	17.01	0.5670	1.0000	94.25	1000.03	94.25
20	5.56	77.60	79.57	14.90	0.5670	1.0000	81.75	1000.03	81.75
21	5.77	74.71	86.76	7.24	0.5670	1.0000	39.01	1000.03	39.01
22	0.00	74.85	88.10	0.00	0.5670	1.0000	0.00	1000.03	0.00
23	0.00	77.92	89.83	0.00	0.5670	1.0000	0.00	1000.03	0.00
24	0.00	87.30	92.90	0.00	0.5670	1.0000	0.00	1000.03	0.00
25	0.00	92.58	87.01	0.00	0.5670	1.0000	0.00	1000.03	0.00
26	20.44	83.23	82.80	5.53	0.5670	1.0000	59.98	1000.03	59.98
27	14.61	92.49	81.96	10.11	0.5670	1.0000	97.14	1000.03	97.14
28	19.11	81.59	81.43	14.11	0.5670	1.0000	146.65	1000.03	146.66
29	19.58	81.75	80.23	24.00	0.5670	1.0000	252.58	1000.03	252.58
30	17.59	85.51	81.37	20.86	0.5670	1.0000	212.03	1000.03	212.03
31	0.00	78.32	92.30	0.00	0.5670	1.0000	0.00	1000.03	0.00
Total	18.27	81.66	80.28	334.84	0.5670		2,641.24		2,641.30

Volume at 14.650 = 2,655.66 Energy = 2,641.30