

Software Engineering Design & Construction

Dr. Michael Eichberg
Fachgebiet Softwaretechnik
Technische Universität Darmstadt


Programming Languages and Design Principles

Making Code Look Like Design

“Designing” with Pseudo-Assembler

What does the following program do?


```
i = 1
TEST: if i < 4
      then goto BODY
      else goto END
BODY: print i
      i = i + 1
      goto TEST
END:
```

A hand-drawn control flow diagram is overlaid on the code. It consists of several black arrows. One arrow starts from the 'if' statement in the TEST block and points to the 'goto BODY' line. Another arrow starts from the 'goto TEST' line in the BODY block and loops back to the 'if' statement in the TEST block. A third arrow starts from the 'goto END' line in the TEST block and points to the 'END:' label. There are also some scribbled-out lines and arrows, suggesting a process of refining the flow.

“Designing” with Pseudo-Assembler

What does the following program do?

```
i = 1  
LOOP: print i  
      i = i + 1  
      if i < 4 goto LOOP  
END:
```



Style can only be
recommended, not
enforced!

Designing with Structured Programming Languages


What does the following program do?

```
i = 1
while ( i < 4 ) {
    print(i)
    i = i + 1
}
```

Style gets enforced!

Better languages, More challenging tasks...

A simple image browser with structured programming



Code for Image Browser Structured into Procedures

Try to identify which method calls which method!

```
main () {
draw_label("Art Browser")
  m = radio_menu(
    {"Whale", "Eagle",
     "Dogfish"})
  q = button_menu({"Quit"})
  while ( !check_buttons(q) ) {
    n = check_buttons(m)
    draw_image(n)
  }
}

set_x (x) {
  current_x = x
}

draw_circle (x, y, r) {
  %%primitive_oval(x, y, 1, r)
}

set_y (y) {
  current_y = y
}
```

```
radio_menu(labels) {
  i = 0
  while (i < labels.size) {
    radio_button(i)
    draw_label(labels[i])
    set_y(get_y()
          + RADIO_BUTTON_H)
    i++
  }
}

radio_button (n) {
  draw_circle(get_x(),
              get_y(), 3)
}

get_x () {
  return current_x
}

get_y () {
  return current_y
}
```

```
draw_image (img) {
  w = img.width
  h = img.height
  do (r = 0; r < h; r++)
    do (c = 0; c < w; c++)
      WINDOW[r][c] = img[r][c]
}

button_menu(labels) {
  i = 0
  while (i < labels.size) {
    draw_label(labels[i])
    set_y(get_y()
          + BUTTON_H)
    i++
  }
}

draw_label (string) {
  w = calculate_width(string)
  print(string, WINDOW_PORT)
  set_x(get_x() + w)
}
```


Structured Programming with Style

```
main()
```

```
gui_radio_button(n)
```

```
gui_button_menu(labels)
```

```
gui_radio_menu(labels)
```

```
graphic_draw_image (img)
```

```
graphic_draw_circle (x, y, r)
```

```
graphic_draw_label (string)
```

```
state_set_y (y)
```

```
state_get_y ()
```


```
state_set_x (x)
```

```
state_get_x ()
```

Designing with Modular Programming Languages

```
module gui {  
    exports:  
        radio_menu(labels)  
        button_menu(labels)  
        check_buttons(menu)  
}
```

Module-based Abstraction




Abstraction mechanisms
enable us to code and
design simultaneously!

"Write what you mean."

"The significant problems we face cannot be solved at the same level of thinking we were at when we created them."

–Einstein

Let's “develop” application families with sophisticated GUIs with uniform look and feel with modular programming...



Designing with Object-Oriented Programming Languages

Object-oriented programming languages introduce new abstraction mechanisms:

- classes
- inheritance
- subtype polymorphism
- virtual methods

(Still) Dominating
Programming Paradigm

The roots of object-oriented programming languages are in the sixties.



Dahl and Nygaard,
Simula 64, 68



Allan Kay,
Smalltalk 70 - 80

[...] improvements in programming techniques and programming languages in particular are overwhelmingly more important than anything else in the software business [...]

[...] programmers are interested in design [...] when more expressive programming languages become available, software developers will adopt them.

–Jack Reeves, To Code is to Design, C++ Report 1992

Designing with Functional, Object-Oriented Programming Languages

Fill an array with n Person objects where each Person has a unique id.

Code:

```
case class Person(id : Int)
```

```
var ids = 0
```

```
def nextId() : Int = { val id = ids ; ids+= 1; id }
```

```
Array.fill(15){ new Person(nextId()) }
```

Result:

```
=> Array[Person] = Array(Person(0), ..., Person(14))
```

Designing with Functional, Object-Oriented Programming Languages **with a Flexible Syntax**

Creating an abstraction to express that we want to repeat something n times.

```
def repeat[T: scala.reflect.ClassTag](times: Int)(f: ⇒ T): Array[T] = {  
    val array = new Array[T](times)  
    var i = 0  
    while (i < times) { array(i) = f; i += 1 }  
    array  
}
```

Now, we can express that we want to read in two values from the command line using our new control-abstraction.

```
val values = repeat(2) { System.in.read() }
```

Designing with Functional, Object-Oriented Programming Languages with a Flexible Syntax vs. Explicit Language Features

Java's native try-with-resources statement

```
File tempFile = File.createTempFile("demo", "tmp");
try (FileOutputStream fout = new FileOutputStream(tempFile)) {
    fout.write(42);
}
```

Using Scala's language features enables us to define a new control structure that resembles Java's try-with-resources statement.


```
def process[C <: Closeable, I](closable: C)(r: C => I): I = {
    try { r(closable) }
    finally { if (closable != null) closable.close() }
}
```

```
val tempFile = File.createTempFile("demo", "tmp");
process(new java.io.FileOutputStream(tempFile)) { fout =>
    fout.write(42);
}
```






Programming Languages with notable Features:

- RUST avoids buffer errors statically (based on ownership)
Graydon Hoare, 2009
- Checked C avoids buffer errors statically and dynamically (introduces new checked pointer types)
David Tardif, June 2016 (v 0.5)
- Perl (3) implements a taint mode to avoid injections dynamically
Larry Wall, 1987
- Java made first steps to avoid cryptographic issues with the “Cryptography Architecture”
- GO, Erlang,... have advanced support for concurrency

Programming Languages are not a Panacea



We need good style to cope with complexity!



General Design Principles

The following principles apply at various abstraction levels!

- Keep it short and simple
- Don't repeat yourself (also just called "DRY-Principle")
- High Cohesion
- Low Coupling
- No cyclic dependencies
- Make it testable
- Open-closed Design Principle
- Make it explicit/use Code
- Keep related things together
- Keep simple things simple
- Common-reuse/Common-closure/Reuse-release principles

Object-Oriented Design Principles

- Liskov Substitution Principle
- Responsibility Driven Design
- ...

Design Constraints

- **Conway's Law**

A system's design is constrained by the organization's communication structure.