

nofu – A Lightweight No-Reference Pixel Based Video Quality Model for Gaming Content.

Steve Göring, Rakesh Rao Ramachandra Rao, Alexander Raake;

Audiovisual Technology Group, Technische Universität Ilmenau, Germany;

Email: [steve.goering, rakesh-rao.ramachandra-rao, alexander.raake]@tu-ilmenau.de

June 6, 2019

tu
TECHNISCHE UNIVERSITÄT
ILMENAU



- ▶ beside classical video streams → gaming content:
 - e.g. Youtube Gaming, Twitch, ...
- ▶ gaming videos →
 - additional requirements / properties: Zadtootaghaj et al. [9]
 - live streaming, low delay, low stalling,
 - high video quality, cgi content, streaming technology
- ▶ focus on video quality of gaming streams
 - gaming qoe and gaming video quality



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective full-reference metrics: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: reference usually not available
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective full-reference metrics: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: reference usually not available
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective full-reference metrics: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: reference usually not available
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective **full-reference metrics**: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: **reference usually not available**
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective **full-reference metrics**: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: **reference usually not available**
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective **full-reference metrics**: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: **reference usually not available**
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu




- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective **full-reference metrics**: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: **reference usually not available**
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu




- ▶ several influencing factors: *Möller, Schmidt, and Zadtootaghaj* [8]
 - video quality factors: content (cgi), encoding (fast),
 - interaction: delay, ...
- ▶ objective **full-reference metrics**: good results: *Barman et al.* [1, 2, 3]
 - VMAF best; problem: **reference usually not available**
- ▶ for live/adaptive encoding:
 - fast, accurate, no-reference quality estimation

→ nofu



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame


- *first, mean, std, groups $g = [1, 2, 3]$: $mean_g, std_g$*
- *→ duration independent 108 values per sequence*

► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset





► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame


- *first, mean, std, groups $g = [1, 2, 3]$: $mean_g$, std_g*
- *→ duration independent 108 values per sequence*

► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset





► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame

- *first, mean, std, groups $g = [1, 2, 3]$: $mean_g$, std_g*
- *→ duration independent 108 values per sequence*


► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame

- *first, mean, std, groups $g = [1, 2, 3]$: $mean_g$, std_g*
- *→ duration independent 108 values per sequence*


► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame

- *first, mean, std, groups $g = [1, 2, 3]$: $mean_g, std_g$*
- → duration independent 108 values per sequence


► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame

- *first, mean, std*, groups $g = [1, 2, 3]$: $mean_g$, std_g
- → duration independent 108 values per sequence


► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame

- *first, mean, std*, groups $g = [1, 2, 3]$: $mean_g$, std_g
- → duration independent 108 values per sequence


► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset



nofu – Features and Approach



► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame


- *first, mean, std*, groups $g = [1, 2, 3]$: $mean_g$, std_g
- → duration independent 108 values per sequence

► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset





► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame


- *first, mean, std*, groups $g = [1, 2, 3]$: $mean_g$, std_g
- → duration independent 108 values per sequence

► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline

→ Evaluation and used Dataset





► features:

- $si^I + ti^M$ [6], fft^I [7], $staticness^I$, $blockiness^I$ [5],
- $cubrow - \{first, last\}^M$, $cubcol - \{first, last\}^M$, $blockmotion^M$ [5]

► speedup: 360p center crop of input video

► temporal pooling: 12 feature values per frame


- *first, mean, std*, groups $g = [1, 2, 3]$: $mean_g$, std_g
- → duration independent 108 values per sequence

► ML algorithm: feature selection + RF

► additional no-ref model: brisque+nique features, similar pipeline


→ Evaluation and used Dataset






- ▶ GamingVideoSET: *Barman et al. [4]*:
 - 24 full-HD sources, 576 distorted videos, 90 with subjective scores
- ▶ two main evaluations: 10-fold cross validation and source fold:
 - (1) based on VMAF, (2) based on subjective scores
 - MOS prediction






- ▶ GamingVideoSET: *Barman et al. [4]*:
 - 24 full-HD sources, 576 distorted videos, 90 with subjective scores
- ▶ two main evaluations: 10-fold cross validation and source fold:
 - (1) based on VMAF, (2) based on subjective scores
- MOS prediction






- ▶ GamingVideoSET: *Barman et al. [4]*:
 - 24 full-HD sources, 576 distorted videos, 90 with subjective scores
- ▶ two main evaluations: 10-fold cross validation and source fold:
 - (1) based on VMAF, (2) based on subjective scores
 - MOS prediction






- ▶ GamingVideoSET: *Barman et al. [4]*:
 - 24 full-HD sources, 576 distorted videos, 90 with subjective scores
 - ▶ two main evaluations: 10-fold cross validation and source fold:
 - (1) based on VMAF, (2) based on subjective scores
- MOS prediction








- ▶ GamingVideoSET: *Barman et al. [4]*:
 - 24 full-HD sources, 576 distorted videos, 90 with subjective scores
 - ▶ two main evaluations: 10-fold cross validation and source fold:
 - (1) based on VMAF, (2) based on subjective scores
- MOS prediction



Evaluation – MOS prediction




pearson (P), spearman (S), kendall (K) and RMSE




► nofu > brisque+niqe > vmaf > ssim

► source video fold evaluation: nofu > brisque+niqe

→ Conclusion



Evaluation – MOS prediction



pearson (P), spearman (S), kendall (K) and RMSE




► $\text{nofu} > \text{brisque} + \text{niqe} > \text{vmaf} > \text{ssim}$

► source video fold evaluation: $\text{nofu} > \text{brisque} + \text{niqe}$

→ Conclusion



Evaluation – MOS prediction



pearson (P), spearman (S), kendall (K) and RMSE

- $\text{nofu} > \text{brisque} + \text{niqe} > \text{vmaf} > \text{ssim}$
- source video fold evaluation: $\text{nofu} > \text{brisque} + \text{niqe}$

→ Conclusion



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nike
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nike
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+niqe
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks



- ▶ introduced **nofu**: no-reference model for gaming video quality
 - **features**: quality-related and gaming-specific
 - **temporal pooling + 360p center crop**
 - machine learning based
- ▶ evaluation using GamingVideoSET [4]
 - **nofu** outperforms other no-ref models + VMAF
 - per source fold: promising results
- ▶ open and next steps:
 - include delay/latency, bitstream features, combine **nofu**+brisque+nique
 - use features/approach for different tasks




Thank you for your attention



..... are there any questions?



- [1] Nabajeet Barman and Maria G Martini. “H. 264/MPEG-AVC, H. 265/MPEG-HEVC and VP9 codec comparison for live gaming video streaming”. In: *Quality of Multimedia Experience (QoMEX), 2017 Ninth International Conference on*. IEEE. IEEE, 2017, pp. 1–6.
- [2] Nabajeet Barman et al. “A Comparative Quality Assessment Study for Gaming and Non-Gaming Videos”. In: *2018 Tenth International Conference on Quality of Multimedia Experience (QoMEX)*. IEEE. 2018, pp. 1–6.
- [3] Nabajeet Barman et al. “An evaluation of video quality assessment metrics for passive gaming video streaming”. In: *Proceedings of the 23rd Packet Video Workshop*. ACM. 2018, pp. 7–12.
- [4] Nabajeet Barman et al. “GamingVideoSET: a dataset for gaming video streaming applications”. In: *2018 16th Annual Workshop on Network and Systems Support for Games (NetGames)*. IEEE. 2018, pp. 1–6.



- [5] Steve Göring et al. “Analyze And Predict the Perceptibility of UHD Video Contents”. In: *Electronic Imaging, Human Vision Electronic Imaging* (2019).
- [6] ITU-T. *Subjective video quality assessment methods for multimedia applications*. Serie P: Telephone Transmission Quality, Telephone Installations, Local Line Networks. Vol. Recommendation ITU-T P.910. International Telecommunication Union. Geneva, 2008.
- [7] Ioannis Katsavounidis, Anne Aaron, and David Ronca. “Native resolution detection of video sequences”. In: *Annual Technical Conference and Exhibition, SMPTE 2015*. SMPTE. 2015, pp. 1–20.
- [8] Sebastodes Möller, Steven Schmidt, and Saman Zadtootaghaj. “New ITU-T Standards for Gaming QoE Evaluation and Management”. In: *2018 Tenth International Conference on Quality of Multimedia Experience (QoMEX)*. IEEE. 2018, pp. 1–6.



References III

- [9] Saman Zadtootaghaj et al. “A classification of video games based on game characteristics linked to video coding complexity”. In: *2018 16th Annual Workshop on Network and Systems Support for Games (NetGames)*. IEEE. 2018, pp. 1–6.

