

Software testing: week 3 report

Tuba Kaya Chomette, Sander Leer, Martijn Stegeman

September 22, 2013

```
module Week3Sol
```

```
where
```

```
import Techniques
import Week3
import Week2Sol
```

```
import System.Random
import Control.Monad
import Data.List
import Data.Char
```

getIntList

The type of this function provides no direct way to limit the amount of random numbers to generate. In order to be able to generate a usable infinite list of numbers, we have to do it lazily.

```
getIntList :: IO [Int]
getIntList = liftM (randomRs (0,15)) getStdGen
```

We also provided a set of functions to demonstrate that `getIntList` indeed works lazily and can be used to generate a list of random numbers.

```
takeM :: Monad m => Int -> m [a] -> m [a]
takeM x = liftM (take x)
```

```
randomInts :: Int -> IO [Int]
randomInts x = takeM x getIntList
```

isPermutation

```
isPermutation :: Eq a => [a] -> [a] -> Bool
isPermutation xs ys = xs `elem` permutations ys
```

Random testing for isPermutation

This function generates a random list and checks if all permutations (according to the standard `permutations` function) are actually permutations.

```

randomTestPerm :: IO Bool
randomTestPerm = do
  x <- randomInts 3
  return (and (map (isPermutation x) (drop 1 (permutations x))))

```

This function generate a random list, adds an extra number in front or at the back, and verifies that they are not permutations of the original.

```

randomTestPerm2 :: IO Bool
randomTestPerm2 = do
  x <- randomInts 3
  return ((not (isPermutation x (0:x))) && (not (isPermutation x (x++[0]))))

```

Testing the Cnf converter

```

checkCNFs :: IO ()
checkCNFs = testForms 50 checkCnf

```

All randomly generated formulas out of testForms pass as correct when converted to CNF formulas. We do notice, however, that the randomly generated formulas also sometimes contain disjunctions or conjunctions without any arguments (e.g. `+()` or `*()`). That is to say: an AND and OR operators without arguments. This should possibly not be a valid formula in logic (or valid CNF). The origin of this problem lies within the random formula generator; it generates conjunctions and disjunctions with 0.5 arguments. This can obviously be [2..] in order to conform more to the usual form of logical formulas.

```

getRandomBool :: IO Bool
getRandomBool = do
  n <- getRandomInt 1
  return (n == 1)

getRandomAtomName :: IO String
getRandomAtomName = do
  n <- getRandomInt 25
  return [chr (n + ord 'A')]

getRandomTermName :: IO String
getRandomTermName = do
  n <- getRandomInt 25
  return [chr (n + ord 'a')]

getRandomTerm :: IO Term

```

```

getRandomTerm = do
  b <- getRandomBool
  s <- getRandomTermName
  if b then do
    return (V s)
  else do
    t <- getRandomTerms 2
    return (F s t)

getRandomTerms :: Int -> IO [Term]
getRandomTerms 0 = return []
getRandomTerms d = do
  t <- getRandomTerm
  ts <- getRandomTerms (d-1)
  return (t:ts)

getRandomFormula :: Int -> IO Formula
getRandomFormula 0 = do
  s <- getRandomAtomName
  t <- getRandomTerms 2
  return (Atom s t)

getRandomFormula d = do
  n <- getRandomInt 8
  case n of
    0 -> do
      s <- getRandomAtomName
      t <- getRandomTerms 2
      return (Atom s t)
    1 -> do
      t1 <- getRandomTerm
      t2 <- getRandomTerm
      return (Eq t1 t2)
    2 -> do
      f <- getRandomFormula (d-1)
      return (Neg f)
    3 -> do
      f1 <- getRandomFormula (d-1)
      f2 <- getRandomFormula (d-1)
      return (Impl f1 f2)
    4 -> do
      f1 <- getRandomFormula (d-1)
      f2 <- getRandomFormula (d-1)
      return (Equi f1 f2)

```

```

5 -> do
    m <- getRandomInt 5
    fs <- getRandomFormulas (d-1) m
    return (Conj fs)
6 -> do
    m <- getRandomInt 5
    fs <- getRandomFormulas (d-1) m
    return (Disj fs)
7 -> do
    s <- getRandomTermName
    f <- getRandomFormula (d-1)
    return (Forall s f)
8 -> do
    s <- getRandomTermName
    f <- getRandomFormula (d-1)
    return (Exists s f)

getRandomFormulas :: Int -> Int -> IO [Formula]
getRandomFormulas _ 0 = return []
getRandomFormulas d n = do
    f <- getRandomFormula d
    fs <- getRandomFormulas d (n-1)
    return (f:fs)

getRandomFrms :: IO Formula
getRandomFrms = do
    d <- getRandomInt 2
    getRandomFormula d

```