MODULE 38 · FOUNDATIONS AND EXAM SKILLS - ALL DOMAINS

Practice exam 2

Twenty fresh questions, weighted like the real exam, with no topic repeated from paper 1.

DOMAIN Practice exam WEIGHT - MODULE 38 of 39

Make this one harder than the last

- Answer within the hold. If you need longer, note which question slowed you down.
- Write a **one-word reason** beside each answer, so you can check your reasoning too.
- Don't look anything up. Learn where the gaps are while it's free to find out.
- Compare your domain profile with paper 1, not just your total.
- A domain that drops twice is where your remaining study time belongs.

> ON THE EXAM
>
> Two papers give you a trend. Three give you confidence. One is just a mood.

> A team has improved the prompt and retrieval settings of a customer assistant. Before releasing, leadership wants evidence that answers are actually better, not just different.
>
> The team has a dataset of representative questions with expected answers.

What should they do before release?

A Ship to 5 percent of users and watch complaint volumes for a week.

B Ask three reviewers to read fifty answers and give an overall verdict.

C Run the same evaluation on both versions and compare the runs.

D Enable tracing and inspect spans for the slowest requests.

◆ PAUSE AND DECIDE

What should they do before release?

A Canary on complaints.

Slow, noisy, and users carry the cost of any regression.

B Reviewer verdict.

Useful signal, but not repeatable or comparable between versions.

C Same evaluation, compare runs.

The evaluation gate: measure both versions on identical data.

D Tracing.

Explains how a request ran, not whether answers improved.

ON THE EXAM

Domain 1. Comparing runs on one dataset is what turns 'it feels better' into evidence.

> A public sector project must run entirely in a single specified Azure region for legal reasons. The team's preferred model is not available there, though three capable alternatives are.
>
> Quality matters, but the region is not negotiable.

How should they choose a model?

A Shortlist models available in that region, then compare.

B Use the preferred model in the nearest region that offers it.

C Use the preferred model globally, and encrypt data in transit.

D Fine-tune a smaller regional model to match the preferred model.

◆ PAUSE AND DECIDE

How should they choose a model?

A Shortlist by region, then compare.

Constraints first: region eliminates, quality decides among survivors.

B Nearest region.

Still outside the required region, so the legal constraint fails.

C Global plus encryption.

Encryption protects data in transit; it doesn't control where processing happens.

D Fine-tune to match.

Fine-tuning shapes behaviour; it can't replicate another model's capability.

ON THE EXAM

Domain 1. Constraints eliminate before quality decides: region, modality, latency, budget.

A publisher classifies two million archived articles by topic. The work has no deadline beyond 'this month', runs unattended, and nobody waits for individual results.

Cost per article is the main concern.

Which deployment type fits best?

A Provisioned, to guarantee steady throughput across the whole job.

B Global Standard, submitting articles as fast as quota allows.

C Data Zone Standard, for predictable regional processing.

D Batch, which processes large jobs asynchronously at lower cost.

◆ PAUSE AND DECIDE

Which deployment type fits best?

A Provisioned.

Reserved capacity priced for steady interactive load, not a one-off archive job.

B Global Standard.

Works, but pays standard rates for work nobody is waiting on.

C Data Zone Standard.

Residency isn't stated as a requirement here, and it costs more than batch.

D Batch.

Asynchronous bulk processing at lower cost: exactly this shape of work.

ON THE EXAM

Domain 1. Nobody waiting plus huge volume plus cost pressure is the batch signal.

> A healthcare assistant passed its safety evaluations at launch six months ago. Leadership wants ongoing assurance that new jailbreak techniques won't quietly start working against it.
>
> They want this without waiting for user complaints.

What should the team set up?

A. A manual penetration test each year, run by an external supplier.

B. Scheduled AI red teaming scans, reviewed in the monitoring dashboard.

C. A stricter content filter threshold across every harm category.

D. Alerting on token usage, since attacks usually produce longer outputs.

◆ PAUSE AND DECIDE

What should the team set up?

A. Annual pen test.
A yearly snapshot, when attack techniques change monthly.

B. Scheduled red teaming.
Repeated automated attack scans, with results in the Monitor tab.

C. Stricter thresholds.
Blocks more legitimate content, and doesn't test for new attacks.

D. Token alerts.
Measures volume, which says nothing about jailbreak success.

ON THE EXAM

Domain 1. Evaluation before release; red teaming, continuously, after it.

> A large organisation now has agents in dozens of Foundry projects, built by different teams. Central IT cannot say how many exist, which models they use, or which have tools that act on systems.
>
> They need one view across the estate.

What should they use?

A Foundry Control Plane, showing the agent fleet.

B Application Insights queries against each project's traces.

C A spreadsheet maintained by each team, reviewed monthly.

D Azure Policy, to prevent teams creating agents without approval.

◆ PAUSE AND DECIDE

What should they use?

A Foundry Control Plane.

Built for fleet-wide visibility and governance across projects.

B Per-project trace queries.

Shows activity where instrumented, not an inventory of what exists.

C Spreadsheet.

Out of date the day it's written.

D Azure Policy.

Controls future creation; it doesn't reveal what's already there.

ON THE EXAM

Domain 1. Governance questions about 'how many, whose, and what can they do' point at the Control Plane.

> An assistant summarises supplier emails. An attacker sends an email containing hidden text instructing the assistant to forward the thread to an external address.
>
> The team wants Prompt Shields to detect this class of attack.

What must they do?

A Enable user prompt attack detection, which covers all incoming text.

B Add the phrase to a blocklist applied to every incoming email.

C Pass the email as document content so document attacks are detected.

D Raise the hate and violence thresholds, since attacks are malicious.

◆ PAUSE AND DECIDE

What must they do?

A User prompt detection only.

Covers what the user types, not instructions hidden in third-party content.

B Blocklist the phrase.

Exact matching, defeated by any rewording.

C Pass it as a document.

Indirect attack detection needs third-party content marked as documents.

D Harm thresholds.

Harm categories don't classify hidden instructions as harmful.

ON THE EXAM

Domain 2. Direct attacks arrive in the prompt; indirect ones arrive in content you passed in.

> A small team must ship an assistant that answers from about 200 product PDFs by the end of the week. There is no existing search index, and no one to maintain a pipeline afterwards.
>
> Answers must cite the document they came from.

What should they use?

A. A custom skillset and indexer built over a new Azure AI Search index.

B. File search, uploading the PDFs to the agent's vector store.

C. Fine-tuning a model on the contents of the 200 PDFs.

D. Pasting the most important PDFs into the agent's instructions.

◆ PAUSE AND DECIDE

What should they use?

A Custom index and skillset.

Powerful, but it's the pipeline nobody can maintain, and slower to build.

B File search.

The service chunks, embeds and cites: fastest path for a set of files.

C Fine-tuning.

Teaches behaviour, not documents, and provides no citations.

D PDFs in instructions.

Doesn't fit, doesn't scale, and costs tokens on every call.

ON THE EXAM

Domain 2. Handing over a set of files, with no index and no pipeline owner, is the file search case.

> A legal client requires that no prompt or response content is retained by the platform after a request completes. The assistant must still hold multi-turn conversations.
>
> The application can store history itself.

How should the team configure it?

A Use conversations, and delete each conversation at the end of the session.

B Use previous_response_id, which keeps history on the service side.

C Enable tracing without content recording, then rely on conversation state.

D Set store to false, and send the history from the application each turn.

◆ PAUSE AND DECIDE

How should the team configure it?

A Conversations, deleted later.

Content is retained during the session, which the requirement forbids.

B previous_response_id.

Depends on the service retaining prior responses.

C Tracing without content.

Limits telemetry, but the platform still stores conversation state.

D store=false plus client history.

Nothing is retained; the application supplies context each turn.

ON THE EXAM

Domain 2. Zero retention means store=false, with your application carrying the history.

> An agent drafts marketing copy, critiques its own draft, then revises. In production, some requests loop for minutes, and a few never return anything usable.
>
> The team wants predictable behaviour without abandoning self-critique.

What should they add?

A. A larger model, so the first draft usually passes its own critique.

B. A second critic agent, so weak drafts are caught more reliably.

C. Acceptance criteria, an iteration cap, and a fallback when it's hit.

D. Temperature zero, so the draft and critique stop varying between runs.

◆ PAUSE AND DECIDE

What should they add?

A Larger model.
Reduces loops on average; nothing stops the worst case.

B Second critic.
More critique, more turns, and still no stopping rule.

C Criteria, cap, fallback.
The three things a reflection loop needs to terminate predictably.

D Temperature zero.
More consistent output, with no bound on iterations.

ON THE EXAM

Domain 2. Every reflection loop needs acceptance criteria, an iteration cap, and a fallback. All three.

> A team connects an agent to a partner's MCP server, which exposes forty tools. The agent only needs two of them, and the security review objects to the rest being reachable.
>
> The partner will not run a separate server for them.

What should the team do?

A Restrict the connection with allowed_tools, listing only the two.

B Instruct the agent, in its system message, to use only those two tools.

C Require approval for every tool call from that MCP server.

D Copy the two tools' schemas into local function tools instead.

◆ PAUSE AND DECIDE

What should the team do?

A allowed_tools.
Limits which of the server's tools the agent can use at all.

B Instruction only.
Instructions are overridable: the other 38 stay reachable.

C Approve everything.
Adds friction without removing reachability.

D Copy schemas locally.
Function tools call your code, not the partner's server.

ON THE EXAM

Domain 2. allowed_tools is the keycard; instructions are the job description.

> An agent has been running in production for two months. The team wants to evaluate how well it actually handled real user requests, including tool use, rather than test cases.
>
> They have Application Insights connected and traces flowing.

What should they evaluate against?

A. A synthetic dataset generated to resemble production questions.

B. The original pre-release test dataset, re-run against the live agent.

C. Manually collected screenshots from the support team's tickets.

D. The agent's production traces, evaluated with agent evaluators.

◆ PAUSE AND DECIDE

What should they evaluate against?

A Synthetic data.
Useful for coverage, but it isn't what real users asked.

B Pre-release dataset.
Measures the same fixed cases, missing real-world variety.

C Screenshots.
Not a dataset, and not evaluable at scale.

D **Production traces.**
Evaluate real interactions, including the tool calls they made.

ON THE EXAM

Domain 2. Traces are an evaluation data source, which is how you grade what actually happened.

> An agent calls a function tool that books couriers. It often passes a date in the wrong format, and sometimes omits the pickup postcode entirely.
>
> The tool's description currently reads: 'Books a courier.'

What is the best fix?

A Retry failed bookings automatically, with the model correcting itself.

B Describe each parameter with format and example; mark required.

C Move the booking logic into an OpenAPI tool instead of a function tool.

D Add a second tool that validates arguments before booking is called.

◆ PAUSE AND DECIDE

What is the best fix?

A Automatic retries.
Repeats bad calls, and a courier booking is consequential.

B Parameter descriptions and strict schema.
The model fills arguments from the schema it's given.

C Switch to OpenAPI.
Changes how it's called, not how arguments are described.

D Validator tool.
Adds a round trip to work around an under-described schema.

ON THE EXAM

Domain 2. Tool schemas are prompts. Vague parameters produce vague arguments.

A team needs a 3,840 pixel wide banner image, in a 16 by 9 shape, generated from a text prompt for a campaign microsite.

Their current code requests 1024 by 1024 images and upscales them, which looks soft.

What should they do?

A Generate with GPT-Image-2, requesting the wide size directly.

B Generate four square images and stitch them into a wide banner.

C Keep upscaling, but raise quality to high before enlarging.

D Use a video model's first frame, which supports wider aspect ratios.

◆ PAUSE AND DECIDE

What should they do?

A GPT-Image-2 at the wide size.

Supports custom sizes up to a 3,840 pixel long edge, at ratios up to 3:1.

B Stitch four squares.

Visible seams, and no coherent single composition.

C Upscale from high quality.

Still enlarging pixels that were never generated.

D Video frame.

A frame from a 1280x720 video is far smaller than required.

ON THE EXAM

Domain 3. The 1-series offers three fixed sizes; GPT-Image-2 takes custom sizes with a long edge up to 3,840.

> A team generates eight-second product videos. The clips reliably start well, then drift: by the final seconds the product is mis-shaped and the camera move stops matching the prompt.
>
> The finished piece may be assembled from parts.

What should they try first?

A Add far more detail to the prompt, describing each second explicitly.

B Switch to portrait size, which the model handles more reliably.

C Use a reference image, so the product's shape stays consistent.

D Generate two four-second clips and stitch them together.

◆ PAUSE AND DECIDE

What should they try first?

A More prompt detail.

A longer prompt in one generation; instruction-following still decays.

B Portrait size.

Orientation doesn't change how well instructions hold over time.

C Reference image.

Helps the first frame; later seconds still drift.

D Two 4-second clips.

Microsoft's guidance: shorter clips follow instructions more reliably.

ON THE EXAM

Domain 3. Microsoft's own advice: two 4-second clips, stitched, often beat one 8-second clip.

> An accessibility team must produce a visual index of a photo archive, recording which objects appear in each photo and exactly where, so an editor can crop around them.
>
> Coordinates must be machine-readable.

What should they use?

A. A multimodal model, asked to describe each photo's contents in detail.

B. Image Analysis object detection, which returns bounding boxes.

C. Content Understanding, with a field schema naming each object type.

D. A model with a structured output listing objects and approximate positions.

◆ PAUSE AND DECIDE

What should they use?

A Model description.
Rich prose, no coordinates.

B Image Analysis objects.
Returns objects with bounding box coordinates: still the documented way.

C Content Understanding fields.
Extracts fields from content; it isn't an object detector.

D Model with positions.
Approximate positions like 'lower left' can't drive a crop.

ON THE EXAM

Domain 3. Where, not what: Image Analysis gives coordinates, until its 2028 retirement.

> An insurer processes 40,000 claim forms a month. They need policy numbers and adjuster codes extracted, formats are stable, and they already have thousands of labelled examples.
>
> Accuracy and consistency matter more than flexibility.

What should they build?

A Prebuilt NER, filtering its output for anything resembling a code.

B A model with a schema describing the two fields in plain language.

C Custom NER, trained on their labelled examples.

D Key phrase extraction, treating the top phrases as candidate codes.

◆ PAUSE AND DECIDE

What should they build?

A Prebuilt NER plus filtering.
Prebuilt categories don't include your policy or adjuster codes.

B Model schema.
Flexible and fast to start, but less consistent at this volume.

C Custom NER.
Your own categories, trained on labelled data: consistent, with offsets.

D Key phrases.
Legacy, and key phrases aren't identifiers.

ON THE EXAM

Domain 4. Stable categories plus labelled data plus high volume is the custom NER case.

> A council must publish planning documents as PDFs with residents' names and addresses removed. The published files must look like the originals, with the same layout, fonts and page breaks.
>
> Thousands of documents are involved.

What should they use?

A Text PII detection, re-creating each document from the redacted text.

B Conversation PII, since planning documents contain recorded statements.

C A model asked to rewrite each document with personal details removed.

D Document PII redaction, which preserves the document's layout.

◆ PAUSE AND DECIDE

What should they use?

A Text PII plus rebuild.
Redacts the words, then throws away the layout.

B Conversation PII.
Tuned for chat and transcripts, not page layout.

C Model rewrite.
Rewrites content, loses layout, and risks changing meaning.

D Document PII.
Native PDF redaction that preserves font, spacing and structure.

ON THE EXAM

Domain 4. Document PII redacts native files and keeps their layout; text PII returns strings.

> A media team receives a single two-hour interview recording at 4pm and needs a full transcript as quickly as possible for a story filing at 5pm.
>
> Nothing is being streamed; the file already exists.

Which option fits best?

A. Fast transcription, faster than real time for a file.

B. Real-time transcription, streaming the file through as it plays.

C. Batch transcription, submitting the file as an asynchronous job.

D. Voice Live, connecting the recording to a conversational agent.

◆ PAUSE AND DECIDE

Which option fits best?

A Fast transcription.

Synchronous, file-based, faster than real time: built for this.

B Real-time.

Streams at playback speed: two hours of audio, two hours of waiting.

C Batch.

For large volumes asynchronously, with no urgency guarantee.

D Voice Live.

A speech-to-speech conversation API, not a transcription service.

ON THE EXAM

Domain 4. Live means real-time; one file quickly means fast transcription; volume means batch.

> A search service is close to its vector index size limit. The team must keep serving vector search over the same corpus without buying a larger tier this quarter.
>
> A small loss of ranking precision is acceptable.

What should they configure?

A Exhaustive KNN, which doesn't consume vector index size quota.

B Quantization on the vector fields, with rescoring to recover quality.

C A semantic configuration, so the ranker compensates for fewer vectors.

D Fewer fields in the index, removing the retrievable text content.

◆ PAUSE AND DECIDE

What should they configure?

A Exhaustive KNN.

Avoids the quota, but brute-force scans won't meet production latency at scale.

B Quantization with rescoring.

Compresses vectors to cut index size, with rescoring to limit quality loss.

C Semantic configuration.

Reranks candidates; it doesn't reduce index size.

D Remove text fields.

Cuts storage but breaks citations and readable results.

ON THE EXAM

Domain 5. Quantization trades a little precision for a lot of index size.

> A team is building a brand-new skillset to chunk technical manuals for RAG. They want semantic chunking, descriptions of embedded figures, and tables that survive page breaks.
>
> They are choosing between two documented skills.

Which should they use?

A The OCR skill, followed by the Text Split skill with a large overlap.

B The Document Extraction skill, with custom post-processing code.

C The Content Understanding skill, recommended for new skillsets.

D The Document Layout skill, which has the longest track record.

◆ PAUSE AND DECIDE

Which should they use?

A OCR plus Text Split.

Splits by size, ignoring structure: tables and figures suffer.

B Extraction plus custom code.

Rebuilds by hand what a documented skill already does.

C Content Understanding skill.

Microsoft's recommendation for new skillsets: semantic chunking, image descriptions, cross-page tables.

D Document Layout skill.

Still supported, but Microsoft directs new skillsets to Content Understanding.

ON THE EXAM

Domain 5. Document Layout keeps working; new skillsets should use the Content Understanding skill.

How did you do?

- **Answer key:** C A D B A, C B D C A D B, A D B, C D A, B C.
- Compare your **domain profile** with paper 1, not just the total.
- Same domain weak twice? That's where the remaining study time goes.
- Improved total but new mistakes? You're guessing well, not knowing yet.
- Below 15 again means modules, not more papers.

> ON THE EXAM
>
> Questions 1-5 Domain 1, 6-12 Domain 2, 13-15 Domain 3, 16-18 Domain 4, 19-20 Domain 5.

Two papers show a **pattern**. Fix the pattern, not the **questions**.