FH-OÖ Hagenberg/HSD
SDP3, WS 2026
Übung 2

Name: Aufwand in h:

Mat.Nr: Punkte:

Übungsgruppe: korrigiert:

Beispiel 1 (24 Punkte) Adressenverwaltung: Eine Software für eine Adressenverwaltung (Adressen und Personen) soll ihre Daten aus Dateien einlesen, Adressen mit Personen richtig verlinken und anschließend in unterschiedlichen Dateiformaten (Ascii und Html) ausgeben.

Die Daten von Personen (Vorname, Nachname, Verweis auf zugehörige Adresse) können in einer oder mehreren Dateien abgelegt sein. Eine Personendatei ist folgendermaßen aufgebaut:

```
##########################
# Datei: pers.txt
# erstellt am: 01.10.2022
##########################
Donald Duck 0
Dagobert Duck 1
Daniel Düsentrieb 2
Max Möchtegern 2
Brid Patt 0
Jack Unterweger 1
Frank Gust 2
...
```

Die Header-Information kann überlesen werden. Die Nummer nach dem Namen entspricht dem Index auf die zugehörige Adresse.

Die Adressen sind in einer einzelnen Datei mit folgendem Aufbau abgelegt:

```
#########################################################
# Datei: adr.txt
# erstellt am: 01.10.2022
# Beschreibung: Datei speichert die Adressen von Personen
#########################################################
Kellergasse 3 4287 Radburg
Diemstrasse 1 2345 Hinterhof
Waldstrasse 45 6785 Burghausen
Domweg 123 9865 Mixbergen
...
```

Die Header-Information kann überlesen werden und die Reihenfolge der einzelnen Adressen entspricht dem Index-Verweis in der Personendatei. Die Adressen und Personen aus den einzelnen Dateien sind einzulesen und in einer entsprechenden Datenstruktur abzulegen. Die Datenstruktur verknüpft die Adressen mit den zugehörigen Personen. Die Einlesereihenfolge der Dateien ist beliebig.

Die Ausgabe der Adressen mit Personen kann entweder in einer Ascii- oder in einer HTML-Datei erfolgen:

```
Adressen mit zugeordneten Personen
----------------------------------
4287 Radburg
Kellergasse 3
    Donald Duck
    Brid Patt


2345 Hinterhof
Diemstrasse 1
    Dagobert Duck
    Jack Unterweger


6785 Burghausen
Waldstrasse 45
    Daniel Düsentrieb
    Max Möchtegern
    Frank Gust


9865 Mixbergen
Domweg 123
```

Adressen mit zugeordneten Personen

4287 Radburg
Kellergasse 3
Donald Duck
Brid Patt

2345 Hinterhof
Diemstrasse 1
Dagobert Duck
Jack Unterweger

6785 Burghausen
Waldstrasse 45
Daniel Düsentrieb
Max Möchtegern
Frank Gust

9865 Mixbergen
Domweg 123

Entwerfen Sie für die gesammte Adressenverwaltung ein Klassendiagramm und implementieren Sie die einzelnen Klassen. Verwenden Sie an geeigneter Stelle das Design-Pattern *Template Method*. Achten Sie zusätzlich auf eine entsprechende Fehlerbehandlung!

Eine Anwendung der Adressenverwaltung durch den Benutzer sieht folgendermaßen aus:

```
1  int main()
2  {
3     AddressManager adrMan;
4     PersonReader persReader;
5     AddressReader adrReader;
6     AsciiWriter ascWriter;
7     HtmlWriter  htmWriter;
8
9     adrMan.ReadFile("pers.txt", &persReader);
10    adrMan.ReadFile("pers2.txt", &persReader);
11    adrMan.ReadFile("adr.txt", &adrReader);
12    adrMan.ReadFile("pers3.txt", &persReader);
13
14    adrMan.WriteAddresses("addresses.txt", &ascWriter);
15    adrMan.WriteAddresses("addresses.html", &htmWriter);
16
17    return 0;
18 }
```

Allgemeine Hinweise: Legen Sie bei der Erstellung Ihrer Übung großen Wert auf eine **saubere Strukturierung** und auf eine **sorgfältige Ausarbeitung!** Dokumentieren Sie alle Schnittstellen und verse-

hen Sie Ihre Algorithmen an entscheidenden Stellen ausführlich mit Kommentaren! Testen Sie ihre Implementierungen ausführlich! Geben Sie den **Testoutput** mit ab!

HSD
OBERÖSTERREICH
FH-HAGENBERG

Systemdokumentation

Addressverwaltung

Version 1.0

J. Rieger, L. Kieweg

Hagenberg, 21. Oktober 2025

Dieses Dokument zeigt den prinzipiellen Aufbau einer Systemdokumentation für Software-Projekte. Die einzelnen Kapitel sind mit Kommentaren versehen, welche die Struktur und den Inhalt erläutern.

Inhaltsverzeichnis

1 Organisatorisches **2**
1.1 Team . . . 2
1.2 Aufteilung der Verantwortungsbereiche . . . 2
1.3 Aufwand . . . 2

2 Anforderungsdefinition (Systemspezifikation) **2**

3 Systementwurf **3**
3.1 Klassendiagram . . . 3
3.2 Designentscheidungen . . . 3

4 Komponentenentwurf **4**

5 Testprotokollierung **4**
5.1 Ausgabe Konsole Testtreiber . . . 4
5.2 Ascii Output File . . . 5
5.3 Html Output File . . . 6

6 Quellcode **7**

1 Organisatorisches

1.1 Team

- Julian Rieger, Matr.-Nr: S2510306023, E-Mail: S25010306023@fhooe.at
- Leander Kieweg, Matr.-Nr: S2510306014, E-Mail: S2510306014@fhooe.at

1.2 Aufteilung der Verantwortungsbereiche

- Julian Rieger
  - Implementierung der Klassen: Address, Person, Reader, AddressReader, PersonReader
  - Implementierung des Testtreibers
  - Verfassen der Systemdokumentation
- Leander Kieweg
  - Implementierung der Klassen: AddressManager, HtmlWriter, AsciiWriter, Writer
  - Design des Klassendiagrams
  - Implementierung des Testtreibers

1.3 Aufwand

- Julian Rieger: geschätzt: 7h, tatsächlich 8h
- Leander Kieweg: geschätzt 7h, tatsächlich 8h

2 Anforderungsdefinition (Systemspezifikation)

Es wird eine Verwaltungssoftware für eine Adressverwaltung bereitgestellt. Das Programm liest aus seperaten Textdateien die Adressen, sowie die Personen ein, und erstellt intern eine Zuweisung der beiden Daten. Das System beruht auf einem Template Method Pattern und besitzt eine abstrakte übergeordnete Basisklasse 'Object'. Die Addressverwaltung erfolgt ausschließlich durch die Klasse AddressManager, und liefert folgende Funktionalität:

- Das Hinzufügen von Adressen durch Auslesen einer Textdatei
- Das Hinzufügen von Personen durch Auslesen eienr Textdatei
- Das Ausgeben der registrierten Datenpaaren formatiert in HTML- und ASCII-Format.

Das Anlegen von Addressen oder Personen wird ausschließlich vom Reader ausgeführt. Das manuelle Manipulieren von den Daten des AddressManager ist nicht möglich bzw. vorgesehen. Für das Lesen und Schreiben verwendet der AddressManager intern ein dediziertes Reader und Writer Objekt, welches diese Funktionalität vollständig übernimmt. Der PersonReader und der AddressReader sind als friend-Klassen beim AddressManager definiert, sodass diese von außen den alleinigen Zugriff auf die Add-Funktionen besitzen.

3 Systementwurf

3.1 Klassendiagram




Abbildung 1: Klassendiagramm AddressManager

Anmerkung: Das Klassendiagram steht für bessere Lesbarkeit ebenfalls im Sysdoku-Ordner zur Verfügung.

3.2 Designentscheidungen

Als Design Pattern wurde das Template Method Pattern festgelegt. Es wird für die Reader und Writer Vererbung genutzt, wobei beide auch von Object erben, um den virtual destructor zu gewährleisten. Dazu zählt der AddressReader, PersonReader, HtmlWriter und AsciiWriter. Diese implementieren ihre eigenen ParseLine() bzw. WriteLine() Funktionen, je nach gewünschtem Format. Diese Funktionen sind in den Basisklassen als pure virtual markiert. Die Funktionen Read() und Write() der Basisklassen sind jedoch bereits in den Basisklassen implementiert. Reader und Writer sind beides abstrakte Klassen, d.h. ihre Konstruktoren sind als protected festgelegt, sodass diese nicht von außen zugänglich sind.

4 Komponentenentwurf

Die HTML-Startdatei befindet sich im Verzeichnis ./../doxy/html/index.html

5 Testprotokollierung

5.1 Ausgabe Konsole Testtreiber

```
[SUCCESS] person and address file are read
[SUCCESS] persons and addresses are stored
[SUCCESS] first person is Donald Duck with address 0
[SUCCESS] first address is Kellergasse 3, 4287 Radburg
[SUCCESS] ascii and html file are written
[SUCCESS] null reader -> invalid_argument
[SUCCESS] null writer -> invalid_argument
[SUCCESS] missing file -> runtime_error
[SUCCESS] wrong line format -> runtime_error
[SUCCESS] wrong address index -> out_of_range
[SUCCESS] wrong person index -> out_of_range
[SUCCESS] person without address -> out_of_range
```

5.2 Ascii Output File

Adressen mit zugeordneten Personen

4287 Radburg
Kellergasse 3
    Donald Duck
    Brid Patt

2345 Hinterhof
Diemstrasse 1
    Dagobert Duck
    Jack Unterweger

6785 Burghausen
Waldstrasse 45
    Daniel Düsentrieb
    Max Möchtegern
    Frank Gust

9865 Mixbergen
Domweg 123

5.3 Html Output File




Abbildung 2: HtmlOutput

6 Quellcode

Listing 1: ../Object.h

```
1  #ifndef OBJECT_H
2  #define OBJECT_H
3  #include <string>
4
5  /// @author Leander Kieweg
6  /// @date 21.10.2026
7  /// @brief Base class of all base classes.
8  ///
9  /// Is the common root class of all classes. If there is no other base class,
10 /// this class is to be selected as the base class.
11 class Object
12 {
13 public:
14    /// @brief Virtual default destructor -> once virtual, always virtual.
15    ///
16    /// It is not necessary to declare another virtual destructor
17    /// in derived classes.
18    virtual ~Object() = default;
19
20 protected:
21    /// @brief Protected default constructor that makes the class abstract.
22    Object() = default;
23 };
24
25 #endif
```

Listing 2: ../Address.cpp

```
1  #include "Address.h"
2
3  Address::Address(const std::string& street, std::size_t number, std::size_t zip,
       const std::string& city)
4      : mStreet(street),
5      mNumber(number),
6      mZip(zip),
7      mCity(city) {
8  }
9
10 const std::string& Address::GetStreet() const {
11     return mStreet;
12 }
13
14 std::size_t Address::GetNumber() const {
15     return mNumber;
16 }
17
18 std::size_t Address::GetZip() const {
19     return mZip;
20 }
21
22 const std::string& Address::GetCity() const {
23     return mCity;
24 }
```

Listing 3: ../Address.h

```
1  #ifndef ADDRESS_H
2  #define ADDRESS_H
3  #include <cstddef>
4  #include <string>
5
6  /// @author Julian Rieger
7  /// @date 21.10.2026
```

```
8  /// @brief Stores a postal address (street, house number, zip code, city).
9  ///
10 /// The class is a simple value class. All data is set in the constructor
11 /// and can only be read afterwards, so an address never changes.
12 class Address {
13 public:
14     /// @brief Creates an address.
15     /// @param[in] street is the name of the street.
16     /// @param[in] number is the house number.
17     /// @param[in] zip is the zip code.
18     /// @param[in] city is the name of the city.
19     Address(const std::string& street, std::size_t number, std::size_t zip, const
           std::string& city);
20
21     /// @brief Access function for the street.
22     /// @returns a constant reference to the name of the street.
23     const std::string& GetStreet() const;
24
25     /// @brief Access function for the house number.
26     /// @returns the house number.
27     std::size_t GetNumber() const;
28
29     /// @brief Access function for the zip code.
30     /// @returns the zip code.
31     std::size_t GetZip() const;
32
33     /// @brief Access function for the city.
34     /// @returns a constant reference to the name of the city.
35     const std::string& GetCity() const;
36
37 private:
38     /// @brief Name of the street.
39     std::string mStreet;
40     /// @brief House number.
41     std::size_t mNumber;
42     /// @brief Zip code.
43     std::size_t mZip;
44     /// @brief Name of the city.
45     std::string mCity;
46 };
47
48 #endif // ADDRESS_H
```

Listing 4: ../Person.cpp

```
1  #include "Person.h"
2
3  Person::Person(const std::string& firstName, const std::string& lastName, std::
       size_t addressID)
4      : mFirstName(firstName),
5      mLastName(lastName),
6      mAddressID(addressID) {
7  }
8
9  const std::string& Person::GetFirstName() const {
10     return mFirstName;
11 }
12
13 const std::string& Person::GetLastName() const {
14     return mLastName;
15 }
16
17 std::size_t Person::GetAddressID() const {
18     return mAddressID;
19 }
```

Listing 5: ../Person.h

```h
#ifndef PERSON_H
#define PERSON_H
#include <cstddef>
#include <string>

/// @author Julian Rieger
/// @date 21.10.2026
/// @brief Stores a person with its name and a link to its address.
///
/// The link is the index of the address in the AddressManager. The person
/// does not know the address itself, so persons and addresses can be read
/// from files in any order.
class Person {
public:
    /// @brief Creates a person.
    /// @param[in] firstName is the first name of the person.
    /// @param[in] lastName is the last name of the person.
    /// @param[in] addressID is the index of the address of the person.
    Person(const std::string& firstName, const std::string& lastName, std::size_t
        addressID);

    /// @brief Access function for the first name.
    /// @returns a constant reference to the first name.
    const std::string& GetFirstName() const;

    /// @brief Access function for the last name.
    /// @returns a constant reference to the last name.
    const std::string& GetLastName() const;

    /// @brief Access function for the address index.
    /// @returns the index of the address of this person.
    std::size_t GetAddressID() const;

private:
    /// @brief First name of the person.
    std::string mFirstName;
    /// @brief Last name of the person.
    std::string mLastName;
    /// @brief Index of the address in the AddressManager.
    std::size_t mAddressID;
};

#endif // PERSON_H
```

Listing 6: ../Reader.cpp

```cpp
#include "Reader.h"
#include <fstream>
#include <stdexcept>

void Reader::Read(const std::string& path, AddressManager& man) const
{
    std::ifstream file(path);
    if (!file.is_open()) {
        throw std::runtime_error("Error in Reader: could not open file '" + path +
            "'");
    }

    std::string line;
    while (std::getline(file, line))
    {
        // Skip the header (lines starting with '#') and empty lines
        if (!std::isalpha(line[0]) || line[0] == '#')
        {
            continue;
        }
        ParseLine(line, man);
    }

```

```
23      // getline also stops at a real read error, not only at the end of the file.
24      if (file.bad()) {
25          throw std::runtime_error("Error in Reader: could not read file '" + path +
                "'");
26      }
27
28      file.close();
29  }
```

Listing 7: ../Reader.h

```
1   #ifndef ADDRESSMANAGEMENT_READER_H
2   #define ADDRESSMANAGEMENT_READER_H
3
4   #include <string>
5   #include "Object.h"
6
7   class AddressManager;
8
9   /// @author Julian Rieger
10  /// @date 21.10.2026
11  /// @brief Abstract base class for all readers.
12  ///
13  /// The class uses the design pattern Template Method. The method Read
14  /// defines the fixed procedure of reading a file: open the file, skip the
15  /// header and empty lines and pass every data line to ParseLine. The derived
16  /// classes only implement ParseLine and so decide about the line format.
17  class Reader : public Object
18  {
19  public:
20      /// @brief Virtual destructor, because readers are used by pointer.
21      virtual ~Reader() = default;
22
23      /// @brief Reads a file and stores its content in the manager.
24      ///
25      /// This is the template method. Lines that start with '#' (header) and
26      /// lines that contain only white space are skipped. Every other line is
27      /// passed to ParseLine.
28      /// @param[in] path is the path of the file to read.
29      /// @param[in,out] man is the manager that stores the parsed data.
30      /// @throws std::runtime_error if the file cannot be opened or read, or
31      ///          if a line has a wrong format.
32      void Read(const std::string& path, AddressManager& man) const;
33
34  protected:
35      /// @brief Protected default constructor that makes the class abstract.
36      Reader() = default;
37
38      /// @brief Parses one data line and adds the result to the manager.
39      /// @param[in] line is the line to parse (without line break).
40      /// @param[in,out] man is the manager that stores the parsed data.
41      /// @throws std::runtime_error if the line has a wrong format.
42      virtual void ParseLine(const std::string& line, AddressManager& man) const =
            0;
43  };
44
45  #endif //ADDRESSMANAGEMENT_READER_H
```

Listing 8: ../AddressReader.cpp

```
1   #include "AddressReader.h"
2   #include <sstream>
3   #include <stdexcept>
4
5   void AddressReader::ParseLine(const std::string& line, AddressManager& man) const
6   {
7       std::string street;
```

```
8       std::size_t number;
9       std::size_t zip;
10      std::string city;
11
12      std::stringstream sstream(line);
13
14      if (sstream >> street >> number >> zip >> city)
15      {
16          Address a{ street, number, zip, city };
17          man.AddAddress(a);
18      }
19      else
20      {
21          throw std::runtime_error("Error in AddressReader: bad stream");
22      }
23  }
```

Listing 9: ../AddressReader.h

```
1   #ifndef ADDRESSREADER_H
2   #define ADDRESSREADER_H
3
4   #include "AddressManager.h"
5   #include "Reader.h"
6   #include <string>
7
8   /// @author Julian Rieger
9   /// @date 21.10.2026
10  /// @brief Reads addresses from a file.
11  ///
12  /// Every data line has the format "street number zip city". The position
13  /// of the address in the file is the index that the persons refer to.
14  class AddressReader : public Reader
15  {
16  protected:
17      /// @brief Parses a line of an address file and adds the address to the
            manager.
18      /// @param[in] line is the line to parse.
19      /// @param[in,out] man is the manager that stores the address.
20      /// @throws std::runtime_error if the line is not "street number zip city".
21      void ParseLine(const std::string& line, AddressManager& man) const override;
22  };
23
24  #endif //ADDRESSREADER_H
```

Listing 10: ../PersonReader.cpp

```
1   #include "PersonReader.h"
2   #include <sstream>
3   #include <stdexcept>
4
5   void PersonReader::ParseLine(const std::string& line, AddressManager& man) const
6   {
7       std::string firstname;
8       std::string lastname;
9       std::size_t number;
10
11      std::stringstream sstream(line);
12
13      if (sstream >> firstname >> lastname >> number)
14      {
15          Person p{ firstname, lastname, number };
16          man.AddPerson(p);
17      }
18      else
19      {
20          throw std::runtime_error("Error in PersonReader: bad stream");
21      }
22  }
```

Listing 11: ../PersonReader.h

```h
#ifndef PERSONREADER_H
#define PERSONREADER_H

#include "AddressManager.h"
#include "Reader.h"
#include <string>

/// @author Julian Rieger
/// @date 21.10.2026
/// @brief Reads persons from a file.
///
/// Every data line has the format "firstname lastname addressIndex".
/// The parsed person is added to the AddressManager.
class PersonReader : public Reader
{
protected:
    /// @brief Parses a line of a person file and adds the person to the manager.
    /// @param[in] line is the line to parse.
    /// @param[in,out] man is the manager that stores the person.
    /// @throws std::runtime_error if the line is not "firstname lastname index".
    void ParseLine(const std::string& line, AddressManager& man) const override;
};

#endif //PERSONREADER_H
```

Listing 12: ../Writer.cpp

```cpp
#include "Writer.h"
#include <fstream>
#include <stdexcept>
#include "AddressManager.h"

void Writer::Write(const std::string& path, const AddressManager& man) const
{
    // Check first, so that no half written file is created.
    for (size_t p = 0; p < man.GetPersonCount(); ++p) {
        if (man.GetPerson(p).GetAddressID() >= man.GetAddressCount())
            throw std::out_of_range("Person " + std::to_string(p) +
                                    " refers to an address that does not exist");
    }

    std::ofstream out(path);
    if (!out)
        throw std::runtime_error("File cannot be written: " + path);

    WriteHeader(out);

    for (size_t a = 0; a < man.GetAddressCount(); ++a) {
        WriteAddress(out, man.GetAddress(a));

        // Write all persons that refer to this address.
        for (size_t p = 0; p < man.GetPersonCount(); ++p) {
            const Person& person = man.GetPerson(p);
            if (person.GetAddressID() == a)
                WritePerson(out, person);
        }
        WriteAddressEnd(out);
    }

    WriteFooter(out);

    if (!out)
        throw std::runtime_error("Error while writing: " + path);
}
```

Listing 13: ../Writer.h

```h
#ifndef WRITER_H
#define WRITER_H
#include <ostream>
#include <string>
#include "Address.h"
#include "Person.h"
#include "Object.h"

class AddressManager;

/// @author Leander Kieweg
/// @date 19.10.2026
/// @brief Abstract base class for all writers.
///
/// The class uses the design pattern Template Method. The method Write
/// defines the fixed order of the output. The derived classes only
/// implement the steps and so decide about the file format.
class Writer : public Object
{
public:
    /// @brief Virtual destructor, because writers are used by pointer.
    virtual ~Writer() = default;

    /// @brief Writes all addresses with their persons to a file.
    ///
    /// This is the template method. The order is: header, then for each
    /// address the address, its persons and the end of the address,
    /// and at last the footer.
    /// @param[in] path is the path of the file to write.
    /// @param[in] man is the manager that holds the data.
    /// @throws std::out_of_range if a person refers to an address that does not
        exist.
    /// @throws std::runtime_error if the file cannot be written.
    void Write(const std::string& path, const AddressManager& man) const;

protected:
    /// @brief Protected default constructor that makes the class abstract.
    Writer() = default;

    /// @brief Writes the beginning of the file.
    /// @param[in] out is the stream to write to.
    virtual void WriteHeader(std::ostream& out) const = 0;

    /// @brief Writes one address.
    /// @param[in] out is the stream to write to.
    /// @param[in] address is the address to write.
    virtual void WriteAddress(std::ostream& out, const Address& address) const = 0;

    /// @brief Writes one person of the current address.
    /// @param[in] out is the stream to write to.
    /// @param[in] person is the person to write.
    virtual void WritePerson(std::ostream& out, const Person& person) const = 0;

    /// @brief Writes the end of the current address block.
    /// @param[in] out is the stream to write to.
    virtual void WriteAddressEnd(std::ostream& out) const = 0;

    /// @brief Writes the end of the file.
    ///
    /// The default writes nothing and can be overridden in derived classes.
    /// @param[in] out is the stream to write to.
    virtual void WriteFooter(std::ostream& out) const {}
};

#endif //WRITER_H
```

Listing 14: ../HtmlWriter.cpp

```cpp
#include "HtmlWriter.h"

void HtmlWriter::WriteHeader(std::ostream& out) const
{
    out << "<!DOCTYPE html>\n"
        << "<html lang=\"de\">\n"
        << "<head>\n"
        << "    <meta charset=\"UTF-8\">\n"
        << "    <title>Adressen mit zugeordneten Personen</title>\n"
        << "</head>\n"
        << "<body>\n"
        << "<h3>Adressen mit zugeordneten Personen</h3>\n"
        << "<hr>\n";
}

void HtmlWriter::WriteAddress(std::ostream& out, const Address& address) const
{
    out << "<p>\n"
        << "<i>" << address.GetZip() << ' ' << address.GetCity() << "<br>\n"
        << address.GetStreet() << ' ' << address.GetNumber() << "</i><br>\n";
}

void HtmlWriter::WritePerson(std::ostream& out, const Person& person) const
{
    out << person.GetFirstName() << ' ' << person.GetLastName() << "<br>\n";
}

void HtmlWriter::WriteAddressEnd(std::ostream& out) const
{
    out << "</p>\n";
}

void HtmlWriter::WriteFooter(std::ostream& out) const
{
    out << "</body>\n"
        << "</html>\n";
}
```

Listing 15: `../HtmlWriter.h`

```cpp
#ifndef HTMLWRITER_H
#define HTMLWRITER_H
#include "Writer.h"

/// @author Leander Kieweg
/// @date 19.10.2026
/// @brief Writes the addresses with their persons as an HTML page.
class HtmlWriter : public Writer
{
protected:
   /// @brief Writes the HTML head, the title and a horizontal line.
   /// @param[in] out is the stream to write to.
   void WriteHeader(std::ostream& out) const override;

   /// @brief Writes an address in italic and opens a new paragraph.
   /// @param[in] out is the stream to write to.
   /// @param[in] address is the address to write.
   void WriteAddress(std::ostream& out, const Address& address) const override;

   /// @brief Writes the name of a person in normal style.
   /// @param[in] out is the stream to write to.
   /// @param[in] person is the person to write.
   void WritePerson(std::ostream& out, const Person& person) const override;

   /// @brief Closes the paragraph of the current address.
   /// @param[in] out is the stream to write to.
   void WriteAddressEnd(std::ostream& out) const override;

   /// @brief Closes the body and the HTML page.
```

```
30     /// @param[in] out is the stream to write to.
31     void WriteFooter(std::ostream& out) const override;
32 };
33
34 #endif //HTMLWRITER_H
```

Listing 16: ../AsciiWriter.cpp

```
1  #include "AsciiWriter.h"
2
3  void AsciiWriter::WriteHeader(std::ostream& out) const
4  {
5      const std::string title = "Adressen mit zugeordneten Personen";
6      out << title << '\n'
7          << std::string(title.size(), '-') << '\n';   // line as long as the title
8  }
9
10 void AsciiWriter::WriteAddress(std::ostream& out, const Address& address) const
11 {
12     out << address.GetZip() << ' ' << address.GetCity() << '\n'
13         << address.GetStreet() << ' ' << address.GetNumber() << '\n';
14 }
15
16 void AsciiWriter::WritePerson(std::ostream& out, const Person& person) const
17 {
18     out << "    " << person.GetFirstName() << ' ' << person.GetLastName() << '\n';
19 }
20
21 void AsciiWriter::WriteAddressEnd(std::ostream& out) const
22 {
23     out << '\n';
24 }
```

Listing 17: ../AsciiWriter.h

```
1  #ifndef ASCIIWRITER_H
2  #define ASCIIWRITER_H
3  #include "Writer.h"
4
5  /// @author Leander Kieweg
6  /// @date 19.10.2026
7  /// @brief Writes the addresses with their persons as plain text.
8  class AsciiWriter : public Writer
9  {
10 protected:
11     /// @brief Writes the title and a line below it.
12     /// @param[in] out is the stream to write to.
13     void WriteHeader(std::ostream& out) const override;
14
15     /// @brief Writes the zip code and city, then the street and number.
16     /// @param[in] out is the stream to write to.
17     /// @param[in] address is the address to write.
18     void WriteAddress(std::ostream& out, const Address& address) const override;
19
20     /// @brief Writes the name of a person, indented by four spaces.
21     /// @param[in] out is the stream to write to.
22     /// @param[in] person is the person to write.
23     void WritePerson(std::ostream& out, const Person& person) const override;
24
25     /// @brief Writes an empty line between two addresses.
26     /// @param[in] out is the stream to write to.
27     void WriteAddressEnd(std::ostream& out) const override;
28 };
29
30 #endif //ASCIIWRITER_H
```

Listing 18: ../AddressManager.cpp

```cpp
#include "AddressManager.h"
#include <stdexcept>
#include "Reader.h"
#include "Writer.h"

void AddressManager::ReadFile(const std::string& path, const Reader* rdr)
{
    if (rdr == nullptr)
        throw std::invalid_argument("Reader is a null pointer");
    rdr->Read(path, *this);
}

void AddressManager::WriteAddresses(const std::string& path, const Writer* wrt)
    const
{
    if (wrt == nullptr)
        throw std::invalid_argument("Writer is a null pointer");
    wrt->Write(path, *this);
}

void AddressManager::AddPerson(const Person& person)
{
    mPersons.push_back(person);
}

void AddressManager::AddAddress(const Address& address)
{
    mAddresses.push_back(address);
}

const Address& AddressManager::GetAddress(size_t index) const
{
    return mAddresses.at(index);   // throws std::out_of_range for a wrong index
}

const Person& AddressManager::GetPerson(size_t index) const
{
    return mPersons.at(index);
}

size_t AddressManager::GetAddressCount() const
{
    return mAddresses.size();
}

size_t AddressManager::GetPersonCount() const
{
    return mPersons.size();
}
```

Listing 19: ../AddressManager.h

```cpp
#ifndef ADDRESSMANAGER_H
#define ADDRESSMANAGER_H
#include <cstddef>
#include <string>
#include <vector>
#include "Person.h"
#include "Address.h"

class Reader;
class Writer;

/// @author Leander Kieweg
/// @date 19.10.2026
/// @brief Manages addresses and persons and links them to each other.
///
/// A person refers to its address by an index. The manager reads its data
```

```
17 /// with a Reader and writes it with a Writer. Both are passed as pointers,
18 /// so the caller decides which file format is used.
19 class AddressManager
20 {
21 public:
22    /// @brief Reads a file with the given reader.
23    /// @param[in] path is the path of the file to read.
24    /// @param[in] rdr is the reader that knows the file format.
25    /// @throws std::invalid_argument if rdr is a null pointer.
26    void ReadFile(const std::string& path, const Reader* rdr);
27
28    /// @brief Writes all addresses with their persons to a file.
29    /// @param[in] path is the path of the file to write.
30    /// @param[in] wrt is the writer that knows the file format.
31    /// @throws std::invalid_argument if wrt is a null pointer.
32    void WriteAddresses(const std::string& path, const Writer* wrt) const;
33
34    /// @brief Access function for an address.
35    /// @param[in] index is the position of the address.
36    /// @returns a constant reference to the address.
37    /// @throws std::out_of_range if the index does not exist.
38    const Address& GetAddress(size_t index) const;
39
40    /// @brief Access function for a person.
41    /// @param[in] index is the position of the person.
42    /// @returns a constant reference to the person.
43    /// @throws std::out_of_range if the index does not exist.
44    const Person& GetPerson(size_t index) const;
45
46    /// @brief Access function for the number of addresses.
47    /// @returns the number of stored addresses.
48    size_t GetAddressCount() const;
49
50    /// @brief Access function for the number of persons.
51    /// @returns the number of stored persons.
52    size_t GetPersonCount() const;
53
54 private:
55    /// Only the readers are allowed to add new entries.
56    friend class PersonReader;
57    friend class AddressReader;
58
59    /// @brief Adds a person to the manager.
60    /// @param[in] person is the person to store.
61    void AddPerson(const Person& person);
62
63    /// @brief Adds an address to the manager.
64    /// @param[in] address is the address to store.
65    void AddAddress(const Address& address);
66
67    /// @brief All persons in the order they were read.
68    std::vector<Person> mPersons;
69
70    /// @brief All addresses. The position is the index used by the persons.
71    std::vector<Address> mAddresses;
72 };
73
74 #endif
```

Listing 20: `../main.cpp`

```
1 #include <iostream>
2 #include <stdexcept>
3 #include <string>
4 #include "Address.h"
5 #include "AddressManager.h"
6 #include "AddressReader.h"
7 #include "AsciiWriter.h"
8 #include "HtmlWriter.h"
```

```
 9 #include "Person.h"
10 #include "PersonReader.h"
11
12 void CheckTest(bool condition, const std::string& testName)
13 {
14     if (condition) std::cout << "[SUCCESS] " << testName << std::endl;
15     else std::cerr << "[FAILED]  " << testName << std::endl;
16 }
17
18 void RunTestDriver();
19
20 int main()
21 {
22     RunTestDriver();
23
24     return 0;
25 }
26
27 void RunTestDriver()
28 {
29     AddressManager man, noAddresses, empty;
30     PersonReader pReader;
31     AddressReader aReader;
32     HtmlWriter hWriter;
33     AsciiWriter aWriter;
34     const std::string personPath{ "../../../pers.txt" };
35     const std::string addressPath{ "../../../adr.txt" };
36     const std::string resultPathHtml{ "../../../result.html" };
37     const std::string resultPathAscii{ "../../../result.txt" };
38
39     try { man.ReadFile(personPath, &pReader); man.ReadFile(addressPath, &aReader);
           CheckTest(true, "person and address file are read"); }
40     catch (const std::exception&) { CheckTest(false, "person and address file are
           read"); }
41     CheckTest(man.GetPersonCount() > 0 && man.GetAddressCount() > 0, "persons and
           addresses are stored");
42     CheckTest(man.GetPerson(0).GetFirstName() == "Donald" && man.GetPerson(0).
           GetLastName() == "Duck" && man.GetPerson(0).GetAddressID() == 0, "first
           person is Donald Duck with address 0");
43     CheckTest(man.GetAddress(0).GetStreet() == "Kellergasse" && man.GetAddress(0).
           GetNumber() == 3 && man.GetAddress(0).GetZip() == 4287 && man.GetAddress
           (0).GetCity() == "Radburg", "first address is Kellergasse 3, 4287 Radburg"
           );
44     try { man.WriteAddresses(resultPathAscii, &aWriter); man.WriteAddresses(
           resultPathHtml, &hWriter); CheckTest(true, "ascii and html file are
           written"); }
45     catch (const std::exception&) { CheckTest(false, "ascii and html file are
           written"); }
46
47     try
48     {
49         man.ReadFile(personPath, nullptr);
50         CheckTest(false, "null reader -> invalid_argument");
51     }
52     catch (const std::invalid_argument&)
53     { CheckTest(true, "null reader -> invalid_argument"); }
54     try
55     { man.WriteAddresses(resultPathAscii, nullptr);
56     CheckTest(false, "null writer -> invalid_argument"); }
57     catch (const std::invalid_argument&)
58     {
59         CheckTest(true, "null writer -> invalid_argument");
60     }
61     try
62     {
63         man.ReadFile("no_such_file.txt", &pReader);
64         CheckTest(false, "missing file -> runtime_error");
65     }
66     catch (const std::runtime_error&)
67     {
```

```
68          CheckTest(true, "missing file -> runtime_error");
69      }
70      try
71      {
72          man.ReadFile(personPath, &aReader);
73          CheckTest(false, "wrong line format -> runtime_error");
74      }
75      catch (const std::runtime_error&)
76      {
77          CheckTest(true, "wrong line format -> runtime_error");
78      }
79      try
80      {
81          man.GetAddress(man.GetAddressCount());
82          CheckTest(false, "wrong address index -> out_of_range");
83      }
84      catch (const std::out_of_range&)
85      {
86          CheckTest(true, "wrong address index -> out_of_range");
87      }
88      try
89      {
90          empty.GetPerson(0); CheckTest(false, "wrong person index -> out_of_range")
                ;
91      }
92      catch (const std::out_of_range&)
93      {
94          CheckTest(true, "wrong person index -> out_of_range");
95      }
96      try
97      {
98          noAddresses.ReadFile(personPath, &pReader);
99          noAddresses.WriteAddresses(resultPathAscii, &aWriter);
100         CheckTest(false, "person without address -> out_of_range");
101     }
102     catch (const std::out_of_range&)
103     {
104         CheckTest(true, "person without address -> out_of_range");
105     }
106 }
```