

WPA2-Enterprise & Aruba Internal Auth Server

Auth Servers AAA Profiles L2 Authentication L3 Authentication User Rules Advanced

NAME	SERVICES	FAIL THROUGH	LOAD BALANCE	SERVER RULES	
default	1	--	--	1	
internal	1	--	--	1	
TestWLAN2_dot1_svg	1	--	--	2	

+

All Servers 1

NAME	TYPE	IP ADDRESS / HOSTNAME	SERVER GROUP	
Internal	-	-	default internal TestWLAN2_dot1_svg	

+

Server > Internal **Users** Options Import Export [Guest user page](#)

USER NAME	ROLE	EMAIL	EXPIRATION	STATIC IP FOR RAPS	ENABLED	
user1	authenticated	--	--	0.0.0.0	Yes	
user2	authenticated	--	--	0.0.0.0	Yes	

+

50 < 1 >

Auth Servers AAA Profiles L2 Authentication L3 Authentication User Rules Advanced

Server Groups 3

NAME	SERVICES	FAIL THROUGH	LOAD BALANCE	SERVER RULES
default	1	--	--	1
internal	1	--	--	1
TestWLAN2_dot1_svg	1	--	--	2

+

Server Group > TestWLAN2_dot1_svg **Servers** Options **Server Rules**

ATTRIBUTE	OPERATION	OPERAND	TYPE	ACTION	VALUE
User-Name	equals	user1	string	set vlan	5
User-Name	equals	user2	string	set vlan	6

+



Server > Internal							Guest user page
Users							
USER NAME	ROLE	EMAIL	EXPIRATION	STATIC IP FOR RAPS	ENABLED		
user1	authenticated	--	--	0.0.0.0	Yes		
user2	authenticated	--	--	0.0.0.0	Yes		



50 < 1 >

Edit User user1

User name: user1

Password: [Generate](#)

Role:

E-mail:

Static inner IP for RAPS:

Enabled: ☒

Expiration:

[Cancel](#) [Submit](#)

WLANs 2

NAME (SSID)	AP GROUP	KEY MANAGEMENT	INFORMATION
TestWLAN	default	WPA2-Personal	--
TestWLAN2	default	WPA2-Enterprise	--



WLANs 2

NAME (SSID)	AP GROUP	KEY MANAGEMENT	INFORMATION
TestWLAN	default	WPA2-Personal	--
TestWLAN2	default	WPA2-Enterprise	--



TestWLAN2 General VLANs Security Access

Name (ssid):

Primary usage: ☒ Employee ☐ Guest

Broadcast on:

Forwarding mode:

WLANs 2			
NAME (SSID)	AP GROUP	KEY MANAGEMENT	INFORMATION
TestWLAN	default	WPA2-Personal	--
TestWLAN2	default	WPA2-Enterprise	--

+

TestWLAN2

General

VLANs

Security

Access

More Secure

Enterprise

Personal

Open

Less Secure

Key management:

WPA2-Enterprise

Internal

+

Auth servers:

Reauth interval:

86400

sec.

Machine authentication:

Disabled

Denylisting:

WLANs 2			
NAME (SSID)	AP GROUP	KEY MANAGEMENT	INFORMATION
TestWLAN	default	WPA2-Personal	--
TestWLAN2	default	WPA2-Enterprise	--

+

TestWLAN2

General

VLANs

Security

Access

Default role:

guest

Derivation method:

Use value returned from clearPass or other auth server

Use rules defined in table below

Role Derivation Rules 2

ATTRIBUTE	CONDITION	MATCH STRING	ASSIGN ROLE	
User-Name	equals	user1	5	
User-Name	equals	user2	6	

+

13:05

   59%

← About this network



TestWLAN2

Connected



Disconnect



Forget



Share

Auto connect

Automatically connect when in range.



Network details

Signal strength

-33 db (Excellent)

Link speed

433 Mbps on 5 GHz

433 Mbps on 5 GHz

Security

WPA/WPA2-Enterprise

MAC address

86:dc:c8:6e:57:e2 (Random)

IPv4 address

192.168.2.3

IPv6 address

13:06

5G   59%

← About this network



TestWLAN2

Connected



Disconnect



Forget



Share

Auto connect

Automatically connect when in range.



Network details

Signal strength

-38 db (Excellent)

Link speed

433 Mbps on 5 GHz

433 Mbps on 5 GHz

Security

WPA/WPA2-Enterprise

MAC address

86:dc:c8:6e:57:e2 (Random)

IPv4 address

192.168.3.2

IPv6 address
