

Let $\mathbb{G}_1, \mathbb{G}_2$ and \mathbb{G}_T be groups of order p and let $e : \mathbb{G}_1 \times \mathbb{G}_2 \rightarrow \mathbb{G}_T$ be the bilinear map. The IBE system works as follows.

Setup: The PKG picks random generators $p_1, g_1 \in \mathbb{G}_1$, generators $q_2, h_1, h_2, h_3 \in \mathbb{G}_2$ and a random $\alpha \in \mathbb{Z}_p$. It sets $g_1 = p_1^\alpha \in \mathbb{G}_1$. It chooses a hash function H_1 and $H_2 : \{0, 1\}^* \rightarrow \{0, 1\}^n$ from a family of universal one-way hash functions. The public *params* and private *masterkey* are given by

$$params = (p_1, q_2, h_1, h_2, h_3, H_1, H_2) \quad masterkey = \alpha$$

KeyGen: To generate a private key for identity $ID \in \mathbb{Z}_p$, the PKG generates random $r_{ID,i} \in \mathbb{Z}_p$ for $i \in \{1, 2, 3\}$, and outputs the private key

$$d_{ID} = \{(r_{ID,i}, h_{ID,i}) : i \in \{1, 2, 3\}\}, \text{ where } h_{ID,i} = (h_i q_2^{-r_{ID,i}})^{\frac{1}{\alpha-ID}} \in \mathbb{G}_2$$

If $ID = \alpha$, the PKG aborts. As before, we require that the PKG always use the same random values $\{r_{ID,i}\}$ for ID .

Encrypt: To encrypt $m \in \{1, 0\}^n$ using identity $ID \in \mathbb{Z}_p$, the sender generates random $s \in \mathbb{Z}_p$, and sends the ciphertext

$$\begin{aligned} C &= \left(g_1^s p_1^{-s \cdot ID}, e(p_1, q_2)^s, m \oplus H_2\{e(p_1, h_1)^s\}, e(p_1, h_2)^s e(p_1, h_3)^{s\beta} \right) \\ &= (u, v, w, y) \end{aligned}$$

Note that $u \in \mathbb{G}_1, v \in \mathbb{G}_T, w \in \{1, 0\}^n$ and $y \in \mathbb{G}_T$. We set $\beta = H_1\{u, v, w\}$. Encryption does not require any pairing computations once $e(p_1, q_2)$, and $\{e(p_1, h_i)\}$ have been pre-computed or alternatively included in *params*.

Decrypt: To decrypt ciphertext $C = (u, v, w, y)$ with ID , the recipient sets $\beta = H_1\{u, v, w\}$ and tests whether

$$y = e\left(u, h_{ID,2} h_{ID,3}^\beta\right) v^{r_{ID,2} + r_{ID,3}\beta}$$

If the check fails, the recipient outputs \perp . Otherwise, it outputs

$$m = w \oplus H_2\{e(u, h_{ID,1}) v^{r_{ID,1}}\}$$

Correctness: Assuming the ciphertext is well-formed for ID :

$$\begin{aligned} &e\left(u, h_{ID,2} h_{ID,3}^\beta\right) v^{r_{ID,2} + r_{ID,3}\beta} \\ &= e\left(p_1^{s(\alpha-ID)}, \left(h_2 h_3^\beta\right)^{\frac{1}{\alpha-ID}} q_2^{\frac{-(r_{ID,2} + r_{ID,3}\beta)}{\alpha-ID}}\right) e(p_1, q_2)^{s(r_{ID,2} + r_{ID,3}\beta)} \\ &= e\left(p_1^{s(\alpha-ID)}, \left(h_2 h_3^\beta\right)^{\frac{1}{\alpha-ID}}\right) = e(p_1, h_2)^s e(p_1, h_3)^{s\beta} \end{aligned}$$

Thus, the check passes. Moreover, as in the ANON-IND-ID CPA scheme,

$$e(u, h_{ID}) v^{r_{ID,1}} = e\left(p_1^{s(\alpha-ID)}, h^{\frac{1}{\alpha-ID}} q_2^{\frac{-r_{ID,1}}{\alpha-ID}}\right) e(p_1, q_2)^{sr_{ID,1}} = e(p_1, h)^s,$$

as required.