


Data Structures and Abstractions with Java™


5th Edition



Chapter 25

Tree Implementations

Nodes in a Binary Tree



© 2019 Pearson Education, Inc.

FIGURE 25-1 A node in a binary tree

Binary Tree Node (Part 1)

```
package TreePackage;
/** A class that represents nodes in a binary tree. */
class BinaryNode<T>
{
    private T      data;
    private BinaryNode<T> leftChild; // Reference to left child
    private BinaryNode<T> rightChild; // Reference to right child

    public BinaryNode()
    {
        this(null); // Call next constructor
    } // end default constructor

    public BinaryNode(T dataPortion)
    {
        this(dataPortion, null, null); // Call next constructor
    } // end constructor

    public BinaryNode(T dataPortion, BinaryNode<T> newLeftChild,
                      BinaryNode<T> newRightChild)
    {
        data = dataPortion;
        leftChild = newLeftChild;
        rightChild = newRightChild;
    } // end constructor
}
```

LISTING 25-1 The class BinaryNode

Binary Tree Node (Part 2)

```
/** Retrieves the data portion of this node.
    @return The object in the data portion of the node. */
public T getData(). {
    return data;
} // end getData

/** Sets the data portion of this node.
    @param newData The data object. */
public void setData(T newData) {
    data = newData;
} // end setData

/** Retrieves the left child of this node.
    @return A reference to this node's left child. */
public BinaryNode<T> getLeftChild()
{
    return leftChild;
} // end getLeftChild

/** Sets this node's left child to a given node.
    @param newLeftChild A node that will be the left child. */
public void setLeftChild(BinaryNode<T> newLeftChild)
{
    leftChild = newLeftChild;
} // end setLeftChild
```

LISTING 25-1 The class BinaryNode

Binary Tree Node (Part 3)

```
/** Detects whether this node has a left child.
    @return True if the node has a left child. */
public boolean hasLeftChild()
{
    return leftChild != null;
} // end hasLeftChild

/* Implementations of getRightChild, setRightChild, and hasRightChild
   are here and are analogous to their left-child counterparts. */

/** Detects whether this node is a leaf.
    @return True if the node is a leaf. */
public boolean isLeaf()
{
    return (leftChild == null) && (rightChild == null);
} // end isLeaf

/** Counts the nodes in the subtree rooted at this node.
    @return The number of nodes in the subtree rooted at this node. */
public int getNumberOfNodes()
{
    // < Coming later — See Segment 25.10. >
} // end getNumberOfNodes
```

LISTING 25-1 The class BinaryNode

Binary Tree Node (Part 4)

```
/** Computes the height of the subtree rooted at this node.  
    @return The height of the subtree rooted at this node. */  
public int getHeight()  
{  
    // < Coming later — See Segment 25.10. >  
} // end getHeight  
  
/** Copies the subtree rooted at this node.  
    @return The root of a copy of the subtree rooted at this node. */  
public BinaryNode<T> copy()  
{  
    // < Coming later — See Segment 25.5. >  
} // end copy  
} // end BinaryNode
```

LISTING 25-1 The class BinaryNode

Interface for a Basic Binary Tree

```
package TreePackage;
/** An interface for the ADT binary tree. */
public interface BinaryTreeInterface<T> extends TreeInterface<T>,
    TreeliteratorInterface<T>
{
    /** Sets the data in the root of this binary tree.
     * @param rootData The object that is the data for the tree's root.
     */
    public void setRootData(T rootData);

    /** Sets this binary tree to a new binary tree.
     * @param rootData The object that is the data for the new tree's root.
     * @param leftTree The left subtree of the new tree.
     * @param rightTree The right subtree of the new tree. */
    public void setTree(T rootData, BinaryTreeInterface<T> leftTree,
        BinaryTreeInterface<T> rightTree);
} // end BinaryTreeInterface
```

Interface for a class of binary trees

Creating a Basic Binary Tree (Part 1)

```
package TreePackage;
import java.util.Iterator;
import java.util.NoSuchElementException;
import StackAndQueuePackage.*; // Needed by tree iterators
/** A class that implements the ADT binary tree. */
public class BinaryTree<T> implements BinaryTreeInterface<T>
{
    private BinaryNode<T> root;

    public BinaryTree()
    {
        root = null;
    } // end default constructor

    public BinaryTree(T rootData)
    {
        root = new BinaryNode<>(rootData);
    } // end constructor

    public BinaryTree(T rootData, BinaryTree<T> leftTree, BinaryTree<T> rightTree)
    {
        initializeTree(rootData, leftTree, rightTree);
    } // end constructor
}
```

LISTING 25-2 A first draft of the class **BinaryTree**

Creating a Basic Binary Tree (Part 2)

```
public void setTree(T rootData, BinaryTreeInterface<T> leftTree,  
                  BinaryTreeInterface<T> rightTree)
```

```
{  
    initializeTree(rootData, (BinaryTree<T>)leftTree,  
                  (BinaryTree<T>)rightTree);  
} // end setTree
```

```
    private void initializeTree(T rootData, BinaryTree<T> leftTree,  
                               BinaryTree<T> rightTree)
```

```
{  
    // < FIRST DRAFT - See Segments 25.4 - 25.7 for improvements. >  
    root = new BinaryNode<T>(rootData);
```

```
    if (leftTree != null)  
        root.setLeftChild(leftTree.root);
```

```
    if (rightTree != null)  
        root.setRightChild(rightTree.root);  
} // end initializeTree
```


```
/* Implementations of setRootData, getRootData, getHeight, getNumberOfNodes,  
   isEmpty, clear, and the methods specified in TreeIteratorInterface are here.  
   ... */
```

```
} // end BinaryTree
```

LISTING 25-2 A first draft of the class **BinaryTree**

Creating a Binary Tree

```
treeA.setTree(a, treeB, treeC);
```



© 2019 Pearson Education, Inc.

FIGURE 25-2 The binary tree `treeA` shares nodes with `treeB` and `treeC`

The Method copy

```
/** Copies the subtree rooted at this node. */  
public BinaryNode<T> copy()  
{  
    BinaryNode<T> newRoot = new BinaryNode<>(data);  
    if (leftChild != null)  
        newRoot.setLeftChild(leftChild.copy());  
  
    if (rightChild != null)  
        newRoot.setRightChild(rightChild.copy());  
  
    return newRoot;  
} // end copy
```


Definition of the method copy in the class BinaryNode

The Method `initializeTree`

```
private void initializeTree(T rootData,  
                             BinaryTree<T> leftTree,  
                             BinaryTree<T> rightTree)  
{  
    root = new BinaryNode<>(rootData);  
    if ((leftTree != null) && !leftTree.isEmpty())  
        root.setLeftChild(leftTree.root.copy());  
    if ((rightTree != null) && !rightTree.isEmpty())  
        root.setRightChild(rightTree.root.copy());  
} // end initializeTree
```

Method `initializeTree` can invoke `copy` to copy the nodes from the two given subtrees

Additional Challenges



© 2019 Pearson Education, Inc.

FIGURE 25-3 `treeA` has identical subtrees

Method `initializeTree` Solution

- If left subtree exists and not empty,
 - attach root node to `r` as left child.
- Create root node `r` containing given data.
- If right subtree exists, not empty, and distinct from left subtree,
 - attach root node to `r` as a right child.
- But if right and left subtrees are same,
 - attach copy of right subtree to `r` instead.
- If the left subtree exists and differs from the tree object used to call `initializeTree`,
 - set the subtree's data field root to null.
- If right subtree exists and differs from the tree object used to call `initializeTree`,
 - set subtree's data field root to null.

Method `initializeTree` Solution

```
private void initializeTree(T rootData,
                           BinaryTree<T> leftTree,
                           BinaryTree<T> rightTree)
{
    root = new BinaryNode<>(rootData);

    if ((leftTree != null) && !leftTree.isEmpty())
        root.setLeftChild(leftTree.root);

    if ((rightTree != null) && !rightTree.isEmpty())
    {
        if (rightTree != leftTree)
            root.setRightChild(rightTree.root);
        else
            root.setRightChild(rightTree.root.copy());
    } // end if

    if ((leftTree != null) && (leftTree != this))
        leftTree.clear();

    if ((rightTree != null) && (rightTree != this))
        rightTree.clear();
} // end initializeTree
```

An implementation of `initializeTree`

BinaryTree Accessor and Mutator Methods

```
public void setRootData(T rootData)
{
    root.setData(rootData);
} // end setRootData
```

```
public T getRootData()
{
    if (isEmpty())
        throw new EmptyTreeException();
    else
        return root.getData();
} // end getRootData
```

```
protected void setRootNode(BinaryNode<T> rootNode)
{
    root = rootNode;
} // end setRootNode
```

```
protected BinaryNode<T> getRootNode()
{
    return root;
} // end getRootNode
```


More BinaryTree Methods

```
public int getHeight()  
{  
    int height = 0;  
    if (root != null)  
        height = root.getHeight();  
    return height;  
} // end getHeight
```

```
public int getNumberOfNodes()  
{  
    int numberOfNodes = 0;  
    if (root != null)  
        numberOfNodes = root.getNumberOfNodes();  
    return numberOfNodes;  
} // end getNumberOfNodes
```

Computing the Height and Counting Nodes

Methods within BinaryNode.

```
public int getHeight()  
{  
    return getHeight(this); // Call private getHeight  
} // end getHeight  
  
private int getHeight(BinaryNode<T> node)  
{  
    int height = 0;  
  
    if (node != null)  
        height = 1 + Math.max(getHeight(node.getLeftChild()),  
                               getHeight(node.getRightChild()));  
  
    return height;  
}
```

Methods within BinaryNode

```
public int getNumberOfNodes()
{
    int leftNumber = 0;
    int rightNumber = 0;

    if (left != null)
        leftNumber = left.getNumberOfNodes();

    if (right != null)
        rightNumber = right.getNumberOfNodes();

    return 1 + leftNumber + rightNumber;
} // end getNumberOfNodes
```

Traversing a binary tree recursively

```
public void inorderTraverse()  
{  
    inorderTraverse(root);  
} // end inorderTraverse
```

```
private void inorderTraverse(BinaryNode<T> node)  
{  
    if (node != null)  
    {  
        inorderTraverse(node.getLeftChild());  
        System.out.println(node.getData());  
        inorderTraverse(node.getRightChild());  
    } // end if  
} // end inorderTraverse
```




FIGURE 25-4 A binary tree

Non-recursive Traversal




FIGURE 25-5 Using a stack to perform an in-order traversal of a binary tree

Non-recursive Traversal

```
public void iterativeInorderTraverse()
{
    StackInterface<BinaryNode<T>> nodeStack = new LinkedStack<>();
    BinaryNode<T> currentNode = root;

    while (!nodeStack.isEmpty() || (currentNode != null))
    {
        // Find leftmost node with no left child
        while (currentNode != null)
        {
            nodeStack.push(currentNode);
            currentNode = currentNode.getLeftChild();
        } // end while

        // Visit leftmost node, then traverse its right subtree
        if (!nodeStack.isEmpty())
        {
            BinaryNode<T> nextNode = nodeStack.pop();
            // Assertion: nextNode != null, since nodeStack was not empty
            // before the pop
            System.out.println(nextNode.getData());
            currentNode = nextNode.getRightChild();
        } // end if
    } // end while
} // end iterativeInorderTraverse
```

Iterative version ...

Traversals That Use An Iterator (Part 1)

```
private class InorderIterator implements Iterator<T>
{
    private StackInterface<BinaryNode<T>> nodeStack;
    private BinaryNode<T> currentNode;

    public InorderIterator()
    {
        nodeStack = new LinkedStack<>();
        currentNode = root;
    } // end default constructor

    public void remove()
    {
        throw new UnsupportedOperationException();
    } // end remove

    public boolean hasNext()
    {
        return !nodeStack.isEmpty() || (currentNode != null);
    } // end hasNext
}
```

LISTING 25-3 The private inner class InorderIterator

Traversals That Use An Iterator (Part 2)

```
public T next()
{
    BinaryNode<T> nextNode = null;


    // Find leftmost node with no left child
    while (currentNode != null)
    {
        nodeStack.push(currentNode);
        currentNode = currentNode.getLeftChild();
    } // end while

    // Get leftmost node, then move to its right subtree
    if (!nodeStack.isEmpty())
    {
        nextNode = nodeStack.pop();
        // Assertion: nextNode != null, since nodeStack was not empty
        // before the pop
        currentNode = nextNode.getRightChild();
    }
    else
        throw new NoSuchElementException();


    return nextNode.getData();
} // end next
} // end InorderIterator
```

LISTING 25-3 The private inner class InorderIterator

Using a Stack to Traverse a Binary Tree



© 2019 Pearson Education, Inc.



© 2019 Pearson Education, Inc.

FIGURE 25-6 Using a stack to traverse a binary tree in preorder and postorder

Using a Queue for Level-Order Traversal




FIGURE 25-7 Using a queue to traverse a binary tree in level order

Implementation of an Expression Tree

```
package TreePackage;
/** An interface for an expression tree. */
public interface ExpressionTreeInterface
    extends BinaryTreeInterface<String>
{
    /** Computes the value of the expression in this tree.
     * @return The value of the expression. */
    public double evaluate();
} // end ExpressionTreeInterface
```

LISTING 25-4 An interface for an expression tree

Implementation of an Expression Tree (Part 1)

```
package TreePackage;
/** A class that implements an expression tree by extending BinaryTree. */
public class ExpressionTree extends BinaryTree<String>
    implements ExpressionTreeInterface
{
    public ExpressionTree()
    {
    } // end default constructor

    public double evaluate()
    {
        return evaluate(getRootNode());
    } // end evaluate

    private double getValueOf(String variable)
    { // Strings allow multicharacter variables

        double result = 0;

        // To be defined.

        return result;
    } // end getValueOf
```

LISTING 25-5 The class ExpressionTree

Implementation of an Expression Tree (Part 1)


```
private double compute(String operator, double firstOperand, double secondOperand)
{
    double result = 0;
    // To be defined.
    return result;
} // end compute
```

```
private double evaluate(BinaryNode<String> rootNode) {
    double result;
    if (rootNode == null)
        result = 0;
    else if (rootNode.isLeaf()) {
        String variable = rootNode.getData();
        result = getValueOf(variable);
    }
    else
    {
        double firstOperand = evaluate(rootNode.getLeftChild());
        double secondOperand = evaluate(rootNode.getRightChild());
        String operator = rootNode.getData();
        result = compute(operator, firstOperand, secondOperand);
    } // end if

    return result;
} // end evaluate
} // end ExpressionTree
```

LISTING 25-5 The class ExpressionTree

Representing General Trees



© 2019 Pearson Education, Inc.

FIGURE 25-8 A node for a general tree


Representing General Trees

```
package TreePackage;
import java.util.Iterator;
/** An interface for a node in a general tree.*/
interface GeneralNodeInterface<T>
{
    public T getData();
    public void setData(T newData);
    public boolean isLeaf();
    public Iterator<GeneralNodeInterface<T>> getChildrenIterator();
    public void addChild(GeneralNodeInterface<T> newChild);
} // end GeneralNodeInterface
```


LISTING 25-6 An interface for a node in a general tree

Representing General Trees

(a) A general tree



(b) An equivalent binary tree



(c) The same binary tree in a conventional form




FIGURE 25-9 A general tree and two views of an equivalent binary tree

End

Chapter 25