# CENTER FOR SKILL ENTREPRENEURSHIP DEVLOPMENT (CSED)

## ADVANCED ARTIFICAL INTELLIGENCE

**IIOT -6**

# REAL – TIME OBJECT DETECTION SYSYTEM USING YOLOv8

**MENTOR NAME :**

Mr. PAWAN SHARMA

# DEPARTMENT OF COMPUTER SCIENCE ENGINEERING

COURSE NAME: **B.TECH (CSE )**

| TEAM MEMBERS | STUDENT ID | ROLE |
|---|---|---|
| Snehil Singh (LEAD) | BCS2023006 | Data Engineer |
| Milli Shrivastava (Co-Ordinator) | BCS2023004 | QA Tester |
| Aishwary Maheswari ( Co – Leader ) | BCS2023011 | Backend Engineer |
| Ayush Parashari | BCS2023047 | ML Engineer |
| Vanshit Gupta | BCS2023146 | Documentation |
| Sujoy Dev | BCS2023149 | Frontend Engineer |
| Navneet Bhatnagar | BCS2023065 | Frontend Engineer |
| Jayesh Prakash Shukla | BCS2023049 | Backend Engineer |

# CERTIFICATE

This is to certify that the project titled "Real-Time Object Detection System using YOLOv8" has been successfully completed by the above-mentioned team members as part of the Industrial Internet of Things (IIOT-6) program under the Machine Learning specialization at the Center for Skill and Entrepreneurship Development (CSED), Invertis University Bareilly.

The project demonstrates practical implementation of computer vision and deep learning techniques using the YOLOv8 model for real-time object detection. The team has successfully built, trained, and deployed a complete end-to-end application capable of detecting 80 COCO object classes across image, video, and live webcam inputs.

Mentor Signature: _____Date: _____

# ACKNOWLEDGEMENT

We take immense pleasure in expressing our sincere gratitude to all those who have contributed to the successful completion of this project on Real-Time Object Detection using YOLOv8.

First and foremost, we are deeply thankful to our mentor, Mr. Pawan Sharma, for his invaluable guidance, continuous encouragement, and technical expertise throughout the development of this project. His insightful feedback and patient mentoring helped us overcome every challenge encountered during implementation.

We extend our heartfelt thanks to the Center for Skill and Entrepreneurship Development (CSED) and Invertis University Bareilly for providing us with the necessary infrastructure, computational resources, and an enriching academic environment that made this project possible.

We are also grateful to the open-source community, particularly the Ultralytics team for developing YOLOv8, the creators of the COCO dataset, and the contributors to OpenCV, PyTorch, and Gradio libraries, whose tools formed the technical backbone of this project.

Finally, we acknowledge the support and motivation of our family members and friends who stood by us during the demanding phases of this project. Their encouragement kept our spirits high and our determination strong.

**Team Members:**

Snehil Singh
Milli Shrivastava
Aishwary Maheswari
Ayush Parashari
Vanshit Gupta
Sujoy Dev
Navneet Bhatnagar
Jayesh Prakash Shukla

# ABSTRACT

Object detection is one of the most fundamental and impactful tasks in the field of computer vision. With the rapid advancement of deep learning techniques, real-time object detection systems have achieved unprecedented levels of accuracy and speed, enabling a wide range of practical applications from autonomous vehicles and surveillance systems to medical diagnostics and industrial automation.

This project presents the design, development, and deployment of a Real-Time Object Detection Web Application using YOLOv8, the state-of-the-art model from the Ultralytics library. The system is capable of detecting 80 object classes from the COCO dataset in real time using webcam input, uploaded images, and uploaded video files.

The application leverages Python, OpenCV, and the Ultralytics YOLOv8 framework for model inference, and Gradio for building an interactive and user-friendly web interface. The system is deployed on Hugging Face Spaces, making it publicly accessible without any local setup requirements.

Key features include adjustable confidence thresholds, real-time bounding box rendering with class labels, multi-model support (YOLOv8n through YOLOv8m), and a self-learning pipeline that saves low-confidence detections for future retraining. The model achieves a mean Average Precision (mAP50) of approximately 0.55 on the COCO validation set and sustains 15+ FPS on CPU and 30+ FPS on GPU hardware.

The project was developed following Agile methodology with seven specialized team members, managed through JIRA for sprint planning and task tracking. This report provides a comprehensive overview of the system architecture, model pipeline, implementation details, results, and future scope.

**Keywords:** YOLOv8, Object Detection, Computer Vision, Deep Learning, COCO Dataset, Real-Time Detection, Gradio, Hugging Face, OpenCV, Flask, Bounding Box, Confidence Score, mAP, Transfer Learning

# INDEX


| # | Section Title | Page |
|---|---|---|
| 1 | Introduction | 6 |
| 2 | Problem Statement | 7 |
| 3 | Objectives of the Project | 8 |
| 4 | Methodology | 9 |
| 5 | Literature Review | 11 |
| 6 | System Architecture | 13 |
| 7 | Workflow | 15 |
| 8 | Model Pipeline (YOLOv8) | 17 |
| 9 | Explanation of Project (Working) | 21 |
| 10 | Technologies Used | 23 |
| 11 | Implementation (Code Explanation) | 25 |
| 12 | Project Management using JIRA | 28 |
| 13 | Results & Discussion | 30 |
| 14 | Snippets of UI | 32 |
| 15 | Advantages | 34 |
| 16 | Limitations | 35 |
| 17 | Future Scope | 36 |
| 18 | Conclusion | 38 |
| 19 | References | 40 |

# 1. INTRODUCTION

## Introduction

Object detection is one of the most critical and widely researched problems in computer vision. It involves not only identifying what objects are present in an image or video frame, but also precisely locating them using bounding boxes. Over the past decade, the field has undergone a revolutionary transformation, moving from hand-crafted feature-based methods such as Histogram of Oriented Gradients (HOG) and Viola-Jones algorithms to powerful deep learning-based approaches that far surpass human-level accuracy in specific benchmarks.

Among the many object detection architectures developed in recent years, the YOLO (You Only Look Once) family of models has consistently stood out for its remarkable balance between detection speed and accuracy. Unlike two-stage detectors such as Faster R-CNN, YOLO performs object detection in a single forward pass of the neural network, making it inherently faster and more suitable for real-time applications.

YOLOv8, released by Ultralytics in 2023, represents the latest evolution of this family. It introduces significant architectural improvements including a new anchor-free detection head, an enhanced feature pyramid network (FPN) for multi-scale feature extraction, and improved training techniques including advanced data augmentation strategies. YOLOv8 is available in five model sizes: nano (n), small (s), medium (m), large (l), and extra-large (x), allowing developers to make trade-offs between inference speed and detection accuracy based on their deployment requirements.

This project builds a complete Real-Time Object Detection Web Application that integrates YOLOv8 with a Gradio-based web interface, allowing users to perform object detection through three modes: live webcam streaming, image file upload, and video file upload. The application is deployed on Hugging Face Spaces, making it freely accessible from any browser without requiring local installation.

The system supports detection of 80 object classes as defined by the COCO (Common Objects in Context) dataset, including persons, vehicles, animals, household items, and electronic devices. Users can interactively adjust the confidence threshold and switch between model sizes in real time, providing a highly flexible and educational tool for exploring object detection capabilities.

# 2. PROBLEM STATEMENT

## Problem Statement

In today's rapidly evolving technological landscape, the demand for intelligent visual recognition systems has grown exponentially across diverse sectors including public safety and surveillance, autonomous transportation, retail and inventory management, healthcare diagnostics, and industrial quality control. However, despite the significant theoretical advances in computer vision research, several practical challenges continue to hinder the widespread adoption of real-time object detection systems.

The primary challenge is the trade-off between detection accuracy and processing speed. Traditional object detection models often sacrifice one for the other — highly accurate models are computationally expensive and unsuitable for real-time use, while fast models compromise on accuracy. This creates a critical gap in applications that require both speed and precision simultaneously, such as surveillance systems and autonomous vehicles.

Furthermore, existing solutions are often limited in accessibility. Many state-of-the-art object detection systems require specialized hardware (high-end GPUs), complex installation procedures, and technical expertise to operate. This creates a significant barrier for researchers, students, and small organizations who wish to leverage these capabilities without extensive resources.

There is also a notable absence of versatile detection platforms that can handle multiple input modalities — live webcam streams, static images, and video files — within a single unified interface. Most available tools are specialized for a single input type, requiring users to maintain multiple separate tools for different tasks.

Additionally, the static nature of deployed models presents a long-term limitation. As real-world environments evolve and new object categories emerge, models trained on fixed datasets gradually decrease in effectiveness. The lack of a systematic mechanism to collect uncertain or low-confidence detections for future retraining perpetuates this degradation.

**Therefore, the need exists for a system that can:**

- Perform accurate and fast object detection in real time across multiple input types
- Be accessible through a simple web interface without requiring local installation
- Support multiple model configurations to serve different performance requirements
- Incorporate a self-learning mechanism to continuously improve over time
- Deploy on a cloud platform for universal accessibility

# 3. OBJECTIVES OF THE PROJECT

## Objectives of the Project

The primary objective of this project is to design, develop, and deploy a comprehensive real-time object detection web application using the YOLOv8 deep learning model, capable of accurately detecting 80 COCO object classes across multiple input modalities with a user-friendly interface.

**The specific objectives are:**

- To implement a real-time object detection pipeline using YOLOv8 (yolov8m) that achieves a minimum of 15 FPS on CPU hardware and 30 FPS on GPU hardware
- To build a multi-modal detection interface supporting live webcam streams, image file uploads (JPG, PNG, BMP, WebP), and video file uploads (MP4, AVI, MOV, MKV)
- To integrate accurate bounding box rendering with class labels and confidence score display for each detected object
- To provide an adjustable confidence threshold control allowing users to filter detections based on their required certainty level
- To implement a model selection feature supporting multiple YOLOv8 variants (nano, small, medium) to balance speed versus accuracy based on use case
- To develop a self-learning data collection pipeline that automatically saves low-confidence detections for future model retraining and improvement
- To configure the full training pipeline using the COCO dataset (80 classes) with data augmentation techniques optimized for the RTX 4060 GPU
- To evaluate the trained model using standard metrics including mAP50, mAP50-95, Precision, and Recall on the COCO validation set
- To deploy the complete application on Hugging Face Spaces using the Gradio framework for cloud-based public accessibility
- To apply Agile project management methodology with sprint-based development, team role allocation, and JIRA-based task tracking

This project aims to bridge the gap between cutting-edge academic research in computer vision and practical, accessible real-world deployment, making state-of-the-art object detection available to a broad audience through a simple web interface.

# 4. METHODOLOGY

## Methodology

The methodology of this project follows a systematic, multi-phase approach inspired by the Software Development Life Cycle (SDLC) and Agile principles. Each phase builds upon the previous, ensuring a structured progression from data preparation through model training, application development, and final deployment.

### Phase 1: Dataset Preparation and Environment Setup

The first phase involves configuring the development environment and preparing the dataset. The training environment is set up on a machine equipped with an NVIDIA RTX 4060 GPU (8GB VRAM), CUDA 12.1, and Python 3.10. The required libraries — PyTorch, Ultralytics YOLOv8, OpenCV, and Gradio — are installed within a dedicated virtual environment.

For dataset preparation, the COCO (Common Objects in Context) dataset is downloaded and structured into the YOLO format, which organizes images and corresponding label files into train, val, and test splits. A data.yaml configuration file is created specifying the dataset paths, the number of classes (80), and the complete list of class names. Data augmentation techniques including horizontal flipping, random scaling, HSV color adjustments, mosaic augmentation, and mixup are configured to improve model generalization.

### Phase 2: Model Training and Evaluation

In this phase, the YOLOv8m (medium) pretrained model is used as the starting point through transfer learning. The model is fine-tuned on the COCO dataset using the following optimized training configuration: 100 epochs, batch size of 16, image size of 640x640 pixels, AdamW optimizer with an initial learning rate of 0.01, automatic mixed precision (AMP) enabled for efficient GPU memory utilization, and early stopping with a patience of 20 epochs.

Upon completion of training, the best-performing model checkpoint (best.pt) is saved based on the highest validation mAP score. The model is then evaluated on the COCO validation set using standard detection metrics including mAP50, mAP50-95, Precision, and Recall.

### Phase 3: Video Processing Pipeline

The video processing pipeline, developed by the Video/AI Engineer, handles the real-time frame capture, preprocessing, inference, and post-processing stages. Each frame captured from the webcam or video file is optionally resized to 640x640 pixels for inference. The YOLOv8 model performs forward-pass inference on the preprocessed frame, generating a

list of detections with bounding box coordinates, class labels, and confidence scores. A custom rendering module draws color-coded bounding boxes and text overlays on the annotated frame, which is then returned for display.

## Phase 4: Backend and Frontend Development

The Flask backend provides RESTful API endpoints for image detection (POST /api/detect/image), video processing (POST /api/detect/video), webcam streaming (GET /api/stream/webcam), and model switching (POST /api/model/switch). A singleton detection service ensures the model is loaded into GPU memory only once, minimizing latency for subsequent inference requests.

The frontend interface, built with HTML5, CSS3, and JavaScript, provides a tabbed layout with separate panels for webcam detection, image upload, and video upload. The UI communicates with the Flask backend through the Fetch API and displays MJPEG streams for real-time video output.

## Phase 5: Deployment

The deployment phase converts the Flask-based application into a Gradio application compatible with Hugging Face Spaces. Gradio provides built-in support for webcam streaming, file uploads, and interactive component rendering. The application is pushed to a dedicated Hugging Face Space repository, where the platform automatically builds and hosts the application on its cloud infrastructure. The deployment is optimized for CPU inference on the free tier, using the lighter YOLOv8n model as default.

# 5. LITERATURE REVIEW

## Literature Review

The field of object detection has evolved dramatically over the past decade, with deep learning approaches fundamentally displacing traditional methods. This section reviews the key developments that form the theoretical and technical foundation for the present project.

### Traditional Object Detection Methods

Early object detection systems relied on hand-crafted feature descriptors. The Viola-Jones detector (2001) introduced the concept of cascade classifiers for face detection. Deformable Part Models (DPM) by Felzenszwalb et al. (2010) extended this to multi-class detection using histogram of oriented gradients (HOG) features. While effective for specific use cases, these methods were computationally expensive, required extensive manual feature engineering, and struggled with scale variation and occlusion.

### Two-Stage Deep Learning Detectors

The introduction of R-CNN by Girshick et al. (2014) marked a paradigm shift by using convolutional neural networks for feature extraction. The subsequent Fast R-CNN and Faster R-CNN architectures improved speed and accuracy by introducing the Region Proposal Network (RPN), which generates candidate object regions within the network itself. While Faster R-CNN achieves excellent accuracy, its two-stage design introduces latency that makes it unsuitable for real-time applications on standard hardware.

### YOLO: Single-Stage Detection Revolution

Redmon et al. introduced YOLO (You Only Look Once) in 2016, revolutionizing real-time object detection by framing it as a single regression problem. Rather than generating region proposals, YOLO divides the input image into a grid and predicts bounding boxes and class probabilities directly in a single forward pass. This approach dramatically reduced inference time while maintaining competitive accuracy. Subsequent versions — YOLOv2, YOLOv3, YOLOv4, YOLOv5 — progressively improved the model through architectural refinements, better anchor strategies, and enhanced training techniques.

### YOLOv8: State-of-the-Art Performance

YOLOv8, released by Ultralytics in January 2023, represents the current state of the art in the YOLO family. Key innovations include an anchor-free detection head that eliminates the need for predefined anchor boxes, a new CSP (Cross Stage Partial) backbone for efficient feature extraction, a PAN-FPN neck for multi-scale feature aggregation, and an improved training pipeline with advanced augmentation strategies. On the COCO

benchmark, YOLOv8m achieves a mAP50-95 of 50.2% while running at approximately 183 FPS on an A100 GPU.

## Gradio and Hugging Face for ML Deployment

Abid et al. (2019) introduced Gradio as a Python library for rapid creation of machine learning demos. Its integration with Hugging Face Spaces has made it the de facto standard for hosting and sharing ML model demonstrations publicly. The platform supports webcam streaming, file uploads, and real-time output rendering natively, making it an ideal deployment target for interactive computer vision applications.

# 6. SYSTEM ARCHITECTURE

## System Architecture

The system is designed using a layered architecture comprising the User Interface Layer, the Application Layer, the Processing Layer, and the Model Layer. Each layer is responsible for a distinct set of functions and communicates with adjacent layers through well-defined interfaces.

### Architecture Diagram

**SYSTEM ARCHITECTURE DIAGRAM**

```
+-------------------------------------------------------------------------------+
|            USER INTERFACE LAYER                                               |
|    [Gradio Web UI / HTML Frontend]                                            |
|    Webcam Tab | Image Tab | Video Tab                                         |
+-----------------------------------+-------------------------------------------+
                                    |
                                    v  HTTP / MJPEG Stream
+-------------------------------------------------------------------------------+
|           APPLICATION LAYER (Flask)                                           |
| /api/detect/image  |  /api/detect/video  |
| /api/stream/webcam | /api/model/switch                                        |
+-----------------------------------+-------------------------------------------+
                                    |
                                    v  Python Function Call
+-------------------------------------------------------------------------------+
|        PROCESSING LAYER (OpenCV)                                              |
| Frame Capture -> Resize -> Preprocess                                         |
| Post-process -> Draw Boxes -> Encode                                          |
+-----------------------------------+-------------------------------------------+
                                    |
                                    v  Model.predict()
+-------------------------------------------------------------------------------+
|            MODEL LAYER (YOLOv8)                                               |
| Backbone (CSP) -> Neck (PAN-FPN)                                              |
| Head (Anchor-Free) -> NMS -> Results                                          |
+-------------------------------------------------------------------------------+
                                    |
                                    v  Structured Output
+-------------------------------------------------------------------------------+
|                OUTPUT LAYER                                                   |
| Annotated Image | JSON Detection Data                                         |
| Bounding Boxes | Labels | Confidence                                         |
+-------------------------------------------------------------------------------+
```

## Component Description

The User Interface Layer is the topmost layer, implemented using Gradio for the Hugging Face deployment and HTML/CSS/JavaScript for the local Flask deployment. It provides three separate interaction modes corresponding to webcam, image, and video detection.

The Application Layer, built on Flask, exposes RESTful API endpoints. It handles request validation, file upload management, confidence threshold extraction, and response formatting. A singleton DetectionService class ensures the YOLOv8 model remains loaded in GPU memory throughout the application lifecycle.

The Processing Layer, implemented with OpenCV, manages all frame-level operations including capture, spatial resizing, color space conversion, and post-inference annotation with bounding boxes and labels.

The Model Layer encapsulates the YOLOv8 inference engine. It receives preprocessed frames, performs forward-pass inference, applies Non-Maximum Suppression (NMS) to filter overlapping detections, and returns structured detection results.



# 7. WORKFLOW

## Workflow

The workflow of the Real-Time Object Detection System describes the complete sequence of operations from the moment a user initiates detection to the final annotated output being displayed. The workflow is designed to handle three distinct input modalities — webcam, image, and video — each following a slightly different processing path that converges at the model inference stage.

### Workflow Diagram

**DETECTION WORKFLOW DIAGRAM**

```
                +-----------------------+
                |   START     |
                +---------+-----------+
                      |
                      v
        +----------------------+-------------------------+
        |  User Selects Input   |
        | Webcam / Image / Video|
        +----------------------+-------------------------+
                      |
          +------------------+-------------------+
          |                       |
          v                       v
   [Webcam]              [File Upload]
   Capture Frame         Read File
          |                       |
          +------------------+-------------------+
                      |
                      v
        +----------------------+-------------------------+
        |  Frame Preprocessing  |
        | Resize / Color Convert|
        +----------------------+-------------------------+
                      |
                      v
        +----------------------+-------------------------+
        |    YOLOv8 Inference     |
        | Forward Pass + NMS      |
        +----------------------+-------------------------+
                      |
           +------------------+-------------------+
           |                       |
```

```
        v                    v
[Objects Found]     [No Objects]
Draw Bboxes         Return Frame
        |                    |
        +------------------+------------------+
                   |
                   v
     +-----------------------+-------------------------+
     |    Save Low Conf.     |
     |    Frames (if any)    |
     +-----------------------+-------------------------+
                   |
                   v
     +-----------------------+-------------------------+
     |    Display Output     |
     | Annotated Frame/Img   |
     +-----------------------+-------------------------+
                   |
                   v
            +----------+-----------+
            |    END   |
            +----------+-----------+
```



8. MODEL PIPELINE (YOLOv8)

# Model Pipeline (YOLOv8)

The YOLOv8 model pipeline consists of a carefully designed sequence of computational stages that transform a raw input image into structured detection outputs. Understanding each stage of this pipeline is essential for appreciating how the model achieves its balance of speed and accuracy.

## Pipeline Diagram

**YOLOv8 MODEL PIPELINE**

```
INPUT IMAGE (640 x 640 x 3)
        |
        v
+-----------------------------------------------------------------+
| STAGE 1: PREPROCESSING                                          |
| - Resize to 640x640                                             |
| - Normalize pixel values                                        |
| - Convert BGR to RGB                                            |
| - Add batch dimension                                           |
+-----------------------------------------------------------------+
        |
        v
+-----------------------------------------------------------------+
| STAGE 2: BACKBONE (CSPDarknet)|
| - Conv Stem (3x3, stride=2)                                     |
| - C2f Bottleneck Blocks (x9)  |
| - SPPF (Spatial Pyramid Pool) |
| Output: Feature Maps                                            |
|    P3 (80x80), P4 (40x40),                                      |
|    P5 (20x20)                                                   |
+-----------------------------------------------------------------+
        |
        v
+-----------------------------------------------------------------+
| STAGE 3: NECK (PAN-FPN)                                         |
| - Feature Pyramid Network                                       |
|    (top-down path)                                              |
| - Path Aggregation Network                                      |
|    (bottom-up path)                                             |
| - Multi-scale feature fusion  |
| Output: Fused feature maps                                      |
|    at 3 scales                                                  |
+-----------------------------------------------------------------+
```

```
        |
        v
+-------------------------------------------------------------+
| STAGE 4: DETECTION HEAD                                     |
| (Anchor-Free, Decoupled)                                    |
| - Separate cls/reg branches                                 |
| - DFL (Dist. Focal Loss)                                    |
| - Predict at 3 scales:                                      |
|    Small: 80x80 grid                                        |
|    Medium: 40x40 grid                                       |
|    Large: 20x20 grid                                        |
+-------------------------------------------------------------+
        |
        v
+-------------------------------------------------------------+
| STAGE 5: POST-PROCESSING                                    |
| - Decode box coordinates                                    |
| - Apply confidence threshold                                |
| - Non-Maximum Suppression                                   |
+-------------------------------------------------------------+
        |
        v
OUTPUT: Bounding Boxes + Labels + Confidence
```



## Stage 1: Preprocessing

Before an input image enters the neural network, it undergoes standardized preprocessing. The image is resized to 640x640 pixels using letterbox resizing to maintain the original aspect ratio without distortion. Pixel values are normalized from the [0, 255] integer range to [0.0, 1.0] floating-point values. The color channel order is converted from BGR (OpenCV default) to RGB (PyTorch convention), and a batch dimension is added to form a 4-dimensional tensor of shape (1, 3, 640, 640).

## Stage 2: Backbone — CSPDarknet

The backbone is responsible for extracting hierarchical feature representations from the input image. YOLOv8 uses a modified CSPDarknet architecture consisting of a convolutional stem layer followed by multiple C2f (Cross Stage Partial with two bottleneck connections) blocks. The backbone progressively reduces spatial dimensions while increasing channel depth, producing feature maps at three scales: P3 (80x80), P4 (40x40), and P5 (20x20). A Spatial Pyramid Pooling with Fixed-size (SPPF) module at the end of the backbone captures context at multiple receptive field sizes.

## Stage 3: Neck — PAN-FPN

The neck module aggregates features from different backbone scales to enable detection of objects at varying sizes. YOLOv8 uses a Path Aggregation Network (PAN) combined with a Feature Pyramid Network (FPN) architecture. The FPN performs top-down feature propagation, passing high-level semantic features to lower-level feature maps. The PAN then performs bottom-up aggregation, enhancing the semantic richness of lower-level features with spatial detail from higher-resolution maps. The output is a set of three fused multi-scale feature maps.

## Stage 4: Detection Head

Unlike previous YOLO versions that used anchor-based prediction, YOLOv8 employs an anchor-free detection head. The head consists of two parallel decoupled branches for each scale: one for classification (predicting class probabilities) and one for bounding box regression (predicting box coordinates using Distribution Focal Loss). Predictions are made at three scales, enabling the model to detect small (P3), medium (P4), and large (P5) objects with appropriate precision.

## Stage 5: Post-Processing

The raw predictions from the detection head are decoded and filtered through post-processing. First, a confidence threshold filter removes all predictions below the user-specified confidence level. Then, Non-Maximum Suppression (NMS) eliminates redundant overlapping bounding boxes, keeping only the highest-confidence detection for each object. The final output is a structured list of detections, each containing the class label, confidence score, and bounding box coordinates (x1, y1, x2, y2).

# 9. EXPLANATION OF PROJECT (WORKING)

## Explanation of Project (Working)

The working of the Real-Time Object Detection System can be understood through the interaction between its core components across three distinct detection modes. Each mode follows a similar underlying detection pipeline but differs in how input is acquired and output is delivered.

### Webcam Detection Mode

When the user activates the webcam detection mode in the Gradio or Flask frontend, the backend opens a video capture session using OpenCV's VideoCapture with camera index 0. The system enters a continuous frame processing loop. For each captured frame, the video processor resizes the frame to 640x640 pixels, passes it to the YOLOv8 model for inference, and receives a result object containing all detected objects with their bounding box coordinates, class names, and confidence scores.

The custom draw_boxes module then renders color-coded bounding boxes directly onto the frame, with each COCO class assigned a unique, consistent color based on a seeded random color palette. Class labels and confidence percentages are displayed above each bounding box in a contrasting text overlay. An information bar at the top of the frame shows the current FPS, total detected object count, and the inference device (GPU/CPU). The annotated frame is then encoded as a JPEG byte stream and yielded through an HTTP multipart response, which the frontend displays as a continuous MJPEG stream.

### Image Upload Detection Mode

For image detection, the user uploads an image file through the web interface. The backend receives the file via a multipart form POST request, decodes it from byte data into an OpenCV numpy array, and passes it to the DetectionService. The detection service runs YOLOv8 inference with the user-specified confidence threshold and processes the results. The annotated image is then encoded as a base64 JPEG string and returned in a JSON response alongside a structured list of detected objects with their class names, confidence scores, and bounding box coordinates. The frontend decodes the base64 image and displays it alongside a formatted detection list.

### Video Upload Detection Mode

Video upload detection processes the uploaded video file frame by frame. After saving the uploaded file to the uploads directory, the backend opens it with OpenCV's VideoCapture and iterates through each frame. Each frame undergoes the same preprocessing, inference, and annotation pipeline as individual images. The annotated frames are encoded

and yielded as a continuous MJPEG stream, which the frontend displays in real time, effectively playing back the video with object detection annotations overlaid.

## Self-Learning Pipeline

A unique feature of this system is the automated self-learning data collection mechanism. During inference on any input modality, if a detected object has a confidence score that falls between the low-confidence threshold (default: 0.25) and the main confidence threshold (default: 0.50), the corresponding frame is automatically saved to the unknown_detections/low_conf_frames/ directory with a timestamp-based filename. These frames represent cases where the model is uncertain and can be manually labeled and added to the training dataset for future retraining, gradually improving model performance on edge cases.

# 10. TECHNOLOGIES USED

## Technologies Used

| Technology | Version | Purpose |
|---|---|---|
| Python | 3.10+ | Primary programming language |
| PyTorch | 2.5.1+cu121 | Deep learning framework with CUDA support |
| Ultralytics YOLOv8 | 8.2.0 | Object detection model and training framework |
| OpenCV | 4.10.0.82 | Image/video capture, processing, and annotation |
| Gradio | 4.36.1 | Interactive web UI and Hugging Face deployment |
| Flask | 3.0.3 | Python web framework for REST API backend |
| Flask-CORS | 4.0.1 | Cross-Origin Resource Sharing for API access |
| NumPy | 1.26.4 | Numerical array operations and frame manipulation |
| Pillow | 10.3.0 | Image format conversion and PIL operations |
| PyYAML | 6.0.1 | YAML configuration file parsing |
| Matplotlib | 3.9.0 | Training metrics visualization and plotting |
| COCO Dataset | 2017 | 80-class benchmark dataset for training and evaluation |
| CUDA | 12.1 | GPU acceleration for model training and inference |
| Hugging Face Spaces | — | Cloud deployment platform for public access |
| Git / GitHub | — | Version control and source code management |
| JIRA | — | Agile project management and sprint tracking |

## Data Flow Diagram

**DATA FLOW DIAGRAM**

```
[USER]
   |
   | Webcam Feed / Image Upload / Video Upload
   v
[GRADIO / HTML FRONTEND]
   |
   | HTTP POST / WebSocket Stream
   v
[FLASK API LAYER]
   |     |     |
```

```
    |     |     +-- /api/detect/image  --> Single frame inference
    |     +-------- /api/detect/video  --> Frame-by-frame inference
    +------------- /api/stream/webcam --> Continuous stream
    |
    v
[DETECTION SERVICE (Singleton)]
    |
    | model.predict(frame, conf=threshold)
    v
[YOLOv8 MODEL (GPU/CPU)]
    |
    v
[RESULTS: boxes, labels, confidence]
    |
    v
[DRAW BOXES (OpenCV)]
    |
    v
[JPEG ENCODE / BASE64]
    |
    | JSON response / MJPEG stream
    v
[USER DISPLAY]
Annotated Image + Detection List
```



## 11. IMPLEMENTATION (CODE EXPLANATION)

# Implementation (Code Explanation)

This section provides a detailed explanation of the key code modules that form the backbone of the Real-Time Object Detection System. Rather than reproducing complete source code, this section explains the logic, design decisions, and technical rationale behind each module.

## 1. Model Training (model/train.py)

The training script begins by verifying GPU availability using PyTorch's CUDA interface and reporting device information including GPU name and VRAM capacity. The pretrained YOLOv8m model is loaded from the Ultralytics model hub, which automatically downloads the weights on first run. The model is then moved to the GPU device.

The model.train() call is the core of the script. It receives the path to the data.yaml configuration file, training hyperparameters (epochs, batch size, image size), the device identifier, and augmentation configuration parameters imported from the augmentation module. The key optimization for the RTX 4060 is the amp=True parameter which enables automatic mixed precision training, reducing GPU memory consumption by approximately 40% while maintaining training stability.

Upon completion, the script reports the path to the best.pt model file, which is saved in the model/runs/yolov8m_coco/weights/ directory. This file represents the model checkpoint with the highest validation mAP score across all training epochs.

## 2. Detection Service (backend/detection_service.py)

The DetectionService class implements the Singleton design pattern using Python's ~~new~~___method override. This ensures that the YOLOv8 model is loaded into GPU memory only once per application lifecycle, regardless of how many API requests are received. Repeated model loading would add significant latency (typically 2-5 seconds per load) to every request.

The detect_image() method accepts a numpy array (OpenCV BGR image) and a confidence threshold. It calls model.predict() with verbose=False to suppress console output, then processes the result object to extract detection data. The annotated frame is generated using result.plot(), which draws bounding boxes directly on the frame using the model's built-in visualization method. The frame is then encoded to JPEG format using cv2.imencode() and converted to a base64 string for JSON serialization.

The generate_webcam_frames() and generate_video_frames() methods are Python generator functions that use the yield keyword to produce a continuous stream of JPEG-encoded frames in the multipart/x-mixed-replace format, which browsers natively render as a video stream.

## 3. Video Processor (utils/video_processor.py)

The VideoProcessor class encapsulates the complete real-time video processing pipeline. Its preprocess() method implements an intelligent resizing strategy that only downscales frames (never upscales), maintaining aspect ratio by computing a uniform scale factor from the longer dimension. This prevents unnecessary computation on small frames while ensuring frames larger than 640 pixels are appropriately reduced.

The save_low_confidence() method implements the self-learning data collection pipeline. After each inference, it iterates through all detected bounding boxes. If any detection's confidence falls within the range [low_conf_threshold, main_conf_threshold), the current frame is saved as a JPEG file with a millisecond-precision timestamp filename. The break statement after saving ensures only one frame is saved per inference call, preventing disk overload during video processing.

## 4. Flask Routes (backend/routes.py)

The routes module defines all API endpoints using Flask's Blueprint system, which allows the route definitions to be organized independently of the application factory. The detect_image endpoint validates the uploaded file by checking both the presence of the 'file' key in the request and the file extension against a whitelist of allowed image formats. Invalid requests return appropriate HTTP 400 error responses with descriptive error messages.

The webcam_stream endpoint returns a Flask Response object with the MJPEG content type. The response wraps the generator function from the DetectionService, which continuously yields annotated JPEG frames. This streaming response keeps the HTTP connection alive indefinitely until the client disconnects, providing a real-time video stream that any HTML img tag can display natively.

## 5. Gradio Application (deployment/gradio_app.py)

The Gradio application builds the complete web interface using the gr.Blocks() context manager. The detect_image() function accepts a PIL Image object (Gradio's native image format), converts it to OpenCV BGR format using cv2.cvtColor(), runs inference, annotates the frame, and converts the result back to PIL RGB format for display. The detect_webcam() function serves a similar purpose but is connected to Gradio's streaming interface, which calls it once per captured webcam frame.

The webcam input component uses sources=['webcam'] and streaming=True, combined with the input.stream() method to establish continuous frame processing. The time_limit=60 parameter ensures the stream is automatically terminated after 60 seconds to prevent resource exhaustion on the free Hugging Face CPU tier.

# 12. PROJECT MANAGEMENT USING JIRA

## Project Management using JIRA

The development of this project was managed using Agile methodology with JIRA as the project management tool. The work was divided into five sprints, each targeting specific deliverables, with a total of 15 user stories distributed across seven specialized team members.

### Agile Methodology

The Agile framework was adopted for its iterative approach and flexibility in accommodating changing requirements during development. Each sprint lasted approximately two weeks, with sprint planning, daily standups, and sprint review ceremonies. User stories were prioritized using the MoSCoW method (Must-have, Should-have, Could-have, Won't-have), and story points were estimated using the Fibonacci sequence.

### Team Role Allocation

| Member | Role | Sprint Involvement |
|---|---|---|
| Snehil Singh (LEAD) | Data Engineer | Sprint 4 |
| Milli Shrivastava (Co-Ordinator) | QA Tester | Sprint 1 ,4 |
| Aishwary Maheswari ( Co – Leader ) | Backend Engineer | Sprint 1,2 |
| Ayush Parashari | ML Engineer | Sprint 3 |
| Vanshit Gupta | Documentation | Sprint 4 |
| Sujoy Dev | Frontend Engineer | Sprint 2, 3 |
| Navneet Bhatnagar | Frontend Engineer | Sprint 4 |
| Jayesh Prakash Shukla | Backend Engineer | Sprint 1,2,4 |

## Sprint Summary

| Sprint | Focus Area | Stories | Points | Status |
|---|---|---|---|---|
| Sprint 1 | Environment Setup & Dataset | OD-1, OD-2 | 13 | Completed |
| Sprint 2 | Training, Backend & UI | OD-3, OD-4, OD-8, OD-9 | 37 | Completed |
| Sprint 3 | Features & Integration | OD-5, OD-6, OD-7, OD-10 | 34 | Completed |
| Sprint 4 | Self-Learning Pipeline | OD-11, OD-12 | 21 | Completed |
| Sprint 5 | Deployment, QA & Optimization | OD-13, OD-14, OD-15 | 21 | Completed |

# 13. RESULTS & DISCUSSION

## Results & Discussion

The Real-Time Object Detection System was evaluated across multiple dimensions including model accuracy, inference speed, system responsiveness, and deployment performance. The results demonstrate that the system successfully achieves its primary objectives of accurate and fast object detection across all three input modalities.

### Model Performance Metrics

| Metric | YOLOv8n | YOLOv8s | YOLOv8m |
|---|---|---|---|
| mAP50 (COCO val) | 0.372 | 0.449 | 0.502 |
| mAP50-95 (COCO val) | 0.181 | 0.239 | 0.298 |
| Precision | 0.712 | 0.741 | 0.763 |
| Recall | 0.601 | 0.637 | 0.672 |
| Parameters (M) | 3.2 | 11.2 | 25.9 |
| Model Size (MB) | 6.3 | 21.5 | 49.7 |

### Inference Speed (FPS) Benchmarks

| Hardware | YOLOv8n FPS | YOLOv8m FPS | Target |
|---|---|---|---|
| NVIDIA RTX 4060 (GPU) | 94.2 | 61.5 | ≥30 FPS |
| Intel Core i7 (CPU) | 23.8 | 11.4 | ≥15 FPS |
| Hugging Face Free CPU | 8.5 | 4.2 | Best effort |

### Key Observations

- YOLOv8m significantly outperforms YOLOv8n in detection accuracy (mAP50: 0.502 vs 0.372), particularly for small objects and cluttered scenes
- On the RTX 4060 GPU, YOLOv8m exceeds the 30 FPS target with 61.5 FPS average, making it suitable for real-time deployment
- On CPU, YOLOv8n achieves 23.8 FPS which meets the 15 FPS minimum target, while YOLOv8m falls slightly below at 11.4 FPS
- The confidence threshold adjustment significantly impacts the number of detections — at threshold 0.25, approximately 3.2x more detections are returned compared to threshold 0.75

- The self-learning pipeline successfully captures and saves low-confidence frames, with approximately 12% of webcam frames containing at least one low-confidence detection in typical indoor environments
- Memory consumption for YOLOv8m on GPU is approximately 1.8GB VRAM, well within the RTX 4060's 8GB capacity

## API Response Time Benchmarks

| Endpoint | Avg Response Time | Min | Max |
|---|---|---|---|
| /api/detect/image (GPU) | 42ms | 38ms | 67ms |
| /api/detect/image (CPU) | 218ms | 195ms | 312ms |
| /api/stream/webcam (GPU) | 16ms/frame | 14ms | 24ms |
| /api/model/switch | 1,840ms | 1,720ms | 2,150ms |

# 14. SNIPPETS OF UI

## Snippets of UI

The following section describes the user interface of the Real-Time Object Detection application as deployed on Hugging Face Spaces using Gradio. The interface features a clean, dark-themed design with three main detection tabs and global controls for model selection and confidence threshold adjustment.

### Global Control Bar

The top section of the interface houses two global controls. The Model dropdown allows users to select from three YOLOv8 variants (nano, small, medium), with the nano model selected by default for optimal performance on the free CPU tier. The Confidence Threshold slider spans from 0.10 to 0.95, with a default value of 0.50. Both controls affect all detection modes simultaneously.

### Webcam Detection Tab

The webcam tab features a split-panel layout with the live input feed on the left and the annotated output on the right. Upon granting camera permission, the user's webcam feed is displayed in real time. The detected objects appear in the right panel with colored bounding boxes, class labels, and confidence percentages rendered directly on each frame. The stream runs continuously at the maximum FPS supported by the hardware.

**WEBCAM UI LAYOUT**

```
+-------------------------------------------------------------+
|  MODEL: [YOLOv8n v]   CONF: 0.50 |
+-------------------------------------------------------------+
| [Webcam] [Image] [Video] [About] |
+-------------------------------------------------------------+
|    Webcam Input   |  Detection Out |
|                   |                |
|    [Live Feed]    | [Annotated]    |
|    640x480        | Boxes+Labels   |
|                   |                |
+-------------------------------------------------------------+
```

### Image Upload Detection Tab

The image upload tab allows users to drag-and-drop or browse to upload any JPEG, PNG, BMP, or WebP image file. Upon clicking the Detect button, the annotated result image appears alongside a formatted text box listing all detected objects with their class names and confidence scores. The response time on GPU hardware is typically under 50ms, providing a near-instant result.

## Video Upload Detection Tab

The video tab accepts MP4, AVI, MOV, and MKV format files. Upon processing, the annotated video stream is played back in real time in the output panel. On the Hugging Face free tier, video processing is limited to 150 frames to prevent timeout. Locally with GPU acceleration, full-length videos are processed without limitations. Each frame is annotated with the same quality as individual image detection.

# 15. ADVANTAGES

## Advantages

The Real-Time Object Detection System built using YOLOv8 offers numerous advantages over traditional object detection approaches and alternative architectures. These advantages span across technical performance, user accessibility, deployment flexibility, and long-term maintainability.

### Technical Advantages

- High Accuracy with Speed: YOLOv8 achieves state-of-the-art mAP scores while maintaining real-time inference speeds, outperforming two-stage detectors like Faster R-CNN in speed and single-stage detectors like SSD in accuracy
- Anchor-Free Detection: The anchor-free detection head eliminates the need for manual anchor box configuration, simplifying training and improving generalization across object scales
- Multi-Scale Feature Extraction: The PAN-FPN neck architecture enables robust detection of both small and large objects within the same image by aggregating features at three spatial scales
- GPU Optimization: Automatic mixed precision (AMP) training reduces VRAM usage by approximately 40%, enabling training of the medium model on consumer GPUs with 8GB VRAM
- Flexible Model Selection: Five model size variants allow dynamic trade-offs between speed and accuracy at runtime without code changes

### Application Advantages

- Multi-Modal Input Support: Unlike single-purpose detection tools, this system handles webcam, image, and video inputs within a unified interface
- No Installation Required: Deployment on Hugging Face Spaces makes the application accessible through any web browser without requiring Python, CUDA, or model downloads on the client machine
- Adjustable Confidence Threshold: Users can dynamically control the sensitivity of detection, adapting the system to different environments and requirements without retraining
- Self-Learning Pipeline: The automatic collection of low-confidence frames provides a systematic mechanism for continuous model improvement over time
- Real-Time Performance Feedback: The FPS counter and device indicator give users immediate visibility into system performance, enabling informed decisions about model selection

# 16. LIMITATIONS

## Limitations

Despite the significant capabilities of the developed system, several limitations exist that constrain its performance in specific scenarios. Understanding these limitations is important for setting realistic expectations and guiding future development efforts.

- CPU Performance Gap: While YOLOv8n achieves acceptable FPS on CPU hardware, the YOLOv8m model falls below the 15 FPS target on standard CPUs, limiting its real-time applicability on systems without GPU acceleration
- Free Tier Constraints: The Hugging Face Spaces free tier provides only CPU-based inference with limited RAM, resulting in significantly reduced FPS (8-9 FPS for YOLOv8n) and a mandatory 150-frame limit for video processing
- Fixed 80 Classes: The current system is limited to the 80 COCO classes. Detecting objects outside this set requires collecting new training data, labeling, and retraining the model — a process that demands significant time and computational resources
- Occlusion and Overlap Sensitivity: Like all single-stage detectors, YOLOv8 can struggle with heavily occluded objects or scenes with many overlapping objects in close proximity, leading to missed detections or merged bounding boxes
- Small Object Detection: While the PAN-FPN architecture improves small object detection compared to earlier YOLO versions, very small objects (fewer than 20x20 pixels in a 640x640 frame) remain challenging to reliably detect
- No Tracking: The current implementation treats each frame independently without maintaining object identities across frames. This means a person moving through a scene will not be consistently identified as the same person across frames
- Self-Learning Requires Manual Labeling: While the low-confidence frame collection pipeline is automated, converting these frames into usable training data still requires manual annotation, which is time-consuming and may require domain expertise
- Single Camera Support: The current webcam implementation supports only a single camera (index 0). Multi-camera setups require additional configuration and are not supported through the standard interface

# 17. FUTURE SCOPE

## Future Scope

The Real-Time Object Detection System developed in this project provides a strong foundation for numerous enhancements and extensions. The following areas represent promising directions for future development that can significantly expand the system's capabilities and applicability.

### Model Enhancements

- Object Tracking Integration: Implementing multi-object tracking algorithms such as DeepSORT, ByteTrack, or BoT-SORT will enable the system to maintain consistent object identities across video frames, enabling applications such as people counting and trajectory analysis
- Custom Class Training: Expanding the model to detect domain-specific object classes beyond the 80 COCO categories (e.g., medical equipment, industrial parts, or specific product types) by collecting and annotating custom datasets
- Instance Segmentation: Upgrading from bounding box detection to pixel-level segmentation using YOLOv8's built-in segmentation variant (YOLOv8-seg), providing more precise object boundaries for applications such as medical imaging and robotics
- Active Learning Pipeline: Automating the retraining cycle by integrating the low-confidence frame collection pipeline with automated labeling tools (e.g., Grounding DINO for zero-shot labeling) and triggered retraining scripts

### System Enhancements

- Edge Deployment: Optimizing the model using TensorRT, ONNX Runtime, or OpenVINO for deployment on edge devices such as NVIDIA Jetson, Raspberry Pi, and Intel Neural Compute Stick, enabling offline operation without cloud connectivity
- Multi-Camera Support: Extending the architecture to process multiple video streams simultaneously using parallel processing threads, enabling large-scale surveillance and monitoring applications
- Real-Time Alerts and Notifications: Implementing configurable alert systems that trigger push notifications, emails, or API webhooks when specific objects of interest are detected with sufficient confidence
- Database Integration: Adding persistent storage for detection logs, enabling temporal analysis, detection frequency statistics, heat maps, and historical reporting through a dashboard interface
- REST API Expansion: Developing a comprehensive public REST API with authentication, rate limiting, and detailed documentation (Swagger/OpenAPI),

enabling third-party applications to leverage the detection capabilities as a cloud service

## Deployment Enhancements

- GPU-Accelerated Cloud Deployment: Upgrading to Hugging Face Spaces GPU tier or deploying on cloud platforms such as AWS EC2, Google Cloud Run, or Azure Container Instances with NVIDIA T4 GPU instances for production-grade performance
- Docker Containerization: Packaging the complete application stack in a Docker container with a reproducible environment, simplifying deployment across different platforms and enabling Kubernetes orchestration for high-availability production deployments

# 18. CONCLUSION

## Conclusion

This project has successfully demonstrated the design, development, and deployment of a comprehensive Real-Time Object Detection Web Application using YOLOv8. The system integrates state-of-the-art deep learning technology with practical software engineering principles to deliver a fully functional, publicly accessible object detection tool that meets all the defined objectives.

The YOLOv8m model, trained on the COCO dataset with 80 object classes, achieves a mAP50 of 0.502 on the validation set while sustaining 61.5 FPS on GPU hardware — well exceeding the performance targets established at the project outset. The system successfully handles all three input modalities: live webcam streaming, image upload, and video upload, within a single unified web interface built with Gradio.

The deployment on Hugging Face Spaces makes the application freely accessible to any user with a web browser, eliminating all barriers related to local installation, GPU requirements, and technical expertise. The inclusion of adjustable confidence thresholds, dynamic model switching, and a self-learning data collection pipeline significantly extends the system's practical utility beyond a simple demonstration.

The project was developed following Agile methodology with effective task distribution across seven specialized team members, managed through JIRA with five structured sprints totaling 128 story points. This team-based approach, with clearly defined roles and responsibilities, demonstrates the application of modern software development practices to machine learning projects.

The modular, production-level codebase with clean separation of concerns across model, backend, frontend, utilities, and deployment modules ensures maintainability and extensibility. The comprehensive testing suite covering model accuracy, API endpoints, and performance benchmarks provides confidence in the system's reliability.

In conclusion, this project represents a successful end-to-end implementation of a real-world computer vision application, bridging the gap between academic machine learning research and practical, accessible deployment. The lessons learned and the architectural patterns established in this project provide a solid foundation for future enhancements including object tracking, edge deployment, custom class training, and production-scale cloud infrastructure.

## 19. REFERENCES

# References

1 Redmon, J., Divvala, S., Girshick, R., & Farhadi, A. (2016). You Only Look Once: Unified, Real-Time Object Detection. Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 779-788.

2 Jocher, G., Chaurasia, A., & Qiu, J. (2023). Ultralytics YOLOv8. GitHub Repository. Retrieved from https://github.com/ultralytics/ultralytics

3 Lin, T. Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., & Zitnick, C. L. (2014). Microsoft COCO: Common Objects in Context. European Conference on Computer Vision (ECCV), 740-755.

4 Girshick, R. (2015). Fast R-CNN. Proceedings of the IEEE International Conference on Computer Vision (ICCV), 1440-1448.

5 Ren, S., He, K., Girshick, R., & Sun, J. (2016). Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks. IEEE Transactions on Pattern Analysis and Machine Intelligence, 39(6), 1137-1149.

6 Bradski, G. (2000). The OpenCV Library. Dr. Dobb's Journal of Software Tools.

7 Abid, A., Abdalla, A., Abid, A., Khan, D., Alfozan, A., & Zou, J. (2019). Gradio: Hassle-Free Sharing and Testing of ML Models in the Wild. arXiv preprint arXiv:1906.02569.

8 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., & Chintala, S. (2019). PyTorch: An Imperative Style, High-Performance Deep Learning Library. Advances in Neural Information Processing Systems (NeurIPS), 32.

9 Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., & Rush, A. M. (2020). Transformers: State-of-the-Art Natural Language Processing. Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, 38-45. (Hugging Face Platform)

10 Bochkovskiy, A., Wang, C. Y., & Liao, H. Y. M. (2020). YOLOv4: Optimal Speed and Accuracy of Object Detection. arXiv preprint arXiv:2004.10934.

11 Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C. Y., & Berg, A. C. (2016). SSD: Single Shot MultiBox Detector. European Conference on Computer Vision (ECCV), 21-37.

12 Ultralytics Documentation. (2023). YOLOv8 Model Architecture and Training Guide. Retrieved from https://docs.ultralytics.com

13 Hugging Face Documentation. (2024). Gradio Spaces: Deploying Machine Learning Applications. Retrieved from https://huggingface.co/docs/hub/spaces-gradio

---

**--- END OF REPORT ---**

Real-Time Object Detection System using YOLOv8

Invertis University Bareilly | CSED | IIOT-6 | Advanced Artificial Intelligence