CSci 127: Introduction to Computer Science



hunter.cuny.edu/csci

Announcements



• Guest Lecturer: Dr. Tiziana Ligorio

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

In Pairs or Triples:

Review: predict what the code will do:

```
motto = "Mihi Cura Futuri"
l = len(motto)
for i in range(l):
    print(motto[i])
for j in range(l-1,-1,-1):
    print(motto[j])
```

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```

5 / 44

Python Tutor

```
motto = "Mihi Cura Futuri"
l = len(motto)
for i in range(l):
    print(motto[i])
for j in range(l-1,-1,-1):
    print(motto[j])
```

(Demo with pythonTutor)

6 / 44

Images

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```

19 March 2019


7 / 44

CSci 127 (Hunter) Lecture 7

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```



```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```



9 / 44

CSci 127 (Hunter) Lecture 7 19 March 2019


```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```



10 / 44


CSci 127 (Hunter) Lecture 7 19 March 2019

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```




• How would you select the lower left corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```




• How would you select the lower left corner? img2 = img[height//2:, :width//2]

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```




- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```




- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[height//2:, width//2:]

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[height//2:, width//2:]
- How would you select the lower right corner?

```
import matplotlib.pyplot as plt
import numpy as np
img = plt.imread('csBridge.png')
plt.imshow(img2)
plt.show()
height = img.shape[0]
width = img.shape[1]
img2 = img[height//2:, width//2:]
plt.imshow(img2)
plt.show()
```



- How would you select the lower left corner? img2 = img[height//2:, :width//2]
- How would you select the upper right corner? img2 = img[height//2:, width//2:]
- How would you select the lower right corner? img2 = img[:height//2, :width//2]

10 / 44

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

 Functions are a way to break code into pieces, that can be easily reused.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- Many languages require that all code must be organized with functions.
- The opening function is often called main()
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

"Hello, World!" with Functions

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
      says hello to the world!
def main():
     print("Hello, World!")
if __name__ == "__main__":
     main()
```

19 March 2019

Python Tutor

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

(Demo with pythonTutor)

CSci 127 (Hunter) Lecture 7

In Pairs or Triples:

Predict what the code will do:

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

Python Tutor

```
def totalWithTax(food,tip):
total = 0
tax = 0.8875
total = food + food * tax
total = total = tip
return(ctotal) = tip
return(ctotal)
Lunch = Floot(inout('inter lunch total: '))
Hip = floot(input('Enter lunch tip: '))
Hip = floot(input('Enter lunch tip: '))
Hip = totalWithTax(lunch, lip)
print('Lunch total is', liotal)
diame= Floot(input('Enter diamer total: '))
diame= Floot(input('Enter diamer tip: '))
diolal = totalWithTax(diamer, diap)
print('Diamer total is', dioda(inner, diap)
print('Diamer total is', dioda(inner, diap)
```

(Demo with pythonTutor)

CSci 127 (Hunter) Lecture 7

16 / 44

Functions can have input parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

17 / 44

```
def totalWithTax(food,tip):
    total = 0
    tox = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
    print('Lunch total is', LTotal)
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
    print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
    print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
    print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters

```
def totalWithTax(food,tip):
    total = 0
    tax = 0.0875
    total = food * food * tax
    total = total + tip
    return(total)

lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
    print('Lunch total is', lTotal)

dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal = totalWithTax(dinner, dTip)
    print('Dinner total is', dTotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters
- Functions can also return
 values to where it was called.

```
def totalWithTax(food,tip):
    total = 0
                        Formal Parameters
    tax = 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal = totalWithTax(lunch, lTip)
print('Lunch total is', [[otal)
                           Actual Parameters
dinner= float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal = totalWithTax dinner, dTip
print('Dinner total is', grotal)
```

- Functions can have input parameters.
- Surrounded by parentheses, both in the function definition, and in the function call (invocation).
- The "placeholders" in the function definition: formal parameters.
- The ones in the function call: actual parameters.
- Functions can also return
 values to where it was called.

In Pairs or Triples:

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is.")
    c = mystery(verse)
    w = enigma(verse.c)
    print(c,w)
def mystery(v):
    print(v)
    c = v.count("jam")
    return(c)
def enigma(v,c):
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

19 March 2019

In Pairs or Triples:

Circle the actual parameters and underline the formal parameters:

```
def prob4():
    verse "jam tomorrow and jam yesterday,"
    print("The rule is,")
    c = hystery (verse)
    w = enigma(verse,c)
                                  *Actual
    print(c,w)
                                   Parameters
def mystery(v):
    print(v)
    c = v.count(fiam
    return(c)
                                     Formal
def enigma(v,c):
                                      Parameters
    print("but never", v[-1])
    for i in range(c):
        print("jam")
    return("day.")
prob4()
```

20 / 44

In Pairs or Triples:

Predict what the code will do.

```
def prob4():
                                                         #Fall 2013 Final Exam. 5
    verse = "jam tomorrow and jam yesterday,"
    print("The rule is.")
                                                         def kuwae( inLst ):
                                                             tot = 1
    c = mystery(verse)
                                                             for item in inLst:
    w = enigma(verse,c)
                                                                tot = tot * item
    print(c,w)
                                                             return tot
def mystery(v):
    print(v)
                                                      def foo( inLst ):
    c = v.count("jam")
                                                             if ( inLst[-1] > inLst[0] ):
    return(c)
                                                                 return kuwae( inLst )
def enigma(v,c):
                                                             else:
    print("but never", v[-1])
                                                                 return -1
    for i in range(c):
        print("iam")
                                                         foo([2, 4, 6, 8])
    return("day.")
prob4()
                                                         foo([4002, 328, 457, 1])
```

Python Tutor

```
def prob4():
   verse = "jam tomorrow and jam yesterday,"
   print("The rule is.")
   c = mystery(verse)
   w = enigma(verse,c)
   print(c.w)
def mystery(v):
   print(v)
   c = v.count("jam")
   return(c)
def enigma(v,c):
   print("but never", v[-1])
   for i in range(c):
      print("iam")
   return("day.")
prob4()
#Fall 2013 Final Exam. 5
                                             (Demo with pythonTutor)
def kuwae( inLst ):
     tot = 1
     for item in inLst:
         tot = tot * item
     return tot
def foo( inLst ):
     if ( inLst[-1] > inLst[0] ):
         return kuwae( inLst )
     else:
         return -1
foo([2, 4, 6, 8])
foo( [4002, 328, 457, 1] )
```

In Pairs or Triples:

Predict what the code will do:

```
#Greet loop example

def greetLoop(person):
    print("Greetings")
    for i in range(5):
        print("Hello", person)

greetLoop("Thomas")
```

```
# From "Teaching with Python" by John Zelle

def happy():
    print("Happy Birthday to you!")

def sing(P):
    happy()
    happy()
    print("Happy Birthday dear " + P + "!")
    happy()

sing("Fred")
sing("Thomas")
sing("Hunter")
```

Python Tutor

```
#Greet loop example
 def greetLoop(person):
      print("Greetings")
     for i in range(5):
          print("Hello", person)
 greetLoop("Thomas")
# From "Teaching with Python" by John Zelle
def happy():
   print("Happy Birthday to you!")
def sing(P):
   happy()
   happy()
   print("Happy Birthday dear " + P + "!")
   happy()
sing("Fred")
sing("Thomas")
sing("Hunter")
```

(Demo with pythonTutor)

In Pairs or Triples:

Fill in the missing code:

```
def monthString(monthNum):
    Takes as input a number, monthNum, and
    returns the corresponding month name as a string.
    Example: monthString(1) returns "January".
    Assumes that input is an integer ranging from 1 to 12
    monthString = ""
     ********************************
    ### FTLL TN YOUR CODE HERE
                                    ###
    ### Other than your name above, ###
    ### this is the only section
                                    ###
    ### you change in this program. ###
    *************
    return(monthString)
def main():
    n = int(input('Enter the number of the month: '))
    mString = monthString(n)
    print('The month is'. mString)
```

IDLE

def main():

n = int(input('Enter the number of the month: '))
mString = monthString(n)
print('The month is', mString)

der onstödsring/ensthäup: Takes as ingut a number, motthäum, and returns the corresponding must be an a staring, results a staring must be an analysis of the staring, results a staring must be an analysis of the staring must be an analysis of

In Pairs or Triples:

Predict what the code will do:

```
#CSci 127 Teaching Staff
#Triangles two ways...
import turtle
def setUp(t. dist. col):
    t.penup()
     t.forward(dist)
     t.pendown()
     t.color(col)
def nestedTriangle(t, side):
    if side > 10:
          for i in range(3):
               t.forward(side)
               t.left(120)
          nestedTriangle(t, side/2)
def fractalTriangle(t, side):
     if side > 10:
          for i in range(3):
               t.forward(side)
               t.left(120)
               fractalTrianale(t. side/2)
```

```
def main():
    nessa = turtle.Turtle()
    setUp(nessa, 100, "violet")
    nestedTriangle(nessa, 160)

    frank = turtle.Turtle()
    setUp(frank, -100, "red")
    fractalTriangle(frank, 160)

if __name__ == "__main__":
    main()
```

IDLE

```
#CSci 127 Teaching Staff
#Triangles two ways...
import turtle
def setUp(t, dist, col):
    t.penup()
    t.forward(dist)
    t.pendown()
    t.color(col)
def nestedTriangle(t, side):
                                               (Demo with IDLE)
    if side > 10:
         for i in range(3):
              t.forward(side)
              t.left(120)
         nestedTriangle(t, side/2)
def fractalTriangle(t, side):
    if side > 10:
         for i in range(3):
              t.forward(side)
             t.left(120)
```

fractalTriangle(t, side/2)

28 / 44

CSci 127 (Hunter) Lecture 7 19 March 2019

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

 Functions are a way to break code into pieces, that can be easily reused.

CSci 127 (Hunter) Lecture 7

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if name == " main ":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if name == " main ":
```

main()

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions,

```
#Name: your name here
#Date: October 2017
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ == "__main__":
    main()
```

- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis: Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.

Today's Topics



- Recap: Slicing & Images
- Introduction to Functions
- NYC Open Data

30 / 44

CSci 127 (Hunter) Lecture 7



Freely available source of data.



- Freely available source of data.
- Maintained by the NYC data analytics team.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.



- Freely available source of data.
- Maintained by the NYC data analytics team.
- We will use several different ones for this class.
- Will use pandas, pyplot & folium libraries to analyze, visualize and map the data.
- Lab 7 covers accessing and downloading NYC OpenData datasets.




ne Data About v Learr


Film Permits

Permits are generally required when asserting the exclusive use of city property, like a sidewalk, a \blacksquare street, or a park. See http://www1.nyc.gov/site/mome/permits/when-permit-required.page


EventID :	EventType :	StartDateTi	EndDateTime :	EnteredOn ↓ :	EventAg	ParkingHeld :	Borou
455063	Shooting Permit	12/06/2018 07:00	12/06/2018 09:00	12/05/2018 12:36	Mayor's Offic	STARR AVENUE b	Queens
454967	Shooting Permit	12/06/2018 07:00	12/06/2018 05:00	12/04/2018 09:11	Mayor's Offic	EAGLE STREET be	Brooklyn
454941	Shooting Permit	12/06/2018 07:00	12/06/2018 07:00	12/04/2018 05:44	Mayor's Offic	SOUTH OXFORD	Brooklyn
454920	Shooting Permit	12/06/2018 10:00	12/06/2018 11:59	12/04/2018 03:28	Mayor's Offic	13 AVENUE betw	Queens
454914	Shooting Permit	12/06/2018 08:00	12/06/2018 11:00	12/04/2018 03:05	Mayor's Offic	ELDERT STREET b	Brooklyn
454909	Shooting Permit	12/05/2018 08:00	12/05/2018 06:00	12/04/2018 02:45	Mayor's Offic	ELDERT STREET b	Brooklyn
454905	Shooting Permit	12/06/2018 07:00	12/06/2018 10:00	12/04/2018 02:17	Mayor's Offic	35 STREET betwe	Queens



• What's the most popular street for filming?



- What's the most popular street for filming?
- What's the most popular borough?



- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?



Download the data as a CSV file and store on your computer.



- Download the data as a CSV file and store on your computer.
- Python program:



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
```



- Download the data as a CSV file and store on your computer.
- Python program:

```
#CSci 127 Teaching Staff
#March 2019
#OpenData Film Permits

#Import pandas for reading and analyzing CSV data:
import pandas as pd
csvFile = "filmPermits.csv"  #Name of the CSV file
tickets = pd.read_csv(csvFile)#Read in the file to a dataframe
print(tickets)  #Print out the dataframe
print(tickets["ParkingHeld"])  #Print out streets (multiple times)
```




- Download the data as a CSV file and store on your computer.
- Python program:



- Download the data as a CSV file and store on your computer.
- Python program:

4 D > 4 P > 4 P > 4 P > B


90 Q



Can approach the other questions in the same way:

- What's the most popular street for filming?
- What's the most popular borough?
- How many TV episodes were filmed?

19 March 2019



Design an algorithm that finds the closest collision.

(Sample NYC OpenData collision data file on back of lecture slip.)

CSci 127 (Hunter) Lecture 7 19 Marc



Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

• Create a "To Do" list of what your program has to accomplish.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - 1 Find data set (great place to look: NYC OpenData).

CSci 127 (Hunter) Lecture 7 19 March 2019 41 / 44

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.

CSci 127 (Hunter) Lecture 7 19 March 2019 41 / 44

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.
 - Open up the CSV file.

CSci 127 (Hunter) Lecture 7 19 March 2019 41 / 44

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - Ask user for current location.
 - Open up the CSV file.
 - Check distance to each to user's location.

41 / 44

CSci 127 (Hunter) Lecture 7

Design an algorithm that uses NYC OpenData collision data and computes the closest collision to the location the user provides.

How to approach this:

- Create a "To Do" list of what your program has to accomplish.
- Read through the problem, and break it into "To Do" items.
- Don't worry if you don't know how to do all the items you write down.
- Example:
 - Find data set (great place to look: NYC OpenData).
 - 2 Ask user for current location.
 - Open up the CSV file.
 - 4 Check distance to each to user's location.
 - Save the location with the smallest distance.

19 March 2019

41 / 44

CSci 127 (Hunter) Lecture 7

• On lecture slip, write down a topic you wish we had spent more time (and why).









- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.





- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:





- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:

Example: print("Hello", "World")





- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 - Example: print("Hello", "World")
- Can write, or define your own functions,





- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 - Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.





- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 - Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.
- Accessing Formatted Data: NYC OpenData






- On lecture slip, write down a topic you wish we had spent more time (and why).
- Functions are a way to break code into pieces, that can be easily reused.
- You call or invoke a function by typing its name, followed by any inputs, surrounded by parenthesis:
 - Example: print("Hello", "World")
- Can write, or define your own functions, which are stored, until invoked or called.
- Accessing Formatted Data: NYC OpenData
- Pass your lecture slips to the aisles for the UTAs to collect.

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', [Total)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



• Since you must pass the final exam to pass the course, we end every lecture with final exam review.

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter lunch tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', Liotal)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter dinner tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).

CSci 127 (Hunter) Lecture 7 19 March 2019 43 / 44

```
#Mame: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!

def main():
    print("Hello, World!")

if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter_lunch_tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', Liotal)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:

CSci 127 (Hunter) Lecture 7 19 March 2019 43 / 44

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter_lunch_tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', [Total)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;

CSci 127 (Hunter) Lecture 7 19 March 2019 43 / 44

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter_lunch_tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', [Total)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - ► followed by answer; and

43 / 44

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 0
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter_lunch_tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', liotal)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - ▶ repeat.

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
def totalWithTax food, tip):
    total = 8
                        Formal Parameters
    tax - 0.0875
    total = food + food * tax
    total = total + tip
    return(total)
lunch = float(input('Enter lunch total: '))
lTip = float(input('Enter_lunch_tip:' ))
lTotal - totalWithTax(lunch, lTip)
print('Lunch total is', [Total)
                           Actual Parameters
dinner- float(input('Enter dinner total: '))
dTip = float(input('Enter_dinner_tip:' ))
dTotal - totalWithTax dinner, dTip
print('Dinner total is', grorat)
```

```
od profile

profile

profile

reful

reful
```

- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - ► followed by answer; and
 - ▶ repeat.
- Past exams are on the webpage (under Final Exam Information).

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
der totalkithe (Got, LTD)

total = 0

Formal Parameters

tax = 0.800 = food * tox

total = total = tip

return(cotal)

Lunch = (Bost(cryon(* fener lunch total; '))

LiTip = floot((prov(* (Gregal Justice, (pr) '))

Trip = floot((prov(* (Gregal Justice, (pr) '))


Trip = floot((prov(* (Gregal Justice, (pr) '))

Trip = floot((prov(* (Gregal Justice, (pr) ')))

diptol = totalkithou(* (Internet (provide)))

diptol = totalkithou(* (Internet (provide)))

diptol = totalkithou(* (Internet (provide)))
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - followed by answer; and
 - ▶ repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions!

CSci 127 (Hunter)

```
#Name: your name here
#Date: October 2017
#This program, uses functions,
# says hello to the world!
def main():
    print("Hello, World!")
if __name__ = "__main__":
    main()
```

```
der totalitäthe (Tod.(TD)

total = 80 Forman Parameters

total = 600 + food * tox

filter = foot(report(* forter lands = 1))

did = foot(report(* forter lands = 1))

did = foot(report(* forter lands = 1))

did = 100 + foot(report(* forter lands = 1))
```



- Since you must pass the final exam to pass the course, we end every lecture with final exam review.
- Pull out something to write on (not to be turned in).
- Lightning rounds:
 - write as much you can for 60 seconds;
 - ► followed by answer; and
 - ▶ repeat.
- Past exams are on the webpage (under Final Exam Information).
- Theme: Functions!
 Starting with F18 Version 2, #4.

Writing Boards



• Return writing boards as you leave...