#3 How to create a basic Bluetooth® Low Energy peripheral in 10 min

Click & Go

Prerequisites Refresh

SW prerequisites

- STM32CubeWBA MCU package (v1.2.0 as basis + optional patch)
- IDE: STM32CubeIDE (1.14.0)
- A serial terminal (e.g. TeraTerm)
- ST BLE ToolBox Smartphone application

NUCLEO STM32WBA55

HW prerequisites

- USB C cable

ST BLE Toolbox

Download on the App Store

GET IT ON Google Play

Basic Peripheral in 10mn : Click & Go :

life.augmented

Purpose

- As a first exercise, Let's start from an existing project example BLE_P2PServer
- Purpose of this session is to modify this code example to customize advertising data (Local name).



BLE_P2PServer

- In the second part of the Hands on we will generate associated code, flash and test over Nucleo-WBA5x board

What is a P2P Server?

P2P is a Generic Attribute Profile (GATT) based on Bluetooth® Low Energy defined by STM with proprietary UUIDs 128bit

ST BLE Toolbox

Download on the App Store

GET IT ON Google Play

GATT Client **GAP central**

GATT Server **GAP peripheral**

What is a P2P Server?

P2P is widely used for direct connection and defined connection between GATT Server and GATT Client

ST BLE Toolbox

Download on the App Store

GET IT ON Google Play

GATT Client **GAP central**

Notification - SWITCH

Write - LED

GATT Server **GAP peripheral**

life.augmented

STM32Cube capabilities

STM32CubeIDE + STM32CubeMX

STM32Cube allow to start design within 3 options

1	**Example application** complete application running over NUCLEO
2	**Board level** all the hardware is already configured (NUCLEO_WBA55)
3	**Chipset level** require to configure your HW (PCB) & your application

Connect the NUCLEO-WBA55CG to the PC

STM32WBA55CG

3 user LEDs
3 user buttons

STLINK-V3MODS
- Programming
- Debugging
- VCOM





START STM32CubeIDE
Open BLE_P2PServer example



START STM32CubeIDE
Open BLE_P2PServer example





At this stage, Default BLE_P2PServer project source code is ready to be modified, built and flash using STM32CubeIDE

life.augmented

Let’s customize this BLE_p2pServer





Double click on .ioc file to Open CubeMx graphical interface

life.augmented

Customize Local Name



Customize Device Name



set same Device name
=
Local Name

iOS displays Local Name (advertising data) prior to a 1st connexion.
After a 1st connexion iOS displays Device name (thanks to look up table : associates BLE MAC @ & Device Name)

Code Generation



Slide 14

MM0 Put a small comment also on the first two tabs

Manuel MARCIAS; 2023-08-03T11:59:22.255

Build and flash modified project

1 Build





Plug the board

2 Flash







life.augmented

Enjoy your first STM32WBA55 project running!

ST BLE Toolbox

Download on the App Store

GET IT ON Google Play

STBLE Toolbox

1



click on device

2



click on connect

STBLE Toolbox

3



access to profile

4



control LED status on Nucleo

STBLE Toolbox

5





push button 1 and notify device

6



click on details to see bytes sent/received

What's next ?

STM32 CubeMX

start and build from turn-key server application

completed

start from chipset, initialize and configure BLE server application



client

Control LED

Send alert



Server

#1 initialize your HW

#2 configure & understand BLE settings (Adv, service, characteristic)

#2 modify application code & build

life.augmented

Our technology starts with You

Find out more at www.st.com

life.augmented

For further support in creating a PowerPoint presentation, including graphic assets, formatting tools and additional information on the ST brand

you can visit the ST Brand Portal

https://brandportal.st.com

life.augmented