
ArrayCAD user guide

ArrayCAD turns a CAD venue model into a d&b ArrayCalc venue file, or an L-Acoustics Soundvision or AFMG EASE Focus 3 project, and converts between the three in any direction.

Drop in a DWG, DXF, glTF, IFC, OBJ or something similar. ArrayCAD merges the model's triangles back into flat planes, lets you bin everything the prediction tool doesn't need, lets you say what each surface *is* (listening, surface, stage) and writes the file.

It runs in the browser with no backend and no upload, so the file never leaves your machine.



> **Before you rely on this:** I've checked the geometry against the applications themselves rather than against a description of them. A `.dbacv` it writes reproduces a real ArrayCalc export **byte for byte** and has been round-tripped through ArrayCalc until every object came back untouched, a written Soundvision file was imported into Soundvision and read back surface by surface, and EASE Focus opened and saved a project of 57 audience planes with all 57 labels and every coordinate intact. 464 tests pin the reduction.
>
> **What none of that proves is acoustic orientation.** No prediction has been run over an imported surface yet, and **a surface wound the wrong way lands right where it should and then silently returns no mapping result.** Check a mapping before you trust a whole design to it.
>
> This codebase was created with AI assistance, directed and reviewed by a human author.

Three formats, and it converts between them

d&b ArrayCalc	`.dbacv`
L-Acoustics Soundvision	*3D room data* `.txt` — the format its own SketchUp and Vectorworks plug-ins write
AFMG EASE Focus 3	`.fc3`

All three open as well, so ArrayCAD converts between the three prediction tools: drop any one in, write any other.

EASE Focus gets the most out of it. It has no geometry import at all (you type coordinates or trace over a picture), so writing the project file is the only way in.

Coming from a lighting visualiser

If the venue's already built in Capture, Depence, WYSIWYG, grandMA3 or Vectorworks, export **MVR** from it and drop that in. MVR is the open interchange format they all share. Their own project files are closed, and nothing else can read them.

An MVR is a whole show, so most of it is rig. ArrayCAD deals with that: truss, fixtures, supports and projectors are recognised by their MVR type rather than their name, so the rig prunes itself even when a truss is called `Sunstrip 12`. Video screens are kept on purpose, because an LED wall is a big hard reflector and belongs in the prediction. Lighting fixtures are left out entirely, for the same reason loudspeakers always have been: the prediction places its own.

The format states millimetres and Z-up, so the units aren't a guess. Check the size against the drawing anyway. The spec doesn't say what units the 3D models inside the archive use, and ArrayCAD warns you if the room comes out an implausible size.

Export .mvr goes back the other way, so a room can come from a visualiser, get pruned and simplified here, and go back. It's the only export that doesn't reduce: MVR carries glTF, which wants the triangles the coplanar merge has already made, so the visualiser gets the *simplified* room with nothing more lost. Plane types travel as MVR classes, so the audience areas can be toggled as a set.

> Not yet confirmed in a visualiser: nobody has opened an ArrayCAD `.mvr` in Capture or Depence. Check the size after importing.

Preparing a model on import

Most of the first ten minutes with a new file goes on work the drawing already describes. The **Prepare** panel does it as the file opens, and every part of it is a decision you can see and undo. Nothing is deleted: the objects it leaves out stay in the tree, ghosted in the view, one click from coming back.

Leave out clutter	Objects named as something other than a room surface: dimensions, text, lighting bars, truss, cable, ductwork, furniture, people — and modelled loudspeakers, since the prediction tools place their own. **Whole words only**, so `TEXTURED PANEL` stays and `TEXT` goes.
Leave out tiny objects	Brackets, fixings, trim and stray facets, under an area you set. **Seating is exempt** — a seat pan is 0.2 m².
Flatten seating into audience planes	Found by name **and by repetition**: hundreds of alike, small, upward-facing objects a metre apart are a bank of chairs whatever they are called. Tiers separated in height become separate planes.
Guess plane types from names	`STAGE` becomes a stage; `WALL` and `CEILING` become surfaces.
Re-cut heavy objects	A meshed flat wall is hundreds of triangles describing one rectangle. Re-cutting from its own outline gives the same shape with a fraction of the triangles. **Anything not genuinely flat, or with a hole in it, is left alone.**

The panel then tells you what it actually did to *your* model, with counts. On the demo venue that's 3,206 triangles down to 1,322 and **116 ArrayCalc objects down to 52** before you've touched anything. On the seat-by-seat plan it's **3,710 objects down to 17.**

Untick a box and it re-runs from the file as imported. It reads the model once, when it opens, using the units in force at that point, **so if the unit guess was wrong, fix it and re-run.**

Rationalising a seat-by-seat plan

An architect's model draws every seat. A sound designer wants the seating *area*.

Pick what to gather up, whichever way suits the drawing:

- **Select in the tree**: right when each seat or block is its own object, as in a glTF or IFC export.
- **Box select**: drag a rectangle in the 3D view.
- **Draw an area**: click the corners of the region. This is the one that matters for a DXF or DWG, where the whole house is usually on *one layer* and no amount of pruning in the tree will separate the stalls from the balcony.

Two settings decide most of the result:

- **Capture**: *Upward faces* (the default) keeps only surfaces pointing up, so a modelled seat reduces to its pan rather than dragging the plane down inside the seat. *All faces* is for a wall or a bare rake.
- **Outline**: *Follow* traces the seating and bridges gaps up to a distance you set. Set it to the row pitch and it joins seat to seat and row to row, and leaves an aisle wider than the pitch standing as an aisle. *Hull* is the convex hull, fine for a rectangular block and wrong for a horseshoe. *Rectangle* squares it off, which a Positioning area has to be.

> **Combine the tree and the drawing.** Select the seating layer first and then draw, and only the seating inside your outline is captured. **Draw with nothing selected and it takes everything under the polygon, including the floor beneath the seats, which fits the plane half a seat height too low.** The panel says which it's about to do.

Read the numbers underneath. Every area reports what the reduction cost, because "these four hundred seats are one surface" is *your* assertion and not the geometry's.

No 3D model? Trace one off the plan

Drop in a PDF or an image instead, set the scale, click inside a room to detect its outline, and type a height at each corner.

If something is wrong

Symptom	Cause
A mapping returns nothing, and the geometry looks right	A surface is wound the wrong way. It lands in the right place and silently maps nothing — check a mapping early.
Everything came in at the wrong scale	The unit guess. Fix it and re-run the import; it reads the model once, with the units in force then.
A seating plane sits half a seat too low	The floor under the seats was captured. Select the seating layer before drawing.
An aisle was swallowed	The follow distance is wider than the aisle. Set it to the row pitch.
A horseshoe came back as a block	*Hull* outline. Use *Follow*.
Something useful was left out	Nothing is deleted — it is ghosted in the tree, one click from coming back.