Companion — PDF Presenter user guide

This is a Bitfocus Companion connection module for PDF Presenter. It lets a Stream Deck (or any other Companion surface) drive the app while it's running: slides, sections, the output window, black/white screen, the laser pointer, slide transitions, and the watched-folder file list.

It talks straight to the app's own OSC listener over UDP and listens for feedback on a local port. There's nothing to install on the app end beyond turning OSC on.

> **This module was built with AI assistance and reviewed by a human.** Check it over before you rely on it for a show. It's **not in the official Companion module store**, so it installs as a developer module, which takes a few more steps. They're below.

Setting it up

1. Install the module. It isn't in the store, so you have to point Companion at it:

```
git clone https://github.com/stoatworks-labs/companion-module-pdf-presenter-lite
cd companion-module-pdf-presenter-lite
npm install
```

In Companion, go to **Settings → Developer modules path** and point it at **the parent folder that contains this repo's folder**, not at the folder itself. Restart Companion, or use "Rescan for developer modules" if your version has it, and "PDF Presenter" turns up as a connection you can install.

2. Turn OSC on in the app. In PDF Presenter, click **Start OSC** in the titlebar. Once you've started it once, it remembers across restarts.

3. Add the connection, and set three fields:

Field	Default	What it is
App host	`127.0.0.1`	The machine running PDF Presenter. The default assumes Companion is on the same machine.
App listen port	`35551`	Where the app listens. Matches the app's own default.
Local feedback port	`35550`	Where this module listens for the app's replies. Matches the app's own default.

If Companion and the app are on different machines, change **App host** to the app's actual IP, *and* make sure the **Feedback host** in the app's own OSC settings panel points back at the Companion

machine's IP, not `127.0.0.1`. Miss that second half and the actions work while every variable stays empty, which is a confusing way for it to go wrong.

Actions

Slides

Action	What it does
Next slide / Previous slide	Step through the deck
Go to slide number	Jump to an absolute slide
Go to first slide / Go to last slide	Ends of the deck

Sections

Action	What it does
Go to first slide of section	Jump to a named section
Go to first slide of next section	Skip forward a section
Go to first slide of previous section	Skip back a section

The named-section action gives you **a live dropdown of whatever the app last reported**, plus a custom value that takes variables, for when you want it to change on the fly.

Output window

Action	What it does
Start Output from first slide	Open the output window at the top of the deck
Start Output from current slide	Open it where you already are
Close Output	Shut the output window
Toggle black screen / Toggle white screen	Cover the output
Toggle laser pointer overlay	Show/hide the pointer
Set current slide as desktop wallpaper	Useful for a holding slide behind the output

Transitions

Action	What it does
Set slide transition (effect, direction and duration)	Set all three in one press
Set slide transition effect	Cut, fade, dip to black/white, push, wipe, cover, uncover, zoom
Set slide transition direction	Where the new slide comes from (push, wipe, cover and uncover only)
Set slide transition duration	50 to 5000 ms; takes variables

The effect and direction dropdowns are fixed lists copied from the app, not discovered from it. **Dynamic** direction brings the slide in from the left going forward and from the right going back, and needs PDF Presenter 1.7.0 or later. The app ignores a name it doesn't recognise, so a typo can't change the look of a live show.

Auto-advance

Action	What it does
Pause auto-advance / Resume auto-advance	Hold and release a timed run

Protocol control

Action	What it does
Enable / Disable OSC actions	Turn remote control off from the surface
Enable / Disable OSC feedback	Turn the app's replies off
Request feedback refresh	Ask the app to re-send everything
Set watched folder	Point the app at a different folder
Request watched-folder file list	Refresh the file dropdown
Open file from watched folder	Load a deck by name

Feedbacks

Four, and only four:

- **Slideshow state:** edit / running / running-with-auto-advance-paused.
- **Slide transition effect:** lights when the chosen effect is the one selected.
- **Slide transition direction:** lights when the chosen direction is the one selected. The app keeps a direction set even under an effect that ignores it, so pair it with the effect feedback if

that matters.

- **OSC file access enabled**.

> **I've left out a feedback for "laser pointer on" or "auto-advance enabled" on purpose.** The app's OSC protocol never broadcasts either as a value of its own (it only sends the combined edit/running/paused state), so a feedback for either would have to make up data the app doesn't provide. If you need a button to *look* like it knows, drive it from the slideshow state instead.

Variables

Variable	Contents
`presentationName`	Presentation file name
`slideCount`	Total slide count
`slideCountVisible`	Total slide count, excluding hidden slides
`state`	Presentation state (edit / running / paused)
`currentSlide`	Current slide number
`slidesRemaining`	Slides left in the deck
`sectionIndex`	Current section index
`sectionName`	Current section name
`sectionSlidesRemaining`	Slides remaining in the current section
`previousSectionName`	Previous section name — "Start of deck" if this is the first
`previousSectionFirstSlide`	First slide of the previous section
`nextSectionName`	Next section name — "End of deck" if this is the last
`nextSectionFirstSlide`	First slide of the next section
`fileAccessEnabled`	Whether OSC file-open access is enabled
`activeFolder`	Watched folder, relative to the home directory
`activeFolderFullPath`	Watched folder, full path
`activeFolderFileCount`	Number of files in the watched folder
`activeFolderFileNames`	JSON array of file names in the watched folder
`transition`	Slide transition, as a JSON object
`transitionEffect`	Slide transition effect
`transitionDirection`	Slide transition direction (push/wipe/cover/uncover only)
`transitionDuration`	Slide transition duration, in milliseconds

The section variables are the handy ones for building a presenter's surface: a button showing `$(<connection-label>:nextSectionName)` tells the operator what's coming up without them having to read the deck. The prefix is whatever you called the connection in Companion.

Troubleshooting

Symptom	Cause
Module doesn't appear in Companion	The developer modules path points at the repo folder rather than **its parent**.
Buttons work, all variables empty	Feedback isn't getting back. On separate machines, the app's **Feedback host** must be the Companion machine's IP, not `127.0.0.1`.
Nothing happens at all	OSC isn't started in the app — click **Start OSC** in its titlebar — or App host / App listen port is wrong.
Section dropdown is empty or stale	The list is whatever the app last reported. Fire **Request feedback refresh**.
File-open action does nothing	File access is disabled in the app; check the `fileAccessEnabled` variable.
No feedback for the laser pointer	Correct, and deliberate — the protocol doesn't broadcast it.

See also

- README: what it does, installing it, and the prior art I looked at for how to structure the module
- PDF Presenter: the app this controls, and its OSC protocol