Support Scripts

Scripts used by support for troubleshooting issues and making changes to customer systems more efficiently.

Script Name	Download Link	Description
crm_fix	crm_fix repo (bitbucket)	Script to implement new CRM templates for versions of SL1 deployed on old ISOs.
rows-behind_mon.sh	Rows Behind Troubleshooting Doc in Confluence	Script to monitor progress on rows behind issues
logParse.py		Script to split silo.log into individual thread logs for easier review. Additional features available and de
System Status	https://docs.sciencelogic.com/system_status/system_status_3.0.sh	Our standard System Status script.
VMWare troubleshooting	VMware Power Pack Troubleshooting Guide#TroubleshootingScriptTroubleshootingScriptandOtherTools	Scripts used in the VMWare PowerPack Troubleshooting guide from engineering
re-init-db.sh	KB Article: https://sciencelogic.lightning.force.com/lightning/r/Knowledge__kav/ka04z000000shIiAAI/view	Script to reinitialize a DB

php_devlog_config.php		Script to enable devlog from the backend when UI is not available. (EM-3
		The script needs to be run as "em7admin" user:
		`[root@ha2 em7admin]# sudo -u em7admin php php_devlog_config.php`
		`usage: -L <level> -T <duration> [-M <mysqli_level>] [-D] -L Total log level from mask (i.e.`
		`  1 = emergency, alert, critical`
		`  2 = error`
		`  4 = warning`
		`  8 = notice, info`
		`  16 = debug`
		`  32 = trace (aliased to LOG_NOTICE)`
		`  64 = undocumented / not supported!`
		`  -T How long to enable logging in minutes`
		`  -M Optional: Total mysqli log level. Defaults to devlog level`
		`  -D Optional: delete log settings (same as waiting for duration to lapse). Ignores other op`
		`  -S Optional: show current runtime config, if set. Ignores other options when set, takes pr`
		`[root@ha2 em7admin]# sudo -u em7admin php php_devlog_config.php -L 63 -T 10`
		`config:`
		`[root@ha2 em7admin]# sudo -u em7admin php php_devlog_config.php -S`
		`Current running config (NOTE: only only some of these can be altered with this script):`
		`Array`
		`(`
		`  [loglevel] => 63`
		`  [logfile] => /var/log/em7/em7php.log`
		`  [logvars] => time,filefunc,line,level,msg`
		`  [logformat] => %s|%-54s|%-4s|%s|%s`
		`  [filefunclen] => 54`
		`  [timeformat] => H:i:`
		`  [mysqli] => /var/log/em7/mysqli.log`
		`  [suppress] => css.em7::127,brandedimage.em7::127,theme_image.em7::127,php_bridge.inc::24`
		`)`
		`[root@ha2 em7admin]# sudo -u em7admin php php_devlog_config.php -D`
		`Clearing log settings. Unlink/dev/shm/php_devlog_runtime_config`
		`[root@ha2 em7admin]# sudo -u em7admin php php_devlog_config.php -S`
		`Current running config (NOTE: only only some of these can be altered with this script):`
		
		Current limitations:
		1. Script can delete configuration that was set from the backend only. If y delete that with "-D" option.
		Configuration is stored as "/dev/shm/php_devlog_runtime_config" file. Re
		2. Setting MySQL log level is not supported in this version of the script.

if_debug.py		Description: This script gather the raw data for an interface for a given period and display it to stdout. Usage: python if_debug.py if_id [-s 'YYYY-MM-DD HH:MM:SS'] [-e 'YYYY-MM HH:MM:SS'] [-v] Features: Given an interface ID, show interface configuration data along with raw data for a given timeframe, defaulting to the past 24 hours.
query_killer.py		Name: query_killer.py Description: This script will search for long running queries matching a given string match pattern and kill them. Usage: On CLI: python query_killer.py -c 3 -t 60 -m "<String>" In cron: PYTHONPATH=/opt/em7/backend:/opt/em7/lib/python:/var/lib/em7/content/ * * * * * /bin/python2.7 /home/silosupport/query_killer.py -s -m "SELECT dap.presentation_id, dadp
flood_finder.py		Description: This tool should allow you to quickly identify devices which are floodin the system with events by checking the count of rows in hf_storage. Th will check all collectors of the selected type and add all results togethe for each device ID. Usage: flood_finder.py [-h] [-i] [--hours {1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22, [-t {DC,MC,Both}] [-v] optional arguments:

Script Name	Download Link	Description
		-h, --help show this help message and exit -i, --individual Show individual collector details --hours {1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24} Number of hours to check -t {DC,MC,Both}, --type {DC,MC,Both} Collector Type -v, --verbose Enable additional verbose output Example Syntax: python2.7 flood_finder.py -i -t MC Features: Provide combined counts of hf_storage objects per device being create Allows for checking data up to the past 24 hours. version .0.2 fixes the tabular output to include the actual top N records
inspector_gadget.py		Description: This tool should allow you to view the full contents of a storage object. For now it just lets you extract the "record" element of the storage object. Usage: On CLI: python2.7 inspector_gadget.py -f hf -s 12345
CanAPReachDB.py		Description: Since APs don't have MySQL client installed, it's often difficult to validate that an AP can access the DB for licensing and otherwise. This script helps to bridge that gap. Usage: python2.7 CanAPReachDB.py
calc_buffer_pool.py		Description: Starting with MariaDB version 10.2, innodb_buffer_pool_size is dynamic, but must be in increments of buffer pool instances * buffer pool chunk siz This script will provide all valid values and provide basic guidance based on historical memory usage (sar). Usage: python calc_buffer_pool.py
read_cache.py (unpickle.py)		Description: Cache values in the data collector database are pickled, which makes it d the value of the key when using 'key='. Usage: python read_cache.py <command> Commands: keys: Lists all keys in cache alphabetically keys=<value> Lists matching keys in cache alphabetically using SQL 'LIK key=<value> Shows the value for the database key <value>
pull_cert.py		Description: Pull a certificate using internal SL1 packages and display the output. Usage: python pull_cert.py 127.0.0.1 127.0.0.2 127.0.0.3... (IP addresses to pull fror Useful for troubleshooting certificate discovery issues. Note: Both SL1 an
clear_async.py		Description: Clear async jobs from collectors, clears 'config_last_poll' for a set of app_ Usage: python clear_async.py [command] Commands: clear_async_job [mid] [proc_id] [←dry-run>] #value of 0 can be us clear_last_poll [mid] [app_id_list] [←dry-run>] #app_id_list can be c poll_cus [mid]

Script Name	Download Link	Description
snmp_getnext.py		Description: Using SL1 internal packages, troubleshoot collection of SNMP data. Usage: python snmp_getnext.py [cred_id] [ip_address]
interface_check.py		Description: As of 11.2.0 and 11.2.1, an upgrade to these versions can cause interfaces This script will print the number of affected interfaces. More info here: **https://support.sciencelogic.com/s/article/9228** Usage: python interface_check.py
backup_tester.sh		Description: Test between an NFS or SMB backup. The script will test mounting and t Usage: sudo bash backup_tester.sh

locate_logs.py		Description:
		Use this script to search through each device's logs, then display a list of
		Commonly used for searching which devices are affected by a current iss
		
		Usage:
		python locate_logs.py [Logs to search]
		
		Example:
		`[em7admin@sl1support-ha2 ~]$ python locate_logs`
		
		`The log 'physical memory' was found in the follo`
		
		`['263', '264', '3', '9']`
		
		`List for copy and paste to the UI search:`
		
		`263,264,3,9`

UnalignDAsViaAPI.py		Description: Use this script to unalign the specified DAs from the specified DIDs. This apps, so you will also need to use a device template on the specified devi Usage: Edit the script to input the credentials for a valid API user add the DIDs ar `python UnalignDAsViaAPI.py`

host_file_entries_generator.py		This script will scan all hosts file entries in a CUG, merge them, remove du
		managed properly by SL1.
		You can also place a text file in the same directory as the script containing
		`python3 host_file_entries_generator.py --help`
		`usage: host_file_entries_generator.py [-h] [--ro`
		`positional arguments:`
		`edit_user The user that will be shown as creatin`
		`cug_id The ID of the Collector Group to sync hos`
		`from`
		`optional arguments:`
		`-h, --help show this help message and exit`
		`--roa_id roa_id The ID of the Organization the I`

powershell_tests.py and ps-credentials-test.py	https://code.eng.sciencelogic.com/projects/TOOL/repos/powershell/browse	Scripts to test powershell credentials and powershell DAs from eng. Not noted in any TSG that I'm aw
collector_toolkit.py	Script for Deploying Files and Running Commands on Remote SL1 Appliances	`sudo python3 collector_toolkit.py`