Agent Cheat Sheet

- Agent Troubleshooting for Support
- ScienceLogic documentation
- Get Agent version
- Start and stop the Agent
- Get Diag file
- Get the conf file
- Edit the conf file
- Turn on DataKeep
- Install a new Agent
- Upgrade an existing Agent
- Run the Agent in debug mode
- Change Windows debug mode log level
- Latest official releases
- System requirements

This document has instructions for the most common Agent commands and tasks.

Agent Troubleshooting for Support

Agent Troubleshooting for Support

ScienceLogic documentation

Official ScienceLogic docs:

Monitoring with the SL1 Agent

Get Agent version

From the device command line (Windows):

```
"C:\Program Files\ScienceLogic\SiloAgent\bin\SiloAgent.exe" --version
```

From the device command line (Linux):

```
scilogd --version
```

From the device command line (AIX, *different than linux*)

```
scilogd -V
```

From the UI (Extended Architecture):

In the SL1 UI, go to the Agents page (Devices>Agents) and look in the version column

From the UI (Classic):
Not possible from the Classic UI, get Agent version from the device.

Start and stop the Agent

From the device command line (Windows):

```
net start SiloAgent
net stop SiloAgent
```

From the device's Windows Services utility:
In the Start menu, search for "Services," or use the Run tool (Win+R) to run "services.msc". Find SiloAgent Service in the list, and right-click on it to start/stop.

From the device command line (Linux):

```
sudo systemctl start scilogd
sudo systemctl stop scilogd
```

Get Diag file

This generates a file containing lots of info about the Agent install, as well as log data from DataKeep and the conf files. Be aware of what directory you are generating the diag file in--will need Administrator/sudo if your current directory is protected.

From the device command line (Windows)

```
cd [some directory you have write privileges]
"C:\Program Files\ScienceLogic\SiloAgent\bin\SiloAgent.exe" --diag
```

From the device command line (Linux)

```
cd [some directory you have write privileges]
scilogd --diag
```

From the device command line (AIX, *different than linux*)

```
ps -ef | grep scilogd   # to find scilogd location
cd [some directory you have write privileges]
scilogd -b sl-diag      # use the correct scilogd location
```

The diag file will be created in your current working directory. For linux it will be named `sl-diag.tar.gz`. For Windows it is named `scilog-<current date>.diag.tgz`.

Get the conf file

The conf file (`scilog.conf`) contains settings used by the Agent, on each device. The WHAT may ask for it. (The conf file is already included in the Diag file.)

Windows: `C:\Program Files\ScienceLogic\SiloAgent\conf\scilog.conf`

Linux: `/etc/scilog/scilog.conf`

Edit the conf file

The conf file contains settings used by the Agent, on each device. Usually the backend writes settings to this file, but we may ask that you edit it manually. Whenever the conf file is edited, the Agent needs to be restarted for the change to take effect. Administrator or sudo privileges are required to edit the conf filed.

Edit the conf file using Notepad (Windows):
Notepad cannot be launched in "Administrator mode," so in order to edit the conf file, copy it to a non-protected directory (like the desktop), edit it there, and paste it back into the `C:\Program Files\ScienceLogic\SiloAgent\conf` directory. When you paste the file, you will be prompted for an Administrator elevation. Allow it, then stop and restart the Agent.

Edit the conf file using Powershell (Windows):
Open an Administrator Powershell prompt, and enter:

```
Add-Content 'C:\Program Files\ScienceLogic\SiloAgent\conf\scilog.conf' "`nDataKeep 20"
```

Where `` `nDataKeep 20 `` is an example of a line you wish to add to the conf file. The `` `n `` indicates a new line, and `DataKeep 20` is an Agent setting. Then, stop and restart the Agent.

Edit the conf file using vim (Linux):

```
sudo vim /etc/cilog/scilog/conf
```

Edit the conf and save. Then, stop and restart the Agent.

Turn on DataKeep

DataKeep is a setting in the conf file (`scilog.conf`) which tells the Agent to keep some number of datafiles saved for some time after they are uploaded, so we can examine them manually. When we say "Turn on DataKeep" or "Set DataKeep to 20" we are saying edit the conf file to include the DataKeep parameter.

Edit the conf file to include the line `DataKeep 20`. This tells the Agent to keep up to 20 data files for us to examine. The files are stored in `C:\Program`

`Files\ScienceLogic\SiloAgent\logs` (Windows) or `/tmp/scilog/data` (Linux). Stop and restart the Agent for the change to take effect. You will see up to 20 data folders appear, one at a time, in the above location.

Usually, after some files are generated, we ask you to send us those files, or create the Diag file and send us that.

Install a new Agent

Extended Architecture
Classic

Upgrade an existing Agent

From the UI (Extended Architecture only): Through the Agents page (Devices>Agents), click the "Upgrade to..." button.

Manual upgrade (Classic or Extended): The A-Team may give you an install file for a newer version of the Agent, or you can download the latest install file right from our release repo. Then follow these instructions with the install file:
Debian/Ubuntu/.deb:

```
sudo dpkg -i sl_agent.deb
```

Red Hat/CentOS/.rpm:

```
sudo rpm -Uhv sl_agent.rpm
```

Windows:

```
SiloAgent-install.exe
```

The new version of the Agent will replace the old one. For upgrades, it is not necessary to include the URLFRONT and TENANT parameters that are used during the initial installation.

Run the Agent in debug mode

Typically the Agent runs as a service ("in the background"). The A-Team may ask you to run the Agent in debug mode to get access to an debug log that is usually hidden.

From the device command line (Windows):
Open an Administrator command prompt and enter:

```
net stop SiloAgent
"C:\Program Files\ScienceLogic\SiloAgent\bin\SiloAgent.exe"
```

The Agent will start “in the foreground” and debug messages will be printed to the console. Wait at least 5 minutes (or as long as it takes for the defective behavior to occur), then press Ctrl-C to stop the Agent. Copy-paste all the output into a text file, and save it for us. Then, start the Agent service again to resume normal monitoring:

```
net start SiloAgent
```

From the device command line (Linux):

```
sudo systemctl stop scilogd
sudo scilogd -d 2>&1 | tee /tmp/scilogd.log
```

The Agent will start “in the foreground” and debug messages will be printed to the console. Let the Agent run for at least 5 minutes (or as long as it takes for the defective behavior to occur), then press Ctrl-C to stop the Agent. Locate the /tmp/scilogd.log file and save it for us. Then, start the Agent service again to resume normal monitoring:

```
sudo systemctl start scilogd
```

Change Windows debug mode log level

When running the Windows Agent in debug mode (above), by default only critical debug messages are logged. To change this:

1. From the Windows Run utility (Win+R), or Start menu search, open “regedit” (Registry Editor)
2. Go to Computer\HKEY_LOCAL_MACHINE\SOFTWARE\ScienceLogic\SiloAgent
3. Modify LogLevel
4. Set LogLevel to AFX_VERBOSE to have the Agent log with greater detail. Set LogLevel to AF_NONE to return to default.
5. Stop the Agent if it is running, and run the Agent in debug mode again to see the changes take effect.

Latest official releases

You can get the latest install files straight from our release repos here.

Windows: https://code.eng.sciencelogic.com/projects/ESP/repos/agent-release-win/browse `SiloAgent-install.exe`

Linux: https://code.eng.sciencelogic.com/projects/ESP/repos/agent-release-lin/browse/installation

Debian/Ubuntu/.deb: `sl_agent_vXXX.deb`

Red Hat/CentOS/.rpm: `sl_agent_vXXX.rpm`

AIX: https://code.eng.sciencelogic.com/projects/ESP/repos/agent-release-aix/browse

`scilogd-0.XXX.0-0.aix7.2.noarch.rpm`

Solaris: https://code.eng.sciencelogic.com/projects/ESP/repos/agent-release-solaris/browse

`scilogd_0.XXX.0_sYY_sparc.pkg` or

`scilogd_0.XXX.0_sYY_i386.pkg`

where XXX is the Agent version, YY is Solaris version (10 or 11).

System requirements

ScienceLogic support page (requires salesforce login):

https://support.sciencelogic.com/s/system-requirements?tabset-e65a2=3&tabset-3429b=3