Datapull Configuration Options

Below are a list of datapull configuration options and what they do. These all would go under the `[DATAPULL]` section in /etc/silo.conf.

Example:

```
[DATAPULL]
log_storage = 1
num_storage_procs = 12
```

Frequency-Specific Config Options

As of 12.3.0, DataPull configuration options can be set for specific frequencies by prepending `<x>f_` in front of the setting. <x> is one of [l, m, h]. These specific settings take precedence over any generic setting.

Example 1:

This will set LF & HF to 8 storage processes using the generic setting, while MF will have 10 storage processes

```
[DATAPULL]
num_storage_procs = 8
mf_num_storage_procs = 10
```

Example 2:

This maintains the configuration from Example 1 and also sets a specific memory limit for each frequency

```
[DATAPULL]
num_storage_procs = 8
mf_num_storage_procs = 10
lf_memory_limit = 1073741824
mf_memory_limit = 4294967296
hf_memory_limit = 2147483648
```

DataPull Configuration Options

These are organized top-down from most commonly used to least commonly used

Here are the color codes for the options:

1. Are frequently used

2. Are almost never used
3. Not useful anymore. Going to be deprecated in a future release
4. Deprecated

Option	Values	Default	Versions Available	Explanation
log_storage	Boolean 1 = True, 0 = False	0	ALL	If True, storage processes will log to files. **If you set this, also turn Debug mode on for the processes and restart them**
num_storage_procs	Integer (Processes)	min(<CPU count>, 16)	ALL	The number of storage processes each frequency will spawn
Environment Variable `SL_EXPORT_METRICS`	Boolean "true" = On	0	12.3.0 +	Set to True if you want to enable Skylar export of data More Info: Supported SL1 Data for Exporting to Skylar ARCHIVED
storage_object_timeout	Integer (Seconds)	60	ALL	Storage process will be restarted if a task doesn't complete in this time
outstanding_storage_tasks_limit	Integer (Tasks)	50000	ALL	The amount of pending storage tasks each frequency will queue up on the CDB. Increase if this queue is getting exhausted during rows behind scenarios
pull_block_size	Integer (Tasks)	5000	ALL	The maximum amount of storage objects to be pulled from a CU in a single pull
storage_process_init_timeout	Integer (Seconds)	60	ALL	The amount of time storage processes are given to startup before they are killed as unresponsive. *This was raised to 60*

				to accommodate py2→py3 mappings and might be reduced in a future version
num_storage_retries	Integer (Retries)	2	ALL	The number of times retry-able storage objects will be retried if they fail
storage_process_refresh_interval	Integer (Tasks)	1000000	ALL	Number of tasks a process will complete before being restarted
memory_limit	Integer (Bytes)	2147483648 (2.15 GB)	ALL	Memory limit for the datapull main process
log_storage_object_stats	Boolean 1 = True, 0 = False	0	ALL	Set to True if you want some extra timing info from processing storage objects logged. More useful in development than for customers
collector_connect_timeout	Integer (Seconds)	5	ALL	If CU doesn't connect in this time, kills and restarts connection
collector_read_timeout	Integer (Seconds)	10	ALL	If CU doesn't respond in this time, kills and restarts connection
collector_thread_pool_size	Integer (Threads)	8	ALL	Number of threads to allocate to the CU operations
force_sync_interval	Integer (Pulls)	5	ALL	Number of pulls from CU before forcing a sync
remote_checkpoint_interval	Integer (Minutes)	5	ALL	Minutes between checkpoints from CU
force_checkpoint_interval	Integer (Pulls)	50	ALL	Number of pulls before we force a checkpoint from CU
allow_deprecated_storage_objects	Boolean 1 = True, 0 = False	0	12.1.2 12.2.1 12.2.1.2 12.2.3	Set to True if you want to allow the processing of pickled storage objects. **WARNING: THIS INTRODUCES A SECURITY VULNERABILITY. DO NOT SET UNLESS ABSOLUTELY NEEDED**

log_unconverted_storage_objects	Boolean 1 = True, 0 = False	True	12.2.x	Logs Py2 storage objects we receive **DEPRECATED**: No longer needed with JSON datapull