

# SAMPLE DRAWING — DEMO ONLY

|            |                         |              |          |
|------------|-------------------------|--------------|----------|
| TITLE:     | CAMERA HOUSING ASSEMBLY | P.N.:        | AC-23456 |
| CUSTOMER:  | ACME Aerospace Inc.     | REV:         | C        |
| CAGE CODE: | AC001                   | DRAWING NO.: | AC-23456 |
| SCALE:     | 1:1                     | SHEET:       | 1 OF 1   |

## MATERIAL

ALUMINUM ALLOY 7075-T651 PER AMS-QQ-A-250/12  
ALTERNATIVE: ALUMINUM ALLOY 6061-T6 PER AMS-QQ-A-250/11

## PRODUCTION ROUTING CHART

| NO. | DESCRIPTION                                     | SPEC           |
|-----|-------------------------------------------------|----------------|
| 10  | CNC MILL — 5-axis                               | AC-PROC-002    |
| 20  | TURN — OD .500" tolerance $\pm 0.0005$          | AC-PROC-005    |
| 30  | DRILL & TAP — M5 $\times$ 0.8 $\times$ 4 places | —              |
| 40  | DEBURR + CLEAN                                  | —              |
| 50  | BLACK ANODIZE TYPE II CLASS 2                   | MIL-A-8625     |
| 60  | EPOXY PRIMER 25-30 microns                      | MIL-PRF-23377K |
| 70  | POLYURETHANE TOPCOAT — RAL 7035 Light Grey      | MIL-PRF-85285E |
| 80  | FLUORESCENT PENETRANT INSPECTION — Type I       | ASTM E1417     |
| 90  | DIMENSIONAL INSPECTION — CMM REPORT             | —              |
| 100 | FINAL APPROVAL — QA STAMP                       | —              |
| 110 | ESD PACKAGING — Individual bag                  | —              |

## NOTES

- ALL DIMENSIONS IN MILLIMETERS.
- PAINT THICKNESS — TOTAL 50-75 microns.
- RoHS COMPLIANT.
- ESD HANDLING REQUIRED — CLEAN ROOM CLASS 100,000.
- TEMPERATURE RANGE -40°C TO +85°C OPERATIONAL.