

## Universal Task Documentation

---

Universal Automation Center support for scheduling  
docker container

ut-docker-cli-push-linux

Associated Activities:

Date: 16 August 2018

Author: Nils Buer

Revision: 01

CONFIDENTIALITY INFORMATION
-----------------------------

Distribution list: Stonebranch Marketplace

Revision	Date	Author	Changes
00	20180814	Nils Buer	Initial Document (WIP)
01	20180814	KM	Update for first 5 Tasks
02	20180821	Nils Buer	Testcases added

### Abstract:

The here described Universal Tasks allows operate your docker container and schedule docker container-based applications as part of any existing or new scheduling workflow.

## Contents

<b>1</b>	<b>Disclaimer .....</b>	<b>3</b>
<b>2</b>	<b>Scope .....</b>	<b>3</b>
<b>3</b>	<b>Introduction.....</b>	<b>3</b>
<b>4</b>	<b>Installation.....</b>	<b>4</b>
4.1	<i>Software Requirements .....</i>	<i>4</i>
4.2	<i>Installation Steps .....</i>	<i>4</i>
<b>5</b>	<b>Universal Task Configuration .....</b>	<b>6</b>
<b>6</b>	<b>Universal Tasks for Docker Container .....</b>	<b>7</b>
6.1	<i>Push an Image .....</i>	<i>7</i>
<b>7</b>	<b>Test Cases .....</b>	<b>8</b>
<b>8</b>	<b>Document References.....</b>	<b>8</b>

## 1 Disclaimer

No support and no warranty are provided by Stonebranch GmbH for this document and the related Universal Task. The use of this document and the related Universal Task is on your own risk.

Before using this task in a production system, please perform extensive testing.

Stonebranch GmbH assumes no liability for damage caused by the performance of the Universal Tasks

## 2 Scope

This document provides a documentation how to install and use the Universal Tasks for docker container. If more Task will be created in the future this document will be updated accordingly.

## 3 Introduction

Universal Automation Center seamlessly integrates your legacy system into your container-based DevOps process without the need to re-design your business process logic, resulting in a shorter time-to-market, improved customer satisfaction, better product quality, more reliable releases, improved productivity and efficiency. As a result, you can make use of all the benefits provided by containers like **portability** from applications, **simplified integration**, **optimized development**, **increased scalability** and **performance**, while at the same time minimizing the risk while introducing a new technology.

Security is an important topic, when working with Containers. Containers are more or less isolated from the host OS system, but they use the same kernel. Due to potential security risks a Container should be executed in most cases using a non-privileged user account. In some cases, it might however be needed to use some kernel functionalities e.g. when mounting e.g. a USB drive. Universal Automation Center allows to centrally maintain individual credentials for each container and provides to start a container using the `--privileged` flag where needed.

**Central Management of all user and groups** with support for SAML, SSL LDAP/AD for legacy and containerized applications

**Central Management of all Application Credentials and Connections** e.g. SAP and Database connections, script credentials ...

**Central Management of all credentials used to connect to a registry**

Our security concept is constantly validated by external BSI certified security companies

Some details about the universal tasks for docker container:

- The here described Universal Tasks are calling the native docker cli. Universal Tasks based on the docker python SDK will be described in a separate document.
- Currently the most important docker cli commands have been implemented. Any missing command can be provided on request or created by the user itself based on an existing task.
- The current Universal Task require a Linux Agent for running the Universal Tasks scripts
- The docker private- and public registry are support. Other registries can be added with minimal efforts.
- Credentials can be provided for each task individually e.g. docker login, user executing the container, you can pass credentials for applications running in the container, ..
- You can select different log-levels e.g. debug

Note:

For details on each docker cli command refer to the docker documentation:

<https://docs.docker.com/engine/reference/commandline/docker/>

## 4 Installation

### 4.1 Software Requirements

**Universal Task name:** *ut-docker-cli-push-linux*

**Related UAC XML Files for template and task:** *Github repository*

**Software used:**

For the set-up you need:

1. Universal Controller 6.4.5.x (any platform: Linux, Windows or SaaS Cloud)
2. Universal Agent 6.4.2.2 or higher installed on a Linux Server
3. Docker engine with version 17.09.1-c or higher installed on a Linux server

### 4.2 Installation Steps

The following describes the installation steps:

#### 1. Install the docker engine and a Universal Agent on a Linux Server e.g. Open SUSE

The following provides a sample set-up for Open SUSE. For other Linux distribution the set-up is similar (check with google). The set-up is provided here to have some guidance on the general step. The steps may vary depending on your landscape.

##### # Install Agent on docker engine

```
sh ./unvinst --network_provider oms --oms_servers 7878@<oms_ip> --oms_port 7878 --  
oms_autostart no --ac_netname OPSAUTOCONF --opscli yes
```

where:

- <oms\_ip> is the IP or hostname of your oms server.
- 7878 is the default oms port

##### # update repro

```
zypper update
```

##### # install docker engine package

```
zypper in docker
```

##### # Start the Docker daemon.

```
systemctl start docker
```

##### # start the docker daemon at boot

```
systemctl enable docker
```

## # Create new docker user

The docker package creates a new group named docker. Users, other than root user, must be part of this group to interact with the Docker daemon. You can add users with this command syntax:

```
sudo /usr/sbin/usermod -a -G docker <linux_user>
```

```
sudo /usr/sbin/usermod -a -G docker ubroker
```

## # enable external network access

OpenSuse: Network Devices -> Network Settings -> Routing menu (f) and check the Enable IPv4 Forwarding box.


## # Test the Docker installation.

Type in a command shell:

```
docker run ubuntu /bin/echo 'Hello world'
```

## 2. Import each docker-cli Universal Task including the Universal Template to your Controller

Go to “All Tasks” and load via the Import functionality the Universal Task configuration into the Controller.



## 5 Universal Task Configuration

### 1. Activate: Resolvable Credentials in Universal Automation Center:

Dashboards	RUN SAPBO REPORT Tasks	Properties
93 Properties		
Name	Value	
Resolvable Credentials Permitted	true	

### 2. Fill Out the Universal Task for each docker cli command, which you want to execute:

In the example below the Task to pull a docker image “*ut-docker-cli-pull-linux*” is shown.

The screenshot shows the 'docker pull images - docker cli Task Details' window. The 'General' tab is active, displaying the task name 'docker pull private registry - docker cli' and version '14'. The task description is 'Pull an image or a repository from a registry'. Below this, there are fields for 'Member of Business Services', 'Resolve Name Immediately', 'Hold on Start', 'Virtual Resource Priority' (set to 10), and 'Hold Resources on Failure'. The 'Further Info's' field contains the URL 'https://docs.docker.com/engine/reference/commandline/pull/'. The 'System' field is empty.

The 'docker pull images - docker cli Details' section shows the following configuration:

- Agent: docker LX AGNT
- Agent Cluster: (empty)
- Agent Variable: (empty)
- Agent Cluster Variable: (empty)
- Credentials: (empty)
- Credentials Variable: (empty)
- Cluster Broadcast: (empty)
- registry\_credentials: docker\_hub\_001
- image\_name: nilsbuer/sb
- img\_version: (empty)
- versionselect: latest\_version
- debug: Yes
- registry: private docker hub

**Fill out or select the required Credentials e.g. for docker private registry.**

In the example below the *docker registry* credentials are shown:

The screenshot shows the 'Credential Details: docker\_hub\_001' window. The 'Credential' tab is active, displaying the name 'docker\_hub\_001' and version '6'. The credential type is 'Resolvable'. The runtime user is 'nilsbuer'. The runtime password is masked with dots. The description is 'Credentials for the private docker hub'.

## 6 Universal Tasks for Docker Container

### 6.1 Push an Image

N#	CMD	Docker CLI	UT-Name
7	Push an image or a repository to a registry	push	ut-docker-cli-push-linux

#### Task Screenshot:

The screenshot shows a configuration window for a Docker CLI task. The 'General' tab is active, displaying fields for 'Task Name' (docker push to private registry - docker cli), 'Task Description' (Push an image or a repository to a registry), 'Member of Business', 'Services', 'Resolve Name Immediately', 'Hold on Start', 'Virtual Resource Priority' (10), 'Further Info's' (https://docs.docker.com/engine/reference/commandline/push/), and 'System'. Below this, the 'docker push image - docker cli Details' section is visible, containing fields for 'Agent' (Agent Variable: true), 'Credentials', 'disable-content-trust' (true), 'registry\_cred' (docker\_hub\_001), 'registry' (private), 'Agent Cluster', 'Agent Cluster Variable', 'Cluster Broadcast', 'registry-host' (docker.io), 'image\_tag' (stonebranch/alpine\_test:3.1), and 'debug' (no).

Figure 1: Universal Task to Push an Image or a repository to a registry

#### Field Description:

Field	Required	Description
Agent	Mandatory	The Linux Universal Agent, which runs on the server, where the docker cli is installed.
Credentials	Optional	The Credentials used on the Linux Server.
Debug	Mandatory	Enable debugging mode (default is No)
Registry_cred	Optional	Credentials to connect to the <i>private</i> docker registry (registry-host is docker.io)

Field	Required	Description
Registry-host	Optional	Hostname and optional port of the registry e.g. docker.io for the private registry e.g. <i>registry-host:5000</i>
Disable-content-trust	Mandatory	Enable/disables Content Trust. Default is disabled
Image_tag	Mandatory	tag the image with the repository and image name

## 7 Test Cases

The following basic test cases has been performed:

Case	Assumed behavior	Result
Push an image or a repository to a registry <ul style="list-style-type: none"><li>Registry: docker private hub</li><li>Image_tag: stonebranch/alpine_test:3.1</li><li>Registry_host: docker.io</li></ul>	Pushes the stonebranch/alpine_test:3.1 to the private docker hub	correct

## 8 Document References

There are no document references.