

Universal Task Documentation

Universal Automation Center support for scheduling docker container

ut-docker-cli-start-linux

Associated Activities:

Date: 16 August 2018

Author: Nils Buer

Revision: 01

CONFIDENTIALITY INFORMATION

Distribution list: Stonebranch Marketplace

Revision	Date	Author	Changes
00	20180814	Nils Buer	Initial Document (WIP)
01	20180814	KM	Update for first 5 Tasks

Abstract:

The here described Universal Tasks allows operate your docker container and schedule docker container-based applications as part of any existing or new scheduling workflow.

Contents

1	Disclaimer	3
2	Scope	3
3	Introduction.....	3
4	Installation.....	4
4.1	<i>Software Requirements</i>	<i>4</i>
4.2	<i>Installation Steps</i>	<i>4</i>
5	Universal Task Configuration	6
6	Universal Tasks for Docker Container	7
6.1	<i>Start container.....</i>	<i>7</i>
7	Test Cases	8
8	Document References.....	8

1 Disclaimer

No support and no warranty are provided by Stonebranch GmbH for this document and the related Universal Task. The use of this document and the related Universal Task is on your own risk.

Before using this task in a production system, please perform extensive testing.

Stonebranch GmbH assumes no liability for damage caused by the performance of the Universal Tasks

2 Scope

This document provides a documentation how to install and use the Universal Tasks for docker container. If more Task will be created in the future this document will be updated accordingly.

3 Introduction

Universal Automation Center seamlessly integrates your legacy system into your container-based DevOps process without the need to re-design your business process logic, resulting in a shorter time-to-market, improved customer satisfaction, better product quality, more reliable releases, improved productivity and efficiency. As a result, you can make use of all the benefits provided by containers like **portability** from applications, **simplified integration**, **optimized development**, **increased scalability** and **performance**, while at the same time minimizing the risk while introducing a new technology.

Security is an important topic, when working with Containers. Containers are more or less isolated from the host OS system, but they use the same kernel. Due to potential security risks a Container should be executed in most cases using a non-privileged user account. In some cases, it might however be needed to use some kernel functionalities e.g. when mounting e.g. a USB drive. Universal Automation Center allows to centrally maintain individual credentials for each container and provides to start a container using the `--privileged` flag where needed.

Central Management of all user and groups with support for SAML, SSL LDAP/AD for legacy and containerized applications

Central Management of all Application Credentials and Connections e.g. SAP and Database connections, script credentials ...

Central Management of all credentials used to connect to a registry

Our security concept is constantly validated by external BSI certified security companies

Some details about the universal tasks for docker container:

- The here described Universal Tasks are calling the native docker cli. Universal Tasks based on the docker python SDK will be described in a separate document.
- Currently the most important docker cli commands have been implemented. Any missing command can be provided on request or created by the user itself based on an existing task.
- The current Universal Task require a Linux Agent for running the Universal Tasks scripts
- The docker private- and public registry are support. Other registries can be added with minimal efforts.
- Credentials can be provided for each task individually e.g. docker login, user executing the container, you can pass credentials for applications running in the container, ..
- You can select different log-levels e.g. debug

Note:

For details on each docker cli command refer to the docker documentation:

<https://docs.docker.com/engine/reference/commandline/docker/>

4 Installation

4.1 Software Requirements

Universal Task name: *ut-docker-cli-start-linux*

Related UAC XML Files for template and task: *Github repository*

Software used:

For the set-up you need:

1. Universal Controller 6.4.5.x (any platform: Linux, Windows or SaaS Cloud)
2. Universal Agent 6.4.2.2 or higher installed on a Linux Server
3. Docker engine with version 17.09.1-c or higher installed on a Linux server

4.2 Installation Steps

The following describes the installation steps:

1. Install the docker engine and a Universal Agent on a Linux Server e.g. Open SUSE

The following provides a sample set-up for Open SUSE. For other Linux distribution the set-up is similar (check with google). The set-up is provided here to have some guidance on the general step. The steps may vary depending on your landscape.

Install Agent on docker engine

```
sh ./unvinst --network_provider oms --oms_servers 7878@<oms_ip> --oms_port 7878 --  
oms_autostart no --ac_netname OPSAUTOCONF --opscli yes
```

where:

- <oms_ip> is the IP or hostname of your oms server.
- 7878 is the default oms port

update repro

```
zypper update
```

install docker engine package

```
zypper in docker
```

Start the Docker daemon.

```
systemctl start docker
```

start the docker daemon at boot

```
systemctl enable docker
```

Create new docker user

The docker package creates a new group named docker. Users, other than root user, must be part of this group to interact with the Docker daemon. You can add users with this command syntax:

```
sudo /usr/sbin/usermod -a -G docker <linux_user>
```

```
sudo /usr/sbin/usermod -a -G docker ubroker
```

enable external network access

OpenSuse: Network Devices -> Network Settings -> Routing menu (f) and check the Enable IPv4 Forwarding box.


Test the Docker installation.

Type in a command shell:

```
docker run ubuntu /bin/echo 'Hello world'
```

2. Import each docker-cli Universal Task including the Universal Template to your Controller

Go to “All Tasks” and load via the Import functionality the Universal Task configuration into the Controller.



5 Universal Task Configuration

1. Activate: Resolvable Credentials in Universal Automation Center:

Dashboards	RUN SAPBO REPORT Tasks	Properties
93 Properties		
Name	Value	
Resolvable Credentials Permitted	true	

2. Fill Out the Universal Task for each docker cli command, which you want to execute:

In the example below the Task to pull a docker image “*ut-docker-cli-pull-linux*” is shown.

The screenshot shows the 'docker pull images - docker cli Task Details' window. The 'General' tab is active, displaying the following configuration:

- Task Name:** docker pull private registry - docker cli
- Version:** 14
- Task Description:** Pull an image or a repository from a registry
- Member of Business Services:** (empty dropdown)
- Resolve Name Immediately:** ☐
- Hold on Start:** ☐
- Virtual Resource Priority:** 10
- Hold Resources on Failure:** ☐
- Further Info's:** <https://docs.docker.com/engine/reference/commandline/pull/>
- System:** (empty dropdown)

The 'docker pull images - docker cli Details' tab is also visible, showing the following configuration:

- Agent:** docker LX AGNT
- Agent Variable:** ☐
- Credentials:** (empty dropdown)
- Credentials Variable:** ☐
- registry_credentials:** docker_hub_001
- img_version:** (empty dropdown)
- debug:** Yes
- Agent Cluster:** (empty dropdown)
- Agent Cluster Variable:** ☐
- Cluster Broadcast:** (empty dropdown)
- image_name:** nilsbuer/sb
- versionselect:** latest_version
- registry:** private docker hub

Fill out or select the required Credentials e.g. for docker private registry.

In the example below the *docker registry* credentials are shown:

The screenshot shows the 'Credential Details: docker_hub_001' window. The 'Credential' tab is active, displaying the following configuration:

- Name:** docker_hub_001
- Version:** 6
- Type:** Resolvable
- Runtime User:** nilsbuer
- Runtime Password:** (masked with dots)
- Description:** Credentials for the private docker hub

6 Universal Tasks for Docker Container

6.1 Start container

N#	CMD	Docker CLI	UT-Name
4	Start one or more stopped containers	start	ut-docker-cli-start-linux

Task Screenshot:

Figure 1: Universal Task to Start one or more stopped containers

Field Description:

Field	Required	Description
Agent	Mandatory	The Linux Universal Agent, which runs on the server, where the docker cli is installed.
Credentials	Optional	The Credentials used on the Linux Server.
Debug	Mandatory	Enable debugging mode (default is No)
Container	Mandatory	Name of the container
Attach	Optional	Attach STDOUT/STDERR and forward signals
Detachkeys	Optional	Override the key sequence for detaching a container
Interactive	Optional	Attach container's STDIN

7 Test Cases

The following basic test cases has been performed:

Case	Assumed behavior	Result
Start one or more stopped containers <ul style="list-style-type: none">• Container: test• Attach: false• Detachkeys: false	Starts the container test	Correct (when attach: true is selected the task stays running)

8 Document References

There are no document references.