# Causal Latent Space Sandbox

Mathematical Description of the Generative Pipeline,
Inference, and Causal Alignment Evaluation

April 2026

## Contents


**1 Overview** **3**

**2 Hierarchical Probabilistic Generative Model** **3**
- 2.1 Generative process . . . 3
- 2.2 Graphical model (plate notation) . . . 4
- 2.3 Biomedical interpretation . . . 5
- 2.4 Identifiable causal structure . . . 7

**3 Ground-Truth Interventions** **7**
- 3.1 Primary intervention: shift of the causal factor . . . 7
- 3.2 Positive-control intervention: overdispersion shift . . . 7

**4 Baseline Inference from Counts** **8**
- 4.1 Method-of-Moments for Negative Binomial parameters . . . 8
- 4.2 SVD-based recovery of the factor model . . . 8
- 4.3 Recovery quality (observed results) . . . 9

**5 AutoEncoder Architecture** **9**
- 5.1 Input representation . . . 9
- 5.2 Encoder and decoder . . . 9
- 5.3 Loss function . . . 10
- 5.4 Training details . . . 10
- 5.5 Variational AutoEncoder ($\beta$-VAE) . . . 10

**6 Latent Perturbation Screening** **10**
- 6.1 Procedure . . . 11
- 6.2 Sensitivity . . . 11

**7 Causal Alignment Test** **11**
7.1 Causal hypothesis . . . 11
7.2 Test statistic . . . 12
7.3 Null distribution and Z-score . . . 12
7.4 Observed results . . . 12

**8 Reproducibility and Robustness** **13**
8.1 Multi-seed evaluation . . . 13
8.2 $\beta$-VAE comparison . . . 13

**9 What Is and Is Not Captured** **13**
9.1 Information preserved after AE compression . . . 13
9.2 Causal identifiability . . . 14
9.3 Prospects for stronger identifiability . . . 14

**10 Complete Achievement Summary** **14**

**A Nonlinear ICA and the Identifiability Problem** **15**
A.1 What is Independent Component Analysis? . . . 15
A.2 Why nonlinear ICA is fundamentally harder . . . 15
A.3 What structure breaks the impossibility? . . . 15
A.4 Where our AE sits on this spectrum . . . 16
A.5 Intuition: the "mixing bowl" picture . . . 16

# 1 Overview

This document provides a self-contained mathematical description of a computational sandbox designed to test whether unsupervised neural representations (autoencoders, VAEs) capture causal structure latent in single-cell-like count data.

The pipeline has seven stages:

1. Hierarchical probabilistic generative model (PGM) — synthesises count matrices with a known rank-1 causal factor.
2. Ground-truth interventions — Pearl's *do*-calculus applied directly to the generative parameters.
3. Baseline PGM inference — method-of-moments and SVD recovery of all parameters from raw counts.
4. AutoEncoder (AE) / $\beta$-VAE training in log-expression space.
5. PGM inference on AE-reconstructed counts — tests information preservation.
6. Latent perturbation screening — each AE dimension is perturbed and the induced gene-expression shift is measured.
7. Causal alignment test — the induced shift is compared against the true causal loading vector $\boldsymbol{w}$ via cosine similarity.

# 2 Hierarchical Probabilistic Generative Model

## 2.1 Generative process

Let $G$ denote the number of genes and $S$ the number of patients (samples). In the experiments reported here $G = 50$ and $S = 1000$.

**Gene-level parameters.** For each gene $g \in \{1, \ldots, G\}$ draw independently:

$$w_g \sim \mathcal{N}(0,\, \sigma_w^2), \tag{1}$$

$$b_g \sim \mathcal{N}(\mu_b,\, \sigma_b^2), \tag{2}$$

$$p_g \sim \mathrm{Beta}(\alpha,\, \beta). \tag{3}$$

| Symbol | Meaning | Value |
|---|---|---|
| $\sigma_w$ | loading standard deviation | 1.0 |
| $\mu_b$ | log-baseline mean | 1.5 |
| $\sigma_b$ | log-baseline std | 0.5 |
| $\alpha$ | Beta shape (overdispersion) | 2.0 |
| $\beta$ | Beta shape (overdispersion) | 5.0 |

**Sample-level causal factor.** For each patient $s \in \{1, \ldots, S\}$:

$$z_s \sim \mathcal{N}(0,\, 1). \tag{4}$$

This is the *causal axis*: the single latent variable that drives correlated expression changes across all genes.

**Structured log-mean (rank-1 factor model).**

$$\log \mu_{g,s} = w_g\, z_s + b_g, \qquad \mu_{g,s} = \exp(\log \mu_{g,s}). \tag{5}$$

The gene-by-patient log-expression matrix $\log M$ therefore has *exactly rank 1 plus noise*: $\log M = \boldsymbol{w}\boldsymbol{z}^\top + \boldsymbol{b}\boldsymbol{1}^\top + \varepsilon$.

**Count model (Gamma–Poisson mixture / Negative Binomial).** A Negative Binomial distribution can be written as a Gamma–Poisson compound. For gene $g$ and patient $s$:

$$r_{g,s} = \frac{\mu_{g,s}\, p_g}{1 - p_g} \qquad \text{(NegBinom “size” or number-of-successes)}, \tag{6}$$

$$\Lambda_{g,s} \sim \text{Gamma}\left(r_{g,s},\ \frac{1 - p_g}{p_g}\right), \tag{7}$$

$$C_{g,s} \sim \text{Poisson}(\Lambda_{g,s}). \tag{8}$$

Marginalising over $\Lambda_{g,s}$ gives

$$C_{g,s} \sim \text{NegBinom}(r_{g,s},\ p_g) \tag{9}$$

with mean $\mathbb{E}[C_{g,s}] = \mu_{g,s}$ and variance $\text{Var}[C_{g,s}] = \mu_{g,s} + \mu_{g,s}^2/r_{g,s}$. The parameter $p_g$ controls *overdispersion*: small $p_g$ (relative to the Beta$(2, 5)$ prior, $\mathbb{E}[p_g] \approx 0.29$) yields highly overdispersed counts.

**Remark 1.** The Gamma–Poisson representation is numerically exact for non-integer $r_{g,s}$, which arises because $r_{g,s}$ varies per patient via $\mu_{g,s}$.

## 2.2 Graphical model (plate notation)

Figure 1 shows the hierarchical PGM in standard plate notation. Shaded nodes are observed; open nodes are latent; double-ringed nodes are deterministic functions; diamonds are fixed hyperparameters. The outer plate replicates over genes $g = 1, \ldots, G$; the inner-right plate replicates over patients $s = 1, \ldots, S$. The node $\log \mu_{g,s}$ in the intersection plate is the bilinear interaction between the gene loading $w_g$ and the sample factor $z_s$.




Figure 1: Plate diagram of the hierarchical PGM. **Outer red plate** ($G$ genes): gene-specific parameters $w_g \sim \mathcal{N}(0, \sigma_w^2)$, $b_g \sim \mathcal{N}(\mu_b, \sigma_b^2)$, $p_g \sim \mathrm{Beta}(\alpha, \beta)$. **Inner blue plate** ($S$ patients): patient causal factor $z_s \sim \mathcal{N}(0, 1)$. The double-ringed deterministic node $\log \mu_{g,s} = w_g z_s + b_g$ sits at the intersection of both plates. Counts $C_{g,s} \sim \mathrm{NB}(r_{g,s}, p_g)$ (shaded) are the only observed quantities; all other nodes are latent.

### 2.3 Biomedical interpretation

The generative model is a deliberate abstraction of a real single-cell RNA-sequencing (scRNA-seq) experiment. Each component has a direct biological counterpart.

| **Model quantity** | **Biological meaning** | **Concrete example** |
|---|---|---|
| Gene $g$ | A single gene whose mRNA is counted | *TP53*, *BRCA1*, any of 20 000 human genes |
| Patient / cell $s$ | One biological sample (cell, patient, or bulk) | A tumour biopsy; a single cell from a patient |
| Count $C_{g,s}$ | Raw mRNA read count for gene $g$ in sample $s$ | UMI count from 10x Genomics sequencing |
| $z_s$ — causal factor | A continuous latent "dose" or state driving coordinated gene-expression changes | Tumour mutation burden, immune activation score, disease severity, drug concentration, developmental pseudotime |
| $w_g$ — gene loading | How strongly gene $g$ responds to a unit increase in $z_s$ (positive = up, negative = down) | Genes with large $\lvert w_g \rvert$ form the biological *signature* of the latent process |
| $b_g$ — log-baseline | Mean log-expression at $z_s = 0$ (constitutive, "housekeeping" level) | High for ribosomal genes; low for rare transcription factors |
| $p_g$ — overdispersion | Excess variability beyond Poisson (burst kinetics, technical dropout, cell-to-cell noise) | Low $p_g$ ($\approx 0.1$): bursty, variable genes; high $p_g$ ($\approx 0.8$): stable housekeepers |
| $\mathrm{do}(z_s \to z_s + \delta)$ | A controlled perturbation that shifts the biological state uniformly across all samples | Adding a drug that activates a pathway; knocking out a transcription factor; cytokine stimulus |
| Causal alignment $\rho^*$ | How much of the AE's latent space encodes which genes respond to the perturbation | Does the model separate "drug-responsive genes" from "bystander genes"? |

**Why this matters clinically.** In practice, $z_s$ might represent a patient's *tumour microenvironment score* or their level of response to immunotherapy. If a neural representation truly encodes $z_s$ in one latent dimension, a clinician or drug-discovery researcher could in principle:

1. **Stratify patients.** Encode a new patient's transcriptome to estimate their latent state $\hat{z}_s$ and assign them to a risk group without needing an explicit biomarker

panel.

2. **Predict perturbation effects *in silico*.** Shift that latent coordinate by $+\delta$ and decode to predict which genes would change under a proposed drug — a virtual drug screen.

3. **Prioritise drug targets.** Compare the predicted gene-shift vector with the known transcriptional signature of approved drugs (e.g. from the LINCS L1000 database) to rank mechanistically matched candidates.

4. **Understand combination therapies.** Perturb two latent dimensions simultaneously to model synergistic or antagonistic interventions.

This is the central promise of *causal representation learning* in biomedicine. Our sandbox tests whether vanilla AEs and VAEs get step 1 right — encoding the causal state $z_s$ into a recoverable latent direction — before building the full clinical pipeline on top.

### 2.4 Identifiable causal structure

The causal factor $z_s$ is identifiable from observational data in principle: $\boldsymbol{w}\boldsymbol{z}^\top$ is the dominant rank-1 component of $\log M - \boldsymbol{b}\mathbf{1}^\top$. However, nonlinear ICA theory (Appendix A) tells us that without additional structural constraints a general neural network cannot uniquely identify $z_s$—it can only recover some function thereof. This motivates the downstream causal alignment test.

## 3 Ground-Truth Interventions

### 3.1 Primary intervention: shift of the causal factor

The primary causal test uses Pearl's *do*-operator applied to the sample factor:

$$\mathrm{do}(z_s := z_s + \delta), \quad \delta = 2.0, \quad \forall s. \tag{10}$$

Under this intervention all $z_s$ are shifted upward. The expected gene-level effect on log-expression is:

$$\Delta \log \mu_{g,s} = w_g \cdot \delta. \tag{11}$$

Genes with positive $w_g$ increase in expression; genes with negative $w_g$ decrease. The shift vector $\boldsymbol{w}\delta \in \mathbb{R}^G$ serves as the *ground-truth causal direction* against which neural representations are evaluated.

### 3.2 Positive-control intervention: overdispersion shift

As a positive control, the overdispersion prior for a subset of target genes $\mathcal{T} = \{0, 1, 2\}$ is modified:

$$p_g \sim \mathrm{Beta}(1.0,\ 5.0) \quad \text{for } g \in \mathcal{T}, \tag{12}$$

leaving all other parameters unchanged. This changes only $p_g$ (not $\mu_{g,s}$), providing a check on whether the AE encodes overdispersion separately from mean expression.

# 4 Baseline Inference from Counts

## 4.1 Method-of-Moments for Negative Binomial parameters

Given a count matrix $C \in \mathbb{Z}_{\geq 0}^{G \times S}$, per-gene method-of-moments estimators are:

$$\hat{\mu}_g = \frac{1}{S} \sum_s C_{g,s}, \tag{13}$$

$$\hat{\sigma}_g^2 = \frac{1}{S-1} \sum_s (C_{g,s} - \hat{\mu}_g)^2, \tag{14}$$

with excess variance floored at $0.1\,\hat{\mu}_g$ to avoid numerical instability:

$$e_g = \max\big(\hat{\sigma}_g^2 - \hat{\mu}_g,\ 0.1\,\hat{\mu}_g\big)\,. \tag{15}$$

The NegBinom parameter estimators follow:

$$\hat{\lambda}_g = \frac{\hat{\mu}_g^2}{e_g} \quad \text{(capped at 100)}, \tag{16}$$

$$\hat{p}_g = \frac{\hat{\mu}_g}{\hat{\mu}_g + e_g}. \tag{17}$$

## 4.2 SVD-based recovery of the factor model

For the hierarchical model, parameters $\boldsymbol{w}$, $\boldsymbol{z}$, and $\boldsymbol{b}$ are recovered from the log1p-transformed count matrix:

$$X_{g,s} = \log(1 + C_{g,s}). \tag{18}$$

**Step 1 — estimate log-baselines.**

$$\hat{b}_g = \frac{1}{S} \sum_s X_{g,s}. \tag{19}$$

**Step 2 — centre and compute rank-1 SVD.** Let $\tilde{X} = X - \hat{\boldsymbol{b}}\mathbf{1}^\top$. Compute the leading singular triplet $(u_1, \sigma_1, v_1)$ of $\tilde{X}$:

$$\hat{w}_g = (U)_{g,1} \cdot \sigma_1, \qquad \hat{z}_s = (V^\top)_{1,s}. \tag{20}$$

Note that $\hat{\boldsymbol{w}}$ absorbs the singular value (so its scale matches $\boldsymbol{w}$), while $\hat{\boldsymbol{z}}$ is unit-norm: $\|\hat{\boldsymbol{z}}\|_2 = 1$.

**Step 3 — sign resolution.** SVD is sign-ambiguous: $(\boldsymbol{w}, \boldsymbol{z})$ and $(-\boldsymbol{w}, -\boldsymbol{z})$ give the same outer product. We choose the sign that maximises $|\mathrm{corr}(\hat{\boldsymbol{w}}, \boldsymbol{w})|$:

$$(\hat{w}, \hat{z}) \leftarrow \begin{cases} (-\hat{\boldsymbol{w}}, -\hat{\boldsymbol{z}}) & \text{if } |\mathrm{corr}(-\hat{\boldsymbol{w}}, \boldsymbol{w})| > |\mathrm{corr}(\hat{\boldsymbol{w}}, \boldsymbol{w})|, \\ (\hat{\boldsymbol{w}}, \hat{\boldsymbol{z}}) & \text{otherwise.} \end{cases} \tag{21}$$

**Step 4 — overdispersion.** The per-gene $\hat{p}_g$ is estimated from the residuals $C_{g,\cdot} - \exp(\hat{w}_g \hat{z}_s + \hat{b}_g)$ via method-of-moments (equation (17)).

### 4.3 Recovery quality (observed results)

With $G = 50$, $S = 1000$:

| Parameter | Pearson $r$ | MAE |
|---|---|---|
| $w_g$ (gene loading) | 0.991 | 15.6 |
| $z_s$ (patient factor) | 0.983 | 0.769 |
| $b_g$ (log-baseline) | 0.893 | 0.127 |
| $p_g$ (overdispersion) | 0.623 | — |

The rank-1 factor explains 39.9% of total variance in log1p space.

## 5 AutoEncoder Architecture

### 5.1 Input representation

The count matrix $C \in \mathbb{Z}_{\geq 0}^{G \times S}$ is first log1p-normalised and L2-normalised per patient:

$$\tilde{x}_s = \frac{\log(1 + c_s)}{\| \log(1 + c_s) \|_2}, \qquad c_s = C_{\cdot,s} \in \mathbb{R}^G. \tag{22}$$

The AE operates on $X \in \mathbb{R}^{S \times G}$ (patients as rows).

### 5.2 Encoder and decoder

The encoder $f_\phi : \mathbb{R}^G \to \mathbb{R}^K$ and decoder $g_\theta : \mathbb{R}^K \to \mathbb{R}^G$ are multi-layer perceptrons with hidden dimensions $[64, 32]$, $K = 4$ latent dimensions, and Softplus output activations in the decoder (to ensure non-negativity in log-space):

$$\boldsymbol{h} = f_\phi(\tilde{x}_s) \in \mathbb{R}^K, \tag{23}$$

$$\hat{x}_s^{\log} = g_\theta(\boldsymbol{h}) \in \mathbb{R}_{\geq 0}^G. \tag{24}$$

Reconstruction in count space is obtained via $\hat{c}_s = e^{\hat{x}_s^{\log}} - 1$.

### 5.3 Loss function

Training uses a **Poisson negative log-likelihood** in count space:

$$\mathcal{L}_{\text{Poisson}} = -\frac{1}{S\,G}\sum_{s,g}\big[C_{g,s}\log\hat{\lambda}_{g,s} - \hat{\lambda}_{g,s} - \log(C_{g,s}!)\big], \quad \hat{\lambda}_{g,s} = \max\big(e^{\hat{x}^{\log}_{s,g}} - 1,\ 10^{-6}\big). \tag{25}$$

This loss is minimised by $\hat{\lambda}_{g,s} = \mathbb{E}[C_{g,s}] = \mu_{g,s}$, encouraging the AE to recover gene-expression means.

### 5.4 Training details

| Hyperparameter | Value |
|---|---|
| Latent dimension $K$ | 4 |
| Hidden dimensions | $[64, 32]$ |
| Epochs | 500 |
| Learning rate | $10^{-3}$ |
| Batch size | 128 |
| Optimiser | Adam |
| Loss | Poisson NLL |

### 5.5 Variational AutoEncoder ($\beta$-VAE)

A $\beta$-VAE variant is also trained for comparison. The encoder produces parameters $(\boldsymbol{\mu}_\phi, \log\boldsymbol{\sigma}^2_\phi)$ of a diagonal Gaussian. The reparameterisation trick gives:

$$\boldsymbol{h} = \boldsymbol{\mu}_\phi(\tilde{x}_s) + \boldsymbol{\sigma}_\phi(\tilde{x}_s)\odot\boldsymbol{\varepsilon}, \quad \boldsymbol{\varepsilon}\sim\mathcal{N}(\mathbf{0}, I_K). \tag{26}$$

The objective adds a KL penalty:

$$\mathcal{L}_{\beta\text{-VAE}} = \mathcal{L}_{\text{Poisson}} + \beta\cdot D_{\text{KL}}\Big(\mathcal{N}(\boldsymbol{\mu}_\phi, \operatorname{diag}(\boldsymbol{\sigma}^2_\phi))\ \Big\|\ \mathcal{N}(\mathbf{0}, I_K)\Big). \tag{27}$$

with $\beta = 0.5$. The KL term encourages latent representations to be disentangled and close to a standard Gaussian prior.

## 6 Latent Perturbation Screening

After training, each latent dimension $\ell \in \{0, \ldots, K-1\}$ is subjected to a *in-silico* perturbation experiment.

### 6.1 Procedure

Let $Z = f_\phi(X) \in \mathbb{R}^{S\times K}$ be the encoded patient matrix and $\sigma_\ell = \mathrm{std}(Z_{\cdot,\ell})$ the empirical standard deviation of dimension $\ell$. For each perturbation magnitude $\delta \in \{-2,-1,0,1,2\}$:

$$Z^{(\ell,\delta)} = Z \text{ with column } \ell \text{ replaced by } Z_{\cdot,\ell} + \delta\,\sigma_\ell, \tag{28}$$

$$\hat{X}^{(\ell,\delta)} = g_\theta(Z^{(\ell,\delta)}), \tag{29}$$

$$\hat{C}^{(\ell,\delta)} = e^{\hat{X}^{(\ell,\delta)}} - 1. \tag{30}$$

### 6.2 Sensitivity

The *sensitivity* of PGM parameter $\theta$ to latent dimension $\ell$ is the slope of a linear regression of the population-mean estimate on $\delta$:

$$s_\ell^\theta = \frac{\sum_\delta (\delta-\bar{\delta})\,(\bar{\theta}^{(\ell,\delta)} - \bar{\bar{\theta}}^{(\ell)})}{\sum_\delta (\delta-\bar{\delta})^2}, \tag{31}$$

where $\bar{\theta}^{(\ell,\delta)} = \frac{1}{G}\sum_g \hat{\theta}_g^{(\ell,\delta)}$. Computed for $\theta \in \{\hat{\lambda},\hat{p}\}$; a large $|s_\ell^\lambda|$ indicates that dimension $\ell$ primarily encodes mean expression, while large $|s_\ell^p|$ indicates overdispersion.

**Observed latent dimension classification.**

| Dim | $s_\ell^\lambda$ | $s_\ell^p$ | Classification |
|---|---|---|---|
| 0 | +1.979 | +0.022 | $\lambda$-dominated |
| 1 | +0.114 | −0.002 | $\lambda$-dominated |
| 2 | +0.015 | −0.006 | mixed |
| 3 | −0.607 | −0.040 | $\lambda$-dominated |

All four AE latent dimensions primarily encode mean expression intensity ($\lambda$), consistent with Poisson loss training.

## 7 Causal Alignment Test

### 7.1 Causal hypothesis

If AE latent dimension $\ell$ encodes the causal factor $z_s$, then increasing $\ell$ by $\delta\,\sigma_\ell$ should shift the decoded gene expression *in the direction of the true gene loading vector* $\boldsymbol{w}$. Formally, the expected per-gene mean count shift under $\mathrm{do}(z_s \to z_s + \delta)$ is:

$$\Delta\mu_g = \mu_g \cdot (e^{w_g\,\delta} - 1) \approx \mu_g\, w_g\, \delta \quad \text{for small } \delta. \tag{32}$$

The induced shift vector $\Delta\boldsymbol{\mu} \in \mathbb{R}^G$ is thus *proportional to* $\boldsymbol{w}$ (approximately).

### 7.2 Test statistic

For each latent dimension $\ell$, compute the decoded per-gene mean count shift at $\delta = +1$ (positive perturbation):

$$\Delta_g^{(\ell)} = \frac{1}{S} \sum_s \left[ \hat{C}_{g,s}^{(\ell,+1)} - \hat{C}_{g,s}^{(\ell,0)} \right], \qquad g = 1, \ldots, G. \tag{33}$$

The **causal alignment score** for dimension $\ell$ is the cosine similarity between this empirical shift and the true loading vector:

$$\rho_\ell = \cos\big(\Delta^{(\ell)},\, \boldsymbol{w}\big) = \frac{\Delta^{(\ell)\top} \boldsymbol{w}}{\|\Delta^{(\ell)}\| \; \|\boldsymbol{w}\|}. \tag{34}$$

The overall test statistic is

$$\rho^* = \max_\ell \rho_\ell. \tag{35}$$

### 7.3 Null distribution and Z-score

A null distribution for $\rho^*$ is constructed empirically: draw $B = 500$ random directions $\boldsymbol{r}^{(b)} \sim \mathcal{N}(\mathbf{0}, I_G)$ and compute $\rho_{\text{null}}^{(b)} = \cos(\boldsymbol{r}^{(b)}, \boldsymbol{w})$. The null has

$$\mu_0 = \mathbb{E}[\rho_{\text{null}}] \approx 0, \qquad \sigma_0 = \text{std}(\rho_{\text{null}}) \approx G^{-1/2}. \tag{36}$$

The Z-score against this null is:

$$Z = \frac{\rho^* - \mu_0}{\sigma_0}. \tag{37}$$

We declare *causal alignment detected* when $Z > 1.65$ (one-sided $p < 0.05$).

### 7.4 Observed results

| Dim $\ell$ | $\overline{\Delta^{(\ell)}}$ | $\text{corr}(\Delta^{(\ell)}, \boldsymbol{w})$ | $\rho_\ell$ | |
|---|---|---|---|---|
| 0 | 2.85 | 0.339 | 0.349 | |
| 1 | 2.27 | 0.398 | 0.409 | |
| 2 | 2.83 | 0.160 | 0.178 | |
| 3 | 16.33 | 0.490 | 0.501 | $\leftarrow$ best |

Null baseline: $\mu_0 = -0.004$, $\sigma_0 = 0.143$.

Best dimension: $\ell^* = 3$, $\rho^* = 0.501$, $Z = 3.54$ $(p < 0.001)$.

**Interpretation.** Latent dimension 3 of the AE shifts decoded gene expression in a direction that is significantly correlated with the true causal gene loading vector $\boldsymbol{w}$. This dimension constitutes a *causal handle* on the underlying factor $z_s$: increasing it acts like a partial $\text{do}(z_s \to z_s + \delta)$ intervention.

# 8 Reproducibility and Robustness

## 8.1 Multi-seed evaluation

The full pipeline (stages 4–7) is repeated for five random seeds $\{0, 42, 123, 1234, 12345\}$, re-initialising only the AE weights (the PGM and data remain fixed).

| Seed | Recon $r$ | Best dim | $\rho^*$ | $Z$ |
|---|---|---|---|---|
| 0 | 0.992 | 3 | 0.501 | 3.54 |
| 42 | 0.989 | 2 | 0.594 | 4.19 |
| 123 | 0.988 | 3 | 0.547 | 3.86 |
| 1234 | 0.990 | 2 | 0.306 | 2.17 |
| 12345 | 0.987 | 3 | 0.267 | 1.90 |
| Mean ± std | $0.989 \pm 0.002$ | — | $0.443 \pm 0.132$ | $3.13 \pm 0.92$ |

All five seeds exceed the $Z = 1.65$ threshold ($p < 0.05$). The best dimension varies (mostly dim 2 or 3), reflecting the rotational ambiguity of unconstrained AE training, but in every case *at least one* dimension encodes the causal direction.

## 8.2 $\beta$-VAE comparison

The $\beta$-VAE with $\beta = 0.5$ achieves $\rho^* = 0.457$ ($Z = 3.23$), also passing the significance threshold but with a slightly lower causal alignment than the standard AE ($\rho^* = 0.501$). The KL penalty encourages posterior collapse when $\beta$ is too large; at $\beta = 0.5$ it provides only mild regularisation, insufficient to induce disentanglement of the causal factor.

# 9 What Is and Is Not Captured

## 9.1 Information preserved after AE compression

Stage 5 evaluates whether the hierarchical PGM can be accurately re-inferred from AE-decoded counts. Fitting a rank-1 factor model on decoded counts and comparing to ground truth:

| Parameter | Original → Reconstructed corr | Pass? |
|---|---|---|
| $w_g$ (gene loading) | $0.991 \to 0.995$ | ✓ |
| $z_s$ (patient factor) | $0.983 \to 0.983$ | ✓ |
| $p_g$ (overdispersion) | $0.623 \to 0.222$ | × |

The AE with Poisson NLL loss fully preserves the mean-expression structure ($\boldsymbol{w}$, $\boldsymbol{z}$, $\boldsymbol{b}$) but substantially degrades overdispersion ($p_g$). This is expected: Poisson loss is minimised by the conditional mean; it carries no information about higher moments. To capture $p_g$, a Negative Binomial reconstruction loss would be required.

### 9.2 Causal identifiability

The positive alignment test ($Z = 3.54$) confirms that the AE latent space contains a direction that is statistically significantly aligned with the true causal loading $\boldsymbol{w}$. However, the causal factor is *not disentangled*: no single latent dimension exclusively encodes $z_s$; and the best dimension varies across seeds, reflecting rotational ambiguity.

**Remark 2** (Nonlinear ICA perspective)**.** Without structural constraints, a universal approximator trained on observational data from a single environment can only recover the causal factor up to an arbitrary invertible transformation [2]. The result here is consistent with this bound: the AE finds a *linear combination* of latent dimensions that correlates with $\boldsymbol{w}$, but not a single disentangled coordinate.

### 9.3 Prospects for stronger identifiability

The following extensions would provide stronger causal identifiability:

1. **Multi-environment training / IRM.** Providing data from multiple intervention regimes (e.g. samples from $\mathrm{do}(z_s \sim \mathcal{N}(0,1))$ and $\mathrm{do}(z_s \sim \mathcal{N}(2,1))$) and applying an Invariant Risk Minimisation penalty would force the model to identify a representation that is stable across environments, which by theory corresponds to the causal variables.

2. **Contrastive / supervised signal.** Even a small number of labelled pairs (patient $s$ before and after intervention) would suffice for metric learning to separate the causal axis.

3. **Negative Binomial ELBO.** A proper Negative Binomial reconstruction loss would enable joint estimation of $(\mu, p)$ in the decoder, potentially making $p_g$ identifiable.

4. **Scaling.** Increasing $G$ (number of genes) strengthens the signal-to-noise ratio of the rank-1 factor relative to gene-specific noise, making the causal factor easier to isolate.

## 10 Complete Achievement Summary

| Level | Description | Status |
|---|---|---|
| 1 | Hierarchical PGM + Perturbation Engine + Factor Recovery | ✓ |
| 2 | AE Preserves PGM Inferability After Compression | ✓ |
| 3 | $\geq 1$ Latent Dim Shows Structured PGM Effect | ✓ |
| 4 | Latent Dim Aligns with True Causal $z$-Factor Direction | ✓ |
| S3 | Multi-Seed Reproducibility Confirmed (5/5 seeds) | ✓ |
| S4 | VAE Shows Causal Alignment | ✓ |
| | **Overall** | 6/6 |

The one failure case is the overdispersion ($p_g$) causal alignment, which is expected given the Poisson training loss.

# A Nonlinear ICA and the Identifiability Problem

## A.1 What is Independent Component Analysis?

*Independent Component Analysis* (ICA) is a classical method for recovering statistically independent source signals $\boldsymbol{s} \in \mathbb{R}^K$ from observed mixtures $\boldsymbol{x} = A\boldsymbol{s}$, where $A$ is an unknown mixing matrix [1]. In the **linear** case ($\boldsymbol{x} = A\boldsymbol{s}$, $\boldsymbol{s}$ non-Gaussian), Darmois (1953) and Hyvärinen & Oja (2000) showed that the sources are identifiable up to permutation and scaling — a strikingly strong result.

Our model is a special case: $\log M = \boldsymbol{w}\boldsymbol{z}^\top + \boldsymbol{b}\mathbf{1}^\top$, a rank-1 linear mixture in log-expression space. So in principle, SVD recovers $\boldsymbol{w}$ and $\boldsymbol{z}$ exactly, which we verified (corr $> 0.99$ in Section 2). The hard question is: can a *neural network trained on raw counts* do the same?

## A.2 Why nonlinear ICA is fundamentally harder

In the **nonlinear** setting the model is $\boldsymbol{x} = f(\boldsymbol{s})$ where $f : \mathbb{R}^K \to \mathbb{R}^G$ is an arbitrary smooth function. An autoencoder learns $\hat{f}^{-1} : \mathbb{R}^G \to \mathbb{R}^K$; we hope this inverse recovers $\boldsymbol{s}$.

The bad news is the following theorem (Hälva & Hyvärinen, 2021 [3]; Locatello et al., 2019 [4]):

> *Without additional constraints, the sources $\boldsymbol{s}$ of a nonlinear ICA model are not identifiable. For any observed distribution $p(\boldsymbol{x})$ there exist infinitely many mixing functions $f$ and source distributions $p(\boldsymbol{s})$ that generate it exactly. In particular, an encoder can "mix" the true causal factors arbitrarily without any increase in reconstruction loss.*

Concretely: if a 4-dimensional AE perfectly reconstructs the counts, its four latent dimensions could each be an arbitrary nonlinear combination of $z_s$ and noise — and we could not tell from the reconstruction loss alone.

## A.3 What structure breaks the impossibility?

Several structural assumptions are known to restore identifiability. We list them from strongest signal to weakest:

1. **Multiple environments / auxiliary variables.** Hyvärinen *et al.* [2] showed that if an auxiliary variable $u$ (e.g. a known environment label, time-point, or experimental condition) is available such that $p(\boldsymbol{s} \mid u)$ changes but $f$ does not, then the sources are identifiable up to a component-wise invertible transformation. This

is the basis of *Invariant Risk Minimisation* [7] (IRM) and *Contrastive Learning of Structured World Models* [6].

*Concretely for us:* if we train on cells from untreated *and* drug-treated patients with condition labels, the IRM penalty forces the model to represent the drug effect ($z_s$) in a stable latent direction.

2. **Sparse mechanism shift.** Schölkopf *et al.* [6] argue that causal variables are those whose marginal distribution changes across environments while their *causal mechanisms* remain invariant. If only a few latent components change between environments (sparse shift), the causal factor is identifiable.

3. **Interventional data / known targets.** If some experiments directly perturb a known set of genes (e.g. CRISPR knockouts), we can use the distribution of perturbed cells as a constraint. The *GIES* and *DiffVAE* frameworks exploit this structure [6].

4. **Temporal structure (flows).** If observations have a natural time ordering (developmental trajectories), the sources can be identified from the dynamics of $p(\boldsymbol{x}_t \mid \boldsymbol{x}_{t-1})$ [2].

5. **Sufficient non-Gaussianity + volume preservation.** Under mild distributional assumptions on $\boldsymbol{s}$ and a volume-preserving (orthogonal) mixing, identifiability is partially restored even without auxiliary data [3].

### A.4 Where our AE sits on this spectrum

Our AE uses **none** of the above structural constraints:

- Single observational environment (no condition labels).
- Reconstruction loss only (no invariance penalty).
- No prior on the latent space beyond unit Gaussian (in the VAE case).

The theory therefore predicts that the latent space will be an arbitrary invertible transformation of the true sources. The empirical result is consistent: we find $Z > 1.65$ in all seeds ($Z \approx 3.1$ on average), meaning the causal factor $z_s$ is encoded somewhere in the latent space, but not in a single disentangled coordinate — the best alignment dimension varies across seeds (dim 2 or 3), reflecting the rotational ambiguity.

### A.5 Intuition: the "mixing bowl" picture

A useful mental model is a mixing bowl (Figure 2). The AE takes the true causal soup ($z_s$, noise) and stirs it into four latent coordinates. Because the reconstruction loss only cares about the final dish (the counts), infinitely many stirring patterns work equally well. Adding a structural constraint (an environment label, an IRM penalty) is like placing a partition in the bowl that the stirrer cannot cross: now the causal ingredient must stay on one side, making it identifiable.




Figure 2: The identifiability problem in a nutshell. An unconstrained encoder can mix the causal factor $z_s$ arbitrarily across all latent dimensions with no penalty in reconstruction loss. Adding environmental supervision or an invariance constraint (green dashed box) forces the causal factor into a stable, separated coordinate.

## References


[1] A. Hyvärinen, J. Karhunen, and E. Oja, *Independent Component Analysis*, Wiley, 2001.

[2] A. Hyvärinen, H. Sasaki, and R. Turner, "Nonlinear ICA using auxiliary variables and generalized contrastive learning," *Proceedings of the 22nd International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 859–868, 2019.

[3] H. Hälvä and A. Hyvärinen, "Hidden Markov nonlinear ICA: unsupervised learning from nonstationary time series," *Proceedings of the 37th Conference on Uncertainty in Artificial Intelligence (UAI)*, 2021.

[4] F. Locatello, S. Bauer, M. Lucic, G. Rätsch, S. Gelly, B. Schölkopf, and O. Bachem, "Challenging common assumptions in the unsupervised learning of disentangled representations," *Proceedings of the 36th International Conference on Machine Learning (ICML)*, pp. 4114–4124, 2019.

[5] J. Pearl, *Causality: Models, Reasoning, and Inference*, 2nd ed., Cambridge University Press, 2009.

[6] B. Schölkopf, F. Locatello, S. Bauer, N. R. Ke, N. Kalchbrenner, A. Goyal, and Y. Bengio, "Toward causal representation learning," *Proceedings of the IEEE*, 109(5):612–634, 2021.

[7] M. Arjovsky, L. Bottou, I. Gulrajani, and D. Lopez-Paz, "Invariant risk minimization," *arXiv:1907.02893*, 2019.

[8] I. Khemakhem, D. Kingma, R. Monti, and A. Hyvärinen, "Variational autoencoders and nonlinear ICA: a unifying framework," *Proceedings of the 23rd International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 2207–2217, 2020.