

[Hummingbird](#) / RequestContextSource

Protocol

RequestContextSource

Protocol for source of request contexts

protocol RequestContextSource

Topics

Instance Properties

`var logger: Logger`

Request Logger

Required Default implementation provided.

Relationships

Inherited By

AuthRequestContext

ChildRequestContext

LambdaRequestContext

RemoteAddressRequestContext

RequestContext

RouterRequestContext

SessionRequestContext

Conforming Types

ApplicationRequestContextSource

BasicAuthRequestContext

BasicLambdaRequestContext

BasicRequestContext

BasicRouterRequestContext

BasicSessionRequestContext

BasicWebSocketRequestContext

LambdaRequestContextSource

See Also

Request context

`protocol RequestContext`

Protocol that all request contexts should conform to. A `RequestContext` is a statically typed metadata container for information that is associated with a [Request](#), and is therefore instantiated alongside the request.

`struct ApplicationRequestContextSource`

RequestContext source for contexts created by [Application](#).

`struct BasicRequestContext`

Implementation of a basic request context that supports everything the Hummingbird library needs

`protocol ChildRequestContext`

A `RequestContext` that can be initialized from another `RequestContext`.

`struct CoreRequestContextStorage`

Request context values required by Hummingbird itself.

protocol RemoteAddressRequestContext

Protocol for request context that stores the remote address of connected client.
