

Language: Swift

WSCore / WebSocketExtensionBuilder

Protocol

# WebSocketExtensionBuilder

Protocol for WebSocket extension builder

```
protocol WebSocketExtensionBuilder : Sendable
```

# **Topics**

#### Instance Methods

```
func clientExtension(from: WebSocketExtensionHTTPParameters) throws
-> (any WebSocketExtension)?
```

construct client version of extension based of server response **Required** Default implementation provided.

```
func clientRequestHeader() -> String
  construct client request header
  Required
```

func serverExtension(from: WebSocketExtensionHTTPParameters) throws
-> (any WebSocketExtension)?

construct server version of extension based of client request **Required** Default implementation provided.

func serverReponseHeader(to: WebSocketExtensionHTTPParameters) ->
String?

construct server response header based of client request

Required

func serverResponseHeader(to: [WebSocketExtensionHTTPParameters]) ->
String?

construct server response header based of all client requests

### Type Properties

static var name: String

name of WebSocket extension name

Required

# Relationships

#### Inherits From

Swift.Sendable

## **Conforming Types**

WebSocketNonNegotiableExtensionBuilder

## See Also

### **Extensions**

protocol WebSocketExtension

Protocol for WebSocket extension

struct WebSocketExtensionContext

Basic context implementation of WebSocketContext.

#### struct WebSocketExtensionHTTPParameters

Parsed parameters from Sec-WebSocket-Extensions header

### struct WebSocketExtensionFactory

Build WebSocket extension builder