CS 245 — Assignment #7 Spring 2006

Due Date: Tuesday, July 11 at 5pm.

Use makeCover to produce a cover page for your assignment and hand in your assignment in the CS 245 assignment box. Assignments are to be done individually.

1. (15 points) Formalize the following sentences in set theory. Do not use types, quantifiers, or set comprehension. Use only the following sets and relations in your formulas:

 $\begin{array}{ccc} People & & - \text{ the set of all people} \\ CS & & - \text{ the set of all CS students} \\ Books & & - \text{ the set of all books} \end{array}$

SciFi – the set of all science fiction books

Poetry – the set of all poetry books

 $owns: People \leftrightarrow Books$ — the relationship between people and the books they own $reads: People \leftrightarrow Books$ — the relationship between people and the books they read

where $CS \subset People$, $SciFi \subset Books$, $Poetry \subset Books$

Sentences to formalize:

1. Fred owns "War and Peace" but hasn't read it.

$$(Fred, WarAndPeace) \in owns \land (Fred, WarAndPeace) \notin reads$$

2. Not every CS student reads books that are not science fiction.

$$\operatorname{dom}((CS \triangleleft reads) \triangleright (Books - SciFi)) \subset CS$$

3. Some CS students read poetry books, but not all of them do.

$$(\operatorname{dom}((CS \triangleleft reads) \triangleright Poetry) \neq \emptyset) \land (\operatorname{dom}((CS \triangleleft reads) \triangleright Poetry) \subset CS)$$

4. Everyone who is not a CS student and doesn't own science fiction books reads some poetry books.

$$(People - CS) \cap (People - dom(owns \triangleright SciFi)) \subseteq dom(reads \triangleright Poetry)$$

5. Some people have read all of the books that they own.

$$dom(owns) - dom(owns - read) \neq \emptyset$$

2. (15 points) Specify the following graduate student contact management system for a professor using Z.

A professor meets with her graduate students at least once each week. Each of her meetings is with an individual graduate student. She can have multiple meetings with the same graduate student each week, but there is a maximum number of meetings that she can have in a week. Each graduate student is either a Master's student or a PhD student. The following operations can be carried out on her schedule. Describe a schema for each operation:

- 1. Schedule a meeting with a graduate student at a certain time provided the professor does not already have a meeting at that time.
- 2. Cancel a meeting with a graduate student at a certain time provided the professor is meeting with that graduate student at another time during the week.
- 3. Output a list of the times the professor meets with her graduate students. The times for the Master's students should be listed separately from the times for the PhD students.

For each operation that might not succeed, write one or more appropriate exception handling schema.

Solution:

There are two generic types used in this specification:

```
[Time]
[GradStudent]
```

and two enumerated types:

```
\begin{array}{lll} \textit{DegreeProgram} ::= & \textit{Masters} \mid \textit{PhD} \\ \textit{Report} ::= & \textit{MeetingAlreadyScheduledForThatTime} \mid \\ & \textit{NoMeetingScheduledForThatTime} \mid \\ & \textit{NoOtherMeetingScheduledForStudent} \end{array}
```

A constant representing the maximum number of meetings the professor can have in a week:

```
MaxMeetings: \mathbb{N}
```

Because the professor must meet with every graduate student, the function *sched* is surjective.

```
Schedule \_
sched: Time \rightarrow GradStudent
status: GradStudent \rightarrow DegreeProgram
\#sched \leq MaxMeetings
\#GradStudent \leq MaxMeetings
```

```
Schedule Meeting \DeltaSchedule time?: Time grad?: GradStudent time? \not\in \text{dom}(\text{sched}) sched' = sched \cup \{(\text{time?, grad?})\} status' = status
```

```
Cancel_Meeting_
\Delta Schedule
time ?: Time
grad?: GradStudent
(time?, grad?) \in sched
grad? \in ran(sched - \{(time?, grad?)\})
sched' = sched - \{(time?, grad?)\}
status' = status
Lookup_{\perp}
\Xi Schedule
reportMasters!: \mathbb{P} Time
reportPhD!: \mathbb{P} \, Time
reportMasters! = dom(sched \triangleright dom(status \triangleright \{Masters\}))
reportPhD! = dom(sched \triangleright dom(status \triangleright \{PhD\}))
. Erroneous\_Schedule\_Meeting\_
\Xi Schedule
time?: Time
grad?: GradStudent
out!: Report
time? \in dom(sched)
out! = \! Meeting Already Scheduled For That Time
.Erroneous\_Cancel\_Meeting1\_
\Xi Schedule
time?: Time
grad?: GradStudent
out!: Report
(time?, grad?) \not\in sched
out! = NoMeetingScheduledForThatTime
.Erroneous\_Cancel\_Meeting2\_\_
\Xi Schedule
time ?: Time
grad?: GradStudent
out!: Report
(time?, grad?) \in sched
grad? \notin ran(sched - \{(time?, grad?)\})
out! = NoOther Meeting Scheduled For Student
```