

Machine Learning for econometrics

Flexible models for tabular data

Matthieu Doutreligne

February 18th, 2025

Reminder from previous session

- Statistical learning 101: bias-variance trade-off
- Regularization for linear models: Lasso, Ridge, Elastic Net
- Transformation of variables: polynomial regression
-

Reminder from previous session

- Statistical learning 101: bias-variance trade-off
- Regularization for linear models: Lasso, Ridge, Elastic Net
- Transformation of variables: polynomial regression
- 🤔 But... How to select the best model? the best hyper-parameters?

Table of contents

1. Model evaluation and selection with cross-validation
2. Tree, random forests and boosting
3. A word on other families of models

Model evaluation and selection with cross-validation

A closer look at model evaluation: Wage example

Example with the Wage dataset

- Raw dataset: (N=534, p=11)

EDUCATION	SOUTH	SEX	EXPERIENCE	UNION	WAGE	AGE	RACE	OCCUPATION	SECTOR	MARR
8	no	female	21	not_member	5.10	35	Hispanic	Other	Manufacturing	Married
9	no	female	42	not_member	4.95	57	White	Other	Manufacturing	Married
12	no	male	1	not_member	6.67	19	White	Other	Manufacturing	Unmarried
12	no	male	4	not_member	4.00	22	White	Other	Other	Unmarried
12	no	male	17	not_member	7.50	35	White	Other	Other	Married

-

-

A closer look at model evaluation: Wage example

Example with the Wage dataset


- Raw dataset: (N=534, p=11)
- Transformation: encoding categorical data, scaling numerical data: (N=534, p=23)

one-hot- encoder__SOUTH_no	one-hot- encoder__SOUTH_yes	one-hot- encoder__SEX_female	one-hot- encoder__SEX_male	one-hot- encoder__UNION_member	one-hot- encoder__UNION_not
1.0	0.0	1.0	0.0	0.0	0.0
1.0	0.0	1.0	0.0	0.0	0.0
1.0	0.0	0.0	1.0	0.0	0.0
1.0	0.0	0.0	1.0	0.0	0.0
1.0	0.0	0.0	1.0	0.0	0.0

A closer look at model evaluation: Wage example


Example with the Wage dataset

- Raw dataset: (N=534, p=11)
- Transformation: encoding categorical data, scaling numerical data: (N=534, p=23)
- Regressor: Lasso with regularization parameter ($\alpha = 10$)




Repeated train/test splits

Splitting once: In red, the training set, in blue, the test set




Repeated train/test splits

But we could have chosen another split ! Yielding a different MAE




Repeated train/test splits

And another split...



Repeated train/test splits

Splitting ten times




🎉 **Distribution of MAE: 3.71 ± 0.26**

Repeated train/test splits = Cross-validation

- In sklearn, it can be instantiated with `cross_validate`.

```
1 from sklearn.model_selection import cross_validate
2 from sklearn.model_selection import ShuffleSplit
3
4 cv = ShuffleSplit(n_splits=40, test_size=0.3, random_state=0)
5 cv_results = cross_validate(
6     regressor, data, target, cv=cv, scoring="neg_mean_absolute_error"
7 )
```



Python

Repeated train/test splits = Cross-validation

- In sklearn, it can be instantiated with `cross_validate`.
- It is a more robust way to evaluate the model's performance.
- We get a more robust estimate by taking the mean over the repetitions.
- We get a better idea of the variability of the model's performance: similar to bootstrapping (but different).

Cross-validation is not model selection

Cross-validation

 Robustly estimate one model's generalization performance

Cross-validation is not model selection

Cross-validation

 Robustly estimate one model's generalization performance

But still, how to select the best model among multiple models with different hyper-parameters?

Naive cross-validation to select the best model

Nested cross-validation to select the best model

Tree, random forests and boosting

Random Forests for predictive inference

Ensemble models

A word on other families of models

Why not use deep learning everywhere?


- Success of deep learning (aka deep neural networks) in image, speech recognition and text
- Why not so used in econometrics?

Deep learning needs a lot of data (typically $N \approx 1$ million)

- Do we have this much data in econometrics?

Limited data settings

- Typically in economics (but also everywhere), we have a limited number of observations




Typical dataset are mid-sized. This does not change with time.¹

¹<https://www.kdnuggets.com/2020/07/poll-largest-dataset-analyzed-results.html>

Deep learning underperforms on data tables

Tree-based methods outperform tailored deep learning architectures (Grinsztajn et al., 2022)

Deep learning underperforms on data tables



DAG for a RCT: the treatment is independent of the confounders

Other well known families of models

Generalized linear models

Support vector machines

Gaussian processes

Bibliography

Grinsztajn, L., Oyallon, E., & Varoquaux, G. (2022). Why do tree-based models still outperform deep learning on typical tabular data?. Advances in Neural Information Processing Systems, 35, 507–520.