
Pulsar Storage on BookKeeper

Seamless Evolution

June 17, 2020

Joe Francis
Rajan Dhabalia

joef@verizonmedia.com
rdhabalia@verizonmedia.com



Confidential and proprietary materials for authorized Verizon personnel and outside agencies only. Use, disclosure or distribution of this material is not permitted to any unauthorized persons or third parties except by written agreement.

Speakers



Joe Francis

Director, Verizon Media



Rajan Dhabalia

Principal Software Engineer, Verizon Media

Agenda

- Pulsar in Verizon Media
- Benchmarking for production use
- Pulsar IO Isolation
- BookKeeper with different storage devices
- Case-study: Kafka use case on Pulsar
- Future


Verizon Media & Pulsar

- Developed as a hosted pub-sub service within Yahoo/VMG
 - open-sourced in 2016
- Global deployment
 - 6 DC (Asia, Europe, US)
 - full mesh replication
- Mission critical use cases
 - Serving applications
 - Lower latency bus for use by other low latency services
 - Write availability


Benchmarking for production

- Most benchmark numbers do not test production scenarios
 - Messaging systems work well when
 - data fits in memory
 - no disk I/O in critical path (write or read)
- Pulsar was designed to work well under real world work load..
 - Lagging consumers, replay
 - Backlog read from disks will occur.
 - Disks and brokers crash/fail
 - Pulsar ack **guarantee**: data is synced to disk on 2+ hosts
 - Latencies remain unaffected by load variations
 - backlog reads (I/O isolation)
 - failures (instantaneous recovery)
- Cost matters
 - Compute (\$) vs Storage (\$\$)
- Benchmark for production use !!!


Data paths



BookKeeper IO Isolation



Pulsar Journey



First Generation Storage - HDD

- JOURNAL-Device HDD with RAID10

- DATA-Device HDD with RAID10

- Index: Interleaved index files

- **HDD**

- Fast low latency sequential writes on HDD with battery backed RAID controller
- Random seek time is much longer for HDD
- Economical

- **Journal Device**

- Fast sequential writes

- **Ledger Device**

- Sequential writes on single entry-log data file for multiple streams
- Most of the IOPs is utilized for
 - Backlog draining (cold reads)
 - Reads and writes on Index files

Optimizing random IOs for Indexing

- **Index on interleaved file**
 - One index file for each topic
 - Random IO while updating index
 - Scaling number of topics increases random IOs and file handles
- **Index on Rocks DB**
 - LSM based **embedded** key-value store
 - Used as a library within bookie process; no additional operational efforts
 - Less write-amplification and better compression
 - Drastically reduces random IOPs for indexing
 - Small footprint (< 10 GB); mostly in RAM



Second Generation: SSD/NVMe

- JOURNAL-Device NVMe/SSD
- DATA-Device NVMe/SSD
- Index: RocksDB

SSD/NVMe

- SSD provides better performance for sequential and random I/O
- NVMe supports large command queue (64K) with parallel IO

Journal Device


- Bookie can use multiple journal directories to utilize parallel write on NVMe
- Achieve 3x Pulsar throughput with low latency, compared to HDD

Ledger Device


- Significantly faster random reads than HDD
- Faster backlog draining while doing cold reads for multiple topics

Storage Device: Sequential Vs Random IO

Sequential/Random IO throughput



Storage Device: Performance Vs Cost



Storage Evolution & Pulsar Adaptation: PMEM

PMEM

- Highest performing block storage device
- Ultra fast, super high throughput with consistent low latency
- Expensive; well suited as small device for WRITE intensive use cases

Journal Device


- WAL/journal is proven design in Databases
 - transactional storage and recovery
 - high throughput
- Write optimized append only structure
- Does not require much storage and keeps short lived transactional data
- Using PMEM for journal device
 - adds < 5% cost for each bookie
 - Increases Pulsar throughput 5x times, and with low publish latency

Pulsar Performance with Different BK-Journal Device

Performance configuration

- Enabled fsync on every published message
- Publish throughput with backlog draining
- SLA: 5ms (99%ile latency)
 - **HDD:** 120MB
 - **SSD:** 200MB
 - **NVMe:** 350MB
 - **PMEM:** 600MB











Latency Vs Throughput (Different drives for journal device)



Case-study: Migrate Kafka Use Case to Pulsar

- Cost and Throughput
 - Using PMEM for journal adds < 5% more cost per host but reduce overall cost and cluster footprints
 - Achieve 5x more throughput with 99%-ile @ <5ms write latency
- Cluster footprint
 - Kafka cluster : 33 Kafka Brokers
 - Pulsar cluster: 10 bookies and 16 brokers
 - Pulsar broker is a stateless component and costs 1/4x than bookie
 - Overall Pulsar cluster resources 1/2 of the Kafka cluster

Case-study: Migrate Kafka Use Case to Pulsar

USE CASES	APACHE PULSAR	APACHE KAFKA
Throughput with low latency		
Cost		
Geo-replication		
Queuing		
Committing messages		

Future

- Use PMDK API to access persistent memory
 - bypass the file system
 - better throughput
- Tiered Storage for historical data use cases
 - relaxed latency requirements
 - cheaper cost
 - Use cases
 - ML model training
 - audit, forensics

Thank you

joef@verizonmedia.com
rdhabalia@verizonmedia.com