

Why another Architecture?

About the need for improvement in Recurrent Neural Networks

- RNNs work sequential
- Example: Natural Language Processing
 - Words are processed one by one hard to parallelize
 - Order of words important, e.g."Alice loves Bob" vs. "Bob loves Alice"
 - Problems with larger sequences (forgetting of past information)
 - hard to train (vanishing or exploding gradients)




Unrolled RNN



Introduction


- Developed in 2017 at Google with focus on translation
- Main benefits:
 - Keeps track of word order
 - No vanishing or exploding gradients
 - Training can be parallelized
 - Allows for huge models



Model Architecture based on paper: Vaswani et. Al. "Attention is all You Need"

How does it work?

- Three main Features:
 - Positional encoding
 - Attention
 - Self-Attention



Model Architecture based on paper: Vaswani et. Al. "Attention is all You Need"


Positional Encoding

- Natural Language Processing word order important.
- RNN:
 - word order understanding based on sequential pass of words
- Transformers:
 - Use positional encoding
 - Simplified example: "I like to code" \rightarrow [("I", 1), ("like", 2), ("to", 3), ("code", 4)]
 - In original paper sine and cosine used for encoding

Attention

- Attention concept introduced in 2015
- Attention focused on each word in source sentence to come up with translation
- Interdependency between words learned during training
- Helps to learn word order, plurality or grammar

Source Sentence in English



Bahdanau, Cho, Bengio: "Neural Machine Translation by Jointly Learning to Align and Translate"

Self-Attention


- Helps to improve internal representation
- Example of word with different meanings:
 - Orange is created by mixing yellow and red.

- An orange is a fruit of various citrus species.
- Self-attention helps to get better context understanding.

Examples

- Google "BERT"
 - Bidirectional Encoder Representations from Transformers
 - 110 Million parameters
- OpenAl "GPT-3"
 - Generative Pre-trained transformers 3
 - 175 Billion parameters
- Google "LaMDA"
 - Language Model for Dialogue Applications
 - 137 Billion parameters

Examples



Source: https://i.redd.it/lq69ol56kk971.png

Domains of Expertise

- NLP
 - Text summarization
 - Classification
 - Sentiment analysis
- Computer Vision
- Time-Series Prediction

Vision Transformers (ViT)


- Pixel basic unit
- Relationships between pixels unfeasible
- Image sections analyzed (positional encoding)
- Relationship for sections calculated
- Patch size, e.g. 16x16
- Stride, e.g. 16x16
- Overlaps of images allowed

Vision Transformers


Transformers | Davide Coccomini | 2021

Source: https://en.wikipedia.org/wiki/Vision transformer#/media/File:Vision Transformer.gif

Vision Transformers (ViT)




Vision Transformers (ViT)



Vision Transformers (ViT)

- ViT outperform CNNs, but only with >100M images
- JFT (Imagenet dataset with up to 300 Million images and 18.000 classes, not public)



Source: https://arxiv.org/pdf/2010.11929.pdf,

Dosovitskiy et. al. "An image is worth 16x16 words: Transformers for Image Recognition at scale."