

## NFS lab setup/troubleshooting

//checking for the nfs server service

```
d17-suse:/home/onemantech # systemctl status nfs-server.service
● nfs-server.service - NFS server and services
   Loaded: loaded (/usr/lib/systemd/system/nfs-server.service; enabled; vendor preset: disabled)
   Drop-In: /usr/lib/systemd/system/nfs-server.service.d
            └─10-options.conf, nfsserver.conf
            /run/systemd/generator/nfs-server.service.d
            └─order-with-mounts.conf
   Active: active (exited) since Wed 2025-10-15 17:40:11 EDT; 22h ago
   Process: 1185 ExecStartPre=/usr/sbin/exportfs -r (code=exited, status=0/SUCCESS)
   Process: 1187 ExecStart=/usr/sbin/rpc.nfsd $NFSD_OPTIONS (code=exited, status=0/SUCCESS)
   Main PID: 1187 (code=exited, status=0/SUCCESS)

Oct 15 17:40:09 d17-suse systemd[1]: Starting NFS server and services...
Oct 15 17:40:11 d17-suse systemd[1]: Finished NFS server and services.
d17-suse:/home/onemantech #
```

//listing created shares for nfs exports on the server

```
d17-suse:/home/onemantech # ls -lsht /nfstest/
total 0
0 drwxr-xr-x 1 onemantech users 28 Oct 15 21:13 nfs2
0 drwxr-xr-x 1 onemantech users 28 Oct 15 21:12 nfs1
0 drwxrwxrwx 1 onemantech users 28 Oct 14 21:00 nfs3
d17-suse:/home/onemantech #
```

//premount checking

```
d17-suse:/home/onemantech # ls -lsht /mnt/nfs{1,2,3}
/mnt/nfs1:
total 0

/mnt/nfs2:
total 0

/mnt/nfs3:
total 0
d17-suse:/home/onemantech #
```

//premount checking of /etc/exports , 'no\_root\_squash' intentionally omitted

```
d17-suse:/home/onemantech # cat /etc/exports
# See the exports(5) manpage for a description of the syntax of this file.
# This file contains a list of all directories that are to be exported to
# other computers via NFS (Network File System).
# This file used by rpc.nfsd and rpc.mountd. See their manpages for details
# on how make changes in this file effective.

/nfstest/nfs1 172.16.10.103(rw,no_subtree_check,sync)
/nfstest/nfs2 172.16.10.103(rw,no_subtree_check,sync)
/nfstest/nfs3 172.16.10.103(rw,no_subtree_check,sync)
d17-suse:/home/onemantech #
```

//premount checking of /etc/fstab, 'user' parameter intentional to allow local user mounts

```
d17-suse:/home/onemantech # cat /etc/fstab
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 / btrfs defaults 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /var btrfs subvol=/@/var 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /usr/local btrfs subvol=/@/usr/local 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /tmp btrfs subvol=/@/tmp 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /srv btrfs subvol=/@/srv 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /root btrfs subvol=/@/root 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /opt btrfs subvol=/@/opt 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /home btrfs subvol=/@/home 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /boot/grub2/x86_64-efi btrfs subvol=/@/boot/grub2/x86_64-efi 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /boot/grub2/i386-pc btrfs subvol=/@/boot/grub2/i386-pc 0 0
UUID=06F4-C67F /boot/efi vfat utf8 0 2
UUID=9ebce4c0-4338-46a4-a324-595c2d067637 swap swap defaults 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /.snapshots btrfs subvol=/@/.snapshots 0 0
172.16.10.103:/zstor/naspool /mnt/zstor nfs rw,user,defaults,noauto 0 0
172.16.10.103:/nfstest/nfs1 /mnt/nfs1 nfs user,defaults,noauto 0 0
172.16.10.103:/nfstest/nfs2 /mnt/nfs2 nfs user,defaults,noauto 0 0
172.16.10.103:/nfstest/nfs3 /mnt/nfs3 nfs user,defaults,noauto 0 0
d17-suse:/home/onemantech #
```

//system re-reading the fstab file and exporting the file system

```
d17-suse:/home/onemantech # mount -a
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # exportfs -rav
exporting 172.16.10.103:/nfstest/nfs3
exporting 172.16.10.103:/nfstest/nfs2
exporting 172.16.10.103:/nfstest/nfs1
d17-suse:/home/onemantech #
```

//mounting of the shares

```
d17-suse:/home/onemantech # mount -v -t nfs 172.16.10.103:/nfstest/nfs1 /mnt/nfs1
mount.nfs: timeout set for Thu Oct 16 16:19:25 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # mount -v -t nfs 172.16.10.103:/nfstest/nfs2 /mnt/nfs2
mount.nfs: timeout set for Thu Oct 16 16:19:33 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # mount -v -t nfs 172.16.10.103:/nfstest/nfs3 /mnt/nfs3
mount.nfs: timeout set for Thu Oct 16 16:19:41 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
d17-suse:/home/onemantech #
```

//post mount checking

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103)
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103)
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103)
d17-suse:/home/onemantech #
```

//enlarged view

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,
6.10.103,local_lock=none,addr=172.16.10.103)
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,
6.10.103,local_lock=none,addr=172.16.10.103)
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs4 (rw,relatime,vers=4.2,rsz=1048576,wsz=1048576,
6.10.103,local_lock=none,addr=172.16.10.103)
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # ls -lsht /mnt/nfs{1,2,3}
/mnt/nfs2:
total 0
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile2

/mnt/nfs1:
total 0
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile1

/mnt/nfs3:
total 0
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile3
d17-suse:/home/onemantech #
```

//showing exports on local/specified server

```
d17-suse:/home/onemantech # showmount -e 172.16.10.103
Export list for 172.16.10.103:
/nfstest/nfs3 172.16.10.103
/nfstest/nfs2 172.16.10.103
/nfstest/nfs1 172.16.10.103
d17-suse:/home/onemantech #
```

//showing rpcinfo [truncated output]

```
d17-suse:/home/onemantech # rpcinfo
  program version netid      address                service  owner
  100000    4      tcp6      ::.0.111               portmapper superuser
  100000    3      tcp6      ::.0.111               portmapper superuser
  100000    4      udp6      ::.0.111               portmapper superuser
  100000    3      udp6      ::.0.111               portmapper superuser
  100000    4      tcp       0.0.0.0.0.111         portmapper superuser
  100000    3      tcp       0.0.0.0.0.111         portmapper superuser
  100000    2      tcp       0.0.0.0.0.111         portmapper superuser
  100000    4      udp       0.0.0.0.0.111         portmapper superuser
  100000    3      udp       0.0.0.0.0.111         portmapper superuser
  100000    2      udp       0.0.0.0.0.111         portmapper superuser
  100000    4      local     /run/rpcbind.sock     portmapper superuser
  100000    3      local     /run/rpcbind.sock     portmapper superuser
  100005    1      udp       0.0.0.0.78.80         mountd   superuser
  100005    1      tcp       0.0.0.0.78.80         mountd   superuser
  100005    1      udp6      ::.78.80               mountd   superuser
  100005    1      tcp6      ::.78.80               mountd   superuser
  100005    2      udp       0.0.0.0.78.80         mountd   superuser
  100005    2      tcp       0.0.0.0.78.80         mountd   superuser
  100005    2      udp6      ::.78.80               mountd   superuser
  100005    2      tcp6      ::.78.80               mountd   superuser
  100005    3      udp       0.0.0.0.78.80         mountd   superuser
  100005    3      tcp       0.0.0.0.78.80         mountd   superuser
  100005    3      udp6      ::.78.80               mountd   superuser
  100005    3      tcp6      ::.78.80               mountd   superuser
  100024    1      udp       0.0.0.0.194.65        status   479
  100024    1      tcp       0.0.0.0.230.97        status   479
```



//testing creation of new file on shares, nfs1 and nfs2 will have permission denied as expected due to 'no\_root\_squash' parameter, while nfs3 will write the file, also due to share permissions of nfs3

```
d17-suse:/home/onemantech # cat /etc/exports
# See the exports(5) manpage for a description of the syntax of this file.
# This file contains a list of all directories that are to be exported to
# other computers via NFS (Network File System).
# This file used by rpc.nfsd and rpc.mountd. See their manpages for details
# on how make changes in this file effective.

/nfstest/nfs1  172.16.10.103(rw,no_root_squash,no_subtree_check,sync)
/nfstest/nfs2  172.16.10.103(rw,no_root_squash,no_subtree_check,sync)
/nfstest/nfs3  172.16.10.103(rw,no_subtree_check,sync)
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # exportfs -rav
exporting 172.16.10.103:/nfstest/nfs3
exporting 172.16.10.103:/nfstest/nfs2
exporting 172.16.10.103:/nfstest/nfs1
d17-suse:/home/onemantech #
```

//reconfigured the /etc/exports file with the correct parameter, re-exported the share and tested the write to the share, executed as expected

```
d17-suse:/home/onemantech # touch /mnt/nfs1/newtestfile
touch: cannot touch '/mnt/nfs1/newtestfile': Permission denied
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # touch /mnt/nfs2/newtestfile
touch: cannot touch '/mnt/nfs2/newtestfile': Permission denied
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # touch /mnt/nfs3/newtestfile
d17-suse:/home/onemantech #
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # ls -lsht /mnt/nfs3
total 0
0 -rw-r--r-- 1 nobody nobody 0 Oct 16 16:25 newtestfile
0 -rw-r--r-- 1 root    root   0 Oct 14 20:48 localtestfile3
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # touch /mnt/nfs1/newtestfile
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # touch /mnt/nfs2/newtestfile
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # ls -lsht /mnt/nfs{1,2,3}
/mnt/nfs2:
total 0
0 -rw-r--r-- 1 root root 0 Oct 16 16:30 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile2

/mnt/nfs1:
total 0
0 -rw-r--r-- 1 root root 0 Oct 16 16:30 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile1

/mnt/nfs3:
total 0
0 -rw-r--r-- 1 nobody nobody 0 Oct 16 16:25 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile3
d17-suse:/home/onemantech #
```

//unmounted the shares

```
d17-suse:/home/onemantech # umount -v /mnt/nfs1
/mnt/nfs1: nfs4 mount point detected
/mnt/nfs1: umounted
d17-suse:/home/onemantech # umount -v /mnt/nfs2
/mnt/nfs2: nfs4 mount point detected
/mnt/nfs2: umounted
d17-suse:/home/onemantech # umount -v /mnt/nfs3
/mnt/nfs3: nfs4 mount point detected
/mnt/nfs3: umounted
d17-suse:/home/onemantech #
```

//showing local user mounting without escalated privileges

```
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs1 /mnt/nfs1
mount.nfs: timeout set for Thu Oct 16 16:38:35 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
onemantech@d17-suse:~>
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs2 /mnt/nfs2
mount.nfs: timeout set for Thu Oct 16 16:38:49 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
onemantech@d17-suse:~>
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs3 /mnt/nfs3
mount.nfs: timeout set for Thu Oct 16 16:38:55 2025
mount.nfs: trying text-based options 'vers=4.2,addr=172.16.10.103,clientaddr=172.16.10.103'
onemantech@d17-suse:~> █
```

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs4 (rw,nosuid,nodev,noexec,relatime,vers=4.2,rsize=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs4 (rw,nosuid,nodev,noexec,relatime,vers=4.2,rsize=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs4 (rw,nosuid,nodev,noexec,relatime,vers=4.2,rsize=1048576,wsz=1048576,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
onemantech@d17-suse:~> █
```

//enlarged

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs4 (rw,nosuid,nodev,noexec,relatime,
sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs4 (rw,nosuid,nodev,noexec,relatime,
sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs4 (rw,nosuid,nodev,noexec,relatime,
sys,clientaddr=172.16.10.103,local_lock=none,addr=172.16.10.103,user=onemantech)
onemantech@d17-suse:~> █
```

```
onemantech@d17-suse:~> ls -lsht /mnt/nfs{1,2,3}
/mnt/nfs2:
total 0
0 -rw-r--r-- 1 root root 0 Oct 16 16:30 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile2

/mnt/nfs1:
total 0
0 -rw-r--r-- 1 root root 0 Oct 16 16:30 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile1

/mnt/nfs3:
total 0
0 -rw-r--r-- 1 nobody nobody 0 Oct 16 16:25 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile3
onemantech@d17-suse:~> █
```

//local server/client packet capture of loopback interface of nfs traffic of writing to the share and the nfsiostat capture

```
d17-suse:/home/onemantech # tcpdump -G 60 -W 1 -i lo 'tcp port 2049' -w /mnt/nfs1/tcpdump-pcap
tcpdump: listening on lo, link-type EN10MB (Ethernet), snapshot length 262144 bytes
Maximum file limit reached: 1
19907 packets captured
57930 packets received by filter
16598 packets dropped by kernel
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # ls -lsht /mnt/nfs1
total 1.5G
1.1G -rw-r--r-- 1 root      root  1.1G Oct 16 16:51 tcpdump-pcap
500M -rw-r--r-- 1 onemantech users 500M Oct 16 16:50 testfile500m
  0 -rw-r--r-- 1 root      root    0 Oct 16 16:30 newtestfile
  0 -rw-r--r-- 1 root      root    0 Oct 14 20:48 localtestfile1
d17-suse:/home/onemantech #
```

```
onemantech@d17-suse:~> dd if=/dev/zero of=/mnt/nfs1/testfile500m bs=1M count=500
500+0 records in
500+0 records out
524288000 bytes (524 MB, 500 MiB) copied, 10.4369 s, 50.2 MB/s
onemantech@d17-suse:~>
```

172.16.10.103:/nfstest/nfs1 mounted on /mnt/nfs1:

ops/s	rpc	bklog
396.000		0.000

	ops/s	kB/s	kB/op	retrans	avg RTT (ms)	avg exe (ms)
read:	0.000	0.000	0.000	0 (0.0%)	0.000	0.000
write:	382.000	391321.539	1024.402	0 (0.0%)	9.565	92.482

172.16.10.103:/nfstest/nfs1 mounted on /mnt/nfs1:

ops/s	rpc	bklog
107.000		0.000

	ops/s	kB/s	kB/op	retrans	avg RTT (ms)	avg exe (ms)
read:	0.000	0.000	0.000	0 (0.0%)	0.000	0.000
write:	118.000	120879.703	1024.404	0 (0.0%)	8.949	206.932



//reading of the pcap file from the cli [truncated]

```
d17-suse:/home/onemantech # tcpdump -r /mnt/nfs1/tcpdump-pcap | less
```

```
16:50:40.304277 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [P.], seq 3232504914:3232505178, ack 450589143, win 512, options [nop,nop,TS val 3544716351 ecr 3544707558], length 264: NFS request xid 1500414384 260 getattr fh 0,2/53
16:50:40.304290 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [..], ack 264, win 24535, options [nop,nop,TS val 3544716351 ecr 3544716351], length 0
16:50:40.304348 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [P.], seq 1:321, ack 264, win 24535, options [nop,nop,TS val 3544716352 ecr 3544716351], length 320: NFS re
ply xid 1500414384 reply ok 316 getattr NON 5 ids 0/-1173032856 sz 1718159639
16:50:40.304352 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [..], ack 321, win 510, options [nop,nop,TS val 3544716352 ecr 3544716352], length 0
16:50:40.304400 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [P.], seq 264:500, ack 321, win 512, options [nop,nop,TS val 3544716352 ecr 3544716352], length 236: NFS re
quest xid 1517191600 232 getattr fh 0,2/53
16:50:40.304405 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [..], ack 500, win 24535, options [nop,nop,TS val 3544716352 ecr 3544716352], length 0
16:50:40.304458 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [P.], seq 321:589, ack 500, win 24535, options [nop,nop,TS val 3544716352 ecr 3544716352], length 268: NFS
reply xid 1517191600 reply ok 264 getattr NON 4 ids 0/-1173032856 sz 1718159639
```

//enlarged

```
16:50:40.304277 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [P.], seq 3232504914:3232505178, ack 450589143, win 512, options [nop,nop,TS val 3544716351 ecr 3544707558], length 264: NFS request xid 1500414384 260 getattr fh 0,2/53
16:50:40.304290 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [..], ack 264, win 24535, options [nop,nop,TS val 3544716351 ecr 3544716351], length 0
16:50:40.304348 IP 172.16.10.103.nfs > 172.16.10.103.863: Flags [P.], seq 1:321, ack 264, win 24535, options [nop,nop,TS val 3544716352 ecr 3544716351], length 320: NFS re
ply xid 1500414384 reply ok 316 getattr NON 5 ids 0/-1173032856 sz 1718159639
16:50:40.304352 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [..], ack 321, win 510, options [nop,nop,TS val 3544716352 ecr 3544716352], length 0
16:50:40.304400 IP 172.16.10.103.863 > 172.16.10.103.nfs: Flags [P.], seq 264:500, ack 321, win 512, options [nop,nop,TS val 3544716352 ecr 3544716352], length 236: NFS re
quest xid 1517191600 232 getattr fh 0,2/53
```

```
ack 450589143, win 512, options [nop,nop,TS val 3544716351 ecr 3544707558], length 0
[nop,nop,TS val 3544716351 ecr 3544716351], length 0
35, options [nop,nop,TS val 3544716352 ecr 3544716351], length 320: NFS re
[nop,nop,TS val 3544716352 ecr 3544716352], length 0
512, options [nop,nop,TS val 3544716352 ecr 3544716352], length 236: NFS re
[nop,nop,TS val 3544716352 ecr 3544716352], length 0
24535, options [nop,nop,TS val 3544716352 ecr 3544716352], length 268: NFS
[nop,nop,TS val 3544716352 ecr 3544716352], length 0
```

//reading output of same file through the wireshark gui

Wireshark packet capture interface showing an NFS transaction. The packet list shows a sequence of messages: V4 Call, ACK, Reply, and SETATTR. The packet details pane shows the structure of the NFS message, including the operation (SETATTR) and file path (testfile500m). The packet bytes pane shows the raw hex and ASCII data.

//similar packet capture with tcpdump equivalent of tshark

```
d17-suse:/home/onemantech # tshark -i lo -a duration:60 -f 'tcp port 2049' -w /mnt/nfs2/tsharkdump-pcap
Running as user "root" and group "root". This could be dangerous.
Capturing on 'Loopback: lo'
** (tshark:17364) 17:01:31.784756 [Main MESSAGE] -- Capture started.
** (tshark:17364) 17:01:31.784823 [Main MESSAGE] -- File: "/mnt/nfs2/tsharkdump-pcap"
7234
17188 packets dropped from lo
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # ls -lsht /mnt/nfs2
total 373M
373M -rw----- 1 root root 373M Oct 16 17:02 tsharkdump-pcap
0 -rw-r--r-- 1 root root 0 Oct 16 16:30 newtestfile
0 -rw-r--r-- 1 root root 0 Oct 14 20:48 localtestfile2
d17-suse:/home/onemantech #
```

//commenting out the /etc/exports, setting the fstab for user mount with protocol udp and version 3 of nfs for the share mounts

```
d17-suse:/home/onemantech # cat /etc/exports
# See the exports(5) manpage for a description of the syntax of this file.
# This file contains a list of all directories that are to be exported to
# other computers via NFS (Network File System).
# This file used by rpc.nfsd and rpc.mountd. See their manpages for details
# on how make changes in this file effective.

#/nfstest/nfs1 172.16.10.103(rw,no_subtree_check,sync)
#/nfstest/nfs2 172.16.10.103(rw,no_subtree_check,sync)
#/nfstest/nfs3 172.16.10.103(rw,no_subtree_check,sync)
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # exportfs -rav
exportfs: No file systems exported!
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # cat /etc/fstab
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 / btrfs defaults 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /var btrfs subvol=@/var 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /usr/local btrfs subvol=@/usr/local 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /tmp btrfs subvol=@/tmp 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /srv btrfs subvol=@/srv 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /root btrfs subvol=@/root 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /opt btrfs subvol=@/opt 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /home btrfs subvol=@/home 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /boot/grub2/x86_64-efi btrfs subvol=@/boot/grub2/x86_64-efi 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /boot/grub2/i386-pc btrfs subvol=@/boot/grub2/i386-pc 0 0
UUID=06F4-C67F /boot/efi vfat utf8 0 2
UUID=9ebce4c0-4338-46a4-a324-595c2d067637 swap swap defaults 0 0
UUID=47c1c763-2b1c-41b9-8c06-463f3a53ff67 /.snapshots btrfs subvol=@/.snapshots 0 0
172.16.10.103:/zstor/naspool /mnt/zstor nfs rw,user,defaults,noauto 0 0
172.16.10.103:/nfstest/nfs1 /mnt/nfs1 nfs user,proto=udp,vers=3,noauto 0 0
172.16.10.103:/nfstest/nfs2 /mnt/nfs2 nfs user,proto=udp,vers=3,noauto 0 0
172.16.10.103:/nfstest/nfs3 /mnt/nfs3 nfs user,proto=udp,vers=3,noauto 0 0
d17-suse:/home/onemantech #
```

```
d17-suse:/home/onemantech # showmount -e 172.16.10.103
Export list for 172.16.10.103:
d17-suse:/home/onemantech #
```

//manual export of shares and mounting, confirmation of version 3 and protocol udp

```
d17-suse:/home/onemantech # exportfs -v -o rw,sync,no_subtree_check 172.16.10.103:/nfstest/nfs1
exportfs: No file systems exported!
exporting 172.16.10.103:/nfstest/nfs1
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # exportfs -v -o rw,sync,no_subtree_check 172.16.10.103:/nfstest/nfs2
exportfs: No file systems exported!
exporting 172.16.10.103:/nfstest/nfs2
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # exportfs -v -o rw,sync,no_subtree_check 172.16.10.103:/nfstest/nfs3
exportfs: No file systems exported!
exporting 172.16.10.103:/nfstest/nfs3
d17-suse:/home/onemantech # █
```

```
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs1 /mnt/nfs1
mount.nfs: timeout set for Thu Oct 16 17:25:46 2025
mount.nfs: trying text-based options 'proto=udp,vers=3,addr=172.16.10.103'
mount.nfs: prog 100003, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100003 vers 3 prot UDP port 2049
mount.nfs: prog 100005, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100005 vers 3 prot UDP port 20048
onemantech@d17-suse:~>
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs2 /mnt/nfs2
mount.nfs: timeout set for Thu Oct 16 17:25:53 2025
mount.nfs: trying text-based options 'proto=udp,vers=3,addr=172.16.10.103'
mount.nfs: prog 100003, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100003 vers 3 prot UDP port 2049
mount.nfs: prog 100005, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100005 vers 3 prot UDP port 20048
onemantech@d17-suse:~>
onemantech@d17-suse:~> mount -v -t nfs 172.16.10.103:/nfstest/nfs3 /mnt/nfs3
mount.nfs: timeout set for Thu Oct 16 17:25:59 2025
mount.nfs: trying text-based options 'proto=udp,vers=3,addr=172.16.10.103'
mount.nfs: prog 100003, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100003 vers 3 prot UDP port 2049
mount.nfs: prog 100005, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100005 vers 3 prot UDP port 20048
onemantech@d17-suse:~> █
```

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs (rw,nosuid,nodev,noexec,relatime,vers=3,rsize=32768,wsiz=32768,namlen=255,hard,proto=udp,timeo=11,retrans=3,sec=sys,moun
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs (rw,nosuid,nodev,noexec,relatime,vers=3,rsize=32768,wsiz=32768,namlen=255,hard,proto=udp,timeo=11,retrans=3,sec=sys,moun
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,local_lock=none,addr=172.16.10.103,user=onemantech)
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs (rw,nosuid,nodev,noexec,relatime,vers=3,rsize=32768,wsiz=32768,namlen=255,hard,proto=udp,timeo=11,retrans=3,sec=sys,moun
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,local_lock=none,addr=172.16.10.103,user=onemantech)
onemantech@d17-suse:~> █
```



//enlarged

```
172.16.10.103:/nfstest/nfs1 on /mnt/nfs1 type nfs (rw,nosuid,no
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,
172.16.10.103:/nfstest/nfs2 on /mnt/nfs2 type nfs (rw,nosuid,no
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,
172.16.10.103:/nfstest/nfs3 on /mnt/nfs3 type nfs (rw,nosuid,no
taddr=172.16.10.103,mountvers=3,mountport=20048,mountproto=udp,
onemantech@d17-suse:~> █
```

```
d17-suse:/home/onemantech # mount -v -t nfs -o vers=3,proto=udp 172.16.10.103:/nfstest/nfs1 /mnt/nfs1
mount.nfs: timeout set for Thu Oct 16 17:42:06 2025
mount.nfs: trying text-based options 'vers=3,proto=udp,addr=172.16.10.103'
mount.nfs: prog 100003, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100003 vers 3 prot UDP port 2049
mount.nfs: prog 100005, trying vers=3, prot=17
mount.nfs: trying 172.16.10.103 prog 100005 vers 3 prot UDP port 20048
d17-suse:/home/onemantech #
d17-suse:/home/onemantech # █
```