

Development test Report

Model Name	Development Rank	Process Level	Development Spec. No.
MSY-JY50VF-VN1	T II Y	-	MCP-22B011-RFD

General Evaluate Testing
MELSHI KASHI-76D001

APPROVAL QA DESK MSR	APPROVAL DEV TEST SM	CHECKED ENG.	CHECKED	REPORT
 QA 21 NOV 2024 MORISHITA	 DEV TEST 28 NOV 2024 Anuwat J.	 RAC FD 25 NOV 2024 Nuttapol P.	 Dev Test 21 NOV 2024 Saranyu.T	 Dev test 21 NOV 2024 NUTTAPOL P.
REPORT NO. <u>DEV-24-FG-0004</u>				

BASE MODEL FOR DESIGN OR SIMILARITY MODEL		
Symbol	Similarity Design Model	Document No.
A	MSY-KX13VF-TH1	VCN21R312
B	MUY-JX18VF-DA1	VCN21R313
C	MSY-JY35VF-VN1	MCP-23E040-RFD
D	MSY-JY60VF-VN1	MCP-23E040-RFD
E	MSY-KX09VF-TH1	VCN21R312

	SSEHI	RISHI
ES NO.	-	ENG-23ES330-B

Power supply : 1 ϕ , 50 Hz, 230V, -
Comp.model : KVB110FZVMT (Ether Oil)
Ref.weight : R32 = 620 g. Pipe : 5.0 m.
C/T+LEV : Ø4.0-2.4"240L+T01-13C25

Classification of Evaluate Item			Outline of Evaluate Condition and Principal Standard Value			Max. MOP		Judg		Test result (n=2)				AVE (n=2)	
Test Item	Detail					Max.	MOP								
Cooling capacity < Rate >	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	MCP [RA-16] ✓	MCP [RA-16] ✓			AVE (n=2)		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	SIN: (230C4211 / 230C4281) ✓	SIN: (230C4211 / 230C4281) ✓			Q = 5365.5 W (101.230%)		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	Q = 5360.6 W (100.000%)	Q = 5360.6 W (100.000%)			P = 1973.0 W (101.201%)		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	P = 1947.1 W (99.951%)	P = 1947.1 W (99.951%)			EER = 2.718 (100.000%) ✓		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	EER = 2.725 (100.158%)	EER = 2.725 (100.158%)			Star ranking = 5★		
	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	MCP [RA-16] ✓	MCP [RA-16] ✓			AVE (n=2)		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	SIN: (230C4211 / 230C4281) ✓	SIN: (230C4211 / 230C4281) ✓			Q = 2655.9 W (99.468%)		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	Q = 2602.7 W (98.215%)	Q = 2602.7 W (98.215%)			P = 561.9 W (99.468%)		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	P = 566.2 W (99.951%)	P = 566.2 W (99.951%)			EER = 4.698		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	EER = 4.597	EER = 4.597			CSPF 5.18 (101.965%)		
Cooling capacity < Half >	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	MCP [RA-16] ✓	MCP [RA-16] ✓			AVE (n=2)		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	SIN: (230C4211 / 230C4281) ✓	SIN: (230C4211 / 230C4281) ✓			Q = 2655.9 W (99.468%)		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	Q = 2602.7 W (98.215%)	Q = 2602.7 W (98.215%)			P = 561.9 W (99.468%)		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	P = 566.2 W (99.951%)	P = 566.2 W (99.951%)			EER = 4.698		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	EER = 4.597	EER = 4.597			CSPF 5.18 (101.965%)		
	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	MCP [RA-16] ✓	MCP [RA-16] ✓			AVE (n=2)		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	SIN: (230C4211 / 230C4281) ✓	SIN: (230C4211 / 230C4281) ✓			Q = 2655.9 W (99.468%)		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	Q = 2602.7 W (98.215%)	Q = 2602.7 W (98.215%)			P = 561.9 W (99.468%)		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	P = 566.2 W (99.951%)	P = 566.2 W (99.951%)			EER = 4.698		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	2	OK	EER = 4.597	EER = 4.597			CSPF 5.18 (101.965%)		
Cooling capacity < Max >	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	MCP [RA-14] ✓	MCP [RA-14] ✓			Star ranking = 5★		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	SIN: (230C4211 / 230C4284) ✓	SIN: (230C4211 / 230C4284) ✓			Star ranking = 5★		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	Q = 5356.4 W	Q = 5356.4 W			Star ranking = 5★		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK					Star ranking = 5★		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK					Star ranking = 5★		
	ISO 5151:2017	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	MCP [RA-14] ✓	MCP [RA-14] ✓			Star ranking = 5★		
	ISO 1555:2036	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	SIN: (230C4211 / 230C4284) ✓	SIN: (230C4211 / 230C4284) ✓			Star ranking = 5★		
	ISO 2134-1:2045	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK	Q = 5356.4 W	Q = 5356.4 W			Star ranking = 5★		
	In DB-27.0 °C, WB-19.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK					Star ranking = 5★		
	Out DB-35.0 °C, WB-24.0 °C	1	Spec.: 1 φ, 50Hz, 230V	Development Target (Ave):		-	1	OK					Star ranking = 5★		
Cooling Overload	In S2.024.0 Out 46.027.0 °C	2	During 2 hr. protector does not work			-	1	OK	Max. Pd = 4.837 MW, 20 min. 220.230V ✓	Max. Pd = 4.837 MW, 20 min. 220.230V ✓			Star ranking = 5★		
	In S21.015.0 Out 21.015.0 °C	3	6hr. No ice & water drop from air outlet			-	1	OK	No problem without the remain ice and water drop. (S21.015.0, Q21.015.0 DSH+ 16.5 deg.	No problem without the remain ice and water drop. (S21.015.0, Q21.015.0 DSH+ 16.5 deg.			Star ranking = 5★		
	In S21.015.0 Out 21.015.0 °C	3	6hr. No ice accumulates & water blow out from nozzle			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	In S27.7.0 Out 24.118 °C	5	During 2 hr. protector does not work			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Heating Capa	6 (F)	Wireless spec. ≥100% ADOP ≥100%			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Le Temp. RH RH	6 (F)	2 °C, RH 95%, Heating Discharge SH ≥10deg-10°C			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Base freezing	6 (F)	Bulgarian condition -3 °C, Humidifier			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Constant decision	6 (F)	Decide constant number			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Step response	6 (F)	Decide of control constant number			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	JIS condition	7 (F)	RH75%, 6hr. No water drop from air outlet			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
GENERAL PREFORMANCE	JIS condition	7 (F)	RH75%, 6hr. No water drop from air outlet			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Internal	7 (F)	RH75% 48hr Operation, Stop 12hr and Operation 24hr			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Evaporating	7 (F)	Refrigerant -50g 4hr. RH75% No water drop			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Clogged Filter	7 (F)	Gauze, air filter 3, air cleaning filter 6			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Disposal	7 (F)	Front, back 2.0 deg., Left, Right 1.3 deg.			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Drain outlet wind	7 (F)	15m/s -not have water attach at electrical part			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Blow-off	7 (F)	No water blow out from air outlet			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Starting test	8 (F)	Start Voltage less than ± 80%V			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Low Temp. Start	8 (F)	Indoor temp. -5°C, outdoor temp. -10°C			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
	Oil circulation	8 (F)	Keep enough quantity of oil in Comp.			-	1	OK	No problem without the remain ice and water drop.	No problem without the remain ice and water drop.			Star ranking = 5★		
Enclosure	JIS condition	16 (F)	Indoor 49.0 dBA, outdoor 54.0 dBA Not over than +0 dBA			-	2	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	PWL	16 (F)	Not Over Than 60dB (Rated Cooling)			-	2	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Abnormal Noise	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Defrost Noise	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Discharge	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Whistle Noise	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Motor Noise	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Cranking Noise	16 (F)	No found noise, small level < 20ms, small level < 100ms			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Moving Part	16 (F)	There is no Abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Piping noise	16 (F)	NO abnormal noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
Noise	Motor noise	16 (F)	When motor OFF, noise is less than 2 dBA			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Low Freq. Noise	16 (F)	Out-max: peak > 46dBA and Out-A: peak > 40dBA			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	High frequency noise	16 (F)	Changing of sound Level is Less than 3 dBA			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Direct change	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	PULSATION NOISE	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Buzzer sound	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Cogging sound	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Feeling Check	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Feeling Check	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Feeling Check	16 (F)	Refer to VMDB164			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
Vibration	Indoor Vibration	17 (F)	For un-balance = 230 μm, No Vibration Noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Outdoor Vibration	17 (F)	Floor Vibration (VM-DB216)			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Vibration Noise	17 (F)	Apply 1.5 times vibration, No vibration noise			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Start-Stop	17 (F)	Depend on damaged stress of suction/discharge pipe			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.			Star ranking = 5★		
	Running	17 (F)	Depend on damaged stress of suction/discharge pipe			-	1	OK	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m: R32: 830~20 g.	Normally to level of Oil return Cool mode / Standard / Freezing / Overload / S.H6S.Low, Pipe-0.0 m: R32: 600~20 g, Pipe-20.0m:					

(Remark)	Amount of Unit Judgement	Number : Amount of Evaluated (Unit Q's)	o : Refer Base model	- : Not Evaluate	x : not require for evaluation
		OK : Pass	Δ : Pass by Have Condition	* : Not Pass	

[illegible]