

Development test Report

Model Name		Development Rank	Process Level	Development Spec. No.		General Evaluate Testing	
MSUJY-GW3SVFD-A1		M1Y	-	VM-21DU219		MELSHI KASHI-7BD001	
BASE MODEL FOR DESIGN OR SIMILARITY MODEL		Document No.	Document No.	ES NO.	SSSH	RSHI	
Symbol	Symbol	MSUJY-GW3SVFD-A1	MSUJY-GW3SVFD-A1			ENG-24E332-A	
J	J	MSUJY-GW3SVFD-A1	MSUJY-GW3SVFD-A1				
P	P	MSUJY-GW3SVFD-A1	MSUJY-GW3SVFD-A1				
W	W	MSUJY-GW3SVFD-A1	MSUJY-GW3SVFD-A1				

Power supply: 1.4, 50 Hz, 230V.
Comp model: KUBO23FYXMC
Refr weight: R32 = 97g.
LEV :
Period of test: 22-Feb-2025 ~ 13-May-2025

1.4, 50 Hz, 230V.
Comp model: KUBO23FYXMC
Refr weight: R32 = 97g.
Pipe: 5.0 m.
LEV :
Period of test: 22-Feb-2025 ~ 13-May-2025

APPROVAL QA DEF MGR	APPROVAL Dev Test SM	CHECKED ENG	CHECKED	REPORT

Classification of Evaluate Item		Outline of Evaluate Condition and Principal Standard Value		MCP	Judg	Test result	
Test Item	Detail	Mezhi Kuzhi Item	in passing	Mei.	Judg	(n=2)	(n=2)
Cooling capacity < Rate >	ISO 5151:2017					MCP [RA-19]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling capacity <Low Temp Half>	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1830.4 W P = 330.4 W EER = 5.540	Q = 1825.5 W (104.594%) P = 334.1 W EER = 5.449
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Freezing	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Freezing	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Freezing	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Freezing	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Freezing	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 3540.0 W P = 870.0 W EER = 4.02 W/W HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.330 (4.5 star)	Q = 3548.8 W (101.474%) P = 877.2 W (100.103%) EER = 4.028 (100.99%) HOT = 7.259 (5.5 star) Mixed = 6.060 (4.5 star) Cold = 6.331 (4.5 star)
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Cooling Freezing(drop)	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	MEPS (AS/NZS3823.2:2011)					Q = 1521.5 W P = 183.3 W EER = 8.303	Q = 1507.7 W (101.433%) P = 186.9 W EER = 8.067
	In DB:27.0 °C, WB:18.0 °C Out DB:35.0 °C, WB:24.0 °C						
Heating Overload	ISO 5151:2017					MCP [RA-2]	MCP [RA-2]
	AS/NZS4353.3.1, AS4343:2014					SIN: (25DC0053/25DC0215)	SIN: (25DC0053/25DC0216)
	ME						