

Development test Report

Model Name	Development Rank	Process Level	Development Spec. No.	General Evaluate Testing
MSY-JA00VF-VN1	T II Y	-	MCP-24B010-RFD-A	MELSHI KASHI-760001
BASE MODEL FOR DESIGN OR SIMILARITY MODEL				
Symbol	Similarity Design Model	Document No.	Test No.	SESHI
M	MSY-J7600F-VN1	MCP-24B0040-RFD	ENG-24E339	ENG-24E3183
R	MUT-J7600F-VN1	MCP-24B0040-RFD		
U	MUT-K240VF-VN1	MCP-24E016-RFD		
X	MUT-K240VF-VN1	MCP-24E016-RFD		
AA	MUT-K240VF-VN1	MCP-24E016-RFD		
Power supply : 1.6, 50 Hz, 230V Comp.model : KV1B10F2UMT Ref.weight : R30 = 630 g CFL-LEV : C11, 94.0, 2.740A, *101-9325 Period of test : 16Dec2025 - 16Dec2025				

APPROVAL	APPROVAL	APPROVAL	CHECKED	CHECKED	REPORT
QA	QA	QA	ENG	ENG	REPORT
12 DEC 2025	12 DEC 2025	12 DEC 2025	10-Dec-25	10-Dec-25	6 DEC 2025
REPORT NO.	REPORT NO.	REPORT NO.	DATE	DATE	DATE
12 DEC 2025	12 DEC 2025	12 DEC 2025	10-Dec-25	10-Dec-25	6 DEC 2025
12 DEC 2025	12 DEC 2025	12 DEC 2025	10-Dec-25	10-Dec-25	6 DEC 2025

Test	Classification of Evaluate Item		Meas	Detailed	Outline of Evaluate Condition and Principal Standard Value	MCP	Judg	Test result
	Item	Detail						
Cooling capacity < Rate >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Half >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
Cooling capacity < Max >	ISO 5151:2017	Development Target (Ave):	-	2	OK	MCP [RA-17]	Q = 6365.9 W (102.033%) P = 2093.1 W (97.897%) EER = 3.157 (102.010%) Star ranking = 5★	
	JIS R134-2016	Q : ≥ 100.0 % P : ≥ 110.0 % EER : ≥ 100.0 %	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:27.0 °C, WB:18.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:35.0 °C, WB:24.0 °C	Q : ± 5 % of full capacity result	-	1	OK	MCP [RA-17]	Q = 3214.2 W (102.038%) P = 580.9 W (122.200%) EER = 5.533 Star ranking = 5★	
	In DB:37.0 °C, WB:16.0 °C	Q : ± 5 % of full capacity result	-					