

RAC PERFORMANCE DATA

CONFIDENTIAL

Model Name : MSY-GZ13VF-TH1 / MUJY-GZ13VF-TH1
Power supply : 1 Ø 50 Hz 220 V
Comp.model : KVB073FXTMC
Ref.weight : (R32) = 470 g.
C/T size : C/T1:Ø4.0-2.4-200L , C/T2:Ø3.0-2.0-260L mm.
LEV : T01 13C 25
Reference design specification no. : 702-RA-24016/MCP-23B009-RFD-A

Indoor unit : MSY-GZ13VF-TH1
-Production date : 21-Jan-25 Line : A
-Lot size : 5000401-5000800 Units 400
Outdoor unit : MUJY-GZ13VF-TH1
-Production date : 10-Mar-25 Line : E
-Lot size : 5005556-5005567 Units 12
Period of test : 24 Mar '25 - 4 Apr '25

APPROVE (QA.Dept.Mgr.)	APPROVE (Dev. Test SM.)	CHECKE	RECORD
REPORT NO.	SAM-25-760-0005		

Reference Product standard : ISO 5151 : 1994 , JIS-C9612 , TIS 2134-2553
Reference Capacity and Performance test standard : ISO 5151 : 1994 , JIS-C9612 , TIS 2134-2553
Reference Sound test standard : ISO 3744:2010 , ISO 3745:2010

Reference Safety test standard : TIS 1155-2557 , TIS 1529-2561
Reference EMC test standard : TIS 1155-2557 , TIS 1529-2561
Reference Other test standard :

1. Test result :

Classification of Evaluate Item		Specification and Tolerance	Q'ty	Judg	Data test result
Cooling • Heating Capacity and General Performance	Cooling capacity [Rate]	Room temp. In DB27.0 °C, WB19.0 °C Out DB35.0 °C, WB24.0 °C Spec. 1 φ, 50 Hz, 220 V Capacity= 12624 Btu/h ≥ 97.2 % Power input= 1020 W ≤ 110 % Current= 5.00 A ≤ - % EER= 12.376 Btu/h.w ≥ - % SEER (Label)= 22.060 Btu/h.w ≥ 97.2 % and ≥ 21.56 EGAT Energy rating = No.5★★★ SEER ≥ 21.56 Pipe length = 7.5 m.	1	OK	S/N : 5000482 / 5005567 [RA-11] / Capacity= 12690.9 Btu/hr (100.530%) ✓ Power input= 980.9 W (96.167%) ✓ Current= 4.76 A (95.200%) ✓ EER= 12.938 Btu/h.w (104.541%) ✓ SEER (Label)= 22.720 Btu/h.w (102.992%) ✓ EGAT Energy rating = No.5★★★ Pipe length = 7.5 m.
	Cooling capacity [Half load]	Room temp. In DB20.0 °C, WB - °C Out DB7.0 °C, WB6.0 °C Spec. 1 φ, 50 Hz, 220 V Capacity= 6345.5 Btu/h(Rate / 2) Q ± 634.6 Btu/h and ± 5 % Power input= 318 W ≤ - % EER= 19.86 ≥ - % Pipe length = 7.5 m.	1	OK	S/N : 5000482 / 5005567 [RA-11] Capacity= 6108.2 Btu/hr (98.130%) ✓ Power input= 299.5 W (94.182%) ✓ EER= 20.395 Btu/h.w (102.704%) ✓ Pipe length = 7.5 m.
	Cooling Overload	In 32.0/23.0, Out 43.0/26.0 °C During 2 Hr. protector does not work and Pd< 4.17 MPa.	1	OK	Max Pd = 3.202 MPa (220 V) Max Td = 94.8 °C (242 V) ✓
	Starting test	In 32.0/23.0, Out 43.0/26.0 °C Low voltage start ≤ 176 V	1	OK	Starting voltage = 166.9 V (75.9 %) ✓
	Freezing disturbance	In 21.0/15.0, Out 21.0/15 °C Ice on indoor coil surface not over 10% of indoor coil area	1	OK	Have not ice on cooler surface and have not water blow out from nozzle. ✓
	Water dripping	In 21.0/15.0, Out 21.0/15 °C 6Hr. No ice & water drop from air outlet	1	OK	Have not ice on cooler surface and have not water blow out from nozzle. ✓
	Water overload	In 27.0/-, Out 24.0/18.0 °C Voltage ± 10% operate 2 Hr. protector does not work			
	Automatic defrost	Low temp High Humidity ratio In 20.0/12.0, Out 2.0/1.0 °C Frost remain less than 1/3 of outdoor coil and during melting frost have not abnormal noise.			
	Enclosure Sweat	In 27.0/24.3, Out 27.0/24.3 °C RH80%, operate 4Hr. indoor fan low must be no water drop from air outlet and disposal of condensated water not found.	1	OK	No condensated water drop and not blow out from nozzle. ✓
	Other test (Depend on change point)				
Sound	Overall (SPL)	Cooling mode : In DB27.0 °C, WB19.0 °C Out DB35.0 °C, WB24.0 °C Indoor side : Fan Rated Hi speed= 43 dBA (1080 rpm) not over + 4dBA Fan Super Hi speed= 43 dBA (1080 rpm) not over + 4dBA Fan Hi speed= 38 dBA (940 rpm) not over + 4dBA Fan Med speed= 31 dBA (800 rpm) not over + 4dBA Fan Low speed= 24 dBA (660 rpm) not over + 4dBA Fan S.Low speed = 19 dBA (520 rpm) not over + 4dBA Outdoor side : Front side= 50 dBA (980 rpm) not over + 4dBA Back side= 50 dBA (980 rpm) not over + 4dBA	-	OK	Reference Test Report : SAM-24-760-0136 (MS(U)Y-GZ13VF-TH1) ✓
	Abnormal noise	Cooling mode : In DB27.0 °C, WB19.0 °C Out DB35.0 °C, WB24.0 °C Feeling check no abnormality noise - Pipe length 5 m.	-	OK	Reference Test Report : SAM-24-760-0136 (MS(U)Y-GZ13VF-TH1) ✓
	Overall (SPL)	Heating mode : In DB20.0 °C, WB - °C Out DB7.0 °C, WB6.0 °C Indoor side : Fan Rated Hi speed= dBA (rpm) not over + 4dBA Fan Super Hi speed= dBA (rpm) not over + 4dBA Fan Hi speed= dBA (rpm) not over + 4dBA Fan Med speed= dBA (rpm) not over + 4dBA Fan Low speed= dBA (rpm) not over + 4dBA Outdoor side : Front side= dBA (rpm) not over + 4dBA Back side= dBA (rpm) not over + 4dBA			
	Abnormal noise	Heating mode : In DB20.0 °C, WB - °C Out DB7.0 °C, WB6.0 °C Feeling check no abnormality noise - Pipe length 5 m.			
	Other test (Depend on change point)				
	Impulse noise	Function operate are not abnormal When voltage supply £ 1.8 KV			
	Operating characteristic	Operate check confirm by IB			
	Other test (Depend on change point)				
	Insulation resistance	10 M.Ω or more / 500 V.	1	OK	100 M.Ω ✓
	Dielectric Withstand Voltage	Cut off current 100 mA : Basic Insulation 1000 V / 1 min Supplementary Insulation 1750 V / 1 min Reinforced Insulation 3000 V / 1 min	1	OK	PASS ✓
Safety	Earthing continuity	25A between earthing and metal parts resistance not exceeding 0.1 W	1	OK	PASS ✓
	Leakage Current	Not exceed 2 mA. per Kilowatt of max power input. (2.04 mA)	1	OK	Max Peak : 0.36 mA. Cabinet (N-E) Start ✓
	Other test (Depend on change point)				
	DT Packing Inspection	Accessories , IB , IM, Guarantee must be packing and check	1	OK	PASS ✓
Final Inspection	Fuction Test at Production Line	Can operate comply with model fuction	1	OK	PASS ✓
	PQI Packing Inspection	Accessories , IB , IM, Guarantee must be packing and check	1	OK	PASS ✓

2. Problem

No.	Detail	Cause	Improvement	Judgement
-----	--------	-------	-------------	-----------

COMMENT :

ตารางที่ 7 เกณฑ์ระดับประสิทธิภาพพลังงานเครื่องปรับอากาศ ชนิด Variable Speed/Inverter

ค่าประสิทธิภาพ : SEER (ใช้ข้อมูลแบบวัด)		เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5
ขนาดเครื่องปรับอากาศ		เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5	เบอร์ 5
ไม่พบ 8,000 บีทียู		17.06 - 18.55	18.56 - 20.05	20.06 - 21.55	21.56 - 23.05	23.06 - 24.55	≥ 24.56
ไม่พบ 12,000 บีทียู		16.04 - 17.15	17.16 - 18.27	18.28 - 19.38	19.39 - 20.50	20.51 - 21.62	≥ 21.63
ไม่พบ 18,000 บีทียู		14.00 - 15.49	15.50 - 16.99	17.00 - 18.49	18.50 - 19.99	20.00 - 21.49	≥ 21.50