ANDH-FULL Unseen Test

Table 1. First improvement: Parse-enhanced Search.

Method	SPL	SR	GP
Supervised Finetuning Methods			
E.T. [28]	1.9	2.8	60.7
HAA-T [7]	4.1	6.3	63.2
LSTM [10]	1.8	1.9	56.4
HAA-LSTM [7]	1.9	2.6	66.5
TA-GAT [35]	--	--	--
TA-GAT w/ at [35]	--	--	--
FELA [36]	--	--	--
FELA w/ at [36]	--	--	--
OpenFly [9]	8.3	13.3	54.3
Training-Free Methods			
GPT-4o [33]	1.8	1.9	-10.2
Qwen-VL-Max [2]	6.4	6.9	1.6
PSC-AVDN (Paper)	12.1	14.4	54.5
PSC-AVDN + Parse (Ours)	**15.0**	**18.1**	**63.6**

Source: out/search/preds_parse_test_unseen_full. SR uses final_iou > 0.4 and equals 78/431 = 18.1%. SPL, SR, and GP are rounded to one decimal place.

ANDH-FULL Unseen Test

Table 2. Second improvement: Parse + SAM3-assisted Search.

Method	SPL	SR	GP
Supervised Finetuning Methods			
E.T. [28]	1.9	2.8	60.7
HAA-T [7]	4.1	6.3	63.2
LSTM [10]	1.8	1.9	56.4
HAA-LSTM [7]	1.9	2.6	66.5
TA-GAT [35]	--	--	--
TA-GAT w/ at [35]	--	--	--
FELA [36]	--	--	--
FELA w/ at [36]	--	--	--
OpenFly [9]	8.3	13.3	54.3
Training-Free Methods			
GPT-4o [33]	1.8	1.9	-10.2
Qwen-VL-Max [2]	6.4	6.9	1.6
PSC-AVDN (Paper)	12.1	14.4	54.5
PSC-AVDN + Parse + SAM3 Search (Ours)	**15.1**	**18.3**	**64.3**

Source: out/search/preds_sam3_test_unseen_full. SR uses final_iou > 0.4 and equals 79/431 = 18.3%. The evaluator processed 431 valid trajectories and skipped one of 432 instructions. SPL, SR, and GP are rounded to one decimal place.