




i have been built a todo app using react but i have some qs

i have submitted the folder structure for better understanding

this is my context

```
import { createContext, useContext } from "react";
```

```
export const TodoContext = createContext({
```

```
  todos: [
```

```
    {
```

```
      id: 1,
```

```
      todo: "Todo message",
```

```
      completed: false,
```

```
    },
```

```
  ],
```

```
  addTodo: (todo) => {},
```

```
  updateTodo: (id, todo) => {},
```

```
  deleteTodo: (id) => {},
```

```
  toggleComplete: (id) => {},
```

```
});
```

```
export const useTodo = () => {
```

```
  return useContext(TodoContext);
```

```
};
```

```
export const TodoProvider = TodoContext.Provider;
```

this is my todo form

```
import React from "react";
```

```
import { useState } from "react";
```

```

import { useTodo } from "../contexts/index.js";

const TodoForm = () => {
  const [todo, setTodo] = useState("");
  const { addTodo } = useTodo();

  const add = (e) => {
    e.preventDefault();
    if (!todo) {
      return;
    }
    addTodo({ todo, completed: false });
    setTodo("");
  };

  return (
    <form className="flex" onSubmit={add}>
      <input
        type="text"
        placeholder="Write Todo..."
        className="w-full border border-black/10 rounded-l-lg px-3
outline-none duration-150 bg-white/20 py-1.5"
        value={todo}
        onChange={(e) => {
          setTodo(e.target.value);
        }}
      />
      <button
        type="submit"
        className="rounded-r-lg px-3 py-1 bg-green-600 text-white
shrink-0"
      >
        Add
      </button>
    </form>
  );
};

export default TodoForm;

this is my todo item

```

```

import React, { useState } from "react";
import { useTodo } from "../contexts/index.js";

const TodoItem = ({ todo }) => {
  const [isTodoEditable, setIsTodoEditable] = useState(false);
  const [todoMsg, setTodoMsg] = useState(todo.todo);
  const { updateTodo, deleteTodo, toggleComplete } = useTodo();

  const editTodo = () => {
    updateTodo(todo.id, { ...todo, todo: todoMsg });
    setIsTodoEditable(false);
  };

  const toggleCompleted = () => {
    toggleComplete(todo.id);
  };

  return (
    <div
      className={flex border border-black/10 rounded-lg px-3 py-1.5
        gap-x-3 shadow-sm shadow-white/50 duration-300 text-black ${
          todo.completed ? "bg-[#c6e9a7]" : "bg-[#ccbed7]"
        }}
    >
      <input
        type="checkbox"
        className="cursor-pointer"
        checked={todo.completed}
        onChange={toggleCompleted}
      />
      <input
        type="text"
        className={border outline-none w-full bg-transparent
          rounded-lg ${
            isTodoEditable ? "border-black/10 px-2" : "border-transparent"
          } ${todo.completed ? "line-through" : ""}}
        value={todoMsg}
        onChange={(e) => setTodoMsg(e.target.value)}
        readOnly={!isTodoEditable}
      />
      {/* Edit, Save Button */}
      <button

```

```

        className="inline-flex w-8 h-8 rounded-lg text-sm border
border-black/10 justify-center items-center bg-gray-50 hover:bg-
gray-100 shrink-0 disabled:opacity-50"
        onClick={() => {
            if (todo.completed) return;

            if (isTodoEditable) {
                editTodo();
            } else setIsTodoEditable((prev) => !prev);
        }}
        disabled={todo.completed}
    >
        {isTodoEditable ? "📁" : "✎"}
    </button>
    { /* Delete Todo Button */}
    <button
        className="inline-flex w-8 h-8 rounded-lg text-sm border
border-black/10 justify-center items-center bg-gray-50 hover:bg-
gray-100 shrink-0"
        onClick={() => deleteTodo(todo.id)}
    >
        ✖
    </button>
</div>
);
};

```

```
export default TodoItem;
```

this is my app.jsx

```

import React, { useState, useEffect } from "react";
import { TodoProvider } from "../contexts/index.js";
import { TodoForm, TodoItem } from "../components/index.js";

```

```

const App = () => {
    const [todos, setTodos] = useState([]);

    //adding toto
    const addTodo = (todo) => {
        setTodos((prev) => [{ id: Date.now(), ...todo }, ...prev]);
    };

```

```

};

//updating todo
const updateTodo = (id, todo) => {
  setTodos((prev) =>
    prev.map((prevTodo) => (prevTodo.id === todo.id ? todo :
prevTodo)),
  );
};

//deleting todo
const deleteTodo = (id) => {
  setTodos((prev) => prev.filter((todo) => todo.id !== id));
};

//togolling todo complete
const toggleComplete = (id) => {
  setTodos((prev) =>
    prev.map((prevTodo) =>
      prevTodo.id === id
        ? { ...prevTodo, completed: !prevTodo.completed }
        : prevTodo,
    ),
  );
};

useEffect(() => {
  const todos = JSON.parse(localStorage.getItem("todos"));
  if (todos && todos.length > 0) {
    setTodos(todos);
  }
}, []);

useEffect(() => {
  localStorage.setItem("todos", JSON.stringify(todos));
}, [todos]);

return (
  <TodoProvider
    value={{ todos, addTodo, updateTodo, deleteTodo,
toggleComplete }}

```

```

>
<div className="bg-[#172842] min-h-screen py-8">
  <div className="w-full max-w-2xl mx-auto shadow-md
rounded-lg px-4 py-3 text-white">
    <h1 className="text-2xl font-bold text-center mb-8 mt-2">
      Manage Your Todos
    </h1>
    <div className="mb-4">
      {/* Todo form goes here */}
      <TodoForm />
    </div>
    <div className="flex flex-wrap gap-y-3">
      {/*Loop and Add TodoItem here */}
      {todos.map((todo) => (
        <div key={todo.id} className="w-full">
          <TodoItem todo={todo} />
        </div>
      ))}
    </div>
  </div>
</div>
</TodoProvider>
);
};

```

export default App;

i have few qs from this now

i declare the context in the context file with some default value right?

in app.jsx every thins that return is wrapped in this

<TodoProvider

value={{ todos, addTodo, updateTodo, deleteTodo, toggleComplete }}

so am i need to provide the default value here like this ?

i i had to pass more value where shoud i give

then 2nd qs is

useEffect(() => {

const todos = JSON.parse(localStorage.getItem("todos"));

```

    if (todos && todos.length > 0) {

        setTodos(todos);

    }

}, []);

useEffect(() => {

    localStorage.setItem("todos", JSON.stringify(todos));

}, [todos]);

```

i have written this 2 useeffect hook so one is when the page will load it will bring things from the local storage and one is for saving the things to local storage but my qs is for the very first time both runs at once as it is use effect hook so will there never be any conflict ?

3rd qs is

```

const addTodo = (todo) => {

    setTodos((prev) => [{ id: Date.now(), ...todo }, ...prev]);

};

```

basically doing destructuring first of prev then adding the new todo at front and doing that destructure also am i modify the id filed so this is a syntax ? what is this ccalled

4th qs is

as i declrae the funtions in the context then declare its funtionality in app.jsx and use it in todo form item there so are they all internally linked?

and in here where i wrap the return before that i declare the addTodo and all funtionality so are they mapped?

```

todos: [

    {

```

```
id: 1,  
  
todo: "Todo message",  
  
completed: false,  
  
},  
  
],  
  
addTodo: (todo) => {},  
  
updateTodo: (id, todo) => {},  
  
deleteTodo: (id) => {},  
  
toggleComplete: (id) => {},  
  
});  
here this todos is just for showig right because it never used or what  
please explain  
and when the todos are rendering each all the funtionality are  
attach to it internally right so that it works finely right? ans this  
doubted qs properly and also mention all key point that i need to  
remeber for further react devolopment
```



Yes — your understanding is **very close**. There are a few important React concepts here that are worth clearing up now because they will help you a lot with Context, Redux, Next.js, etc.

Let's go question by question.

1. `createContext()` default value vs `<TodoProvider value={...}>`

You have:

```
js
```

```
export const TodoContext = createContext({
  todos: [
    {
      id: 1,
      todo: "Todo message",
      completed: false,
    },
  ],

  addTodo: (todo) => {},
  updateTodo: (id, todo) => {},
  deleteTodo: (id) => {},
  toggleComplete: (id) => {},
});
```

You are correct that this creates the **context with a default value**.

But there is an important distinction:

createContext(defaultValue) ≠ actual application data

This:

```
js

createContext({
  todos: [...],
  addTodo: () => {},
})
```

basically says:

"If someone uses this context but there is no Provider above them, this is the value they should receive."

It's mainly a **fallback/default structure**.

Then what is this?

In App.jsx :

```
jsx

<TodoProvider
  value={{
    todos,
    addTodo,
    updateTodo,
```

```
      deleteTodo,  
      toggleComplete,  
    }  
  }  
>
```

This is the **actual value being provided to your components**.

So your flow is:

text

```
createContext()  
  ↓  
creates TodoContext  
  ↓  
TodoProvider  
  ↓  
value={{ todos, addTodo, updateTodo, ... }}  
  ↓  
TodoForm / TodoItem can access it
```

You do NOT need to repeat the default value here.

You don't do:

```
jsx  
  
<TodoProvider  
  value={{  
    todos: [...],  
    addTodo: ...,  
    updateTodo: ...,  
  }}  
>
```

Instead, you give the **real current values/functions**:

```
jsx  
  
<TodoProvider  
  value={{  
    todos,  
    addTodo,  
    updateTodo,  
    deleteTodo,  
    toggleComplete,  
  }}  
>
```

If you want to pass more values

Suppose later you create:

```
js

const clearAllTodos = () => {
  setTodos([]);
};

const todoCount = todos.length;
```

Then simply add them to the provider:

```
jsx

<TodoProvider
  value={{
    todos,
    addTodo,
    updateTodo,
    deleteTodo,
    toggleComplete,
    clearAllTodos,
    todoCount,
  }}
>
```

And then any child can access them:

```
js

const {
  todos,
  addTodo,
  clearAllTodos,
  todoCount
} = useTodo();
```

Important rule

The object inside:

```
jsx

<TodoProvider value={{ ... }}>
```

is the **actual data/functions available through the context**.

2. Your two `useEffect` s — do they conflict on first render?

This is an **excellent question**.

You have:

Effect 1 — load

```
js

useEffect(() => {
  const todos = JSON.parse(localStorage.getItem("todos"));

  if (todos && todos.length > 0) {
    setTodos(todos);
  }
}, []);
```

Effect 2 — save

```
js

useEffect(() => {
  localStorage.setItem("todos", JSON.stringify(todos));
}, [todos]);
```

You're asking:

"Both are `useEffect` , so during the first render don't they both execute at the same time and cause a conflict?"

Technically, yes, both effects run after the initial render.

But they don't execute at exactly the same time.

React runs them in the order they appear.

Initially:

```
js

todos = []
```

React renders.

Then roughly:

```
text
```

```
Initial render
  ↓
Effect 1 runs
  ↓
read localStorage
  ↓
setTodos(savedTodos)
  ↓
Effect 2 runs
  ↓
save current todos
```

There is a subtle issue here.

If localStorage already contains todos, the second effect can initially see:

```
js

todos = []
```

and potentially write `[]` before the state update from the first effect takes effect.

However, React processes the state update and subsequent render/effect cycle, so in common React behavior your saved todos are then written back. Still, **this pattern can cause an unnecessary initial write and is better handled more deliberately.**

A common solution is to initialize state directly from localStorage:

```
js

const [todos, setTodos] = useState(() => {
  const storedTodos = localStorage.getItem("todos");
  return storedTodos ? JSON.parse(storedTodos) : [];
});
```

Then you only need:

```
js

useEffect(() => {
  localStorage.setItem("todos", JSON.stringify(todos));
}, [todos]);
```

Now the flow is cleaner:

```
text

Component starts
  ↓
```

```
useState reads localStorage
  ↓
todos gets saved data
  ↓
render
  ↓
useEffect saves whenever todos changes
```

Why the function form?

```
js

useState(() => {
  ...
})
```

This is called a **lazy initializer**.

The function is used to calculate the initial state.

For your app, I'd prefer this approach.

3. This line

You asked about:

```
js

setTodos((prev) => [{ id: Date.now(), ...todo }, ...prev]);
```

This is actually several concepts combined.

Let's break it down.

First:

```
js

(prev) => ...
```

This is an **arrow function**.

React gives your function the previous state.

So:

```
js
```

```
setTodos((prev) => ...)
```

means:

"Take the previous `todos` state and calculate the new state from it."

If:

```
js

prev = [
  { id: 1, todo: "Study" },
  { id: 2, todo: "Exercise" }
]
```

Then:

```
js

{ id: Date.now(), ...todo }
```

This is an **object literal with the spread operator**.

Suppose:

```
js

todo = {
  todo: "Learn React",
  completed: false
}
```

Then:

```
js

{
  id: Date.now(),
  ...todo
}
```

produces something like:

```
js

{
  id: 1758123456789,
```

```
    todo: "Learn React",  
    completed: false  
  }  
}
```

So yes — you're **adding an id property** to the object.

Then:

```
js  
  
...prev
```

This spreads all elements of the previous array.

Suppose:

```
js  
  
prev = [  
  { id: 1, todo: "Study" },  
  { id: 2, todo: "Exercise" }  
]
```

Then:

```
js  
  
[  
  { id: 3, todo: "Learn React" },  
  ...prev  
]
```

becomes:

```
js  
  
[  
  { id: 3, todo: "Learn React" },  
  { id: 1, todo: "Study" },  
  { id: 2, todo: "Exercise" }  
]
```

So you're **adding the new todo at the beginning of the array**.

The whole thing:

```
js
setTodos((prev) => [
  { id: Date.now(), ...todo },
  ...prev
]);
```

means:

"Take the previous todo array, create a new todo with a unique-ish timestamp ID, put it at the beginning, and make that the new state."

Important React concept

You are **not modifying** `prev` .

You're creating a **new array**.

That's very important in React.

❌ Don't do:

```
js
prev.push(newTodo);
return prev;
```

Instead:

```
js
return [newTodo, ...prev];
```

This is **immutable state updating**.

Remember this concept.

4. Are your Context functions internally linked?

Yes — but let's understand exactly how.

Your Context declares:

```
js
export const TodoContext = createContext({
  todos: [...],
  addTodo: (todo) => {},
  updateTodo: (id, todo) => {},
  deleteTodo: (id) => {},
});
```

```
toggleComplete: (id) => {},  
});
```

This establishes the **shape/API of the context**.

Then `App.jsx` actually creates the functions:

```
js
```

```
const addTodo = (todo) => {  
  setTodos((prev) => [{ id: Date.now(), ...todo }, ...prev]);  
};
```

```
js
```

```
const updateTodo = ...
```

```
js
```

```
const deleteTodo = ...
```

```
js
```

```
const toggleComplete = ...
```

Then you pass those functions into the Provider:

```
jsx
```

```
<TodoProvider  
  value={{  
    todos,  
    addTodo,  
    updateTodo,  
    deleteTodo,  
    toggleComplete  
  }}  
>
```

So yes, they are connected.

Think of Context like a delivery box 📦

Your `App` creates the actual things:

```
js
```

```
todos
addTodo
updateTodo
deleteTodo
toggleComplete
```

Then:

```
jsx

<TodoProvider value={{ ... }}>
```

puts them into a shared box.

Then:

```
js

const { addTodo } = useTodo();
```

takes `addTodo` out of that box.

So when `TodoForm` does:

```
js

addTodo({ todo, completed: false });
```

it's calling the **exact** `addTodo` function that was created inside `App.jsx` .

There isn't another `addTodo` magically being created by Context.

5. Then what are these functions in `createContext()` ?

This part:

```
js

addTodo: (todo) => {},
updateTodo: (id, todo) => {},
deleteTodo: (id) => {},
toggleComplete: (id) => {},
```

does **not** contain your real functionality.

These are basically placeholder/default functions.

For example:

```
js
```

```
addTodo: (todo) => {}
```

means:

"If somebody accesses the context without a Provider, `addTodo` exists, but it doesn't do anything."

Your real function comes from:

```
jsx
```

```
<TodoProvider  
  value={{  
    addTodo,  
    ...  
  }}  
>
```

6. What about this `todos` inside `createContext` ?

You asked a very important question.

You have:

```
js
```

```
createContext({  
  todos: [  
    {  
      id: 1,  
      todo: "Todo message",  
      completed: false,  
    },  
  ],  
})
```

And you're thinking:

"This `todos` isn't actually used, so why is it there?"

You're basically right.

In your actual application, when `TodoProvider` exists, this default `todos` is **not the `todos` your application uses**.

Your actual `todos` are:

```
js
const [todos, setTodos] = useState([]);
```

and then:

```
jsx
<TodoProvider value={{ todos, ... }}>
```

overrides the context value.

So:

```
js
createContext({
  todos: [...]
})
```

is just the **fallback value**.

You could simplify your context to something like:

```
js
export const TodoContext = createContext({
  todos: [],
  addTodo: () => {},
  updateTodo: () => {},
  deleteTodo: () => {},
  toggleComplete: () => {},
});
```

And your application would still work because the Provider supplies the real values.

7. Then why have a default value at all?

Because `useContext()` needs something to return if there is **no Provider above it**.

Imagine you accidentally render:

```
jsx
<TodoForm />
```

without:

```
jsx
```

```
<TodoProvider>
```

Then `useTodo()` would receive the default context value.

That's why the default object is useful.


But don't confuse it with your actual application state.

8. How does TodoForm actually get `addTodo` ?

Look at your tree.

Your `App` effectively creates:

text



Provider says:

js

```
value={{
  todos,
  addTodo,
  updateTodo,
  deleteTodo,
  toggleComplete
}}
```

Then `TodoForm` says:

js

```
const { addTodo } = useTodo();
```

Therefore:

text

App's addTodo
↓

```
TodoProvider
  ↓
TodoContext
  ↓
useTodo()
  ↓
TodoForm
```

So when you call:

```
js

addTodo(...)
```

inside `TodoForm`, you're calling the function from `App`.

9. And `TodoItem` works the same way

You have:

```
js

const {
  updateTodo,
  deleteTodo,
  toggleComplete
} = useTodo();
```

So `TodoItem` gets references to those actual functions.

For example:

```
js

deleteTodo(todo.id)
```

calls:

```
js

const deleteTodo = (id) => {
  setTodos((prev) =>
    prev.filter((todo) => todo.id !== id)
  );
};
```

Then:

text

TodoItem


```
deleteTodo(id)
```


App's deleteTodo()


```
setTodos()
```


todos changes

App re-renders

TodoItem gets updated todo

That's the core React flow.

10. Are the functions "attached" to each Todo?

Not exactly.

This is an important distinction.

When you do:

jsx

```
{todos.map((todo) => (  
  <TodoItem todo={todo} />  
))}
```

you're passing each **todo object** as a prop:

js

```
todo={todo}
```

The functions are **not stored inside each todo**.

Instead, each `TodoItem` independently gets access to the Context:

js

```
const {
  updateTodo,
  deleteTodo,
  toggleComplete
```

```
} = useTodo();
```

So conceptually:

text



Every `TodoItem` can access the same functions.

The `todo.id` tells the function **which todo to operate on**.

For example:

```
js  
  
deleteTodo(todo.id)
```

means:

"Use the shared delete function, but delete THIS particular todo."

11. Why does `toggleComplete(todo.id)` know which `TodoItem`?

Suppose you have:

```
js  
  
todos = [  
  { id: 101, todo: "Study", completed: false },  
  { id: 102, todo: "Exercise", completed: false },  
  { id: 103, todo: "Code", completed: false }  
]
```

The second `TodoItem` receives:

```
js  
  
todo = {  
  id: 102,  
  todo: "Exercise",  
  completed: false  
}
```

When you click its checkbox:

```
js  
  
toggleComplete(todo.id);
```

that's:

```
js  
  
toggleComplete(102);
```

Then App does:

```
js  
  
prev.map((prevTodo) =>  
  prevTodo.id === id  
    ? {  
      ...prevTodo,  
      completed: !prevTodo.completed  
    }  
    : prevTodo  
)
```

Only ID 102 changes.

12. One more important thing: Context doesn't automatically map functions to todos


This misconception is worth eliminating now.

Context isn't doing:

```
text  
  
Todo 1 → delete function  
Todo 2 → delete function  
Todo 3 → delete function
```

Instead:

```
text  
  
      Context  
      |  
_____|_____
```



The `id` tells the shared function which todo to modify.

13. One small issue in your `updateTodo`

You have:

```
js

const updateTodo = (id, todo) => {
  setTodos((prev) =>
    prev.map((prevTodo) =>
      prevTodo.id === todo.id ? todo : prevTodo
    ),
  );
};
```

You pass:

```
js

updateTodo(todo.id, { ...todo, todo: todoMsg });
```

Since the object already contains the same `id`, it works.

But logically you're passing `id` and then not using it.

You could make it cleaner:

```
js

const updateTodo = (id, updatedTodo) => {
  setTodos((prev) =>
    prev.map((prevTodo) =>
      prevTodo.id === id ? updatedTodo : prevTodo
    )
  );
};
```

Then your `id` parameter actually does the job it was intended to do.

14. The most important React concepts from this project

Since you're moving toward Next.js, **remember these**.

① State belongs to the component that owns it

```
js

const [todos, setTodos] = useState([]);
```

Here `App` owns the todo state.

② State updates should be immutable

Instead of:

```
js

prev.push(todo);
```

use:

```
js

[...prev, todo]
```

Instead of modifying an object directly:

```
js

todo.completed = true;
```

use:

```
js

{
  ...todo,
  completed: true
}
```

③ `setState(prev => ...)` is useful when new state depends on old state

```
js

setTodos((prev) => [...prev, newTodo]);
```

Because you're calculating the new state from the previous state.

④ Context is for sharing data/functions

text

```
App
  ↓
Provider
  ↓
Context
  ↓
Any descendant component
```

It helps avoid passing props through many intermediate components.

⑤ createContext(defaultValue) is a fallback

js

```
createContext(defaultValue)
```

does **not** mean:

"This is my application's actual state."

The Provider's:

jsx

```
value={...}
```

is what your components normally receive.

⑥ useContext() reads the nearest Provider's value

js

```
const { addTodo } = useTodo();
```

gets the value from the nearest:

jsx

```
<TodoProvider value={...}>
```

above that component.

⑦ Functions can be passed through Context

Context isn't only for data:

```
js

{
  todos,
  addTodo,
  deleteTodo,
  updateTodo
}
```

is perfectly normal.

⑧ `useEffect` is for synchronizing with external things

Your `localStorage` example is a perfect use case:

```
text

React state
  ↓
useEffect
  ↓
localStorage
```

`LocalStorage` exists outside React's state system, so the effect synchronizes the two.

⑨ `useEffect(..., [])` means "after initial mount"

```
js

useEffect(() => {
  ...
}, []);
```

It doesn't mean literally "only once under every possible React development configuration"—React Strict Mode in development can intentionally run effect setup/cleanup more than once. But conceptually, it means **no dependency-driven reruns after mounting**.

⑩ `useEffect(..., [todos])` means "when `todos` changes"

js


```
useEffect(() => {  
  localStorage.setItem("todos", JSON.stringify(todos));  
}, [todos]);
```

It runs after the initial render and again whenever React detects that `todos` changed.

Finally, your entire Todo app in one mental model


Keep this picture in your head:

text



And localStorage sits alongside it:

text



One sentence to remember:

createContext() creates the sharing mechanism and its fallback; **<Provider value={...}>** supplies the real data/functions; **useContext()** consumes them; state changes in the owner (**App**) cause React to re-render the components using that state.

Your Todo app is actually a very good project for understanding **state** → **context** → **components** → **re-render** → **localStorage**, which are foundational React concepts you'll use again in larger applications.