

Explanatory Material [SRC_BAPIv2.2_REGISTER]

1. Function Overview

This package is used for data registration using BAPI

2. Function Diagram


* Function Overview

STEP1

- Use "UiPath.SAP.BAPI.Activities.2.2." or later to create a workflow for registration.
- "UiPath.SAP.BAPI.Activities" outputs an Excel Template for registration.
- From the Workflow and Excel Template above, if necessary change the Workflow to be able to register multiple headers / multiple items.
- > **This Component can simply be used with the Workflow and Input File for each BAPI without the above development.**

Ex : BAPI_USER_CREATE1

Workflow and Input File included in this Component



Input File

A screenshot of an Excel spreadsheet template for data registration. It has multiple columns and rows, with some cells containing text like 'BAPI_USER_CREATE1' and 'BAPI_TRANSACTION_COMMIT'.

STEP2

Execute "SRC_BAPIv2.2_REGISTER" and register the inputted data of Input File.

Also check the setting method of AUTHORITY_CHECK included in the "SRC_BAPIv2.2_REGISTER" explanation material of "Common Reusable Components".

The registration Workflow and Commit Work are executed, and various data can be registered.

SAP Application Scope

AUTHORITY_CHECK

SRC_BAPI_USER_CREATE1_v2.2.xml

BAPI_TRANSACTION_COMMIT

Input file after data registration

A screenshot of an Excel spreadsheet showing the result of data registration. It has the same structure as the input file but with data filled in the cells.

- 1 Use UiPath.SAP.BAPI.Activities.2.2 or later to call BAPI and call various data registration workflows to access SAP.
- 2 Reads data input to Input File.
- 3 If there is a BAPI user input in the config file, use the function module "AUTHORITY_CHECK" to perform an authorization check.
(Only when the entered BAPI User has authority, the registration process to SAP is executed.)
- 4 Execute registration processing with SAP.
- 5 Log is output by LogType of Config File.

Explanatory Material [SRC_BAPIv2.2_REGISTER]

3. How to Use

The following arguments must be configured prior as input parameters.

<Input>

Argument Name	Type	Description	Required
in_ConfigFilePath	String	Config file save destination and file name (Set the relative path or complete path.)	Yes
in_LoginUser	String	SAP User	
in_LoginPassword	SecureString	SAP Logon Password	

<Input / Output>

Argument Name	Type	Description	Required
io_Option	Dictionary<String, Object>	It is used to input / output necessary information according to each BAPI.	Yes

About authority check

Use the function module "AUTHORITY_CHECK" to check the authorization.
The authority value is not in the Config File etc., so enter it directly in the required Workflow.

Enter the required value for "AUTHORITY_CHECK" of Build Data Table in "CheckAuthority.xml".
(Example: When creating a purchase order document, only document type "NB" can be "registered")

Build Data Table									
	New_B uffering (String) ✓	User (String) ✓	Object (String) ✓	Field1 (String) ✓	Value1 (String) ✓	Field2 (String) ✓	Value2 (String) ✓	Field3 (String) ✓	Value3 (String) ✓
x			M_BEST_BS	BSART	NB	ACTVT	01		
x									

- * "BAPI User" of Config File is set to User.
Check whether the SAP user entered in BAPI USER has the above authorization
and only run the registration process if you have the authorization.
(Checking whether the return value to the exception is "USER_IS_AUTHORIZED")

Transaction code: When executing AUTHORITY_CHECK from SE37.

Test for function group	SUSR
Function module	AUTHORITY_CHECK
Uppercase/Lowercase	☐
RFC target sys:	
Import parameters	
NEW_BUFFERING	0
USER	TEST_USER
OBJECT	M_BEST_BS
FIELD1	BSART
VALUE1	NB
FIELD2	ACTVT
VALUE2	01

Explanatory Material [SRC_BAPIv2.2_REGISTER]

4. Reference

The input contents of Argument File are as follows.
(Please input all Argument File as String)

Sheet : Settings

Property	Description	Required
BAPIName	Function module name to execute (BAPI name)	Yes
InputFilePath	Input File save destination and file name (Set a relative or full path.)	Yes
CallWorkflowPath	Workflow save destination and file name for each BAPI (Set a relative or full path.)	Yes
DataCountSheet	Worksheet name of header data (worksheet where key items of input data are registered)	Yes
Client	Client information for SAP connection	
Language	SAP connection language (EN: English, JA: Japanese)	
SncLibraryPath	Absolute path of SNC shared library used for SAP connection	
SncMode	Determine if the connection to SAP is protected by SNC. (0 : Do not use SNC, 1 : Use SNC)	
SncPartnerName	ID used for the destination server, if required by the SNC solution.	
SncQOP	Quality of service level used for SNC communication on the destination server. (1 : Authentication only, 2 : Integrity protection, 3 : Privacy protection, 8 : Default, 9 : Maximum security)	
SncSSO	Credentials when using SNC (0 : Login with user / password, 1 : Login with SNC ID)	
AdvancedParameters	A semicolon-separated list of name / value pairs for additional RFC configuration parameters.	
AppServer	SAP Application Server host name.	
LogonGroup	Logon group from which the message server selects the application server	
MessageServer	The host name of the central instance message server in the SAP system.	
SAPRouter	SAP router used to establish connection.	
StatefulConnection	Decide whether to establish a stateful connection, defaults to True. (True, False)	
SystemID	3-character system ID of the SAP system	
SystemNumber	SAP system number	
Commit	Commit execution flag (X: Commit is executed, other than X: Commit is not executed) (Because this function is committed inside BAPI, it will be committed even if this flag is deleted.)	
LogFolderPath	Log data file save destination (Set a relative or full path.)	Yes
LogFileName	Log data file name	
LogType	Output type of log data (TEXT: text, EXCEL: Excel)	Yes
LogOutputLine	Number of output to Excel	Yes

In CheckRequiredfield.xml, check logic for required items is included, but please add logic if necessary.

(In order to support single sign-on, the mandatory check of user ID and password, which was mandatory check in the previous version, has been deleted)

Sheet : Option

Sheet for managing information for use with individual BAPIs.

Property	Description	Required
BAPIUser	Authorization check (AUTHORITY_CHECK) BAPI user name at execution (Blank: Do not perform authorization check, otherwise: Perform authorization check)	
PasswordSuffix	Suffix given to password when executing password change (BAPI_USER_CHANGE) #DATE# : yyyyMMdd is assigned #RANDOM# : random number is assigned Other character : choose value is assigned	

5. Important Notes

- The Workflow Template provided in "Common Reusable Components" of UiPath Connect Marketplace, saved in the "SRC_Common" folder, when using UiPath Reusable Component for S/4HANA, you must save it together.
- Do not start Excel when executing.