

Deep Learning

Application 6

TensorFlow application which used for Loss Reduction.

```
1 import tensorflow as tf
2
3 print("Marvellous Infosystems : Machine Learning")
4
5 #Model parameter
6 w = tf.compat.v1.Variable([.3],tf.float32)
7 b = tf.compat.v1.Variable([-3],tf.float32)
8
9 # Input and Output
10 x = tf.compat.v1.placeholder(tf.float32)
11
12 linear_model = w * x + b
13
14 y = tf.compat.v1.placeholder(tf.float32)
15
16 # Loss function
17 squared_delta = tf.square(linear_model-y)
18 loss = tf.reduce_sum(squared_delta)
19
20 # Optimiser
21 optimiser = tf.compat.v1.train.GradientDescentOptimizer(0.01)
22 train = optimiser.minimize(loss)
23
24 init = tf.compat.v1.global_variables_initializer()
25
26 # Run computational graph
27 sobj = tf.compat.v1.Session()
28
29 sobj.run(init)
30
31 for i in range(1000):
32     sobj.run(train,{x:[1,2,3,4], y:[0,-1,-2,-3]})
33
34 print(sobj.run([w,b]))
35
```

Output of above application

```
(base) MacBook-Pro-de-MARVELLOUS:TensorApplications|  
marvellous$ python3 TensorLossOptimizer.py  
Marvellous Infosystems : Machine Learning  
2019-06-08 22:53:38.358539: I tensorflow/core/platform/cp  
u_feature_guard.cc:142] Your CPU supports instructions th  
at this TensorFlow binary was not compiled to use: AVX2  
FMA  
[array([-0.9999969], dtype=float32), array([0.9999908],  
dtype=float32)]  
(base) MacBook-Pro-de-MARVELLOUS:TensorApplications  
marvellous$ █
```

